



Data Dictionary

**micros®**  
Fidelio Suite8

Version 8.9.6.2  
MICROS Fidelio Suite8  
Documentation

This document has been prepared by MICROS-Fidelio GmbH and is available to a select group of individuals for informational purposes. This is a confidential document that contains concepts, methods and other proprietary information. Readers are to treat the information herein as confidential.

Information in this document is subject to change without notice.

MICROS-Fidelio GmbH. makes no warranty of any kind with regard to this material, including but not limited to the implied warranties of marketability and fitness for a particular purpose.

MICROS-Fidelio GmbH Ltd. shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Copyright © 2014 MICROS-Fidelio GmbH. All Rights Reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express prior written consent of the publisher.

### AACC

AR Accounts (former fa\_cust)

Field Name	Type	Length	Decimals	Not NULL	
AACC_ID	NUMBER	30		N	Unique Identifier for A/R Accounts
AACC_ATYP_ID	NUMBER	30		N	Account Type Link
AACC_XCMS_ID	NUMBER	30		N	Profile ID
AACC_NUMBER	VARCHAR2	20		Y	AR number of account
AACC_CREDITLIMIT	NUMBER	30	4	Y	Credit limit of account
AACC_BATCH	NUMBER	1		N	1 = true
AACC_PERMANENT	NUMBER	1		N	1 = true
AACC_OBSOLETE	NUMBER	1		N	1 = true
AACC_XADR_ID	NUMBER	30		N	must be an address of aacc_xcms_id, we fill automatically the billing address , if not exist the primary address
AACC_CONTACT_XCMS_ID	NUMBER	30		Y	A/R Contact for this A/R Account
AACC_PAYMENTS_ZFAC_ID	NUMBER	30		Y	we automatically create one zfac_type to zfac record where we store all payments to the ar account. we do not allow movement of these charges nor check out of these accounts
AACC_MIN_DAYS_BETWEEN_REM	NUMBER	3		Y	minimum days between reminder letters

### AAGP

Aging

Field Name	Type	Length	Decimals	Not NULL	
AAGP_ID	NUMBER	30		N	unique id
AAGP_ATYP_ID	NUMBER	30		N	link to account type
AAGP_AACC_ID	NUMBER	30		N	link to ar account
AAGP_NUMBER_OF_DAYS	NUMBER	3		N	number of days from invoice date

### ACMP

AR Compressions

Field Name	Type	Length	Decimals	Not NULL	
ACMP_ID	NUMBER	30		N	Unique Identifier for Compression Table
ACMP_DATE	DATE			N	Compression Fidelio System Date
ACMP_PCDATE	DATE			N	PC Date of Compression
ACMP_USER_XCMS_ID	NUMBER	30		N	Id of the user which performed the compression.
ACMP_COMMENT	VARCHAR2	60		Y	Comments to Compression.
ACMP_ACTIVE	NUMBER	1		Y	1 = active, last compression
ACMP_PREVIEW	NUMBER	1		Y	1 = preview compression report; 0 or null - compression

### ACMP

AR Compressions

Field Name	Type	Length	Decimals	Not NULL
ACMP_NUMBER	VARCHAR2	60		Y

### ACPL

AR Compression link

Field Name	Type	Length	Decimals	Not NULL	
ACPL_ID	NUMBER	30		N	Unique identifier of compression - invoice link
ACPL_AINV_ID	NUMBER	30		N	Link to A/R record
ACPL_ACMP_ID	NUMBER	30		N	Link to Compression ID

### ADET

Invoice detail table for Egyptian A/R Invoice printing

Field Name	Type	Length	Decimals	Not NULL
ADET_ID	NUMBER	30		N
ADET_AHDR_ID	NUMBER	30		N
ADET_DESCRIPTION	VARCHAR2	120		Y
ADET_AMOUNT	NUMBER	30	4	Y

### AHDR

Table for Egyptian A/R Invoice printing

Field Name	Type	Length	Decimals	Not NULL
AHDR_ID	NUMBER	30		N
AHDR_INVOICEDATE	DATE			Y
AHDR_ORIGINALINVOICENO	VARCHAR2	60		Y
AHDR_VOUCHERNO	VARCHAR2	60		Y
AHDR_FOLIONO	VARCHAR2	60		Y
AHDR_ARNO	VARCHAR2	20		Y
AHDR_MEALS	VARCHAR2	100		Y
AHDR_GUEST_XCMS_ID	NUMBER	30		Y
AHDR_AACC_ID	NUMBER	30		Y
AHDR_AINV_ID	NUMBER	30		Y
AHDR_CHECKIN	DATE			Y
AHDR_CHECKOUT	DATE			Y

### AHDR

Table for Egyptian A/R Invoice printing

Field Name	Type	Length	Decimals	Not NULL
AHDR_DUEDATE	DATE			Y
AHDR_ZCUR_ID	NUMBER	30		Y
AHDR_AMOUNT	NUMBER	30	4	Y
AHDR_EXCHANGERATE	NUMBER	30	4	Y
AHDR_FOREIGNAMOUNT	NUMBER	30	4	Y

### AINV

AR invoices, former gzahl and gdeb

Field Name	Type	Length	Decimals	Not NULL	
AINV_ID	NUMBER	30		N	Unique Identifier for A/R Records
AINV_AACC_ID	NUMBER	30		N	Link to A/R Account
AINV_PAYM_ZPOS_ID	NUMBER	30		N	Link to the payment record in zpos which created this A/R record.
AINV_AMOUNT	NUMBER	30	4	N	Amount of A/R Record.
AINV_DESCRIPTOR	VARCHAR2	30		Y	Description of A/R record.
AINV_ZCAS_ID	NUMBER	30		N	Link to Cashier ID
AINV_TRANSFER_DATE	DATE			Y	filled when accepted from the holding area
AINV_CD	NUMBER	1		N	1 = debit 5 = credit (payment)
AINV_CLOSEDTIME	DATE			Y	Filled when fully paid. WUSS setting controls how long closed records are shown
AINV_ADJUST_AINV_ID	NUMBER	30		Y	For Adjustments we store here the AINV_ID of the adjusted record in both records, original and new avin record
AINV_REMARKS	VARCHAR2	50		Y	For Remarks
AINV_POSTDATE	DATE			Y	Fidelio Date of A/R record.
AINV_PCDATE	DATE			Y	PC Date of creation of A/R record.
AINV_ORIGINAL_AINV_ID	NUMBER	30		Y	in case of transferring a record from one aacc_id to another we store the original ainv_id here. We store always the previous id here (for repeating transfers this allows to control the flow)
AINV_MANUALPOST	NUMBER	1		Y	1 - Old AR Balance Posting (manual).
AINV_REALPOSTDATE	DATE			Y	Real Fidelio Date of A/R record. Different from POSTDATE for old balance postings.
AINV_TRANSFER_INFO	VARCHAR2	50		Y	Transaction transfer information (from account, to account)
AINV_CR	NUMBER	30	4	N	
AINV_DB	NUMBER	30	4	N	
AINV_ORIGINAL_ZPOS_ID	NUMBER	30		Y	
AINV_ORIGINAL_ZPOS_ZDCO_ID	NUMBER	30		Y	
AINV_ORIGINAL_MANUALPOST	NUMBER	1		Y	

### AIPL

AR Invoice Payment Link

Field Name	Type	Length	Decimals	Not NULL	
AIPL_ID	NUMBER	30		N	Unique Identifier of A/R Invoice Payment Link
AIPL_DEBIT_AINV_ID	NUMBER	30		N	A/R record ID of the record where the payment applies to.
AIPL_CREDIT_AINV_ID	NUMBER	30		N	A/R record ID of the record of the applied payment
AIPL_AMOUNT	NUMBER	30	4	N	Payment amount applied.
AIPL_ZCAS_ID	NUMBER	30		N	Cashier ID.
AIPL_PCTIME	DATE			N	PC Date when payment was applied.
AIPL_POSTDATE	DATE			Y	Fidelio Date when Payment was applied.

### AREM

Reminder Cycle Setup

Field Name	Type	Length	Decimals	Not NULL	
AREM_ID	NUMBER	30		N	Unique Identifier of the Reminder Cycle Setup
AREM_LONGDESC	VARCHAR2	30		N	Reminder Cycle Description
AREM_VALIDFROM	NUMBER	3		Y	Valid after these amount of days
AREM_DISPLORDER	NUMBER	3		N	Display Order
AREM_WRPT_ID	NUMBER	30		N	Link to Reminder Template
AREM_STATEMENT	NUMBER	1		Y	1 = is statement.
AREM_DEFAULT	NUMBER	1		Y	1 = Default

### ARLD

Reminder Log Details

Field Name	Type	Length	Decimals	Not NULL	
ARLD_ID	NUMBER	30		N	Unique Identifier of the Reminder Log.
ARLD_AINV_ID	NUMBER	30		N	Reminded A/R Record.
ARLD_AREM_ID	NUMBER	30		Y	ARLD_AREM_ID is of ARLD
ARLD_ARLG_ID	NUMBER	30		N	Reminder Log Link.
ARLD_ORIGINALAMOUNT	NUMBER	30	4	N	Original Amount to be reminded
ARLD_PAIDAMOUNT	NUMBER	30	4	N	So far Paid Amount. Means ARLD_ORIGINALAMOUNT-ARLD_PAIDAMOUNT is the open Amount which gets reminded.

### ARLG

Reminder Log, for parameter setting 'SeperateReminderLetter' we create one record per reminder cycle, else one.

Field Name	Type	Length	Decimals	Not NULL	
ARLG_ID	NUMBER	30		N	Unique Identifier of A/R Reminder Log.
ARLG_DATE	DATE			N	Fidelio Date
ARLG_PCDATE	DATE			N	PC Date
ARLG_AACC_ID	NUMBER	30		N	Account ID
ARLG_USER_XCMS_ID	NUMBER	30		N	Reminder Creation User ID
ARLG_PRINTED	NUMBER	1		Y	1 = Printed.
ARLG_AREM_ID	NUMBER	30		Y	Reminder Level Link
ARLG_DOCTYPE	NUMBER	1		Y	1 = Reminder Letter; 2 = Statement; 3 = Compression Report

### ARPL

AR reminder letter/statement print log

Field Name	Type	Length	Decimals	Not NULL	
ARPL_ID	NUMBER	30		N	Unique identifier
ARPL_ARLG_ID	NUMBER	30		N	Link to document binary storage
ARPL_ZTXT_ID	NUMBER	30		Y	Link to document binary storage
ARPL_WMAI_ID	NUMBER	30		Y	Link to document EMail send log
ARPL_SAVEDONLY	NUMBER	1		N	0 if the document was printed, 1 - temporary saved copy
ARPL_ORIGINAL_ARPL_ID	NUMBER	30		Y	Original ARPL_ID
ARPL_EDITOR_XCMS_ID	NUMBER	30		Y	Editor User ID
ARPL_EDITOR_DATE	DATE			Y	Edit Date
ARPL_REVISION	NUMBER	30		Y	Revision Number (in case stored document has been changed)
ARPL_NOTE	VARCHAR2	200		Y	Reason why document has been changed

### ARPR

AR Payment Receipt Data table

Field Name	Type	Length	Decimals	Not NULL	
ARPR_ID	NUMBER	30		N	
ARPR_ZFAC_ID	NUMBER	30		Y	
ARPR_INVOICENO	VARCHAR2	60		Y	
ARPR_INVOICENAME	VARCHAR2	100		Y	
ARPR_INVOICEDATE	DATE			Y	
ARPR_ORIGINALAMOUNT	NUMBER	30	4	Y	

### ARPR

AR Payment Receipt Data table

Field Name	Type	Length	Decimals	Not NULL
ARPR_ALREADYPAID	NUMBER	30	4	Y
ARPR_PAIDNOW	NUMBER	30	4	Y
ARPR_TOTALBALANCE	NUMBER	30	4	Y
ARPR_AINV_ID	NUMBER	30		Y

### ATLK

Account Type link to XCCA

Field Name	Type	Length	Decimals	Not NULL	
ATLK_ID	NUMBER	30		N	Unique Identifier
ATLK_ATYP_ID	NUMBER	30		N	Link to Account Type
ATLK_XCCA_ID	NUMBER	30		N	Link to Profile Types
ATLK_CREDITLIMIT	NUMBER	30	4	Y	Default Credit Limit

### ATRC

Account Types Reminder Configuration

Field Name	Type	Length	Decimals	Not NULL	
ATRC_ID	NUMBER	30		N	Unique Identifier for Account Types Reminder Configuration
ATRC_ATYP_ID	NUMBER	30		Y	Link to Account Types
ATRC_AREM_ID	NUMBER	30		N	Link to reminder.
ATRC_DISPLORDER	NUMBER	3		N	Display Order
ATRC_AACC_ID	NUMBER	30		Y	link to ar account

### ATYP

A/R Account Types

Field Name	Type	Length	Decimals	Not NULL	
ATYP_ID	NUMBER	30		N	Unique Identifier for A/R Account Types
ATYP_SHORTDESC	VARCHAR2	3		N	A/R Account Type Short Description
ATYP_LONGDESC	VARCHAR2	30		N	A/R Account Type Description
ATYP_DISPLORDER	NUMBER	3		N	Display Order
ATYP_MIN_DAYS_BETWEEN_REM	NUMBER	3		Y	Minimum days between reminder letters

### BPAR

Application parameters for the V8BankImport program

Field Name	Type	Length	Decimals	Not NULL	
BPAR_ID	NUMBER	30		N	Unique ID
BPAR_IMPORT	VARCHAR2	256		Y	Path to the Import directory
BPAR_BACKUP	VARCHAR2	256		Y	Path to the Backup directory
BPAR_DUPLICATES	NUMBER	1		Y	Only import payments once
BPAR_LANGUAGE	VARCHAR2	2		Y	User interface language
BPAR_PROTOCOL	VARCHAR2	30		Y	Bank transfer file Protocol

### BPID

Payment Identifiers for the V8BankImport program

Field Name	Type	Length	Decimals	Not NULL	
BPID_ID	NUMBER	30		N	Unique ID
BPID_DESCRIPTION	VARCHAR2	30		N	Description for the Payment Identifier
BPID_TYPE	NUMBER	1		N	Type of import: 0=Deposit Payment, 1=City Ledger Payment
BPID_DEPARTMENT	NUMBER	5		N	Department code (ZDCO.ZDCO_NUMERICDESC)
BPID_IDENTIFIER	VARCHAR2	2		N	2-digit payment identifier code

### BTRX

Bank transaction history for the V8BankImport program

Field Name	Type	Length	Decimals	Not NULL	
BTRX_ID	NUMBER	30		N	Unique ID
BTRX_SEQUENCE	VARCHAR2	10		N	Sequence of the transaction in the Bank Receipt file
BTRX_REFERENCE	VARCHAR2	30		N	Unique payment reference
BTRX_TRANSACTIONDATE	DATE			Y	Date the payment was made on the bank account
BTRX_PROCESSEDDATE	DATE			Y	Date of processing
BTRX_AMOUNT	NUMBER	30	4	Y	Amount (with sign)
BTRX_INFORMATION	VARCHAR2	256		N	Structured or free-format communication information
BTRX_ACCOUNTHOLDER	VARCHAR2	60		N	Holder of the Bank Account
BTRX_ACCOUNTNUMBER	VARCHAR2	30		N	Bank Account Number
BTRX_STATUSCODE	NUMBER	2		Y	Status code of the transaction (1=Success, 2=Warning, 3=Failed)
BTRX_INFOCODE	NUMBER	2		Y	Additional information on the status
BTRX_ZPOS_ID	NUMBER	30		Y	ZPOS_ID is of ZPOS
BTRX_ISLOST	NUMBER	1		Y	Flag if payment is on the lost account 0=NO, 1=YES

### BTRX

Bank transaction history for the V8BankImport program

Field Name	Type	Length	Decimals	Not NULL	
BTRX_PASSED_ID	NUMBER	30		Y	Reservation identifier passed, eg: YRES.YRES_ID
BTRX_IDENTIFIER	VARCHAR2	2		Y	Payment Identifier (only if structured message)

### CART

Certificate articles

Field Name	Type	Length	Decimals	Not NULL	
CART_ID	NUMBER	30		N	Article ID
CART_NAME	VARCHAR2	100		N	Article name
CART_TYPE	NUMBER	3		Y	Article type (depends on redemption system)
CART_PRICE	NUMBER	30	4	Y	Article price
CART_COUPONTEXT	VARCHAR2	200		Y	Coupon text
CART_COUPONDESCR	VARCHAR2	4000		Y	Coupon description
CART_PAYMENT_ZDCO_ID	NUMBER	30		Y	Department code for payments
CART_DISPLORDER	NUMBER	3		Y	
CART_SELL_ZDCO_ID	NUMBER	30		Y	Department where we post selling of the voucher
CART_DEFAULT_DUARTION	NUMBER	4		Y	1 if partial redemption allowed
CART_PARTIAL_REDEMPTION	NUMBER	1		Y	
CART_EXTERNALTYPE	VARCHAR2	10		Y	used by 3rd party voucher interface. For reporting purposes only
CART_WEBENABLED	NUMBER	1		Y	
CART_WEBNAME	VARCHAR2	300		Y	
CART_WEBSHORTDESCRIPTION	VARCHAR2	300		Y	
CART_WEBLONGDESCRIPTION	VARCHAR2	2000		Y	
CART_WIMG_ID	NUMBER	30		Y	
CART_VOUCHERTYPE	NUMBER	1		Y	0 - Product voucher; 1 - Value Voucher; 2 - Arrangement voucher
CART_YRES_ID	NUMBER	30		Y	
CART_COMPLIMENTARY	NUMBER	1		Y	1 = complimentary voucher type
CART_WEB_CUSTOMIZABLE	NUMBER	1		Y	1 = some voucher conditions can be adjusted on the web
CART_LETTER_WRPT_ID	NUMBER	30		Y	
CART_VOUCHER_WRPT_ID	NUMBER	30		Y	
CART_ZINN_ID	NUMBER	30		Y	
CART_NUMBERTEMPLATE	VARCHAR2	60		Y	
CART_TAXWHENUSED	NUMBER	1		Y	when 1, Tax will be calculated when the voucher is used, not when the voucher is created
CART_OVERRIDEREDEEMAMOUNT	NUMBER	1		Y	if 1, redemption amount will be requested

### CBCC

Barcode prefixes configuration

Field Name	Type	Length	Decimals	Not NULL	
CBCC_ID	NUMBER	30		N	CBCC ID
CBCC_DESC	VARCHAR2	30		Y	Description
CBCC_ROLE	NUMBER	1		N	1 = Voucher Handling 2 = Rebate 3=Loyalty Services Voucher 4=Bonus Card 5= Rebate Cards
CBCC_REGEXP	VARCHAR2	60		N	Regular expression to test
CBCC_DISPLORDER	NUMBER	4		Y	

### CORD

Voucher orders

Field Name	Type	Length	Decimals	Not NULL	
CORD_ID	NUMBER	30		N	
CORD_ORDERNAME	VARCHAR2	100		Y	
CORD_DESCRIPTION	VARCHAR2	4000		Y	gift certificate description
CORD_TEXT	VARCHAR2	1000		Y	Text for the gift certificate
CORD_ISSUE	DATE			Y	Date of issue of the gift certificate
CORD_VALIDFROM	DATE			Y	Start of date where the gift certificate is valid
CORD_VALIDUNTIL	DATE			Y	End of date where the gift certificate is valid
CORD_XCMS_ID	NUMBER	30		Y	Ordering Profile
CORD_QUANTITY	NUMBER	30		N	Number of vouchers
CORD_CART_ID	NUMBER	30		Y	Article Link
CORD_ZFAC_ID	NUMBER	30		Y	
CORD_FINALIZED	NUMBER	1		Y	
CORD_DEDICATION	VARCHAR2	4000		Y	
CORD_CONSUMING_XCMS_ID	NUMBER	30		Y	Consuming Guest
CORD_INTERNAL_INFO	VARCHAR2	1000		Y	
CORD_ORDER_REASON	VARCHAR2	100		Y	
CORD_YRES_ID	NUMBER	30		Y	Reservation link for Arrangement vouchers
CORD_AMOUNT	NUMBER	30	4	Y	
CORD_VOID_ZFAC_ID	NUMBER	30		Y	Link to FA of the void payments to the vouchers related to the order
CORD_CSHP_ID	NUMBER	30		Y	
CORD_SENDBYMAIL	NUMBER	1		Y	1 - to be send
CORD_SHIP_MULTIPLY	NUMBER	1		Y	1 - Shiping charges will be multiplied by number of vouchers

## COUP

Gift coupon info

Field Name	Type	Length	Decimals	Not NULL	
COUP_ID	NUMBER	30		N	Coupon ID
COUP_NUMBER	VARCHAR2	30		Y	Complete number of the gift certificate
COUP_DESCRIPTION	VARCHAR2	4000		Y	gift certificate description
COUP_TEXT	VARCHAR2	1000		Y	Text for the gift certificate
COUP_ISSUE	DATE			Y	Date of issue of the gift certificate
COUP_VALIDFROM	DATE			Y	Start of date where the gift certificate is valid
COUP_VALIDUNTIL	DATE			Y	End of date where the gift certificate is valid
COUP_CLEARINGDATE	DATE			Y	Date of clearing
COUP_XCMS_ID	NUMBER	30		Y	Ordering Profile
COUP_CART_ID	NUMBER	30		Y	Article Link
COUP_AMOUNT	NUMBER	30	4	N	Amount of gift certificates
COUP_AMOUNTREDEEMED	NUMBER	30	4	Y	Amount which has been redeemed
COUP_ZFAC_ID	NUMBER	30		Y	The reason why voucher marked as inactive
COUP_INACTIVE	NUMBER	1		Y	
COUP_INACTIVEDATE	DATE			Y	
COUP_INACTIVECOMMENT	VARCHAR2	500		Y	
COUP_PRINTED	NUMBER	1		Y	0 = Has not been printed yet. 1 = Has been printed
COUP_VOUCHERTYPE	NUMBER	1		Y	0 - Product voucher; 1 - Value Voucher; 2 - Arrangement voucher
COUP_YRES_ID	NUMBER	30		Y	Reservation link for Arrangement vouchers
COUP_FINALIZED	NUMBER	1		Y	When 1, Arrangement voucher reservation cannot be edited anymore
COUP_WLOP_ID	NUMBER	30		Y	Obsolete. Please use WLOR_COUP_ID
COUP_CONSUMING_XCMS_ID	NUMBER	30		Y	Consuming Guest
COUP_INTERNAL_INFO	VARCHAR2	1000		Y	
COUP_ORDER_REASON	VARCHAR2	100		Y	
COUP_ONHOLD	NUMBER	1		Y	
COUP_ONHOLDREASON	VARCHAR2	100		Y	
COUP_SENDBYMAIL	NUMBER	1		Y	1 - to be send, 2 - sent (0 or null, printed online)
COUP_DEDICATION	VARCHAR2	4000		Y	
COUP_PICKUP_YRES_ID	NUMBER	30		Y	
COUP_VOID_ZFAC_ID	NUMBER	30		Y	Link to FA of the voided voucher
COUP_FULLYPAID	NUMBER	1		Y	when 1, means that voucher has been fully paid (V* voucher management only)
COUP_ORDERING_XCMS_ID	NUMBER	30		Y	
COUP_CORD_ID	NUMBER	30		Y	Link to the Voucher Order

## COUP

Gift coupon info

Field Name	Type	Length	Decimals	Not NULL
COUP_REDEMPTIONNOTE	VARCHAR2	1000		Y
COUP_CSHP_ID	NUMBER	30		Y

## CPOS

List of postings linked to the voucher

Field Name	Type	Length	Decimals	Not NULL	
CPOS_ID	NUMBER	30		N	Primary key
CPOS_COUP_ID	NUMBER	30		N	Voucher link
CPOS_ZPOS_ID	NUMBER	30		N	Posting link

## CRVD

Certificate's revenue departments

Field Name	Type	Length	Decimals	Not NULL	
CRVD_ID	NUMBER	30		N	Primary key
CRVD_CART_ID	NUMBER	30		N	Link to the certificate
CRVD_ZDCO_ID	NUMBER	30		N	Link to the department

## CSCO

Shipping charge applicatble to the countries. Link table

Field Name	Type	Length	Decimals	Not NULL
CSCO_ID	NUMBER	30		N
CSCO_XCOU_ID	NUMBER	30		N
CSCO_CSHP_ID	NUMBER	30		N

## CSHC

Shiping charge price configuration

Field Name	Type	Length	Decimals	Not NULL
CSHC_ID	NUMBER	30		N
CSHC_CSHP_ID	NUMBER	30		N
CSHC_ZDCO_ID	NUMBER	30		N
CSHC_PRICE	NUMBER	30	4	Y

### CSHP

Shipping charge types configuration

Field Name	Type	Length	Decimals	Not NULL
CSHP_ID	NUMBER	30		N
CSHP_NAME	VARCHAR2	300		N
CSHP_WEBENABLED	NUMBER	1		Y
CSHP_WEBDESCRIPTION	VARCHAR2	300		Y
CSHP_FOLIODESCRIPTION	VARCHAR2	300		Y
CSHP_FREEWHENTOTALMORE	NUMBER	30	4	Y
CSHP_ROLE	NUMBER	2		Y
CSHP_INSTANTPAYMENT	NUMBER	1		Y
CSHP_DISPLORDER	NUMBER	4		Y

### FPLD

MF pos price level definition

Field Name	Type	Length	Decimals	Not NULL	
FPLD_ID	NUMBER	30		N	
FPLD_SHORTDESC	VARCHAR2	3		N	
FPLD_LONGDESC	VARCHAR2	30		N	
FPLD_DISPLAYORDER	NUMBER	5		N	
FPLD_ROLE	NUMBER	1		N	role can be 1 = follower, 2 = stand alone
FPLD_INACTIVE	NUMBER	1		Y	
FPLD_VALIDFROM	DATE			Y	
FPLD_VALIDUNTIL	DATE			Y	

### FPLI

MF pos price level item link

Field Name	Type	Length	Decimals	Not NULL	
FPLI_ID	NUMBER	30		N	
FPLI_FPLD_ID	NUMBER	30		N	
FPLI_YOUT_ID	NUMBER	30		Y	
FPLI_YCMI_ID	NUMBER	30		Y	
FPLI_PRICE	NUMBER	30	4	Y	
FPLI_EXCLUDE	NUMBER	1		Y	if set, this article is not sold when this level is active
FPLI_FLEX	NUMBER	1		N	if set, the price can be overwritten by waiter

### FPLI

MF pos price level item link

Field Name	Type	Length	Decimals	Not NULL
FPLI_VALIDFROM	DATE			Y
FPLI_VALIDUNTIL	DATE			Y

### FPLS

MF pos price level sales item link

Field Name	Type	Length	Decimals	Not NULL	
FPLS_ID	NUMBER	30		N	
FPLS_FPLD_ID	NUMBER	30		N	
FPLS_YOUT_ID	NUMBER	30		Y	
FPLS_YSME_ID	NUMBER	30		Y	
FPLS_PRICE	NUMBER	30	4	N	
FPLS_EXCLUDE	NUMBER	1		Y	if set, this sales menu item is not sold when this level is active
FPLS_FLEX	NUMBER	1		N	if set, the price can be overwritten by waiter

### GHAA

Alternate storage for profile addresses xadr table

Field Name	Type	Length	Decimals	Not NULL
GHAA_ID	NUMBER	30		N
GHAA_STREET1	VARCHAR2	60		Y
GHAA_STREET2	VARCHAR2	60		Y
GHAA_STREET3	VARCHAR2	60		Y
GHAA_ZIP	VARCHAR2	15		Y
GHAA_CITY	VARCHAR2	60		Y
LASTMODIFIED	DATE			Y

### GHAD

Alternate storage for individual profiles xcid table

Field Name	Type	Length	Decimals	Not NULL
GHAD_ID	NUMBER	30		N
GHAD_TITLE	VARCHAR2	30		Y
GHAD_ADDRGREET	VARCHAR2	30		Y
GHAD_LETTGREET	VARCHAR2	60		Y

### GHAD

Alternate storage for individual profiles xcid table

Field Name	Type	Length	Decimals	Not NULL
LASTMODIFIED	DATE			Y

### GHAG

Alternate storage for profile xcms table

Field Name	Type	Length	Decimals	Not NULL
GHAG_ID	NUMBER	30		N
GHAG_WLAN_ID	NUMBER	30		Y
GHAG_NAME1	VARCHAR2	35		Y
GHAG_NAME2	VARCHAR2	35		Y
GHAG_NAME3	VARCHAR2	35		Y
LASTMODIFIED	DATE			Y

### IACC

Account\_Posting\_Table

Field Name	Type	Length	Decimals	Not NULL	
IACC_ID	NUMBER	30		N	IACC_ID identifies IACC
IACC_ICFG_ID	NUMBER	30		N	Link to the Interface ID in ICFG.ICFG_ID
IACC_IDCO_POST_TYPE	VARCHAR2	3		Y	the DepartmentCode selection POST_TYPE in IDCO for this Payment.
IACC_PAY_METH	VARCHAR2	30		Y	the PayMethod selector
IACC_LONGDESC	VARCHAR2	30		Y	Text field for explanations, which the installer may want to add manually.
IACC_SAL_OUTL	VARCHAR2	128		Y	the SalesOutlet selector
IACC_DEST_TYPE	NUMBER	1		Y	the type of the IACC_DEST_ID IRMS_ID=-1 (don't use) YRMS_ID=0 ZFAC_ID=1
IACC_DEST_ID	NUMBER	30		Y	the RoomNum ID (reference to Destination ID selection by DEST_TYPE: IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1)

### IACT

CommandTable(ex IFC\_ACT->cmd\_valid))

Field Name	Type	Length	Decimals	Not NULL	
IACT_ID	NUMBER	30		N	IACT_ID identifies IACT
IACT_ICFG_ID	NUMBER	30		N	IACT_ICFG_ID is of IACT
IACT_ACT_NAME	VARCHAR2	64		Y	the ActionName
IACT_DATE	DATE			Y	the TimeStamp
IACT_PRIOR	NUMBER	2		Y	the Priority

### IACT

CommandTable(ex IFC\_ACT->cmd\_valid))

Field Name	Type	Length	Decimals	Not NULL	
IACT_SRC_IP	VARCHAR2	20		Y	the FO_WS IP address
IACT_SRC_NAME	VARCHAR2	64		Y	the FO-WS ComputerName
IACT_DATA	LONG			Y	the XmlAction

### ICFG

Global\_Config\_Table(ex IFC\_CTRL, I)=PMS-related configuration

Field Name	Type	Length	Decimals	Not NULL	
ICFG_ID	NUMBER	30		N	ICFG_ID identifies ICFG
ICFG_HOTEL_ID	NUMBER	30		N	ICFG_HOTEL_ID, Check size and handling with FO Applications
ICFG_ZCAS_ID	NUMBER	30		N	the FO-CashierNumber (ZCAS_ID)
ICFG_ACTIVE	NUMBER	1		N	1 = true 0 = false
ICFG_TYPE	VARCHAR2	3		N	PBX = Telephone Managment System POS = Point of Sale DLS = Door Locking Sytem VID = Video System MBS = Minibar / Vendor Systems EMS = Building / Energy Managment Systems WWW = Internet Systems MSC = Misc. Systems
ICFG_STATUS	NUMBER	1		Y	Possible Status: -2 = LinkEnd -1 = LinkStart
ICFG_VERS	VARCHAR2	20		Y	0 = LinkAlive IFC8 Version Information
ICFG_LONGDESC	VARCHAR2	30		Y	Interface name (text field for explanations, which the installer may want to add manually).
ICFG_ZDCO_ID	NUMBER	30		N	the DepartmentCode ID (reference to FO database)
ICFG_CMD_CHK	NUMBER	2		Y	send Check-IN/OUT commands 4 = send new NameDisplay upon sharer GuestOut via GuestdataChange 2 = send RoomEquipment 1 = send GuestIn/Out 0 = false
ICFG_CMD_RM	NUMBER	2		Y	is RoomMove active (send a GuestChange instate of Chk-In/Out) 1 = true 0 = false
ICFG_CMD_MSG	NUMBER	2		Y	is MessageHandling active ? 0 = false 1 = MessLight 2 = MessText 4 = VoiceMail
ICFG_CMD_WAK	NUMBER	10		Y	is WakeUp active ? 2 = true (external) 1 = true (internal) 0 = false
ICFG_CMD_VN	NUMBER	2		Y	is VirtualNumber active ? 1 = true 0 = false
ICFG_CMD_CC	NUMBER	2		Y	CreditCard commands active ? 1 = true 0 = false
ICFG_CMD_KEY	NUMBER	2		Y	MakeKey commands active ? 1 = true 0 = false
ICFG_CMD_NA	NUMBER	2		Y	is NightAudit command active ? 1 = true 0 = false
ICFG_CMD_BIL	NUMBER	2		Y	BillView commands active ? 2 = true (Online Update) 1 = true (Request Mode) 0 = false
ICFG_START_DATE	DATE			Y	START_DATE of IFC
ICFG_DLS_TYP	NUMBER	1		Y	Dls_Type_Config(Keys are room or guest related) 1 = Guest 0 = Room
ICFG_ZERO_CRGE	NUMBER	1		Y	post Zero Charges to account 0 = don't post ZeroCharges 1 = post ZeroCharges
ICFG_INT_SPLT	NUMBER	1		Y	enable the internal split feature
ICFG_FKT_LOGO	VARCHAR2	20		Y	the Fkt-Logo for DBS configuration

### ICRD

Table for sent KeyRequest Actions

Field Name	Type	Length	Decimals	Not NULL	
ICRD_ID	NUMBER	30		N	ICRD_ID identifies ICRD
ICRD_ICFG_ID	NUMBER	30		N	ICRD_ICFG_ID is of ICRD
ICRD_DEST_ID	NUMBER	30		Y	the RoomNum ID (reference to Destination ID selection by DEST_TYPE: IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1
ICRD_DEST_TYPE	NUMBER	1		Y	the type of the ICRD_DEST_ID IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1
ICRD_ACTIVE	NUMBER	1		Y	DisCard is 0=NotActive 1=Active
ICRD_ANSWERSTAT	VARCHAR2	2		Y	AnswerStat for this KeyRequest
ICRD_YRES_ID	NUMBER	30		Y	ICRD_YRES_ID is of ICRD
ICRD_XCMS_ID	NUMBER	30		Y	ICRD_XCMS_ID is of ICRD
ICRD_KEYTYPE	VARCHAR2	1		Y	""D""=DuplicateKey "N"=NewKey 'O'=OneShotKey
ICRD_KEYOPTIONS	VARCHAR2	20		Y	KeyOptions for this Card
ICRD_SUITEINFO	VARCHAR2	128		Y	the SuiteInfo for this key
ICRD_TRACK1	VARCHAR2	64		Y	TRACK1 data
ICRD_TRACK2	VARCHAR2	64		Y	TRACK2 data
ICRD_TRACK3	LONG			Y	TRACK2 data
ICRD_DATE	DATE			Y	TimeStamp for creating this Card
ICRD_SEQ_NUM	NUMBER	3		Y	ICRD_SEQ_NUM is of ICRD
ICRD_USERID	VARCHAR2	64		Y	Key made/update by User
ICRD_WSNUM	VARCHAR2	64		Y	Key made/update via WsNum
ICRD_GN_FRM	VARCHAR2	64		Y	the GuestFormattedname
ICRD_TRACK3_CHAR	VARCHAR2	256		Y	Track3 data as substring (special usage for PMS reporting)

### ICTD

TimeDiscountTable

Field Name	Type	Length	Decimals	Not NULL	
ICTD_ID	NUMBER	30		N	ICTD_ID identifies ICTD
ICTD_ICFG_ID	NUMBER	30		N	ICTD_ICFG_ID is of ICTD
ICTD_ICTT_ID	NUMBER	30		Y	the reffernce to the TarifGroup in ICTT
ICTD_DATE	VARCHAR2	10		Y	Date range information for discount calculations
ICTD_DAY	VARCHAR2	4		Y	Day range information for discount calculations
ICTD_TIME	VARCHAR2	10		Y	Time range information for discount calculations
ICTD_DISC	NUMBER	3		Y	Multiplicator for discount calculations

### ICTD

TimeDiscountTable

Field Name	Type	Length	Decimals	Not NULL	
ICTD_LONGDESC	VARCHAR2	64		Y	ICTD_LONGDESC is of ICTD

### ICTS

Group\_Type\_Translation(ex ???CT\_S)

Field Name	Type	Length	Decimals	Not NULL	
ICTS_ID	NUMBER	30		N	ICTS_ID identifies ICTS
ICTS_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
ICTS_ICTT_ID	NUMBER	30		Y	the refference to the TarifGroup in ICTT
ICTS_EXT_TYPE	VARCHAR2	3		Y	the Type of Extension (ex IFC_ROOM.Type "R"/"B"/"H")
ICTS_VIP	NUMBER	3		Y	VIP code selector
ICTS_CAS_TYPE	NUMBER	1		Y	the CallAccounting overwrite type: 0=NULL = don't calculate with CallAccounting 1 = calculate with CallAccounting if TotalAmount=0 2 = calculate with CallAccounting if Units(MeterPulse)=0 3 = calculate with CallAccounting if TotalAmount=0 AND Units(MeterPulse)=0 4 = calculate always with CallAccounting
ICTS_CAS_TRUNK	VARCHAR2	20		Y	CallAccounting; calculate based on TrunkId (PostRoute attribute)
ICTS_CAS_PRFX	VARCHAR2	4		Y	access code for external line as received from the PBX
ICTS_CAS_DIAL	VARCHAR2	10		Y	the DialPrefix for CallAccounting
ICTS_CAS_TIME	NUMBER	10	5	Y	CallAccounting: the time for one unit(MeterPulse) in sec.
ICTS_CAS_GRACE	NUMBER	10	5	Y	CallAccounting Grace period: if negativ> the grace period will be always subtracted from the call Duration if positiv> the Call will be posted with the full Duration time if the Duration > ICTS_CAS_GRACE
ICTS_PCAS_PRICE	NUMBER	10		Y	the Price for PartialCallAccounting
ICTS_LONGDESC	VARCHAR2	30		Y	ICTS_LONGDESC is of ICTS

### ICTT

Unit\_Group\_Translation(ex ???\_CT\_T)

Field Name	Type	Length	Decimals	Not NULL	
ICTT_ID	NUMBER	30		N	ICTT_ID identifies ICTT
ICTT_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
ICTT_UNIT_0	NUMBER	10		N	UnitNumber from 0 up to ... (use -1 for all)
ICTT_PRICE_0	NUMBER	30		N	UnitPrice for UnitNumber from 0 up to ICTT_UNIT_0
ICTT_UNIT_1	NUMBER	10		Y	UnitNumber from ICTT_UNIT_0 up to ... (use -1 for all)
ICTT_PRICE_1	NUMBER	30		Y	UnitPrice from ICTT_UNIT_0 up to ICTT_UNIT_1
ICTT_UNIT_2	NUMBER	10		Y	UnitNumber from ICTT_UNIT_1 up to ... (use -1 for all)

### ICTT

Unit\_Group\_Translation(ex ???\_CT\_T)

Field Name	Type	Length	Decimals	Not NULL	
ICTT_PRICE_2	NUMBER	30		Y	UnitPrice from ICTT_UNIT_1 up to ICTT_UNIT_2
ICTT_UNIT_3	NUMBER	10		Y	UnitNumber from 0 up to ... (use -1 for all)
ICTT_PRICE_3	NUMBER	30		Y	UnitPrice from ICTT_UNIT_2 up to ICTT_UNIT_3
ICTT_UNIT_4	NUMBER	10		Y	UnitNumber from 0 up to ... (use -1 for all)
ICTT_PRICE_4	NUMBER	30		Y	UnitPrice from ICTT_UNIT_3 up to ICTT_UNIT_4
ICTT_UNIT_5	NUMBER	10		Y	UnitNumber from 0 up to ... (use -1 for all)
ICTT_PRICE_5	NUMBER	30		Y	UnitPrice from ICTT_UNIT_4 up to ICTT_UNIT_5
ICTT_UNIT_6	NUMBER	10		Y	UnitNumber from 0 up to ... (use -1 for all)
ICTT_PRICE_6	NUMBER	30		Y	UnitPrice from ICTT_UNIT_5 up to ICTT_UNIT_6
ICTT_INT_SPLT	VARCHAR2	128		Y	define the internal split for the current tariff (ICFG_INT_SPLT must be enabled)
ICTT_LONGDESC	VARCHAR2	30		Y	ICTT_LONGDESC is of ICTT

### IDCO

DepartmentCode\_Translation (ex ???\_DC)

Field Name	Type	Length	Decimals	Not NULL	
IDCO_ID	NUMBER	30		N	IDCO_ID identifies IDCO
IDCO_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IDCO_ZDCO_ID	NUMBER	30		N	the DepartmentCode ID (reference to FO database)
IDCO_PSAC_ID	NUMBER	30		Y	the PMS AccessPoint identifier for AreaAccess handling
IDCO_LONGDESC	VARCHAR2	30		Y	Text field for explanations, which the installer may want to add manually.
IDCO_MULTI	NUMBER	10	5	Y	if selection by SalesItem(IDCO_SUB_TTL)) then multiply the Item with IDCO_MULTI
IDCO_POST_TYPE	VARCHAR2	3		Y	the DC-SplittCod
IDCO_EXT_TYPE	VARCHAR2	8		Y	the DC-SplittCod
IDCO_SUB_TTL	VARCHAR2	8		Y	the DC-SplittCod> by SalesItem use "S1" ... "S63" for SubTotal1...63 use "T1" ... "T63" for TaxTotal1...63 use "D1" ... "D63" for DiscountTotal1...63 use "C1" ... "C63" for SeviceChargeTotal1...63 use "X1" for Tip use "DF" for differences
IDCO_SAL_OUTL	VARCHAR2	8		Y	the DC-SplittCod> by SalesOutlet (RevenueCenter)
IDCO_SERV_TIME	VARCHAR2	8		Y	the DC-SplittCod> by ServingTime (ServingPeriod)
IDCO_DIAL_NUM	VARCHAR2	8		Y	the DC-SplittCod> by Dialed Number (-prefix) def. as Char.-Field if we get alphanumeric info from Vendor
IDCO_ROUTE	VARCHAR2	8		Y	the DC-SplittCod> by PostRoute info (e.g. Trunk-Id)
IDCO_USER_ID	VARCHAR2	8		Y	the DC-SplittCod> by UserID (i.e. Waiter)
IDCO_WS_NUM	VARCHAR2	8		Y	the DC-SplittCod> by WorkStationNumber (Terminal-Id)

### IDCO

DepartmentCode\_Translation (ex ???\_DC)

Field Name	Type	Length	Decimals	Not NULL	
IDCO_VIP	NUMBER	3		Y	the DC-SplittCod> by VIP code
IDCO_CALL_TYPE	VARCHAR2	8		Y	the DC-SplittCod> by PostCalltype info (e.g. int./nat./loc.)

### IDLR

KeyOption Translation (build the Xml-"KeyOption" Attribute value by XPDA\_IFC\_CODE as Ref.)

Field Name	Type	Length	Decimals	Not NULL	
IDLR_ID	NUMBER	30		N	IDLR_ID identifies IDLR
IDLR_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IDLR_PRIORITY	NUMBER	3		Y	the Priority of the IDLR_KEY_CODE_VAL if the IDLR_KEY_CODE_POS is equal.
IDLR_XPDA_IFC_CODE	NUMBER	2		Y	the IfcKeyCode received from the FO-WS
IDLR_KEY_CODE_POS	NUMBER	2		Y	the character position in the XmlKeyCode-Attr. (AN,20)
IDLR_KEY_CODE_VAL	VARCHAR2	1		Y	the value of the character in XmlKeyCode-Attr.
IDLR_LONGDESC	VARCHAR2	30		Y	Text field for explanations, which the installer may want to add manually.

### IDMP

WS\_Encoder\_Translation

Field Name	Type	Length	Decimals	Not NULL	
IDMP_ID	NUMBER	30		N	IDMP_ID identifies IDMP
IDMP_ICFG_ID	NUMBER	30		N	Link to the Interface ID in ICF.ICFG_ID
IDMP_PMS_WS	VARCHAR2	30		Y	the FO-WS PC-Name
IDMP_DLS_ID	VARCHAR2	30		Y	EncoderIDof the eencoder, which is next to the "source"-PMMS workstation
IDMP_LONGDESC	VARCHAR2	30		Y	Text field for explanations, which the installer may want to add manually.

### IDRF

definition table for Xml-Attributes DefRef(0...15) by ActionType in ACT\_TYPE (if ACT\_TYPE=NULL use for all ActionTypes) Note! DefRef(0) is reserved for XCMS\_ID

Field Name	Type	Length	Decimals	Not NULL	
IDRF_ID	NUMBER	30		N	IDRF_ID identifies IDRF
IDRF_ICFG_ID	NUMBER	30		N	Link to the Interface ID in ICFG_ID
IDRF_VIEW_NAME	VARCHAR2	30		N	View name, from which IFC will read the requested value. Currently ONLY V8_IFC_RESERVATIONSEARCH is supported. DO NOT alter this view !! Altering the view will breal most Interface functionality and will seriously slow down the database.
IDRF_CONDITION	LONG			Y	Used to enter the requested FieldNames/Separators for V8_IFC_RESERVATIONSEARCH or SQL-Condition for all other views

### IDRF

definition table for Xml-Attributes DefRef(0...15) by ActionType in ACT\_TYPE (if ACT\_TYPE=NULL use for all ActionTypes) Note!  
 DefRef(0) is reserved for XCMS\_ID

Field Name	Type	Length	Decimals	Not NULL	
IDRF_LONGDESC	VARCHAR2	64		Y	Text field for explanations, which the installer may want to add manually.

### IDRV

Driver\_Config\_Table(ex IFC\_CTRL )=IFC-related configuration

Field Name	Type	Length	Decimals	Not NULL	
IDRV_ID	NUMBER	30		N	IDRV_ID identifies IDRV
IDRV_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IDRV_FEATURES	VARCHAR2	256		Y	special Driver features: "TaxEx"=Posting with TaxExclude "NoDiffCheck"=DifferenceCheck for Posting disabled (no Autobalance) "NoDiffPost"=deny Posting with difference (not with "NoDiffCheck") "PosPagePl"=continue the PostListItems once "MaximumGuestsNum" was reached.
IDRV_IHST	NUMBER	3		Y	send charges to Callhist(IHST) ? 0 = false 1 = true / set HoldDays to default (60 days) 2...999 = true / days to hold the Postings in IHST
IDRV_IDCO_SELECT	VARCHAR2	20		Y	the rules for DC selection in IDCO if empty use default DC in ICFG "P" by PostType "E" by ExtentionType (def. in IRMS) "I" by SalesItem (SubTotal/Discount/Tax/ServiceCharge/Tip) "O" by SalesOutlet (revenue center) "D" by DialedDigits "R" by PostRoute (Truk-ID) "T" by ServingTime "U" by UserID (waiter) "W" by WsNum (terminal ID) "V" by Vip code
IDRV_POST_TYPE	VARCHAR2	3		Y	the rules for a posting with more then one possibilities. This will be override the PostType-Attrs. ("T"/"C"/"M") in the posting XML-record: IDRV_POST_TYPE=empty -> use the PostType-Attr from XML-record IDRV_POST_TYPE="T" -> post with MeterPulse if possible IDRV_POST_TYPE="C" -> post with TotalAmount if possible IDRV_POST_TYPE="CT" -> first try TotalAmount then MeterPulse
IDRV_ACCT_TYPE	NUMBER	1		Y	Account Posting Configuration (ex Feature 14) 1 = true 2 = true (with auto balancing) 0 = false
IDRV_NO_POST	NUMBER	1		Y	is NoPost active (bar command send, if NoPost is active) ? 1 = true 0 = false
IDRV_AN_PREF	VARCHAR2	10		Y	the ArticleNumber prefix (i.e. for minibar posting by ArtNum)
IDRV_CREDLMT	NUMBER	1		Y	CreditLimit check configuration 0= no CreditLimit check 1...9= CreditLimit check
IDRV_VM_NOTIFY	NUMBER	1		Y	Get notification upon VM-event 0 = no 1 = as MessageLightstatus 2 = as GuestMess (text) 3 = as GuestMess (text) and MessageLightstatus
IDRV_VCKO	NUMBER	1		Y	is Video Check Out active ? 2 = true (allow RemoteChko on event EFT_RESULT) 1 = true (allow RemoteChko on event FO_RESULT) 0 = false
IDRV_FO_CARD	NUMBER	1		Y	activate FO_CARD table (currently not used) 1 = true 0 = false
IDRV_VIP_CT	NUMBER	1		Y	use VIP-Code for charging 1 = true 0 = false
IDRV_TR2_NUM	NUMBER	10		Y	Track2 type definition: 0 = Track2-function disabled 1 = Track2 PMS-Standard format (HotelId[1]/RoomNum[7]/ResNum[8]) 2 = Track2 user definable format (IDRF) 4 = get Track2 info from vendor (IDRF)
IDRV_CAS	NUMBER	1		Y	is CallAccounting active ? 1 = PartialCallAccounting 2 = FullCallAccounting 0 = false

### IDRV

Driver\_Config\_Table(ex IFC\_CTRL )=IFC-related configuration

Field Name	Type	Length	Decimals	Not NULL	
IDRV_WAK_RETNUM	NUMBER	3		Y	Number of WakeRetrys
IDRV_WAK_RETTIME	NUMBER	10		Y	Time between WakeupRetrys
IDRV_DIAL_MSK	NUMBER	2		Y	the number of digits which should masked in DialedDigits (this will be ignored if any other IRMS_DIAL_MSK defined for an current ExtensionNumber)
IDRV_YRES_PRFX	VARCHAR2	30		Y	the current YRES_ID prefix for VendorActions
IDRV_YMES_PRFX	VARCHAR2	30		Y	the current YMES_ID prefix for VendorActions
IDRV_IRND_TYPE	NUMBER	1		Y	Round_up_or_down: 0 = don't use IRND / no rounding 1 = round ralway DOWN 2 = round alway UP 3 = round exactly (round 0.5 DOWN) 4 = round exactly (round 0.5 UP) 5 = round mathematical exactly (round 1.5 UP / round 2.5 DOWN)

### IERR

Error\_Message\_Table

Field Name	Type	Length	Decimals	Not NULL	
IERR_ID	NUMBER	30		N	IERR_ID identifies IERR
IERR_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IERR_ACT_TYPE	VARCHAR2	30		Y	the corresponding ActionType (e.g. "PostAnswer")
IERR_REQ_TYPE	NUMBER	5		Y	the corresponding ReqeType 1 =Post by PaymentMethod 2 =Post by Track2 4 =Post by RoomNum 8 =Post by GuestName 16=Post by GuestNum
IERR_ANS_STAT	VARCHAR2	2		Y	the corresponding AnswerStatus: Code / InterfaceType / Meaning "BM" / VSS / remote check-out / Balance mismatch "BY" / Wakeup / Key Services / Busy "CD" / VSS / remote check-out / Check-out date is not today "CO" / All PostingRequest Systems / Posting denied because overwrite CreditLimit is not allowed "DN" / EFT / Request denied "FX" / All systems / Guest related requests"Guest"not allowed this feature "IA" / All systems / Guest related requests"Invalid account "NA" / All systems / Night Audit "NF" / VSS / remote check-out / Feature not enabled or Check-Out process not running "NG" / All info requests / Guest not found "NM" / All Message systems / Message / Locator request Message / Locator not found "NP" / All PostingRequest Systems / Posting denied because NoPost is set "NR" / Wakeup / No Response "SV" / Wakeup / Sent to Vendor System "OK" / All systems / Command or request successful "RF" / EFT / Referral (pls. Call for Auth) "RY" / All systems / Retry "UR" / All requests / Unprocessable request, this request cannot be carried out, no retry "DE" / Wakeup / WakeUp is deleted
IERR_TXT_DEF	VARCHAR2	64		Y	the ClearText definition
IERR_LONGDESC	VARCHAR2	30		Y	IERR_LONGDESC is of IERR

### IGST

GuestData which sent to VendorSystem

Field Name	Type	Length	Decimals	Not NULL	
IGST_ID	NUMBER	30		N	IGST_ID identifies IGST
IGST_ICFG_ID	NUMBER	30		N	IGST_ICFG_ID is of IGST
IGST_IRMS_ID	NUMBER	30		N	Link-ID to IRMS
IGST_YRES_ID	NUMBER	30		Y	the GuestNumber (FO ReservationNumber=YRES_ID)
IGST_XCMS_ID	NUMBER	30		Y	the FO-GuestNum sent with "DefRef0"-Attr.
IGST_CHKIN	NUMBER	1		Y	the Interface CheckIn state 0=False 1=True
IGST_VIP	NUMBER	3		Y	the VIP-status
IGST_GN	VARCHAR2	35		Y	the GuestName
IGST_GN_FRM	VARCHAR2	64		Y	the GuestFormattedname
IGST_GL	VARCHAR2	3		Y	the GuestLanguage
IGST_SHARE	VARCHAR2	1		Y	the ShareFlag
IGST_SWAP_NUM	NUMBER	30		Y	IGST_SWAP_NUM is of IGST

### IHST

Call\_History\_Table(needed because FO does not manage admin extensions)

Field Name	Type	Length	Decimals	Not NULL	
IHST_ID	NUMBER	30		N	IHST_ID identifies IHST
IHST_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IHST_DEST_ID	NUMBER	30		Y	RoomNum ID (reference to FO database i.e. YRMS_ID) for this Posting
IHST_DEST_TYPE	NUMBER	1		Y	the type of the IRMS_DEST_ID IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1
IHST_EXT_NUM	VARCHAR2	20		Y	the ExtensionNumber (ex Line_Num)
IHST_DATE	DATE			Y	the third party Date- -stamp
IHST_DATE_POST	DATE			Y	the IFC posting Date- -stamp
IHST_LENGTH	VARCHAR2	8		Y	the Length of Call (hh:mm:ss)
IHST_DIAL_NUM	VARCHAR2	30		Y	the Dialed Number (def. as Char-Field for other Supplement-Infos)
IHST_CHARGE	NUMBER	30		Y	the charge of the call
IHST_UNITS	NUMBER	30		Y	Number of telephone units
IHST_ZDCO_ID	NUMBER	30		Y	the DepartmentCode_ID (posted by IFC)
IHST_GUEST_ID	NUMBER	30		Y	the Guest-ID (FO)
IHST_POST_ID	NUMBER	30		Y	the Account-ID(FO) of this Call
IHST_ANSW_STAT	VARCHAR2	3		Y	the AnswerStatus from FO
IHST_EXT_TYPE	VARCHAR2	3		Y	Extension Type (e.g. H = House, R = Room etc)

### IHST

Call\_History\_Table(needed because FO does not manage admin extensions)

Field Name	Type	Length	Decimals	Not NULL	
IHST_TYPE_INFO	VARCHAR2	10		Y	the PostType info (IFC- and PMS- PostType): i.e. "C->T" means a IFC-PostType=charge which is in PMS posted as a MeterPulseType
IHST_TRUNK	VARCHAR2	8		Y	Trunk ID from the Telephone system
IHST_CAS_INFO	VARCHAR2	35		Y	Additional info from Full Call Accounting: [ICTS_ID]/[ICTS_CAS_DIAL]
IHST_CHECK_NUM	VARCHAR2	20		Y	the GuestCheck number
IHST_SUPPL_DEF	VARCHAR2	60		Y	the Supplement text (sent to FO)
IHST_PMS_INVISIBLE	NUMBER	1		Y	Defines if a posting was sent to PMS as visible or not. 0 = visible    1 = invisible on bill    2 = invisible on reports 3 = invisible on both bills and reports

### ILAN

Language\_Translation

Field Name	Type	Length	Decimals	Not NULL	
ILAN_ID	NUMBER	30		N	ILAN_ID identifies ILAN
ILAN_PMS	VARCHAR2	8		Y	Language as configured in the PMS.
ILAN_IFC	VARCHAR2	8		Y	Language as per XML-definition: (e.g. EA, GR, FR, SP etc)
ILAN_LONGDESC	VARCHAR2	30		Y	Text field for explanations, which the installer may want to add manually.

### IMSQ

the definition of (MSMQ) message queues for FO-WS -Server

Field Name	Type	Length	Decimals	Not NULL	
IMSQ_ID	NUMBER	30		N	IMSQ_ID identifies IMSQ
IMSQ_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IMSQ_PORT	NUMBER	4		Y	the MsqType: 0 = MSMQ    1...9999 = TcpMqPort
IMSQ_MQ_NAME	VARCHAR2	30		Y	the NAME of the MsQueue without the "IFC" or "PMS" prefix
IMSQ_PC_IFC	VARCHAR2	64		Y	the IFC_SERV computer name (MSQ-FormatName)
IMSQ_AUTH	VARCHAR2	64		Y	IFC8 connection authorization information

### IPOL

the PoolId definition by IRMS\_EXT\_TYPE

Field Name	Type	Length	Decimals	Not NULL	
IPOL_ID	NUMBER	30		N	IPOL_ID identifies IPOL
IPOL_ICFG_ID	NUMBER	30		N	IPOL_ICFG_ID is of IPOL
IPOL_EXT_TYPE	VARCHAR2	3		Y	IPOL_EXT_TYPE is of IPOL

## IPOL

the PoolId definition by IRMS\_EXT\_TYPE

Field Name	Type	Length	Decimals	Not NULL	
IPOL_POOL_INFO	VARCHAR2	64		Y	supported Pool-Ids for this extension type (use " " as separator)
IPOL_LONGDESC	VARCHAR2	30		Y	IPOL_LONGDESC is of IPOL

## IPRN

IFC\_Printer

Field Name	Type	Length	Decimals	Not NULL	
IPRN_ID	NUMBER	30		N	IPRN_ID identifies IPRN
IPRN_ICFG_ID	NUMBER	30		N	Link to the Interface ID in ICF.ICFG_ID
IPRN_PMS_WS	VARCHAR2	30		Y	the FO-WS PC-Name
IPRN_ACT_TYPE	VARCHAR2	30		Y	the corresponding ActionType (e.g. "RoomEquipment")
IPRN_PRN_NAME	VARCHAR2	256		Y	the selected printer name
IPRN_TRAY	NUMBER	4		Y	the used PaperTray for the selected Printer
IPRN_FRM	NUMBER	4		Y	Format options for the selected Printer
IPRN_SIZE	NUMBER	4		Y	the PageSize for the selected Printer
IPRN_DATA	LONG			Y	IPRN_DATA is of IPRN

## IRMS

Extension\_Translation\_Config, (ex IFC\_ROOM)

Field Name	Type	Length	Decimals	Not NULL	
IRMS_ID	NUMBER	30		N	IRMS_ID identifies IRMS
IRMS_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
IRMS_IO	NUMBER	1		Y	Extension In-/Out-Flag 0= for both 2= only for outgoing commands 1= only for incoming commands
IRMS_DEST_ID	NUMBER	30		N	the RoomNum ID (reference to Destination ID selection by DEST_TYPE: IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1
IRMS_DEST_TYPE	NUMBER	1		N	the type of the IRMS_DEST_ID IRMS_ID=-1 YRMS_ID=0 ZFAC_ID=1
IRMS_SHORTDESC	VARCHAR2	20		Y	the ShortDescription of the RommNumber if DEST_TYPE= -1
IRMS_EXT_NUM	VARCHAR2	20		Y	the Extension number
IRMS_EXT_TYPE	VARCHAR2	3		Y	the Type of Extension (ex IFC_ROOM.Type "R"/"B"/"H")
IRMS_ST_COS	VARCHAR2	3		Y	the ClassOfService Status: 0= off 1...9= on (other)
IRMS_AL_COS	NUMBER	1		Y	Extension Status change for COS Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_ML	VARCHAR2	3		Y	the MessageLightstatus: 0= off 1...9= on (other)

### IRMS

Extension\_Translation\_Config, (ex IFC\_ROOM)

Field Name	Type	Length	Decimals	Not NULL	
IRMS_AL_ML	NUMBER	1		Y	Extension Status change for ML Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_MR	VARCHAR2	3		Y	the MinibarRights: 0= off 1...9= on (other)
IRMS_AL_MR	NUMBER	1		Y	Extension Status change for MR Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_DND	VARCHAR2	3		Y	the DoNotDisturb Status 0= off 1...9= on (other)
IRMS_AL_DND	NUMBER	1		Y	Extension Status change for DND Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_VR	VARCHAR2	3		Y	the VideoRight Status 0= off 1...9= on (other)
IRMS_AL_VR	NUMBER	1		Y	Extension Status change for VR Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_TV	VARCHAR2	3		Y	the TVRight Status 0= off 1...9= on (other)
IRMS_AL_TV	NUMBER	1		Y	Extension Status change for TV Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_GR	VARCHAR2	3		Y	the GameRight Status 0= off 1...9= on (other)
IRMS_AL_GR	NUMBER	1		Y	Extension Status change for GR Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_ST_WWW	VARCHAR2	3		Y	the Internet Status 0= off 1...9= on (other)
IRMS_AL_WWW	NUMBER	1		Y	Extension Status change for WWW Allowed 0= not available / not allowed 1= available, allways ON 2= available, allways OFF 5= available, freely switchable
IRMS_AL_WAK	VARCHAR2	2		Y	Extension Status change for WakeUp Allowed 0= no WakeUp on this extension 5= available for all WakeUp types
IRMS_DIAL_MSK	NUMBER	2		Y	the number of digits which should masked in DialedDigits for the current ExtensionNumber
IRMS_ST_RS	VARCHAR2	3		Y	the last sent RoomStatus

### IRND

Rounding\_Rule\_Table

Field Name	Type	Length	Decimals	Not NULL	
IRND_ID	NUMBER	30		N	IRND_ID identifies IRND
IRND_ICFG_ID	NUMBER	30		N	IRND_ICFG_ID is of IRND
IRND_POST_TYPE	VARCHAR2	2		Y	select by PostType
IRND_EXT_TYPE	VARCHAR2	3		Y	select by ExtensionType
IRND_DIGITS	NUMBER	1		Y	the number of digits for rounding: 1 = round to 10 2 = round to 100 ... Etc.

### IRND

Rounding\_Rule\_Table

Field Name	Type	Length	Decimals	Not NULL	
IRND_PRECISION	NUMBER	3	2	Y	the rounding precision (IRND_PRECISION * IRND_DIGITS) e.g.: if IRND_PRECISION=1 - IRND_DIGITS =1 means round to the next 10 if IRND_PRECISION=5 - IRND_DIGITS =1 means round to the next 50
IRND_LONGDESC	VARCHAR2	64		Y	Text field for manual descriptions of this sepcific rounding method.

### ISCH

the LinkDescription and Schema table

Field Name	Type	Length	Decimals	Not NULL	
ISCH_ID	NUMBER	30		N	ISCH_ID identifies ISCH
ISCH_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
ISCH_NAME	VARCHAR2	30		Y	the NAME of the Schema
ISCH_DATA	LONG			Y	the LinkDescription or Schema content

### ISUP

Supplement text configuration (ex IFC\_CTRL.FLAG16) used for Fo PostingFunction

Field Name	Type	Length	Decimals	Not NULL	
ISUP_ID	NUMBER	30		N	ISUP_ID identifies ISUP
ISUP_ICFG_ID	NUMBER	30		N	Link-ID to ICFG
ISUP_FIELD	VARCHAR2	8		Y	the SupplementInfo destination field. crrently support: [any other] = not active "TEL" = the TelNumber info in ZPOS "SUP" = the default supplement field in ZPOS
ISUP_TYPE	VARCHAR2	1		Y	used to select the right FO-PostType (not IFC_PostType may be is override by IDR_V_POST_TYPE): "M"=by "Minibar" article posting "C"=by "TotalAmount" charge posting "T"=by "MeterPulse" unit posting
ISUP_PREF_0	VARCHAR2	30		Y	First Prefix
ISUP_ATTR_0	VARCHAR2	30		Y	The XML-Attribute definition which which should be sent to supplement info text:
ISUP_PREF_1	VARCHAR2	30		Y	Second Prefix
ISUP_ATTR_1	VARCHAR2	30		Y	The XML-Attribute definition which which should be sent to supplement info text:
ISUP_PREF_2	VARCHAR2	30		Y	Third Prefix
ISUP_ATTR_2	VARCHAR2	30		Y	The XML-Attribute definition which which should be sent to supplement info text:
ISUP_PREF_3	VARCHAR2	30		Y	Fourth Prefix
ISUP_ATTR_3	VARCHAR2	30		Y	The XML-Attribute definition which which should be sent to supplement info text:
ISUP_PREF_4	VARCHAR2	30		Y	Fifth prefix
ISUP_ATTR_4	VARCHAR2	30		Y	The XML-Attribute definition which which should be sent to supplement info text:

### IWKC

WakeUp\_Config\_Table

Field Name	Type	Length	Decimals	Not NULL	
IWKC_ID	NUMBER	30		N	IWKC_ID identifies IWKC
IWKC_ICFG_ID	NUMBER	30		N	Link to the Interface ID in ICFG
IWKC_IRMS_ID	NUMBER	30		Y	Link to the extension in IRMS
IWKC_RESULT	VARCHAR2	3		Y	The WakeUp Result in AnswerStat format: "BY"= Busy "DN"= Request denied "NG"= Guest/Room not found "NR"= No Response from Vendor "SV"= Sent to Vendor System "OK"= Command or request successful "RY"= Retrys expired (No Response from Guest) "UR"= Unprocessable request, request cannot be carried out, no retry "DE"= WakeUp is deleted
IWKC_RESULT_DESC	VARCHAR2	128		Y	IWKC_RESULT_DESC is of IWKC
IWKC_LANG	VARCHAR2	30		Y	Wakeup Language (currently not supported)
IWKC_RES_DATE	DATE			Y	Date when the result for the wakeup was received
IWKC_SET_DATE	DATE			Y	Date on which the wakeup call was entered
IWKC_SET_USR	VARCHAR2	64		Y	User, which entered the wakeup call (if available)
IWKC_RES_USR	VARCHAR2	64		Y	User which sent/entered the result (if available)
IWKC_RETRY	NUMBER	1		Y	Number of retries for this wakeup
IWKC_START	DATE			Y	Wakeup Date and Time
IWKC_GRP_ID	VARCHAR2	30		Y	The GroupID (YRMS) (-> Not yet implemented)

### LMBG

Major Part Group definition

Field Name	Type	Length	Decimals	Not NULL	
LMBG_ID	NUMBER	30		N	
LMBG_SHORTDESC	VARCHAR2	10		Y	
LMBG_LONGDESC	VARCHAR2	200		Y	
LMBG_DISPLORDER	NUMBER	3		Y	

### LMGR

Family Group Definition

Field Name	Type	Length	Decimals	Not NULL	
LMGR_ID	NUMBER	30		N	
LMGR_SHORTDESC	VARCHAR2	10		Y	
LMGR_LONGDESC	VARCHAR2	200		Y	
LMGR_DISPLORDER	NUMBER	3		Y	

### LMGR

Family Group Definition

Field Name	Type	Length	Decimals	Not NULL	
LMGR_TYPE	NUMBER	1		Y	1 = Software, 2 = Hardware, 3 = Services
LMGR_IS_MAINPRODUCT	NUMBER	1		Y	
LMGR_LMBG_ID	NUMBER	30		Y	

### LPAR

Parts

Field Name	Type	Length	Decimals	Not NULL	
LPAR_ID	NUMBER	30		N	
LPAR_PARTNUMBER	VARCHAR2	200		Y	
LPAR_PRODUCTNAME	VARCHAR2	2000		Y	
LPAR_PRODUCTID	VARCHAR2	200		Y	
LPAR_LMGR_ID	NUMBER	30		Y	
LPAR_COMMERCIAL_COMMENT	VARCHAR2	2000		Y	
LPAR_TECHNICAL_COMMENT	VARCHAR2	2000		Y	
LPAR_CREATEDDATE	DATE			Y	
LPAR_CREATEDBY_XCMS_ID	NUMBER	30		Y	
LPAR_MODIFIEDDATE	DATE			Y	
LPAR_MODIFIEDBY_XCMS_ID	NUMBER	30		Y	
LPAR_VALIDUNTILDATE	DATE			Y	
LPAR_EXTERNAL_REFERENCED	NUMBER	1		Y	1 = Should be referenced to other systems (like oracle financial)
LPAR_EXTERNAL_REFERENCEDDATE	DATE			Y	Date when the reference to external system was established
LPAR_LSTA_ID	NUMBER	30		Y	Status link

### LPLP

Linkage of Parts to Pricelist

Field Name	Type	Length	Decimals	Not NULL	
LPLP_ID	NUMBER	30		N	
LPLP_LPAR_ID	NUMBER	30		N	
LPLP_LPRL_ID	NUMBER	30		N	
LPLP_VENDOR_ZCUR_ID	NUMBER	30		Y	
LPLP_VENDOR_BUYPRICE	NUMBER	30	4	Y	
LPLP_LOCAL_ZCUR_ID	NUMBER	30		Y	

### LPLP

Linkage of Parts to Pricelist

Field Name	Type	Length	Decimals	Not NULL
LPLP_LOCAL_BUYPRICE	NUMBER	30	4	Y
LPLP_ENTEREDIN_ZCUR_ID	NUMBER	30		Y
LPLP_TRANSFERPRICE	NUMBER	30	4	Y
LPLP_MSRP	NUMBER	30	4	Y
LPLP_PERCENTAGEMODIFIER	NUMBER	30	4	Y
LPLP_VALIDUNTILDATE	DATE			Y
LPLP_MODIFIEDDATE	DATE			Y
LPLP_MODIFIEDBY_XCMS_ID	NUMBER	30		Y

### LPRL

Price List

Field Name	Type	Length	Decimals	Not NULL
LPRL_ID	NUMBER	30		N
LPRL_SHORTDESC	VARCHAR2	5		Y
LPRL_LONGDESC	VARCHAR2	200		Y
LPRL_DEFAULT	NUMBER	1		Y
LPRL_DISPLORDER	NUMBER	30		Y

### LSTA

Status

Field Name	Type	Length	Decimals	Not NULL
LSTA_ID	NUMBER	30		N
LSTA_SHORTDESC	VARCHAR2	10		Y
LSTA_LONGDESC	VARCHAR2	200		Y
LSTA_DISPLORDER	NUMBER	3		Y

### MAVL

Default Room types and Rate Codes for Online Availabliltiy Requests

Field Name	Type	Length	Decimals	Not NULL	
MAVL_ID	NUMBER	30		N	Unique Identifier
MAVL_TYPE	VARCHAR2	2		N	RC for RateCodes and RT for RoomTypes
MAVL_CODE_ID	NUMBER	30		N	if MAVL_TYPE='RC' YRCH_ID and if MAVL_TYPE='RT' YCAT_ID

### MAVL

Default Room types and Rate Codes for Online Availabliltiy Requests

Field Name	Type	Length	Decimals	Not NULL	
MAVL_INACTIVE	NUMBER	1		Y	option to inactivate a code
MAVL_CUR_ID	NUMBER	30		Y	currency id for of rate code
MAVL_ZCNV_ID	NUMBER	30		Y	id to zcnv to link to mmod.
MAVL_UPLOAD_RATE	NUMBER	1		Y	indicates whether the rate code is used for rate upload
MAVL_UPLOAD_RAVL	NUMBER	1		Y	indicates whether the rate code is used for ravl upload

### MBIL

Table of MBIL

Field Name	Type	Length	Decimals	Not NULL	
MBIL_ID	NUMBER	30		N	Unique id of the record
MBIL_MMOD_ID	NUMBER	30		N	module id to which the BI belongs
MBIL_ZBIC_ID	NUMBER	30		N	link to zbic. Billing instruction
MBIL_ZFAC_ID	NUMBER	30		Y	link to zfac. Financel Account
MBIL_ROUTING_OPT	NUMBER	1		N	0=no routing, 1=routing to group's financel accounts, 2=routing to special financel account
MBIL_WINDOW	NUMBER	2		Y	MBIL_WINDOW is of MBIL
MBIL_ZBIC_SHORTDESC	VARCHAR2	3		Y	MBIL_ZBIC_SHORTDESC is of MBIL
MBIL_BITYPE	NUMBER	1		Y	1 = Same Room

### MCDE

mirror configuration data extract

Field Name	Type	Length	Decimals	Not NULL	
MCDE_ID	NUMBER	30		N	
MCDE_WPHS_ID	NUMBER	30		N	
MCDE_TABLENAME	CHAR			N	
MCDE_IDINMIRROR	NUMBER	30		N	
MCDE_SHORTDESC	VARCHAR2	10		N	
MCDE_LONGDESC	VARCHAR2	60		N	
MCDE_DISPLORDER	NUMBER	5		Y	
MCDE_INACTIVE	NUMBER	1		N	
MCDE_COMMENT	VARCHAR2	200		Y	
MCDE_OBSOLETE	NUMBER	1		Y	

## MCFG

Myfidelio Config

Field Name	Type	Length	Decimals	Not NULL	
MCFG_ID	NUMBER	30		N	Unique Id internal use
MCFG_DISP_LOGFILE	VARCHAR2	100		N	Log file for the dispatcher module
MCFG_DISP_LOGLEVEL	NUMBER	1		N	Log level of the dispatcher, 0=debug, 1=trace, 2=Warning, 3=Error, 4=system
MCFG_MSMQ_REQUEST_TIME	NUMBER	5		Y	Time schedule for polling in secs, default 2 sec's
MCFG_API_APPPATH	VARCHAR2	100		N	Application path of API.dll (MFNV8API.DLL)
MCFG_API_LOGFILE	VARCHAR2	100		Y	Log file of API module
MCFG_API_LOGLEVEL	NUMBER	1		N	Log Level, Default 3; 0=debug, 1=trace, 2=Warning, 3=Error, 4=system
MCFG_API_MODULENAME	VARCHAR2	100		N	Module name of the API dll, usually C:\Program Files\Micros-Fidelio\V8OnlineIfc\MFNV8API.DLL
MCFG_MAP_LOGFILE	VARCHAR2	100		Y	Log file for all mapper modules
MCFG_MAP_LOGLEVEL	NUMBER	1		N	0=debug, 1=trace, 2=Warning, 3=Error, 4=system
MCFG_LOGFILE_SIZE	NUMBER	5		N	Max Size of Logfile, valid for all log files
MCFG_READ_LOGFILE	VARCHAR2	100		Y	Name and Path of the log file for the Filereader
MCFG_READ_LOGLEVEL	NUMBER	1		Y	Log Level for Filereader
MCFG_READ_INTERVAL	NUMBER	5		Y	Time Interval to read the input directory
MCFG_BACKUP_PURGE_DAYS	NUMBER	2		N	MCFG_BACKUP_PURGE_DAYS is of MCFG
MCFG_READ_NO_FILES	NUMBER	2		Y	number of files read by filereader in one loop
MCFG_TR_MSMQ_EVENT	NUMBER	1		Y	2Way request queue event driven ?
MCFG_TR_MSMQ_REQUEST_TIME	NUMBER	5		Y	# of msec between 2 checks of the request queue if not event driven
MCFG_TR_REQUEST_QUEUE	VARCHAR2	30		Y	Name of the request queue for the 2way functionality
MCFG_HTTP_LOGFILE	VARCHAR2	100		Y	MCFG_HTTP_LOGFILE is of MCFG
MCFG_HTTP_LOGLEVEL	NUMBER	1		Y	MCFG_HTTP_LOGLEVEL is of MCFG
MCFG_HTTP_INTERVAL	NUMBER	5		Y	Time Interval for requesting internet
MCFG_TR_INTERVAL	NUMBER	5		Y	interval in secs to read trigger from V8
MCFG_HTTP_STATUS_INTERVAL	NUMBER	5		Y	Interval for sending status to ORS or other CRS
MCFG_HTTP_UPLOAD_INTERVAL	NUMBER	5		Y	Time interval for trigger upload
MCFG_DEBUG_MODE	NUMBER	1		Y	indicates, whether ifc runs with fidelio debug mode
MCFG_READ_TW_INTERVAL	NUMBER	5		Y	interval of uploading files by filereader
MCFG_2WDISP_LOGFILE	VARCHAR2	100		Y	Log file for the 2W dispatcher module
MCFG_2WDISP_LOGLEVEL	NUMBER	1		Y	Log level of the 2W dispatcher, 0=debug, 1=trace, 2=Message, 3=Warning, 4=Error, 5=system, 6=fatal
MCFG_TRR_LOGFILE	VARCHAR2	100		Y	Log file for the trigger reader module
MCFG_TRR_LOGLEVEL	NUMBER	1		Y	Log level of the trigger reader, 0=debug, 1=trace, 2=Message, 3=Warning, 4=Error, 5=system, 6=fatal
MCFG_MLOG_PURGE_DAYS	NUMBER	2		Y	number of days to purge mlog
MCFG_SVC_MAX_MEM	NUMBER	4		Y	Indicates the maximum memory amount a service can use before the monitor restarts the service

### MCFG

Myfidelio Config

Field Name	Type	Length	Decimals	Not NULL	
MCFG_MON_LOGLEVEL	NUMBER	1		Y	logging level for the interface monitor
MCFG_MASTER	NUMBER	1		Y	indicates the master hotel

### MCNV

Conversion Table

Field Name	Type	Length	Decimals	Not NULL	
MCNV_ID	NUMBER	30		N	Unique Identifier
MCNV_TYPE	VARCHAR2	3		N	RC= rate code, RT= room type, MC= market code, SC= source code, CH= channel, GT= guarantee type, PM= payment method, CC= credit card, CO= country, ST= state, CU= currency, LA= language, BC= block code, SP= specials, FE= features, CR= cancellation reason, DO= document type, CT= card type, AT= address type, CM= communication type, SA= Salutation codes, PA= Packages, II= Inventory Items, AL= Airlines, PT= Pickup types, RA= rate category, used for OXI rate code request, CA= child age category, VC= VIP code, DC= Department code, used for OXI rate code request, WL= Waitlist reason, NA= nationality, BI= Billing Instructions -> this is not yet an conversion type, NT= Note Types, BS= Block Status, CD= Commission Code, TR= Traces, X0= user defined type, X1= user defined type, X2= user defined type, X3= user defined type, X4= user defined type, X5= user defined type, X6= user defined type, X7= user defined type, X8= user defined type, X9= user defined type
MCNV_CRS_CODE	VARCHAR2	30		N	The vendor specific code
MCNV_PMS_CODE	NUMBER	30		N	PMS unique ID, like YRCH_ID for Rate Code ID
MCNV_CRS_DEFAULT	NUMBER	1		N	1 = Default ( if more than one CRS_CODE is found in one MCNV_TYPE when one of them should be marked as default)
MCNV_PMS_DEFAULT	NUMBER	1		N	1 = Default ( if more than one PMS_CODE is found in one MCNV_TYPE when one of them should be marked as default)
MCNV_INACTIVE	NUMBER	1		Y	indicates the use of this value for conversion.
MCNV_ZCNV_ID	NUMBER	30		Y	id to zcnv to link to mmod.
MCNV_SUBTYPE	NUMBER	2		Y	Extened sub types for each Type e.g. for Address Type (AT) there can be spearate mapping records for different profile types
MCNV_CRS_CATEGORY	VARCHAR2	30		Y	crs room type category
MCNV_PMS_PROF_ID	NUMBER	30		Y	we can link a profile of a specific type to a specfic code. i.e a source profile to a source code

### MCOP

MMOD Conversion Setup

Field Name	Type	Length	Decimals	Not NULL	
MCOP_ID	NUMBER	30		N	Unique Identifier

### MCOP

MMOD Conversion Setup

Field Name	Type	Length	Decimals	Not NULL	
MCOP_TYPE	VARCHAR2	3		N	conversion type code like RC, RT, etc.
MCOP_USED	NUMBER	1		N	1 = used for conversion, 0 = not used for conversion
MCOP_CONFIGURABLE	NUMBER	1		N	1 = shown on configuration screen, 0 = not shown on configuration screen
MCOP_ZCNV_ID	NUMBER	30		Y	id to zcnv to link to mmod.
MCOP_DESC	VARCHAR2	40		Y	description of user defined conversion type

### MCOR

Company Availabilitiy Requests

Field Name	Type	Length	Decimals	Not NULL	
MCOR_ID	NUMBER	30		N	Unique Identifier
MCOR_CORP_ID	VARCHAR2	25		Y	MCOR_CORP_ID is of MCOR
MCOR_COMPANY	VARCHAR2	50		Y	MCOR_COMPANY is of MCOR
MCOR_XCMS_ID	NUMBER	30		Y	company or travel agent id linked to the corp id sent by myfidelio

### MCRC

Table of MCRC

Field Name	Type	Length	Decimals	Not NULL	
MCRC_ID	NUMBER	30		N	Unique Identifier
MCRC_YRCH_ID	NUMBER	30		N	MCRC_YRCH_ID is of MCRC
MCRC_MCOR_ID	NUMBER	30		N	MCRC_MCOR_ID is of MCRC

### MCRT

Field Name	Type	Length	Decimals	Not NULL	
MCRT_ID	NUMBER	30		N	unique id
MCRT_MCNV_ID	NUMBER	30		N	linkage to the master room type in mcnv
MCRT_CRS_CODE	VARCHAR2	30		Y	additional crs code
MCRT_MIN_NUM_PERSONS	NUMBER	2		Y	indicates the min. number of persons of the room type
MCRT_MAX_NUM_PERSONS	NUMBER	2		Y	indicates the max. number of persons of the room type

### MDEF

V8 Online IFC Defaults

Field Name	Type	Length	Decimals	Not NULL	
MDEF_ID	NUMBER	30		N	Unique Identifier
MDEF_TYPE	VARCHAR2	3		N	Type, Same as MCVN_TYPE
MDEF_CODE_ID	VARCHAR2	30		N	Link to selected Default, like YRCH_ID, YCAT_ID etc. or for Defaults which are not ID's we can fill Defaults manually, for dates 'YYYYMMDD'
MDEF_ZCNV_ID	NUMBER	30		Y	id to zcnv to link to mmod.

### MIMP

Field Name	Type	Length	Decimals	Not NULL	
MIMP_ID	NUMBER	30		N	unique id
MIMP_MMOD_ID	NUMBER	30		N	link to mmod
MIMP_RECEIVED	DATE			N	timestamp of incoming ASCII message
MIMP_FILENAME	VARCHAR2	50		N	name of ASCII request file
MIMP_MSG_LINE	VARCHAR2	3000		Y	one booking from the request store in one line
MIMP_MSG_TYPE	NUMBER	1		Y	Indicates type of message. 1 = Reservation, 2 = Pprofile
MIMP_TABLE_ID	NUMBER	30		Y	record id of reservation, profile, depending on msg type

### MLOG

Field Name	Type	Length	Decimals	Not NULL	
MLOG_ID	NUMBER	30		N	unique id
MLOG_TIME	DATE			N	timestamp of entry
MLOG_SYSDAT	DATE			N	actual date
MLOG_TYPE	NUMBER	1		N	service id. 1 = 1W Dispatcher, 2 = 2WDispatcher, 3 = Listener, 4 = FileReader, 5 = Trigger Reader
MLOG_TEXT	VARCHAR2	100		Y	message send by the service

### MMAP

Field Name	Type	Length	Decimals	Not NULL	
MMAP_ID	NUMBER	30		N	
MMAP_MMOD_ID	NUMBER	30		N	
MMAP_CRS_ITEM_NAME	VARCHAR2	200		Y	Name of the item. For XML message format it is the node name.
MMAP_CRS_ITEM_POS	NUMBER	3		Y	Position of the item in the request file. Used by MyTravel

## MMAP

Field Name	Type	Length	Decimals	Not NULL	
MMAP_FIELD_NAME	VARCHAR2	100		Y	The name of the field in yrcf or yrdf
MMAP_TABLE_NAME	VARCHAR2	4		Y	The table name of the field. Either YRCF or YRDF
MMAP_FIELD_SIZE	NUMBER	3		Y	Field size or precision, depending on the field type
MMAP_FIELD_SCALE	NUMBER	1		Y	Scale of the field, if oracle field type is number
MMAP_FIELD_TYPE	NUMBER	1		Y	Field type of the customer field: 0=Boolean, 1=Float, 2=Date, 3=String, 4=Integer
MMAP_DESCRIPTION	VARCHAR2	100		Y	Field description
MMAP_ISATTRIBUTE	NUMBER	1		Y	Indicates in case of XML, whether value comes from an attribute or from a node
MMAP_RECORD_TYPE	NUMBER	2		Y	Indicates for MyTravel from which record type the custom field comes
MMAP_CONV_TYPE	NUMBER	2		Y	indicates conversion type of the custom field 0 = no conversion 1 = source code 2 = channel code 3 = market code

## MMOD

### Mapper Modules

Field Name	Type	Length	Decimals	Not NULL	
MMOD_ID	NUMBER	30		N	Unique Identifier
MMOD_MCFG_ID	NUMBER	30		N	Link to MCFG_ID, even if we only expect at this time one record in MCFG
MMOD_WPSS_ID	NUMBER	30		Y	MMOD_WPSS_ID is of MMOD
MMOD_MODULENAME	VARCHAR2	100		N	Module name of the mapper
MMOD_VENDOR_ID	VARCHAR2	20		N	Vendor Id, sent with the message
MMOD_VENDOR_DESC	VARCHAR2	100		Y	Description of Vendor
MMOD_WAIT_FOR_RESPONSE	NUMBER	1		N	Indicates whether ifc has to send a response message for this vendor
MMOD_FILE_MASK	VARCHAR2	20		Y	File Mask of files in Input folders, for instance *.AMF
MMOD_CONVERSION	NUMBER	1		N	MMOD_CONVERSION is of MMOD
MMOD_NO_SHARE_CHANGE	NUMBER	1		N	MMOD_NO_SHARE_CHANGE is of MMOD
MMOD_CHANGE_PROFILE	NUMBER	1		N	MMOD_CHANGE_PROFILE is of MMOD
MMOD_YGRT_ID	NUMBER	30		Y	Id of the group template used to create new group profiles
MMOD_CHECKYIELD	NUMBER	1		Y	1 = if this crs interface checks the hurdle rates
MMOD_PROPERTY_NAME	VARCHAR2	30		Y	MMOD_PROPERTY_NAME is of MMOD
MMOD_AVLREQ	NUMBER	1		N	MMOD_AVLREQ is of MMOD
MMOD_WAIT_FOR_RESP_TIME	NUMBER	5		N	MMOD_WAIT_FOR_RESP_TIME is of MMOD
MMOD_LEADTIME	NUMBER	3		N	is the time span between arrival date and cancellation date
MMOD_BILLING_INST	NUMBER	1		N	1=Using Billing instructions, 0=Not using Billing instructions
MMOD_ENABLED	NUMBER	1		Y	1=IFC is enabled, 0=IFC is disabled

## MMOD

### Mapper Modules

Field Name	Type	Length	Decimals	Not NULL	
MMOD_WATY_ID	NUMBER	30		Y	Selected Child Age Category for V8 Online Interface
MMOD_XCNC_ID	NUMBER	30		Y	Notes category id used for reservation remarks
MMOD_XCMS_ID	NUMBER	30		Y	Travel Agent profile id used for Billing Instructions
MMOD_REINSTATE	NUMBER	1		Y	1 = Reinstate functionality is on, 0 = reinstate is off complete new res will be created
MMOD_XCCA_ID	NUMBER	30		Y	profile category for financial account group profile
MMOD_CHK_AVL_RES	NUMBER	1		Y	Indicates whether availability check is processed for each reservation request
MMOD_PROCESS_FA	NUMBER	1		Y	Indicates the mfnMapper to process res request as financial account
MMOD_ZFAC_ZDCO_ID	NUMBER	30		Y	Default department code for financial account
MMOD_ZFAC_ZCAS_ID	NUMBER	30		Y	Default cashier for financial account postings
MMOD_ZFAC_POST_DESC	VARCHAR2	30		Y	Description of financial account posting
MMOD_ZFAG_ID	NUMBER	30		Y	Default account type for financial accounts
MMOD_DO_POSTINGS	NUMBER	1		Y	Indicates whether postings are done for financial account
MMOD_HTTP_PROXYUSER	VARCHAR2	30		Y	proxy user for http communication
MMOD_HTTP_PROXYPWD	VARCHAR2	30		Y	proxy pwd for http communication
MMOD_YWLP_ID	NUMBER	30		Y	priority for waitlist reason used for ywlt
MMOD_TWOWAY	NUMBER	1		N	Indicates whether the Mapper has 2way Functionality
MMOD_RATE_PER_GUEST	NUMBER	1		N	Indicates use of the corresponding option in V8
MMOD_ONEWAY	NUMBER	1		N	indicates whether the mapper is using httplistener for download
MMOD_RES_DOWNLOAD	NUMBER	1		Y	Indicates whether the mapper accepts reservation download
MMOD_RATES_DOWNLOAD	NUMBER	1		Y	Indicates whether the mapper accepts rate code download
MMOD_RAVL_DOWNLOAD	NUMBER	1		Y	Indicates whether the mapper accepts rate availability restriction download
MMOD_BLOCK_DOWNLOAD	NUMBER	1		Y	Indicates whether the mapper accepts allotment download
MMOD_WDAYS_OFFSET	NUMBER	1		Y	weekend days offset. In V8 start the week with Monday=1. Other CRS starts with Sunday=1
MMOD_VAT	NUMBER	5	2	Y	in case we get net values from CRS but we need gross, you can set the VAT percentage
MMOD_DL_REQ_BACKUP	NUMBER	1		Y	Indicates whether download requests should be backed up
MMOD_DL_RESP_BACKUP	NUMBER	1		Y	Indicates whether download responses should be backed up. If yes only those indicating not success
MMOD_UL_REQ_BACKUP	NUMBER	1		Y	Indicates whether the V8 trigger xml should be backed up
MMOD_UL_RESP_BACKUP	NUMBER	1		Y	Indicates whether upload messages should be backed up
MMOD_LINK_GRP_CODES	NUMBER	1		Y	indicates whether the attributes like rate, source, channel, market code for a res should taken from block
MMOD_HTTP_PROVIDER_ID	VARCHAR2	20		Y	provider id for HTML submit functionality
MMOD_THRESHOLD	NUMBER	1		Y	indicates whether inventory upload also use threshold settings of room types
MMOD_BLOCK_INC_TENT	NUMBER	1		Y	indicates whether also tentative bocks should be uploaded

## MMOD

### Mapper Modules

Field Name	Type	Length	Decimals	Not NULL	
MMOD_BLOCK_BOOKER	NUMBER	30		Y	default booker for blocks
MMOD_CHK_AVL_TENT	NUMBER	1		Y	indicates whether tentative values for room type availability check is used
MMOD_XCAC_ID	NUMBER	30		Y	Default child categorie for rate code down and upload
MMOD_ADD_OVERBOOK	NUMBER	1		Y	indicates whether overbooking values are used for rtav
MMOD_HOTEL_KEY	VARCHAR2	128		Y	extra hotel key for WebRes
MMOD_HTTP_USER	VARCHAR2	30		Y	User name for http request
MMOD_HTTP_PWD	VARCHAR2	30		Y	User password for http request
MMOD_HTTP_URL1	VARCHAR2	100		Y	Second url to split download and upload
MMOD_YALG_ID	NUMBER	30		Y	Availability Limit Group Id
MMOD_YRCH_ID	NUMBER	30		Y	Rate Code id for Expedia
MMOD_USEFTP	NUMBER	1		Y	Indicates use of FTP within FileReader
MMOD_AUTH_USER	VARCHAR2	30		Y	authentication user for HTTP access
MMOD_AUTH_PWD	VARCHAR2	30		Y	authentication pwd for HTTP access
MMOD_HTTP_TIMEOUT_RESOLVE	NUMBER	5		Y	Resolve timeout for http communication.
MMOD_HTTP_TIMEOUT_CONNECT	NUMBER	5		Y	connect timeout for http communication
MMOD_HTTP_TIMEOUT_SEND	NUMBER	5		Y	send timeout for http communication
MMOD_HTTP_TIMEOUT_RECEIVE	NUMBER	5		Y	receive timeout for http communication
MMOD_FTP_PATH	VARCHAR2	100		Y	FTP path
MMOD_FTP_PATH1	VARCHAR2	100		Y	FTP Output path
MMOD_USE_NET_RATES	NUMBER	1		Y	indicates whether net or gross rates are used
MMOD_HTTP_DOWNLOAD	NUMBER	1		Y	Indicates whether the listener is used also for downloads
MMOD_DL_RESP_BACKUP1	NUMBER	1		Y	Indicates whether the only warnings/errors or all download responses should be backuped
MMOD_COMBINE_DEF_TENT	NUMBER	1		Y	indicates whether we should upload definite and tentative avl in one field
MMOD_CHILD_RATE_BUCKETS	NUMBER	1		Y	Indicates use of child rate buckets for myfidelio
MMOD_USE_RES_ATTR	NUMBER	1		Y	Indicates whether userdefine reservation attributes are used
MMOD_HTTP_URL2	VARCHAR2	100		Y	3rd URL used by Expedia for booking Confirmation request
MMOD_HTTP_RESEND_INTERVAL	NUMBER	2		Y	resend interval in case URL is not available
MMOD_USE_FREETEXT	NUMBER	1		Y	Indicates whether comment also stored in Freetext2 field in yres
MMOD_ERR_NOTIFY_EMAIL	VARCHAR2	2000		Y	email address of receiver of error email
MMOD_WFTP_ID	NUMBER	30		Y	Link to the FTP account tabel
MMOD_USE_SALEDATE	NUMBER	1		Y	indicates whether the crs booking date is stored in yres_saledate
MMOD_NOGUESTS_ALLOWED	NUMBER	1		Y	indicates whether a reservation can be created with number of guests 0. Default = No
MMOD_USE_FA	NUMBER	1		Y	indicates whether a financial account will be created for a new group. Default = Yes

## MMOD

### Mapper Modules

Field Name	Type	Length	Decimals	Not NULL	
MMOD_USE_RT_CATEGORY	NUMBER	1		Y	Indicates the use of a room type list to simulate a rate category
MMOD_CODE_TO_PROFILE	NUMBER	1		Y	Indicates the conversion of a code like source code or channel also to a profile category like Source Profile
MMOD_USE_SELL_LIMIT	NUMBER	1		Y	Indicates whether the mapper uses sell limits instead of standard inventory handling
MMOD_USE_RR_FROM_RC	NUMBER	1		Y	Indicates whether we upload minlos/maxlos from rate code if ravl indicates open
MMOD_UPLOAD_DERIVED_RATE	NUMBER	1		Y	indicates whether rates of derived rate code (BaseRate in Suite8) will be uploaded
MMOD_ALTERNATE_PROFILE_DATA	NUMBER	1		Y	indicates the use of alternate profile data for names and address
MMOD_RATE_DAYS_IN_ADVANCE	NUMBER	4		Y	Number of days in advance for rate and rate restriction upload. CRS determines this value
MMOD_INV_DAYS_IN_ADVANCE	NUMBER	4		Y	Number of days in advance for inventory upload. CRS determines this value
MMOD_UPLOAD_WEEKEND_RATES	NUMBER	1		Y	indicates whether weekend rates will be uploaded
MMOD_UPLOAD_CHILDREN_RATES	NUMBER	1		Y	indicates whether children rates will be uploaded
MMOD_UPLOAD_ONLY_DEFAULT_RATE	NUMBER	1		Y	indicates whether only the default rate will be loaded or all rates
MMOD_DOWNLOAD_RES	NUMBER	1		Y	indicates whether CRS downloads reservation. Not configurable on config screen
MMOD_MAX_ADULT_RATES	NUMBER	1		Y	maximal number of adult rates supported by the CRS
MMOD_FTP_PASSIVE	NUMBER	1		Y	Indicates whether the ftp is used in passive mode
MMOD_FTP_BACKUP	NUMBER	1		Y	Indicates whether the interface makes a backup on the ftp of received file
MMOD_FTP_BACKUPPATH	VARCHAR2	100		Y	backup path on the ftp
MMOD_FTP_PROTOCOL	NUMBER	1		Y	0 = FTP, 1 = FTPS, 2 = SFTP
MMOD_FTP_ENCRYPTION	NUMBER	1		Y	0 = Explicit FTP over TLS, 1 = Implicit FTP over TLS, 2 = plain FTP
MMOD_FTP_LOGON_TYPE	NUMBER	1		Y	0 = Anonymous, 1 = Normal
MMOD_FTP_LOGLEVEL	NUMBER	1		Y	0 = No Logging, 1 = Logging (Command/Response)
MMOD_FTP_CERTIFICATE	VARCHAR2	100		Y	Filename inclusive path of certification file
MMOD_FTP_CERT_PWD	VARCHAR2	1024		Y	password for certification
MMOD_FTP_COMPRESSION	NUMBER	1		Y	use compression for data transfer
MMOD_FTP_ENCRYPT_DATA_CHANNEL	NUMBER	1		Y	use encryption for data channel which is the default
MMOD_FTP_CERT_FORMAT	NUMBER	1		Y	certificate format 0 = DER, 1 = PEM, 2 = PFX, 3 = SPC
MMOD_FTP_SSL_SESSION_RESUMPTION	NUMBER	1		Y	Indicates whether ssl session resumption is used. Not all server work correctly using this option. Default should be 0
MMOD_FTP_USE_SSL	NUMBER	1		Y	Indicates the use of SSL/TLS for FTPS
MMOD_INCL_ADD_TO_RATE	NUMBER	1		Y	indicates whether add to rate packages should be uploaded within the reservation rate
MMOD_ALLOW_ZERO_PRICE_PACKAGES	NUMBER	1		Y	indicates whether an interface accepts zero rates for packages. If not the price from Suite8 will be used
MMOD_ALTERNATIVE_RES_ATTR	NUMBER	1		Y	Trust Voyager option to setup the use of specific attributes in the reservation message as source, channel and market code

## MMSG

Field Name	Type	Length	Decimals	Not NULL	
MMSG_ID	NUMBER	30		N	unique id
MMSG_TYPE	NUMBER	1		Y	Indicates who made the entry 1 = API, 2 = Mapper
MMSG_TIME	DATE			Y	timestamp of entry
MMSG_LEVEL	NUMBER	1		Y	message level 0 = debug, 1 = trace, 2 = message, 3 = warning, 4 = error, 5 = system
MMSG_FROM	NUMBER	1		Y	direction 0 = 1way, 1 = 2way, 2 = system
MMSG_LOCATION	VARCHAR2	100		Y	name of the function in which the message were created
MMSG_TEXT	VARCHAR2	500		Y	log message
MMSG_BACKUP_FILE	VARCHAR2	50		Y	CRS message file processed, when log message were created

## MPRO

Field Name	Type	Length	Decimals	Not NULL	
MPRO_ID	NUMBER	30		N	unique id
MPRO_MMOD_ID	NUMBER	30		N	link to mmod
MPRO_XCMS_ID	NUMBER	30		N	profile id
MPRO_PURPOSE	NUMBER	1		N	purpose of default profile. 1 = Reservation, 2 = Billing Instructions, 3 = Blocks, 4 = Financial Accounts
MPRO_INTERNALCATEGORY	NUMBER	2		N	internal profile category, used to speed up profile handling for download

## MQU1

Field Name	Type	Length	Decimals	Not NULL	
MQU1_ID	NUMBER	30		N	unique id
MQU1_VENDOR_NO	NUMBER	30		Y	Vendor number of the vendor to whom the message belongs
MQU1_GUID	VARCHAR2	40		Y	GUID identifies message later for deletion
MQU1_TYPE	VARCHAR2	5		Y	Type of message like RES, RTAV etc.
MQU1_PROPERTY_NAME	VARCHAR2	30		Y	hotel code identifies the hotel to whom message belongs
MQU1_FILENAME	VARCHAR2	50		Y	file name of message used for file based interfaces for backups, request messages
MQU1_BUILDING	VARCHAR2	3		Y	only used by MyTravel
MQU1_MESSAGE	CLOB			Y	request message send by the crs
MQU1_HTTPVALUES	VARCHAR2	200		Y	contains special query strings for http communication
MQU1_RECEIVED	DATE			Y	timestamp when message received
MQU1_MMOD_ID	NUMBER	30		Y	

## MQU2

Field Name	Type	Length	Decimals	Not NULL	
MQU2_ID	NUMBER	30		N	unique id
MQU2_VENDOR_NO	NUMBER	30		Y	Vendor number of the vendor to whom the message belongs
MQU2_GUID	VARCHAR2	40		Y	GUID identifies message later for deletion
MQU2_TYPE	VARCHAR2	5		Y	Type of message like RES, RTAV etc.
MQU2_PROPERTY_NAME	VARCHAR2	30		Y	hotel code identifies the hotel to whom message belongs
MQU2_FILENAME	VARCHAR2	50		Y	file name of message used for file based interfaces for backups, response messages
MQU2_BUILDING	VARCHAR2	3		Y	only used by MyTravel
MQU2_MESSAGE	CLOB			Y	response message send by the interface
MQU2_HTTPVALUES	VARCHAR2	200		Y	contains special query strings for http communication
MQU2_RECEIVED	DATE			Y	timestamp when message received
MQU2_RESEND	NUMBER	1		Y	Indicates whether message could not yet be sent
MQU2_MMOD_ID	NUMBER	30		Y	

## MQU3

Field Name	Type	Length	Decimals	Not NULL	
MQU3_ID	NUMBER	30		N	unique id
MQU3_VENDOR_NO	NUMBER	30		Y	Vendor number of the vendor to whom the message belongs
MQU3_GUID	VARCHAR2	40		Y	GUID identifies message later for deletion
MQU3_TYPE	VARCHAR2	5		Y	Type of message like RES, RTAV etc.
MQU3_PROPERTY_NAME	VARCHAR2	30		Y	hotel code identifies the hotel to whom message belongs
MQU3_FILENAME	VARCHAR2	50		Y	file name of message used for file based interfaces for backups, trigger request messages
MQU3_BUILDING	VARCHAR2	3		Y	only used by MyTravel
MQU3_MESSAGE	CLOB			Y	trigger request message send by the interface
MQU3_HTTPVALUES	VARCHAR2	200		Y	contains special query strings for http communication
MQU3_RECEIVED	DATE			Y	timestamp when message received
MQU3_MMOD_ID	NUMBER	30		Y	

## MQU4

Field Name	Type	Length	Decimals	Not NULL	
MQU4_ID	NUMBER	30		N	unique id

### MQU4

Field Name	Type	Length	Decimals	Not NULL	
MQU4_VENDOR_NO	NUMBER	30		Y	Vendor number of the vendor to whom the message belongs
MQU4_GUID	VARCHAR2	40		Y	GUID identifies message later for deletion
MQU4_TYPE	VARCHAR2	5		Y	Type of message like RES, RTAV etc.
MQU4_PROPERTY_NAME	VARCHAR2	30		Y	hotel code identifies the hotel to whom message belongs
MQU4_FILENAME	VARCHAR2	50		Y	file name of message used for file based interfaces for backups, trigger request messages
MQU4_BUILDING	VARCHAR2	3		Y	only used by MyTravel
MQU4_MESSAGE	CLOB			Y	trigger response message send by the interface
MQU4_HTTPVALUES	VARCHAR2	200		Y	contains special query strings for http communication
MQU4_RECEIVED	DATE			Y	timestamp when message received
MQU4_RESEND	NUMBER	1		Y	Indicates whether message could not yet be sent
MQU4_MMOD_ID	NUMBER	30		Y	

### MQU5

Field Name	Type	Length	Decimals	Not NULL	
MQU5_ID	NUMBER	30		N	unique id
MQU5_VENDOR_NO	NUMBER	30		Y	Vendor number of the vendor to whom the message belongs
MQU5_GUID	VARCHAR2	40		Y	GUID identifies message later for deletion
MQU5_TYPE	VARCHAR2	5		Y	Type of message like RES, RTAV etc.
MQU5_PROPERTY_NAME	VARCHAR2	30		Y	hotel code identifies the hotel to whom message belongs
MQU5_FILENAME	VARCHAR2	50		Y	file name of message used for file based interfaces for backups, request messages
MQU5_BUILDING	VARCHAR2	3		Y	only used by MyTravel
MQU5_MESSAGE	CLOB			Y	request message send by the crs
MQU5_HTTPVALUES	VARCHAR2	200		Y	contains special query strings for http communication
MQU5_RECEIVED	DATE			Y	timestamp when message received

### MRAT

Field Name	Type	Length	Decimals	Not NULL	
MRAT_ID	NUMBER	30		N	unique id
MRAT_ZCNV_ID	NUMBER	30		N	link to zcnv and mmod
MRAT_XPAC_ID	NUMBER	30		N	xpac id

### MRAT

Field Name	Type	Length	Decimals	Not NULL	
MRAT_TYPE	VARCHAR2	2		Y	conversion type. possible values are X0..X9
MRAT_RESORDET	NUMBER	1		Y	Indicates whether attribute is linked to yres or ydet

### MRTL

Field Name	Type	Length	Decimals	Not NULL	
MRTL_ID	NUMBER	30		N	unique id
MRTL_MCNV_ID	NUMBER	30		N	linkage to the master room type in mcnv
MRTL_YCAT_ID	NUMBER	30		Y	linkage to the linked room type in ycat
MRTL_DISPLORDER	NUMBER	3		Y	Selection order of roomtypes for availability check
MRTL_ZCNV_ID	NUMBER	30		Y	link to mapper used to select only unused roomtypes for linked list

### MURL

Field Name	Type	Length	Decimals	Not NULL	
MURL_ID	NUMBER	30		N	unique id
MURL_MMOD_ID	NUMBER	30		N	link to mmod
MURL_MSG_NAME	VARCHAR2	100		Y	name of xml message
MURL_URL	VARCHAR2	150		Y	URL used to send message
MURL_DIRECTION	NUMBER	1		Y	direction of message 0 = download, 1 = upload
MURL_INACTIVE	NUMBER	1		Y	Indicates which setup URL is really used
MURL_LASTREQUEST	TIMESTAMP		6	Y	timestamp of last successful booking request

### MWSV

Field Name	Type	Length	Decimals	Not NULL	
MWSV_ID	NUMBER	30		N	unique id
MWSV_MMOD_ID	NUMBER	30		N	linkage to mmod
MWSV_SERVICE_NAME	VARCHAR2	100		N	service name used to identify url in listener
MWSV_URL	VARCHAR2	100		N	webservice url used for connection
MWSV_INACTIVE	NUMBER	1		Y	Indicates which setup webservice is really used
MWSV_LASTREQUEST	TIMESTAMP		6	Y	timestamp of last successful booking request

## NEAT

Configuration table for Products that are used with the Europaeische.at Web Services

Field Name	Type	Length	Decimals	Not NULL	
NEAT_ID	NUMBER	30		N	
NEAT_CODE	VARCHAR2	5		N	Code of the product, IN611 for example
NEAT_PRODUCTNAME	VARCHAR2	256		Y	Name of the product, Hotelstorno Plus (Vermittlerinkasso) for example, to show in the selection
NEAT_DEFAULT	NUMBER	1		N	1 = default, 0 = not default
NEAT_DISPLAYORDER	NUMBER	2		Y	
NEAT_ZDCO_ID	NUMBER	30		N	Link to the department code where the booked insurance fee should be posted

## PCAD

Field Name	Type	Length	Decimals	Not NULL	
PCAD_ID	NUMBER	30		N	
PCAD_PCAL_ID	NUMBER	30		Y	
PCAD_PRICE	NUMBER	30	4	Y	
PCAD_MINUTES	NUMBER	30		Y	
PCAD_ZDCO_ID	NUMBER	30		Y	

## PCAL

Field Name	Type	Length	Decimals	Not NULL	
PCAL_ID	NUMBER	30		N	
PCAL_PRIC_ID	NUMBER	30		Y	
PCAL_DAYTYPE	NUMBER	2		Y	
PCAL_TIMEFROM	DATE			Y	
PCAL_TIMETO	DATE			Y	

## PDLP

Field Name	Type	Length	Decimals	Not NULL	
PDLP_ID	NUMBER	30		N	
PDLP_PDSC_ID	NUMBER	30		Y	
PDLP_PDSP_ID	NUMBER	30		Y	

### PDLP

---

Field Name	Type	Length	Decimals	Not NULL
PDLP_FROMDATE	DATE			Y
PDLP_TODATE	DATE			Y

### PDSC

---

Field Name	Type	Length	Decimals	Not NULL
PDSC_ID	NUMBER	30		N
PDSC_SHORTDESC	VARCHAR2	3		Y
PDSC_LONGDESC	VARCHAR2	30		Y
PDSC_INACTIVE	NUMBER	1		Y

### PDSP

---

Field Name	Type	Length	Decimals	Not NULL
PDSP_ID	NUMBER	30		N
PDSP_PERCENTAGE	NUMBER	30		Y
PDSP_PSEC_ID	NUMBER	30		Y
PDSP_FLATAMOUNT	NUMBER	30	4	Y
PDSP_TYPE	NUMBER	1		Y

### PHOL

---

Field Name	Type	Length	Decimals	Not NULL
PHOL_ID	NUMBER	30		N
PHOL_LONGDESC	VARCHAR2	200		Y
PHOL_DAY	NUMBER	2		Y
PHOL_MONTH	NUMBER	2		Y

### PMKL

---

Field Name	Type	Length	Decimals	Not NULL
PMKL_ID	NUMBER	30		N

### PMKL

Field Name	Type	Length	Decimals Not NULL
PMKL_ZFAC_ID	NUMBER	30	Y
PMKL_TIMESTAMP	DATE		Y

### PPRL

Field Name	Type	Length	Decimals Not NULL
PPRL_ID	NUMBER	30	N
PPRL_PPRO_ID	NUMBER	30	Y
PPRL_PRIC_ID	NUMBER	30	Y

### PPRO

Field Name	Type	Length	Decimals Not NULL
PPRO_ID	NUMBER	30	N
PPRO_SHORTDESC	VARCHAR2	3	Y
PPRO_LONGDESC	VARCHAR2	200	Y
PPRO_DISPLORDER	NUMBER	5	Y
PPRO_INACTIVE	NUMBER	1	Y
PPRO_VALIDFROM	DATE		Y
PPRO_VALIDUNTIL	DATE		Y
PPRO_WCOL_ID	NUMBER	30	Y

### PRIC

Field Name	Type	Length	Decimals Not NULL
PRIC_ID	NUMBER	30	N
PRIC_SHORTDESC	VARCHAR2	3	Y
PRIC_LONGDESC	VARCHAR2	30	Y
PRIC_FOLIOTEXT	VARCHAR2	30	Y
PRIC_PSEC_ID	NUMBER	30	Y
PRIC_IMMEDIATEPOST	NUMBER	1	Y
PRIC_GRACEMINUTES	NUMBER	3	Y

### PRIC

Field Name	Type	Length	Decimals	Not NULL	
PRIC_DISPLORDER	NUMBER	5		Y	
PRIC_DAYEXTENDTYPE	NUMBER	1		Y	which price to post when guest stay extends a day: 0 - no post, 1 - check in day's price, 2 - current day's price
PRIC_CALCTYPE	NUMBER	1		Y	1 - if the price should be reposted after the set amount of minutes (pcad) has passed

### PSAC

Field Name	Type	Length	Decimals	Not NULL	
PSAC_ID	NUMBER	30		N	
PSAC_IN_PSEC_ID	NUMBER	30		Y	
PSAC_OUT_PSEC_ID	NUMBER	30		N	
PSAC_SHORTDESC	VARCHAR2	3		Y	
PSAC_LONGDESC	VARCHAR2	100		Y	
PSAC_EXTERNALID	VARCHAR2	200		Y	
PSAC_DISPLORDER	NUMBER	3		Y	

### PSEC

Field Name	Type	Length	Decimals	Not NULL	
PSEC_ID	NUMBER	30		N	
PSEC_SHORTDESC	VARCHAR2	3		Y	
PSEC_LONGDESC	VARCHAR2	30		Y	
PSEC_GLOBALAREA	NUMBER	1		Y	
PSEC_INACTIVE	NUMBER	1		Y	
PSEC_DISPLORDER	NUMBER	5		Y	
PSEC_AUTOOUT	NUMBER	1		Y	
PSEC_AUTOOUTMINUTES	NUMBER	4		Y	
PSEC_AUTO_ERRORENTY	NUMBER	2		Y	
PSEC_AUTOOUT_PSAC_ID	NUMBER	30		Y	

### PTIK

Ticket Configuration Header

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

## PTIK

Ticket Configuration Header

Field Name	Type	Length	Decimals	Not NULL	
PTIK_ID	NUMBER	30		N	
PTIK_SHORTDESC	VARCHAR2	10		Y	
PTIK_LONGDESC	VARCHAR2	60		Y	
PTIK_INACTIVE	NUMBER	1		Y	
PTIK_WCOL_ID	NUMBER	30		Y	
PTIK_DISPLORDER	NUMBER	5		Y	
PTIK_ZDGT_ID	NUMBER	30		N	
PTIK_SALESDESC	VARCHAR2	30		Y	
PTIK_ZFST_ID	NUMBER	30		Y	link to barcode ticket folio style
PTIK_ZYTG_ID	NUMBER	30		Y	Link to Ticket groups
PTIK_ZYTT_ID	NUMBER	30		Y	
PTIK_INTERFACEACCESSCODE	VARCHAR2	10		Y	Interface Access Code Value
PTIK_TICKETCREATIONLEVEL	NUMBER	3		Y	Ticket Creation Level
PTIK_EXCLUSIVE_XCMS_ID	NUMBER	30		Y	Ticket Checkout Limitations, if set, the ticket can only be checked out to this profile
PTIK_EXCLUSIVE_PAYMENT_ZDCO_ID	NUMBER	30		Y	Ticket Checkout Limitations, if set, the ticket can only be checked out using this payment department code
PTIK_DONT_SEND_IFC	NUMBER	1		Y	1. do not send Key interface commands for this Ticket type

## PTLG

Field Name	Type	Length	Decimals	Not NULL	
PTLG_ID	NUMBER	30		N	
PTLG_TIMESTAMP	DATE			Y	
PTLG_USER_XCMS_ID	NUMBER	30		Y	
PTLG_ZFAC_ID	NUMBER	30		Y	
PTLG_PTIK_ID	NUMBER	30		Y	
PTLG_PPRO_ID	NUMBER	30		Y	
PTLG_PRIC_ID	NUMBER	30		Y	
PTLG_PSAC_ID	NUMBER	30		Y	
PTLG_PCAD_ID	NUMBER	30		Y	
PTLG_POSTEDAMOUNT	NUMBER	30	4	Y	
PTLG_POSTINGDATE	DATE			Y	
PTLG_ZPOS_ID	NUMBER	30		Y	
PTLG_TYPE	NUMBER	1		Y	1-checkin, 2-Movement, 3-checkout

## PTLG

---

Field Name	Type	Length	Decimals	Not NULL
PTLG_TRIGGERGENERATED	NUMBER	1		Y
PTLG_FIDELIODATE	DATE			Y

## PTPL

Ticket Header - Ticket Detail Link

---

Field Name	Type	Length	Decimals	Not NULL
PTPL_ID	NUMBER	30		N
PTPL_FROMDATE	DATE			N
PTPL_TODATE	DATE			N
PTPL_PPRO_ID	NUMBER	30		Y
PTPL_PTIK_ID	NUMBER	30		Y

## PTSQ

Processing queue for TI IFC

---

Field Name	Type	Length	Decimals	Not NULL
PTSQ_ID	NUMBER	30		N
PTSQ_CARD	VARCHAR2	6		Y
PTSQ_PSAC_ID	NUMBER	30		N
PTSQ_ZFAC_ID	NUMBER	30		N
PTSQ_XCMS_ID	NUMBER	30		Y
PTSQ_THIRDPARTYDATE	DATE			N
PTSQ_RECEIVED	DATE			N
PTSQ_PROCESSED	DATE			Y
PTSQ_PROCESSEDNULL	NUMBER	1		Y

## QNRA

---

Field Name	Type	Length	Decimals	Not NULL
QNRA_ID	NUMBER	30		N
QNRA_QNRF_ID	NUMBER	30		N
QNRA_WQUE_ID	NUMBER	30		Y
QNRA_WQAN_ID	NUMBER	30		Y

### QNRA

Field Name	Type	Length	Decimals	Not NULL	
QNRA_WQNL_ID	NUMBER	30		Y	Answer link to questionare
QNRA_TEXT	VARCHAR2	1000		Y	Guest entered answers/comments

### QNRFB

Field Name	Type	Length	Decimals	Not NULL	
QNRFB_ID	NUMBER	30		N	
QNRFB_WQNR_ID	NUMBER	30		N	
QNRFB_GUEST_XCMS_ID	NUMBER	30		Y	
QNRFB_YRES_ID	NUMBER	30		Y	
QNRFB_COMMENT	VARCHAR2	2000		Y	
QNRFB_XCMS_ID	NUMBER	30		Y	
QNRFB_ENTERED	DATE			Y	
QNRFB_LASTMODIFIED	DATE			Y	
QNRFB_INPUTSOURCE	NUMBER	1		Y	Questionnaire input source 1. manual 2.web page
QNRFB_YBOM_ID	NUMBER	30		Y	Link to booking id
QNRFB_FILLOUTDATE	DATE			Y	Questionnaire Fillout date

### RDAY

table reservation. day messages

Field Name	Type	Length	Decimals	Not NULL	
RDAY_ID	NUMBER	30		N	primary key
RDAY_RRST_ID	NUMBER	30		N	link to the restaurant
RDAY_STARTDATE	DATE			N	message start day
RDAY_ENDDATE	DATE			N	message end day
RDAY_MESSAGE	VARCHAR2	1000		N	message
RDAY_USER_XCMS_ID	NUMBER	30		N	user entered the message

### RDET

table reservation attached tables

Field Name	Type	Length	Decimals	Not NULL	
RDET_ID	NUMBER	30		N	

### RDET

table reservation attached tables

Field Name	Type	Length	Decimals	Not NULL	
RDET_RRES_ID	NUMBER	30		N	link to reservation
RDET_RTAB_ID	NUMBER	30		N	link to table

### ROTM

restaurant opening times (seasons)

Field Name	Type	Length	Decimals	Not NULL	
ROTM_ID	NUMBER	30		N	
ROTM_STARTDATE	DATE			N	time frame opening date
ROTM_ENDDATE	DATE			N	time frame end date
ROTM_RRST_ID	NUMBER	30		N	restaurant id
ROTM_DISPLAYSTARTTIME	DATE			Y	

### RPAS

Autosetup Drawings

Field Name	Type	Length	Decimals	Not NULL	
RPAS_ID	NUMBER	30		N	Unique ID
RPAS_NAME	VARCHAR2	256		Y	Name
RPAS_RPDW_ID	NUMBER	30		Y	Link to drawing

### RPCB

Roomplanner clipboard items

Field Name	Type	Length	Decimals	Not NULL	
RPCB_ID	NUMBER	30		N	Unique ID
RPCB_NAME	VARCHAR2	256		Y	Name
RPCB_RPDW_ID	NUMBER	30		Y	Link to drawing

### RPCF

Roomplanner colour scheme

Field Name	Type	Length	Decimals	Not NULL	
RPCF_ID	NUMBER	30		N	Unique ID
RPCF_NAME	VARCHAR2	256		Y	Name of Colour Scheme

### RPDW

Roomplanner drawings

Field Name	Type	Length	Decimals	Not NULL	
RPDW_ID	NUMBER	30		N	Unique ID
RPDW_LAYOUT	LONG RAW			N	Roomplanner drawing
RPDW_TYPE	NUMBER	2		N	0= Function Space   1= Linked Seating to a FS   2= Event   3= Symbol   4=bitmap symbol  5= Seating   9= clipboard drawing   15= autoseup drawing
RPDW_DEFAULT_YSSL_ID	NUMBER	30		Y	Original Link to Function Space Seating
RPDW_EDITED	NUMBER	1		Y	1= Yes
RPDW_ACCEPTED_NOOFATTENDEES	NUMBER	30		Y	Original no. of attendees
RPDW_BASE_DRAWING_EDITED	NUMBER	1		Y	1= Yes
RPDW_RPPL_ID	NUMBER	30		Y	Link to Print Layout
RPDW_PRINT_X	FLOAT			Y	Centered point
RPDW_PRINT_Y	FLOAT			Y	1= Centered point
RPDW_PRINT_SCALE	FLOAT			Y	Print Scale

### RPLS

Roomplanner Layer

Field Name	Type	Length	Decimals	Not NULL	
RPLS_ID	NUMBER	30		N	Unique ID
RPLS_RPCF_ID	NUMBER	30		N	Link to Colour Scheme
RPLS_ORD	NUMBER	10		N	Layer Number
RPLS_NAME	VARCHAR2	200		N	Layer Name
RPLS_RED	FLOAT			N	Fill Colour Red
RPLS_GREEN	FLOAT			N	Fill Colour Green
RPLS_BLUE	FLOAT			N	Fill Colour Blue
RPLS_ALPHA	FLOAT			N	Fill Colour Alpha
RPLS_LRED	FLOAT			N	Line Colour Red
RPLS_LGREEN	FLOAT			N	Line Colour Green
RPLS_LBLUE	FLOAT			N	Line Colour Blue
RPLS_LALPHA	FLOAT			N	Line Colour Alpha
RPLS_LINEWIDTH	FLOAT			N	Line Width
RPLS_STIPPLE	NUMBER			N	Line Style
RPLS_HASFILL	NUMBER	1		N	0 = No
RPLS_HASLINES	NUMBER	1		N	0 = No
RPLS_HASDIMENSIONFONTS	NUMBER	1		N	Layer can have dimension 0 = No

### RPLS

Roomplanner Layer

Field Name	Type	Length	Decimals	Not NULL	
RPLS_DIM_TYPEFACE	VARCHAR2	32		Y	Name of the dimension font
RPLS_DIM_RED	FLOAT			Y	Dimension Font Colour Red
RPLS_DIM_GREEN	FLOAT			Y	Dimension Font Colour Green
RPLS_DIM_BLUE	FLOAT			Y	Dimension Font Colour Blue
RPLS_DIM_ALPHA	FLOAT			Y	Dimension Font Colour Alpha
RPLS_DIM_BOLD	NUMBER	1		Y	1= Yes
RPLS_DIM_ITALIC	NUMBER	1		Y	1= Yes
RPLS_DIM_UNDERLINE	NUMBER	1		Y	1= Yes
RPLS_DIM_STRIKEOUT	NUMBER	1		Y	1= Yes
RPLS_LABEL_TYPEFACE	VARCHAR2	32		Y	Name of the label font
RPLS_LABEL_FONTSIZE	FLOAT			Y	Size of font
RPLS_LABEL_RED	FLOAT			Y	Label Colour Red
RPLS_LABEL_GREEN	FLOAT			Y	Label Colour Green
RPLS_LABEL_BLUE	FLOAT			Y	Label Colour Blue
RPLS_LABEL_ALPHA	FLOAT			Y	Label Colour Alpha
RPLS_LABEL_BOLD	NUMBER	1		Y	1= Yes
RPLS_LABEL_ITALIC	NUMBER	1		Y	1= Yes
RPLS_LABEL_UNDERLINE	NUMBER	1		Y	1 = Yes
RPLS_LABEL_STRIKEOUT	NUMBER	1		Y	1 = Yes
RPLS_HASLABELFONTS	NUMBER	1		Y	1= Yes
RPLS_DIM_FONTSIZE	FLOAT			Y	Dimension Font Size

### RPPL

Print Layout

Field Name	Type	Length	Decimals	Not NULL	
RPPL_ID	NUMBER	30		N	Unique ID
RPPL_NAME	VARCHAR2	256		Y	Name
RPPL_LAYOUT	LONG RAW			N	Binary representation

### RPRF

Profiles linked to the table reservations.

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### RPRF

Profiles linked to the table reservations.

Field Name	Type	Length	Decimals	Not NULL	
RPRF_ID	NUMBER	30		N	Link ID
RPRF_RRES_ID	NUMBER	30		N	Table reservation ID
RPRF_XCMS_ID	NUMBER	30		N	Profile ID

### RPSL

Report security level description table

Field Name	Type	Length	Decimals	Not NULL	
RPSL_ID	NUMBER	30		N	
RPSL_LONGDESC	VARCHAR2	30		Y	
RPSL_NUMERICDESC	NUMBER	3		Y	Number between 0 and 99 which will be compared to the reports securitylevel
RPSL_USER	NUMBER	1		Y	null or 0=used on report level side, 1=used on user level side
RPSL_DEFAULT	NUMBER	1		Y	1=default report or user level (depending on user flag) for new reports,sections or new user, usergroup
RPSL_INACTIVE	NUMBER	1		Y	

### RPSY

Roomplanner Symbols

Field Name	Type	Length	Decimals	Not NULL	
RPSY_ID	NUMBER	30		N	Unique ID
RPSY_YCIT_ID	NUMBER	30		Y	Link to Misc. Item
RPSY_RPDW_ID	NUMBER	30		Y	Link to drawing
RPSY_NAME	VARCHAR2	256		Y	Symbol Name
RPSY_DEFAULT_LAYER	NUMBER	10		Y	0= Background   1= On view controls   2= Grab points   3= Snap points   4= Snap areas   5= Selection   6= Grid   7= Ruler   8 = Crosshair   9 = Warning hints   10 = Background Symbol editor   11= Walls   12= Moveable walls   13= Door sweeps   14= Drawing layer   15= Electric layer   16= chairs and tables   17= Miscellaneous   18= Dimensions   19= Labels   20= Autosetups   21= Numbering
RPSY_ROLE	NUMBER	30		Y	1= Generic   2= Chair   3= Table   4= Hotel Logo
RPSY_IS_BITMAP	NUMBER	1		Y	1= Yes
RPSY_UNIQUE_STAMP	VARCHAR2	64		Y	Unique Stamp for import / export
RPSY_IS_ARCHIVED	NUMBER	1		Y	1= Yes - symbol has been deleted but remains in the table

### RRER

Link table reservations to the PMS reservations

Field Name	Type	Length	Decimals	Not NULL	
RRER_ID	NUMBER	30		N	Primary key
RRER_RRES_ID	NUMBER	30		N	Link to the table reservation
RRER_YRES_ID	NUMBER	30		Y	

### RRES

table reservations

Field Name	Type	Length	Decimals	Not NULL	
RRES_ID	NUMBER	30		N	
RRES_DATE	DATE			N	reservation date
RRES_STARTTIME	DATE			N	starting time
RRES_ENDTIME	DATE			N	estimated end time
RRES_PAX	NUMBER	3		Y	number of person
RRES_RRST_ID	NUMBER	30		N	link to the restaurant
RRES_DESCRIPTION	VARCHAR2	128		Y	reservation description
RRES_WCOL_ID	NUMBER	30		Y	reservation color
RRES_CANCELED	NUMBER	1		Y	1 - if reservation was canceled. Maintained only for compatibility. Please refer to rres_resstatus/RRES_NOAVAILREASON
RRES_TABLECARD	VARCHAR2	2000		Y	tablecard printout information
RRES_PLACEDTIME	DATE			Y	Used by POS to indicate that guests have been placed
RRES_LEFTTABLETIME	DATE			Y	Indicates when user has left the table
RRES_SHARABLE	NUMBER	1		Y	Allow this reservation to be shared
RRES_CRSSYSTEM	VARCHAR2	30		Y	
RRES_PRICE	NUMBER	30	4	Y	Price of the resource reservation. Not available for tables
RRES_FIXED	NUMBER	1		Y	only user with special rights are allowed to changed fixed table
RRES_RESSTATUS	NUMBER	1		Y	1=definitive 3=not effecting availability, as an example waitlist /canceled entries will have a RRES_RESSTATUS=3
RRES_NOAVAILREASON	NUMBER	1		Y	Reason why not affecting availability. 1 = Waitlist 3 = Canceled
RRES_INTERNALINFO	VARCHAR2	1000		Y	

### RRGL

reservation age link from rres into xcac

Field Name	Type	Length	Decimals	Not NULL	
RRGL_ID	NUMBER	30		N	rrgl_id identifies rrgl

### RRGL

reservation age link from rres into xcac

Field Name	Type	Length	Decimals	Not NULL	
RRGL_RRES_ID	NUMBER	30		N	rrgl_rres_id is the link into rres.
RRGL_XCAC_ID	NUMBER	30		N	rrgl_xcac_id is the link into xcac.
RRGL_NUMBER	NUMBER	3		N	rrgl_number is the number of selected age for selected rres record.

### RRSC

Restaurant closing times

Field Name	Type	Length	Decimals	Not NULL	
RRSC_ID	NUMBER	30		N	RRSC PK
RRSC_RRST_ID	NUMBER	30		N	Restaurant link
RRSC_STARTDATE	DATE			N	Restaurant closed from..
RRSC_ENDDATE	DATE			N	Restaurant closed to..

### RRST

restaurants setup

Field Name	Type	Length	Decimals	Not NULL	
RRST_ID	NUMBER	30		N	
RRST_SHORTDESC	VARCHAR2	3		N	
RRST_NAME	VARCHAR2	30		N	restaurant name
RRST_DEF_DURATION	NUMBER	3		Y	default reservation duration
RRST_SETUP_TIME	NUMBER	3		Y	setup time between reservations
RRST_DISPLORDER	NUMBER	3		Y	
RRST_OPEN_MON	NUMBER	1		Y	
RRST_OPEN_TUE	NUMBER	1		Y	
RRST_OPEN_WED	NUMBER	1		Y	
RRST_OPEN_THU	NUMBER	1		Y	
RRST_OPEN_FRI	NUMBER	1		Y	
RRST_OPEN_SAT	NUMBER	1		Y	
RRST_OPEN_SUN	NUMBER	1		Y	
RRST_INACTIVE	NUMBER	1		Y	
RRST_YFSC_ID	NUMBER	30		Y	Link to the function space
RRST_WEBINFO	VARCHAR2	2000		Y	Web Short Information
RRST_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information

### RRST

restaurants setup

Field Name	Type	Length	Decimals	Not NULL	
RRST_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information for Mobile Device
RRST_MD_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information for Mobile Device
RRST_WEBENABLED	NUMBER	1		Y	
RRST_THRESHOLD	NUMBER	3		Y	Number of persons closed for web booking.
RRST_AUTOEXTEND	NUMBER	1		Y	Auto extend seated reservations
RRST_WEBONLYSTDTIMES	NUMBER	1		Y	In Suite 8 Homepage, only standard reservation times will be used for this restaurant

### RRYB

Table reservations linked to CCM

Field Name	Type	Length	Decimals	Not NULL	
RRYB_ID	NUMBER	30		N	
RRYB_RRES_ID	NUMBER	30		N	Table Reservation ID
RRYB_YBOM_ID	NUMBER	30		Y	Booking ID
RRYB_YEVM_ID	NUMBER	30		Y	Event ID
RRYB_YEBS_ID	NUMBER	30		Y	Function Space Booked ID

### RSPL

Restaurant plan

Field Name	Type	Length	Decimals	Not NULL	
RSPL_ID	NUMBER	30		N	
RSPL_RRST_ID	NUMBER	30		N	
RSPL_PICTURE	LONG RAW			Y	
RSPL_NAME	VARCHAR2	30		Y	
RSPL_DEFAULT	NUMBER	1		Y	
RSPL_DISPLORDER	NUMBER	1		Y	
RSPL_PICTURE_C	VARCHAR2	2000		Y	

### RSPT

Restaurant plan times

Field Name	Type	Length	Decimals	Not NULL	
RSPT_ID	NUMBER	30		N	
RSPT_RSPL_ID	NUMBER	30		N	

### RSPT

Restaurant plan times

Field Name	Type	Length	Decimals	Not NULL
RSPT_STARTTIME	DATE			Y
RSPT_ENDTIME	DATE			Y

### RSTF

standard opening times for timeframe

Field Name	Type	Length	Decimals	Not NULL	
RSTF_ID	NUMBER	30		N	id
RSTF_RTFR_ID	NUMBER	30		N	reference to time frame
RSTF_START	DATE			N	start time
RSTF_END	DATE			N	end time
RSTF_WEBENABLED	NUMBER	1		Y	

### RTAB

tables setup

Field Name	Type	Length	Decimals	Not NULL	
RTAB_ID	NUMBER	30		N	
RTAB_RRST_ID	NUMBER	30		N	link to restaurant
RTAB_NUMBER	NUMBER	5		N	table number
RTAB_DESCRIPTION	VARCHAR2	30		Y	description
RTAB_STD_PAX	NUMBER	3		N	standard number of person
RTAB_MAX_PAX	NUMBER	3		N	maximum number of person
RTAB_DISPLORDER	NUMBER	5		Y	display order
RTAB_INACTIVE	NUMBER	1		Y	

### RTAT

table attribute links

Field Name	Type	Length	Decimals	Not NULL	
RTAT_ID	NUMBER	30		N	primary key
RTAT_XPAC_ID	NUMBER	30		N	link to attribute categories
RTAT_XPDA_ID	NUMBER	30		N	link to attribute value
RTAT_RTAB_ID	NUMBER	30		N	link to table

## RTFR

restaurant opening time frames by seasons

Field Name	Type	Length	Decimals	Not NULL
RTFR_ID	NUMBER	30		N
RTFR_ROTID	NUMBER			N link to season
RTFR_STARTTIME	DATE			N time of opening
RTFR_ENDTIME	DATE			N time of closing

## RTLN

setup of linkage between tables which can get connected / combined

Field Name	Type	Length	Decimals	Not NULL
RTLN_ID	NUMBER	30		N
RTLN_MASTER_RTAB_ID	NUMBER	30		N master table
RTLN_LINKED_RTAB_ID	NUMBER	30		N possible to combine with

## SAAR

HCN - Central Aging Report

Field Name	Type	Length	Decimals	Not NULL
SAAR_ID	NUMBER	30		N
SAAR_AACC_ID	NUMBER	30		N
SAAR_AACC_ATYP_ID	NUMBER	30		Y
SAAR_XCMS_ID	NUMBER	30		Y
SAAR_ACCOUNTNAME	VARCHAR2	100		Y
SAAR_ACCOUNTNUMBER	VARCHAR2	60		Y
SAAR_DATE	DATE			Y
SAAR_OPENAMOUNT	NUMBER	30	4	Y
SAAR_CREATEDDATE	DATE			Y
SAAR_IMPORTED	NUMBER	1		N
SAAR_PARTNER_ID	NUMBER	30		Y
SAAR_WPHS_ID	NUMBER	30		Y
SAAR_ATYP_SHORTDESC	VARCHAR2	3		Y
SAAR_ATYP_LONGDESC	VARCHAR2	30		Y
SAAR_AINV_ID	NUMBER	30		Y
SAAR_REMARKS	VARCHAR2	50		Y

## SBUD

### Budgets

Field Name	Type	Length	Decimals	Not NULL	
SBUD_ID	NUMBER	30		N	Unique Identifier
SBUD_DATE	DATE			N	Budget Date
SBUD_TABLENAME	VARCHAR2	4		N	TableName: ZDCO for Departmentcode Budget
SBUD_TABLE_ID	NUMBER	30		N	Corresponding ID of SBUD_TABLENAME
SBUD_VALUE	NUMBER	30	4	N	Budget Amount per Day
SBUD_MONTH_VALUE	NUMBER	30	4	N	the budget amount entered for the month
SBUD_TYPE	NUMBER	2		N	1 = Net Revenue 2 = Gross Revenue 3 = Room Nights
SBUD_MONTHVALUE2	NUMBER	30	4	Y	
SBUD_YEARVALUE	NUMBER	30	4	Y	
SBUD_WPHS_ID	NUMBER	30		Y	
SBUD_PARTNER_ID	NUMBER	30		Y	
SBUD_IMPORTED	NUMBER	1		N	

## SFFD

### Sales force field details

Field Name	Type	Length	Decimals	Not NULL	
SFFD_ID	NUMBER	30		N	
SFFD_ROLE	NUMBER	2		N	Salesforce object type 1.Account , 2.Contact, 3.User, 4.Oppertunity
SFFD_FIELD_NAME	VARCHAR2	30		Y	Sales force Field Name
SFFD_FIELD_LABEL	VARCHAR2	100		Y	
SFFD_FIELD_TYPE	NUMBER	2		Y	Sales force Field Type 1.string, 2. number. 3.currency
SFFD_MAXLENGTH	NUMBER	5		Y	Maximum Field Length
SFFD_MANDATORY_FIELD	NUMBER	1		Y	Mandatory flag
SFFD_CUSTOM_FIELD	NUMBER	1		Y	Custom field
SFFD_PICKLIST_FIELD	NUMBER	1		Y	
SFFD_REFERENCE_FIELD	NUMBER	1		Y	Linked field
SFFD_REFERENCE_TABLE	VARCHAR2	20		Y	Linked type
SFFD_EXTENDED_FIELD	NUMBER	1		Y	
SFFD_READONLY	NUMBER	1		Y	
SFFD_INACTIVE	NUMBER	1		Y	

## SFFV

Salesforce field values linked Suite8 fields

Field Name	Type	Length	Decimals	Not NULL	
SFFV_ID	NUMBER	30		N	
SFFV_TABLENAME	VARCHAR2	10		Y	Suite 8 Table Name
SFFV_RECID	NUMBER	30		Y	Suite8 Table Record id
SFFV_SFFD_ID	NUMBER	30		Y	linked SFFD id
SFFV_VALUE	VARCHAR2	1000		Y	Field Value

## SFOR

forecast table similar to shis history

Field Name	Type	Length	Decimals	Not NULL	
SFOR_ID	NUMBER	30		N	
SFOR_DATE	DATE			N	
SFOR_YRES_ID	NUMBER	30		Y	
SFOR_ZFAC_ID	NUMBER	30		Y	
SFOR_YDET_ID	NUMBER	30		Y	
SFOR_YRES_ACTARRTIME	DATE			Y	
SFOR_YRES_ACTDEPTIME	DATE			Y	
SFOR_YRES_EXPARRTIME	DATE			Y	
SFOR_YRES_EXPDEPTIME	DATE			Y	
SFOR_YRES_RESSTATUS	NUMBER	1		Y	
SFOR_YRES_NOAVAILREASON	NUMBER	1		Y	
SFOR_XCMS_ID	NUMBER	30		Y	
SFOR_GUESTNAME	VARCHAR2	35		Y	
SFOR_YCLN_1_XCMS_ID	NUMBER	30		Y	
SFOR_COMPANYNAME	VARCHAR2	35		Y	
SFOR_YCLN_2_XCMS_ID	NUMBER	30		Y	
SFOR_TAGENTNAME	VARCHAR2	35		Y	
SFOR_YCLN_3_XCMS_ID	NUMBER	30		Y	
SFOR_SOURCENAME	VARCHAR2	35		Y	
SFOR_YCLN_4_XCMS_ID	NUMBER	30		Y	
SFOR_INDINAME	VARCHAR2	35		Y	
SFOR_YCLN_5_XCMS_ID	NUMBER	30		Y	
SFOR_VENDNAME	VARCHAR2	35		Y	
SFOR_YCLN_6_XCMS_ID	NUMBER	30		Y	

## SFOR

forecast table similar to shis history

Field Name	Type	Length	Decimals	Not NULL
SFOR_MPLANNAME	VARCHAR2	35		Y
SFOR_YCLN_7_XCMS_ID	NUMBER	30		Y
SFOR_BOOKERNAME	VARCHAR2	35		Y
SFOR_YDET_YGRP_ID	NUMBER	30		Y
SFOR_GROUPNAME	VARCHAR2	30		Y
SFOR_YBLH_ID	NUMBER	30		Y
SFOR_YBLH_SHORTDESC	VARCHAR2	10		Y
SFOR_YDET_YRMS_ID	NUMBER	30		Y
SFOR_YRMS_SHORTDESC	VARCHAR2	10		Y
SFOR_YDET_YCAT_ID	NUMBER	30		Y
SFOR_YCAT_SHORTDESC	VARCHAR2	5		Y
SFOR_YDET_YRCH_ID	NUMBER	30		Y
SFOR_YRCH_SHORTDESC	VARCHAR2	10		Y
SFOR_YDET_XCMA_ID	NUMBER	30		Y
SFOR_XCMA_SHORTDESC	VARCHAR2	3		Y
SFOR_SOURCE_ID	NUMBER	30		Y
SFOR_SOURCE	VARCHAR2	30		Y
SFOR_CHANNEL_ID	NUMBER	30		Y
SFOR_CHANNEL	VARCHAR2	30		Y
SFOR_YDET_ADULTNO	NUMBER	3		Y
SFOR_YDET_SHARENUM	NUMBER	30		Y
SFOR_TOTALYRGL_NUMBER	NUMBER	30	4	Y
SFOR_GROSSROOMREV	NUMBER	30	4	Y
SFOR_NETROOMREV	NUMBER	30	4	Y
SFOR_GROSSFBREV	NUMBER	30	4	Y
SFOR_NETFBREV	NUMBER	30	4	Y
SFOR_GROSSMINIBARREV	NUMBER	30	4	Y
SFOR_NETMINIBARREV	NUMBER	30	4	Y
SFOR_GROSSTELEREV	NUMBER	30	4	Y
SFOR_NETTELEREV	NUMBER	30	4	Y
SFOR_GROSSMISCREV	NUMBER	30	4	Y
SFOR_NETMISCREV	NUMBER	30	4	Y
SFOR_NETREV	NUMBER	30	4	Y

## SFOR

forecast table similar to shis history

Field Name	Type	Length	Decimals	Not NULL
SFOR_GROSSREV	NUMBER	30	4	Y
SFOR_ARR_ID	NUMBER	1		Y
SFOR_DEP_ID	NUMBER	1		Y
SFOR_YDET_NOOFROOMS	NUMBER	3		Y
SFOR_XCOU_ID	NUMBER	30		Y
SFOR_HOTELCODE	VARCHAR2	5		Y
SFOR_WPHS_ID	NUMBER	30		Y
SFOR_PARTNER_ID	NUMBER	30		Y
SFOR_IMPORTED	NUMBER	1		N
SFOR_YRCH_COMPSTATUS	NUMBER	1		Y
SFOR_VIPCODE	VARCHAR2	3		Y
SFOR_VIPCODE_LONGDESC	VARCHAR2	30		Y
SFOR_YBOM_ID	NUMBER	30		Y
SFOR_XSTA_ID	NUMBER	30		Y

## SFPV

Salesforce Pickup Values

Field Name	Type	Length	Decimals	Not NULL	
SFPV_ID	NUMBER	30		N	
SFPV_SFFD_ID	NUMBER	30		Y	linked SFFD_id
SFPV_DESCRIPTION	VARCHAR2	100		Y	Pick up option Description
SFPV_VALUE	VARCHAR2	100		Y	Pickup value

## SFTX

Folio Tax

Field Name	Type	Length	Decimals	Not NULL	
SFTX_ID	NUMBER	30		N	Unique Identifier
SFTX_ZTXC_ID0	NUMBER	30		Y	Link to Tax Setup
SFTX_NET0	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX0	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID1	NUMBER	30		Y	Link to Tax Setup
SFTX_NET1	NUMBER	30	4	Y	Net Amount for this Tax Code

## SFTX

Folio Tax

Field Name	Type	Length	Decimals	Not NULL	Description
SFTX_TAX1	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID2	NUMBER	30		Y	Link to Tax Setup
SFTX_NET2	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX2	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID3	NUMBER	30		Y	Link to Tax Setup
SFTX_NET3	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX3	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID4	NUMBER	30		Y	Link to Tax Setup
SFTX_NET4	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX4	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID5	NUMBER	30		Y	Link to Tax Setup
SFTX_NET5	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX5	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID6	NUMBER	30		Y	Link to Tax Setup
SFTX_NET6	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX6	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID7	NUMBER	30		Y	Link to Tax Setup
SFTX_NET7	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX7	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID8	NUMBER	30		Y	Link to Tax Setup
SFTX_NET8	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX8	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_ZTXC_ID9	NUMBER	30		Y	Link to Tax Setup
SFTX_NET9	NUMBER	30	4	Y	Net Amount for this Tax Code
SFTX_TAX9	NUMBER	30	4	Y	Tax Amount for this Tax Code
SFTX_FOLIONUMBER	VARCHAR2	60		N	Folio Number
SFTX_LASTREVISION	NUMBER	1		Y	Last Revision of this Folio Number
SFTX_TOTAL	NUMBER	30	4	N	Total Amount
SFTX_ROOM	VARCHAR2	30		N	Room Number
SFTX_INVOICE_TO_XCMS_ID	NUMBER	30		Y	Guest ID to whom the invoice was charged
SFTX_XCMS_ID	NUMBER	30		Y	Guest ID
SFTX_PAYMENT	VARCHAR2	100		Y	Payment
SFTX_DATE	DATE			Y	Date

## SFTX

Folio Tax

Field Name	Type	Length	Decimals	Not NULL	
SFTX_ZWIN_ID	NUMBER	30		Y	Link to billing window
SFTX_ZINV_ID	NUMBER	30		Y	Link to invoice history

## SHIB

History Matrix for CCM Bookings

Field Name	Type	Length	Decimals	Not NULL	
SHIB_ID	NUMBER	30		N	Unique ID
SHIB_WDAT_DATE	DATE			N	WDAT_DATE
SHIB_YBOM_ID	NUMBER	30		Y	Booking ID
SHIB_ZFAC_ID	NUMBER	30		Y	Financial Account ID
SHIB_YBOM_ARRIVAL	DATE			Y	Arrival Date
SHIB_YBOM_DEPARTURE	DATE			Y	Departure Date
SHIB_YBOM_ARRIVAL_F	NUMBER	3		Y	1= First Day
SHIB_YBOM_DEPARTURE_F	NUMBER	3		Y	1= Last Day
SHIB_YBOM_CON_YEST_ID	NUMBER	30		Y	Conference Status ID
SHIB_YBOM_CON_YEST_SHORTDEVARCHAR2 SC		3		Y	Conference Status Code
SHIB_YBOM_RMS_YEST_ID	NUMBER	30		Y	Rooms Status ID
SHIB_YBOM_RMS_YEST_SHORTDEVARCHAR2 SC		3		Y	Rooms Status Code
SHIB_YBOM_XCMS_ID	NUMBER	30		Y	Company ID
SHIB_YBOM_COMPANY	VARCHAR2	35		Y	Company Name
SHIB_YBOM_IND_XCMS_ID	NUMBER	30		Y	Contact ID
SHIB_YBOM_CONTACT	VARCHAR2	35		Y	Contact Name
SHIB_YBOM_NOOFATTENDEES	NUMBER	5		Y	No. of attendees
SHIB_YBML_1_XCMS_ID	NUMBER	30		Y	Linked Company Profile ID. If more than 1 company has been linked ONLY the first linked company will be considered.
SHIB_COMPANYNAME	VARCHAR2	35		Y	Linked Company Name. If more than 1 company has been linked ONLY the first linked company will be considered.
SHIB_YBML_2_XCMS_ID	NUMBER	30		Y	Linked Travel Agent Profile ID. If more than 1 travel agent has been linked ONLY the first linked travel agent will be considered.
SHIB_TAGENTNAME	VARCHAR2	35		Y	Linked Travel Agent Name. If more than 1 travel agent has been linked ONLY the first linked travel agent will be considered.
SHIB_YBML_3_XCMS_ID	NUMBER	30		Y	Linked Source Profile ID. If more than 1 source has been linked ONLY the first linked source will be considered.
SHIB_SOURCENAME	VARCHAR2	35		Y	Linked Source Name. If more than 1 source has been linked ONLY the first linked source will be considered.
SHIB_YBML_4_XCMS_ID	NUMBER	30		Y	Linked Individual Profile ID. If more than 1 individual has been linked ONLY the first linked individual will be considered.

## SHIB

History Matrix for CCM Bookings

Field Name	Type	Length	Decimals	Not NULL	Description
SHIB_INDNAME	VARCHAR2	35		Y	Linked Individual Name. If more than 1 individual has been linked ONLY the first linked individual will be considered.
SHIB_YBML_5_XCMS_ID	NUMBER	30		Y	Linked Vendor Profile ID. If more than 1 vendor has been linked ONLY the first linked vendor will be considered.
SHIB_VENDNAME	VARCHAR2	35		Y	Linked Vendor Name. If more than 1 vendor has been linked ONLY the first linked vendor will be considered.
SHIB_YBML_6_XCMS_ID	NUMBER	30		Y	Linked Meeting Planner Profile ID
SHIB_MPLANNAME	VARCHAR2	35		Y	Linked Meeting Planner Name
SHIB_YBML_7_XCMS_ID	NUMBER	30		Y	Linked Booker Profile ID
SHIB_BOOKERNAME	VARCHAR2	35		Y	Linked Booker Profile Name
SHIB_YGRP_ID	NUMBER	30		Y	Linked Group ID
SHIB_YGRP_NAME	VARCHAR2	60		Y	Linked Group Name
SHIB_YBLH_ID	NUMBER	30		Y	Linked Block ID
SHIB_YBLH_SHORTDESC	VARCHAR2	10		Y	Linked Block Code
SHIB_YBOM_YFTY_ID	NUMBER	30		Y	Linked Function Type ID
SHIB_YFTY_SHORTDESC	VARCHAR2	3		Y	Linked Function Type Code
SHIB_YFTY_LONGDESC	VARCHAR2	30		Y	Linked Function Type Description
SHIB_YBOM_XCMA_ID	NUMBER	30		Y	Linked Market Segment ID
SHIB_XCMA_SHORTDESC	VARCHAR2	3		Y	Linked Market Segment Code
SHIB_XCMA_LONGDESC	VARCHAR2	30		Y	Linked Market Segment Description
SHIB_YBOM_YRAS_ID	NUMBER	30		Y	Linked Source ID
SHIB_YRAS_SHORTDESC	VARCHAR2	3		Y	Linked Source Code
SHIB_YRAS_LONGDESC	VARCHAR2	30		Y	Linked Source Description
SHIB_XCED_ID_ACC	NUMBER	30		Y	Linked Account Mgr. ID
SHIB_XCED_INITIALS_ACC	VARCHAR2	3		Y	Linked Account Mgr. Initial
SHIB_XCED_NAME_ACC	VARCHAR2	75		Y	Linked Account Mgr. Name
SHIB_XCED_ID_CONF	NUMBER	30		Y	Linked Conference Mgr. ID
SHIB_XCED_INITIALS_CONF	VARCHAR2	3		Y	Linked Conference Mgr. Initial
SHIB_XCED_NAME_CONF	VARCHAR2	75		Y	Linked Conference Mgr. Name
SHIB_XCED_ID_RMS	NUMBER	30		Y	Linked Rooms Mgr. ID
SHIB_XCED_INITIALS_RMS	VARCHAR2	3		Y	Linked Rooms Mgr. Initial
SHIB_XCED_NAME_RMS	VARCHAR2	75		Y	Linked Rooms Mgr. Name
SHIB_POSTED_GROSSREV	NUMBER	30	4	Y	Gross Posted of booking
SHIB_POSTED_NETREV	NUMBER	30	4	Y	Net Posted of booking
SHIB_GROSSROOMREV	NUMBER	30	4	Y	Gross Revenue Rooms (ZDCO_STATS_TYPE=1)

## SHIB

History Matrix for CCM Bookings

Field Name	Type	Length	Decimals	Not NULL	
SHIB_NETROOMREV	NUMBER	30	4	Y	Net Revenue Rooms (ZDCO_STATS_TYPE=1)
SHIB_GROSSFBREV	NUMBER	30	4	Y	Gross Revenue Food and Beverage (ZDCO_STATS_TYPE=2)
SHIB_NETFBREV	NUMBER	30	4	Y	Net Revenue Food and Beverage (ZDCO_STATS_TYPE=2)
SHIB_GROSSMISCREV	NUMBER	30	4	Y	Gross Revenue Miscellaneous (ZDCO_STATS_TYPE=5)
SHIB_NETMISCREV	NUMBER	30	4	Y	Gross Revenue Miscellaneous (ZDCO_STATS_TYPE=5)
SHIB_GROSSMINIBARREV	NUMBER	30	4	Y	Gross Revenue Minibar (ZDCO_STATS_TYPE=3)
SHIB_NETMINIBARREV	NUMBER	30	4	Y	Net Revenue Food and Beverage (ZDCO_STATS_TYPE=3)
SHIB_GROSSTELEREV	NUMBER	30	4	Y	Gross Revenue Telephone (ZDCO_STATS_TYPE=4)
SHIB_NETTELEREV	NUMBER	30	4	Y	Net Revenue Telephone (ZDCO_STATS_TYPE=4)
SHIB_XCOU_ID	NUMBER	30		Y	Country ID of Booker
SHIB_WPHS_ID	NUMBER	30		Y	Unique ID of partner hotel (Hotel Connector)
SHIB_PARTNER_ID	NUMBER	30		Y	SHIB_ID of Partner Hotel (Hotel Connector)
SHIB_IMPORTED	NUMBER	1		Y	Import control flag
SHIB_SHIS_XCMS_ID	NUMBER	30		Y	XCMS_ID from SHIS
SHIB_SHIS_GUESTNAME	VARCHAR2	35		Y	GUESTNAME from SHIS
SHIB_YRES_ID	NUMBER	30		Y	YRES_ID from SHIS

## SHIE

History Matrix for CCM Events

Field Name	Type	Length	Decimals	Not NULL	
SHIE_ID	NUMBER	30		N	Unique ID
SHIE_WDAT_DATE	DATE			N	WDAT_DATE. Start date of event. Only 1 records for each event.
SHIE_YBOM_ID	NUMBER	30		Y	Booking ID
SHIE_YEVM_ID	NUMBER	30		Y	Event ID
SHIE_YBOM_ZFAC_ID	NUMBER	30		Y	Booking Financial Account ID
SHIE_YEVM_STARTTIME	DATE			Y	Event Start Date
SHIE_YEVM_ENDTIME	DATE			Y	Event Start Date
SHIE_YEVM_YEST_ID	NUMBER	30		Y	Event Status ID
SHIE_YEST_SHORTDESC	VARCHAR2	3		Y	Event Status Code
SHIE_YEVM_NOOFATTENDEES	NUMBER	5		Y	No. of attendees
SHIE_YEVM_YETY_ID	NUMBER	30		Y	Linked Event Type
SHIE_YETY_SHORTDESC	VARCHAR2	3		Y	Event Type Code
SHIE_YETY_LONGDESC	VARCHAR2	30		Y	Event Type Description

## SHIE

History Matrix for CCM Events

Field Name	Type	Length	Decimals	Not NULL	
SHIE_POSTED_GROSSREV	NUMBER	30	4	Y	Gross Posted of event
SHIE_POSTED_NETREV	NUMBER	30	4	Y	Net Posted of event
SHIE_GROSSROOMREV	NUMBER	30	4	Y	Gross Revenue Rooms (ZDCO_STATS_TYPE=1)
SHIE_NETROOMREV	NUMBER	30	4	Y	Net Revenue Rooms (ZDCO_STATS_TYPE=1)
SHIE_GROSSFBREV	NUMBER	30	4	Y	Gross Revenue Food and Beverage (ZDCO_STATS_TYPE=2)
SHIE_NETFBREV	NUMBER	30	4	Y	Net Revenue Food and Beverage (ZDCO_STATS_TYPE=2)
SHIE_GROSSMISCREV	NUMBER	30	4	Y	Gross Revenue Miscellaneous (ZDCO_STATS_TYPE=5)
SHIE_NETMISCREV	NUMBER	30	4	Y	Gross Revenue Miscellaneous (ZDCO_STATS_TYPE=5)
SHIE_GROSSMINIBARREV	NUMBER	30	4	Y	Gross Revenue Minibar (ZDCO_STATS_TYPE=3)
SHIE_NETMINIBARREV	NUMBER	30	4	Y	Net Revenue Minibar (ZDCO_STATS_TYPE=3)
SHIE_GROSSTELEREV	NUMBER	30	4	Y	Gross Revenue Telephone (ZDCO_STATS_TYPE=4)
SHIE_NETTELEREV	NUMBER	30	4	Y	Net Revenue Telephone (ZDCO_STATS_TYPE=4)
SHIE_WPHS_ID	NUMBER	30		Y	Unique ID of partner hotel (Hotel Connector)
SHIE_PARTNER_ID	NUMBER	30		Y	SHIE_ID of Partner Hotel (Hotel Connector)
SHIE_IMPORTED	NUMBER	1		Y	Import control flag

## SHIS

History Matrix for several statistics

Field Name	Type	Length	Decimals	Not NULL	
SHIS_ID	NUMBER	30		N	SHIS_ID identifies SHIS
SHIS_WDAT_DATE	DATE			N	SHIS_WDAT_DATE is of SHIS
SHIS_YRES_ID	NUMBER	30		Y	SHIS_YRES_ID is of SHIS
SHIS_ZFAC_ID	NUMBER	30		Y	SHIS_ZFAC_ID is of SHIS
SHIS_YDET_ID	NUMBER	30		Y	SHIS_YDET_ID is of SHIS
SHIS_YRES_ACTARRTIME	DATE			Y	SHIS_YRES_ACTARRTIME is of SHIS
SHIS_YRES_ACTDEPTIME	DATE			Y	SHIS_YRES_ACTDEPTIME is of SHIS
SHIS_YRES_EXPARRTIME	DATE			Y	SHIS_YRES_EXPARRTIME is of SHIS
SHIS_YRES_EXPDEPTIME	DATE			Y	SHIS_YRES_EXPDEPTIME is of SHIS
SHIS_YRES_RESSTATUS	NUMBER	1		Y	SHIS_YRES_RESSTATUS is of SHIS
SHIS_YRES_NOAVAILREASON	NUMBER	1		Y	SHIS_YRES_NOAVAILREASON is of SHIS
SHIS_XCMS_ID	NUMBER	30		Y	SHIS_XCMS_ID is of SHIS
SHIS_GUESTNAME	VARCHAR2	35		Y	SHIS_GUESTNAME is of SHIS
SHIS_YCLN_1_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_1_XCMS_ID is of SHIS

## SHIS

History Matrix for several statistics

Field Name	Type	Length	Decimals	Not NULL	
SHIS_COMPANYNAME	VARCHAR2	35		Y	SHIS_COMPANYNAME is of SHIS
SHIS_YCLN_2_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_2_XCMS_ID is of SHIS
SHIS_TAGENTNAME	VARCHAR2	35		Y	SHIS_TAGENTNAME is of SHIS
SHIS_YCLN_3_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_3_XCMS_ID is of SHIS
SHIS_SOURCENAME	VARCHAR2	35		Y	SHIS_SOURCENAME is of SHIS
SHIS_YCLN_4_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_4_XCMS_ID is of SHIS
SHIS_INDINAME	VARCHAR2	35		Y	SHIS_INDINAME is of SHIS
SHIS_YCLN_5_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_5_XCMS_ID is of SHIS
SHIS_VENDNAME	VARCHAR2	35		Y	SHIS_VENDNAME is of SHIS
SHIS_YCLN_6_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_6_XCMS_ID is of SHIS
SHIS_MPLANNAME	VARCHAR2	35		Y	SHIS_MPLANNAME is of SHIS
SHIS_YCLN_7_XCMS_ID	NUMBER	30		Y	SHIS_YCLN_7_XCMS_ID is of SHIS
SHIS_BOOKERNAME	VARCHAR2	35		Y	SHIS_BOOKERNAME is of SHIS
SHIS_YDET_YGRP_ID	NUMBER	30		Y	SHIS_YDET_YGRP_ID is of SHIS
SHIS_GROUPNAME	VARCHAR2	30		Y	SHIS_GROUPNAME is of SHIS
SHIS_YBLH_ID	NUMBER	30		Y	SHIS_YBLH_ID is of SHIS
SHIS_YBLH_SHORTDESC	VARCHAR2	10		Y	SHIS_YBLH_SHORTDESC is of SHIS
SHIS_YDET_YRMS_ID	NUMBER	30		Y	SHIS_YDET_YRMS_ID is of SHIS
SHIS_YRMS_SHORTDESC	VARCHAR2	10		Y	SHIS_YRMS_SHORTDESC is of SHIS
SHIS_YDET_YCAT_ID	NUMBER	30		Y	SHIS_YDET_YCAT_ID is of SHIS
SHIS_YCAT_SHORTDESC	VARCHAR2	5		Y	SHIS_YCAT_SHORTDESC is of SHIS
SHIS_YDET_YRCH_ID	NUMBER	30		Y	SHIS_YDET_YRCH_ID is of SHIS
SHIS_YRCH_SHORTDESC	VARCHAR2	10		Y	SHIS_YRCH_SHORTDESC is of SHIS
SHIS_YDET_XCMA_ID	NUMBER	30		Y	SHIS_YDET_XCMA_ID is of SHIS
SHIS_XCMA_SHORTDESC	VARCHAR2	3		Y	SHIS_XCMA_SHORTDESC is of SHIS
SHIS_SOURCE_ID	NUMBER	30		Y	SHIS_SOURCE_ID is of SHIS
SHIS_SOURCE	VARCHAR2	30		Y	SHIS_SOURCE is of SHIS
SHIS_CHANNEL_ID	NUMBER	30		Y	SHIS_CHANNEL_ID is of SHIS
SHIS_CHANNEL	VARCHAR2	30		Y	SHIS_CHANNEL is of SHIS
SHIS_YDET_ADULTNO	NUMBER	3		Y	SHIS_YDET_ADULTNO is of SHIS
SHIS_YDET_SHARENUM	NUMBER	30		Y	SHIS_YDET_SHARENUM is of SHIS
SHIS_TOTALYRGL_NUMBER	NUMBER	3		Y	SHIS_TOTALYRGL_NUMBER is of SHIS
SHIS_GROSSROOMREV	NUMBER	30	4	Y	SHIS_GROSSROOMREV is of SHIS

## SHIS

History Matrix for several statistics

Field Name	Type	Length	Decimals	Not NULL	
SHIS_NETROOMREV	NUMBER	30	4	Y	SHIS_NETROOMREV is of SHIS
SHIS_GROSSFBREV	NUMBER	30	4	Y	SHIS_GROSSFBREV is of SHIS
SHIS_NETFBREV	NUMBER	30	4	Y	SHIS_NETFBREV is of SHIS
SHIS_GROSSMINIBARREV	NUMBER	30	4	Y	SHIS_GROSSMINIBARREV is of SHIS
SHIS_NETMINIBARREV	NUMBER	30	4	Y	SHIS_NETMINIBARREV is of SHIS
SHIS_GROSSTELEREV	NUMBER	30	4	Y	SHIS_GROSSTELEREV is of SHIS
SHIS_NETTELEREV	NUMBER	30	4	Y	SHIS_NETTELEREV is of SHIS
SHIS_GROSSMISCREV	NUMBER	30	4	Y	SHIS_GROSSMISCREV is of SHIS
SHIS_NETMISCREV	NUMBER	30	4	Y	SHIS_NETMISCREV is of SHIS
SHIS_NETREV	NUMBER	30	4	Y	SHIS_NETREV is of SHIS
SHIS_GROSSREV	NUMBER	30	4	Y	SHIS_GROSSREV is of SHIS
SHIS_ARR_ID	NUMBER	1		Y	SHIS_ARR_ID is of SHIS
SHIS_DEP_ID	NUMBER	1		Y	SHIS_DEP_ID is of SHIS
SHIS_YDET_NOOFROOMS	NUMBER	3		Y	SHIS_YDET_NOOFROOMS is of SHIS
SHIS_XCOU_ID	NUMBER	30		Y	SHIS_XCOU_ID is of SHIS
SHIS_WPHS_ID	NUMBER	30		Y	Unique ID of partner hotel (Hotel Connector)
SHIS_PARTNER_ID	NUMBER	30		Y	Partner Hotel ID (spare field for Hotel Connector)
SHIS_IMPORTED	NUMBER	1		N	Import control flag
SHIS_YRCH_COMPSTATUS	NUMBER	1		Y	
SHIS_VIPCODE	VARCHAR2	3		Y	
SHIS_VIPCODE_LONGDESC	VARCHAR2	30		Y	
SHIS_YBOM_ID	NUMBER	30		Y	
SHIS_XSTA_ID	NUMBER	30		Y	
SHIS_YDET_YCAT_ID_RATE	NUMBER	30		Y	
SHIS_YCAT_SHORTDESC_RATE	VARCHAR2	30		Y	

## SMAD

Field Name	Type	Length	Decimals	Not NULL	
SMAD_ID	NUMBER	30		N	
SMAD_DATE	DATE			N	
SMAD_YCAD_ID	NUMBER	30		N	
SMAD_ADULTS_D	NUMBER	5		Y	

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_ADULTS_M	NUMBER	5		Y
SMAD_ADULTS_Y	NUMBER	7		Y
SMAD_CHILDS_D	NUMBER	5		Y
SMAD_CHILDS_M	NUMBER	5		Y
SMAD_CHILDS_Y	NUMBER	7		Y
SMAD_ROOMS_OCC_D	NUMBER	5		Y
SMAD_ROOMS_OCC_M	NUMBER	5		Y
SMAD_ROOMS_OCC_Y	NUMBER	7		Y
SMAD_ROOMSINHOTEL_D	NUMBER	5		Y
SMAD_ROOMSINHOTEL_M	NUMBER	5		Y
SMAD_ROOMSINHOTEL_Y	NUMBER	7		Y
SMAD_ROOMS_OOO_D	NUMBER	5		Y
SMAD_ROOMS_OOO_M	NUMBER	5		Y
SMAD_ROOMS_OOO_Y	NUMBER	7		Y
SMAD_WALKIN_D	NUMBER	5		Y
SMAD_WALKIN_M	NUMBER	5		Y
SMAD_WALKIN_Y	NUMBER	7		Y
SMAD_ARR_ROOMS_D	NUMBER	5		Y
SMAD_ARR_ROOMS_M	NUMBER	5		Y
SMAD_ARR_ROOMS_Y	NUMBER	7		Y
SMAD_DEP_ROOMS_D	NUMBER	5		Y
SMAD_DEP_ROOMS_M	NUMBER	5		Y
SMAD_DEP_ROOMS_Y	NUMBER	7		Y
SMAD_ARR_ADULTS_D	NUMBER	5		Y
SMAD_ARR_ADULTS_M	NUMBER	5		Y
SMAD_ARR_ADULTS_Y	NUMBER	7		Y
SMAD_ARR_CHILDS_D	NUMBER	5		Y
SMAD_ARR_CHILDS_M	NUMBER	5		Y
SMAD_ARR_CHILDS_Y	NUMBER	7		Y
SMAD_DEP_ADULTS_D	NUMBER	5		Y
SMAD_DEP_ADULTS_M	NUMBER	5		Y
SMAD_DEP_ADULTS_Y	NUMBER	7		Y
SMAD_DEP_CHILDS_D	NUMBER	5		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_DEP_CHILDS_M	NUMBER	5		Y
SMAD_DEP_CHILDS_Y	NUMBER	7		Y
SMAD_TOTALGROSSREV_D	NUMBER	30	4	Y
SMAD_TOTALGROSSREV_M	NUMBER	30	4	Y
SMAD_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMAD_TOTALNETREV_D	NUMBER	30	4	Y
SMAD_TOTALNETREV_M	NUMBER	30	4	Y
SMAD_TOTALNETREV_Y	NUMBER	30	4	Y
SMAD_COMPROOMS_D	NUMBER	5		Y
SMAD_COMPROOMS_M	NUMBER	5		Y
SMAD_COMPROOMS_Y	NUMBER	7		Y
SMAD_HOUSEUSERROOMS_D	NUMBER	5		Y
SMAD_HOUSEUSERROOMS_M	NUMBER	5		Y
SMAD_HOUSEUSERROOMS_Y	NUMBER	7		Y
SMAD_BEDSINHOTEL_D	NUMBER	5		Y
SMAD_BEDSINHOTEL_M	NUMBER	5		Y
SMAD_BEDSINHOTEL_Y	NUMBER	7		Y
SMAD_REPEATGUESTARRROOM_D	NUMBER	5		Y
SMAD_REPEATGUESTARRROOM_M	NUMBER	5		Y
SMAD_REPEATGUESTARRROOM_Y	NUMBER	7		Y
SMAD_RESMADETODAY_D	NUMBER	5		Y
SMAD_RESMADETODAY_M	NUMBER	5		Y
SMAD_RESMADETODAY_Y	NUMBER	7		Y
SMAD_RESCANCELEDTODAY_D	NUMBER	5		Y
SMAD_RESCANCELEDTODAY_M	NUMBER	5		Y
SMAD_RESCANCELEDTODAY_Y	NUMBER	7		Y
SMAD_ARRADULTSTOMORROW_D	NUMBER	5		Y
SMAD_DEPADULTSTOMORROW_D	NUMBER	5		Y
SMAD_ARRROOMSTOMORROW_D	NUMBER	5		Y
SMAD_DEPROOMSTOMORROW_D	NUMBER	5		Y
SMAD_COMPANY_ROOMS_D	NUMBER	5		Y
SMAD_COMPANY_ROOMS_M	NUMBER	5		Y
SMAD_COMPANY_ROOMS_Y	NUMBER	7		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMAD_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMAD_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_AGENT_ROOMS_D	NUMBER	5		Y
SMAD_AGENT_ROOMS_M	NUMBER	5		Y
SMAD_AGENT_ROOMS_Y	NUMBER	7		Y
SMAD_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMAD_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMAD_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_IND_ROOMS_D	NUMBER	5		Y
SMAD_IND_ROOMS_M	NUMBER	5		Y
SMAD_IND_ROOMS_Y	NUMBER	7		Y
SMAD_IND_REV_GROSS_D	NUMBER	30	4	Y
SMAD_IND_REV_GROSS_M	NUMBER	30	4	Y
SMAD_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_VIPADULTS_D	NUMBER	5		Y
SMAD_VIPADULTS_M	NUMBER	5		Y
SMAD_VIPADULTS_Y	NUMBER	7		Y
SMAD_PAYMENTS_D	NUMBER	30	4	Y
SMAD_PAYMENTS_M	NUMBER	30	4	Y
SMAD_PAYMENTS_Y	NUMBER	30	4	Y
SMAD_ROOMREVGROSS_D	NUMBER	30	4	Y
SMAD_ROOMREVGROSS_M	NUMBER	30	4	Y
SMAD_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMAD_ROOMREVNET_D	NUMBER	30	4	Y
SMAD_ROOMREVNET_M	NUMBER	30	4	Y
SMAD_ROOMREVNET_Y	NUMBER	30	4	Y
SMAD_CANCFORTODAY_D	NUMBER	5		Y
SMAD_CANCFORTODAY_M	NUMBER	5		Y
SMAD_CANCFORTODAY_Y	NUMBER	7		Y
SMAD_DEPNOTPAID_D	NUMBER	5		Y
SMAD_DEPNOTPAID_M	NUMBER	5		Y
SMAD_DEPNOTPAID_Y	NUMBER	7		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_NOSHOWROOMS_D	NUMBER	5		Y
SMAD_NOSHOWROOMS_M	NUMBER	5		Y
SMAD_NOSHOWROOMS_Y	NUMBER	7		Y
SMAD_DAYUSERROOMS_D	NUMBER	5		Y
SMAD_DAYUSERROOMS_M	NUMBER	5		Y
SMAD_DAYUSERROOMS_Y	NUMBER	7		Y
SMAD_MAXBEDSINHOTEL_D	NUMBER	5		Y
SMAD_MAXBEDSINHOTEL_M	NUMBER	5		Y
SMAD_MAXBEDSINHOTEL_Y	NUMBER	7		Y
SMAD_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMAD_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMAD_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMAD_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMAD_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMAD_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMAD_COMPANY_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_COMPANY_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_COMPANY_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMAD_ROOMNHTLREVNET_M	NUMBER	30	4	Y
SMAD_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_FBREVGROSS_D	NUMBER	30	4	Y
SMAD_FBREVGROSS_M	NUMBER	30	4	Y
SMAD_FBREVGROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_FBREVNET_D	NUMBER	30	4	Y
SMAD_FBREVNET_M	NUMBER	30	4	Y
SMAD_FBREVNET_Y	NUMBER	30	4	Y
SMAD_FBNHTLREVNET_D	NUMBER	30	4	Y
SMAD_FBNHTLREVNET_M	NUMBER	30	4	Y
SMAD_FBNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_OCCTOMORROW	NUMBER	30	4	Y
SMAD_OCCNEXTSEVENDAYS	NUMBER	30	4	Y
SMAD_OCCUNTILENDMONTH	NUMBER	30	4	Y
SMAD_OCCENDYEAR	NUMBER	30	4	Y
SMAD_OCCNEXTFOURWEEKS	NUMBER	30	4	Y
SMAD_SOURCE_ROOMS_D	NUMBER	5		Y
SMAD_SOURCE_ROOMS_M	NUMBER	5		Y
SMAD_SOURCE_ROOMS_Y	NUMBER	7		Y
SMAD_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMAD_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMAD_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_BOOKER_ROOMS_D	NUMBER	5		Y
SMAD_BOOKER_ROOMS_M	NUMBER	5		Y
SMAD_BOOKER_ROOMS_Y	NUMBER	7		Y
SMAD_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMAD_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMAD_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_VENDOR_ROOMS_D	NUMBER	5		Y
SMAD_VENDOR_ROOMS_M	NUMBER	5		Y
SMAD_VENDOR_ROOMS_Y	NUMBER	7		Y
SMAD_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMAD_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMAD_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_MPLANER_ROOMS_D	NUMBER	5		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_MPLANER_ROOMS_M	NUMBER	5		Y
SMAD_MPLANER_ROOMS_Y	NUMBER	7		Y
SMAD_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMAD_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMAD_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_MPLANER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_MPLANER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_MPLANER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_MINIREVGROSS_D	NUMBER	30	4	Y
SMAD_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_TELEREVGROSS_D	NUMBER	30	4	Y
SMAD_TELNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_MISCREVGROSS_D	NUMBER	30	4	Y
SMAD_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_MINIREVGROSS_M	NUMBER	30	4	Y
SMAD_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_TELEREVGROSS_M	NUMBER	30	4	Y
SMAD_TELNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_MISCREVGROSS_M	NUMBER	30	4	Y
SMAD_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_MINIREVGROSS_Y	NUMBER	30	4	Y
SMAD_MININHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_TELEREVGROSS_Y	NUMBER	30	4	Y
SMAD_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_MISCREVGROSS_Y	NUMBER	30	4	Y
SMAD_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_MINIREVNET_D	NUMBER	30	4	Y
SMAD_MININHTLREVNET_D	NUMBER	30	4	Y
SMAD_TELEREVNET_D	NUMBER	30	4	Y
SMAD_TELENHTLREVNET_D	NUMBER	30	4	Y
SMAD_MISCREVNET_D	NUMBER	30	4	Y
SMAD_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMAD_NOSTATREVNET_D	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMAD_MINIREVNET_M	NUMBER	30	4	Y
SMAD_MININHTLREVNET_M	NUMBER	30	4	Y
SMAD_TELEREVNET_M	NUMBER	30	4	Y
SMAD_TELENHTLREVNET_M	NUMBER	30	4	Y
SMAD_MISCREVNET_M	NUMBER	30	4	Y
SMAD_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMAD_NOSTATREVNET_M	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMAD_MINIREVNET_Y	NUMBER	30	4	Y
SMAD_MININHTLREVNET_Y	NUMBER	30	4	Y
SMAD_TELEREVNET_Y	NUMBER	30	4	Y
SMAD_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMAD_MISCREVNET_Y	NUMBER	30	4	Y
SMAD_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_NOSTATREVNET_Y	NUMBER	30	4	Y
SMAD_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_WALKEDFORTODAY_D	NUMBER	5		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_WALKEDFORTODAY_M	NUMBER	6		Y
SMAD_WALKEDFORTODAY_Y	NUMBER	7		Y
SMAD_RESWALKEDTODAY_D	NUMBER	5		Y
SMAD_RESWALKEDTODAY_M	NUMBER	6		Y
SMAD_RESWALKEDTODAY_Y	NUMBER	7		Y
SMAD_DOMESTICCHILDS_D	NUMBER	5		Y
SMAD_DOMESTICCHILDS_M	NUMBER	5		Y
SMAD_DOMESTICCHILDS_Y	NUMBER	5		Y
SMAD_ARR_DOMESTICCHILDS_D	NUMBER	5		Y
SMAD_ARR_DOMESTICCHILDS_M	NUMBER	5		Y
SMAD_ARR_DOMESTICCHILDS_Y	NUMBER	5		Y
SMAD_DEP_DOMESTICCHILDS_D	NUMBER	5		Y
SMAD_DEP_DOMESTICCHILDS_M	NUMBER	5		Y
SMAD_DEP_DOMESTICCHILDS_Y	NUMBER	5		Y
SMAD_OCCNEXTFOURWEEKS_D	NUMBER	30	4	Y
SMAD_OCCTOMORROW_D	NUMBER	30	4	Y
SMAD_OCCNEXTSEVENDAYS_D	NUMBER	30	4	Y
SMAD_OCCUNTILENDMONTH_D	NUMBER	30	4	Y
SMAD_OCCENDYEAR_D	NUMBER	30	4	Y
SMAD_OCCNEXTFOURWEEKS_T	NUMBER	30	4	Y
SMAD_OCCTOMORROW_T	NUMBER	30	4	Y
SMAD_OCCNEXTSEVENDAYS_T	NUMBER	30	4	Y
SMAD_OCCUNTILENDMONTH_T	NUMBER	30	4	Y
SMAD_OCCENDYEAR_T	NUMBER	30	4	Y
SMAD_DAYCOUNT	NUMBER	5		Y
SMAD_PARTNER_ID	NUMBER	30		Y
SMAD_IMPORTED	NUMBER	1		Y
SMAD_WPHS_ID	NUMBER	30		Y
SMAD_ROOMS_OOS_D	NUMBER	5		Y
SMAD_ROOMS_OOS_M	NUMBER	5		Y
SMAD_ROOMS_OOS_Y	NUMBER	7		Y
SMAD_ROOMS_OCC_DFS_D	NUMBER	5		Y
SMAD_ROOMS_OCC_DFS_M	NUMBER	5		Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_ROOMS_OCC_DFS_Y	NUMBER	7		Y
SMAD_COMP_ADULTS_D	NUMBER	5		Y
SMAD_COMP_ADULTS_M	NUMBER	5		Y
SMAD_COMP_ADULTS_Y	NUMBER	7		Y
SMAD_COMP_CHILDS_D	NUMBER	5		Y
SMAD_COMP_CHILDS_M	NUMBER	5		Y
SMAD_COMP_CHILDS_Y	NUMBER	7		Y
SMAD_ARRCHILDSTOMORROW_D	NUMBER	5		Y
SMAD_DEPCHILDSTOMORROW_D	NUMBER	5		Y
SMAD_D_TOTALGROSSREV_D	NUMBER	30	4	Y
SMAD_D_TOTALGROSSREV_M	NUMBER	30	4	Y
SMAD_D_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMAD_D_TOTALNETREV_D	NUMBER	30	4	Y
SMAD_D_TOTALNETREV_M	NUMBER	30	4	Y
SMAD_D_TOTALNETREV_Y	NUMBER	30	4	Y
SMAD_D_PAYMENTS_D	NUMBER	30	4	Y
SMAD_D_PAYMENTS_M	NUMBER	30	4	Y
SMAD_D_PAYMENTS_Y	NUMBER	30	4	Y
SMAD_D_ROOMREVGROSS_D	NUMBER	30	4	Y
SMAD_D_ROOMREVGROSS_M	NUMBER	30	4	Y
SMAD_D_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_ROOMREVNET_D	NUMBER	30	4	Y
SMAD_D_ROOMREVNET_M	NUMBER	30	4	Y
SMAD_D_ROOMREVNET_Y	NUMBER	30	4	Y
SMAD_D_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMAD_D_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMAD_D_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMAD_D_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMAD_D_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMAD_D_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMAD_D_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_D_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_ROOMNHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_D_FBREVGROSS_D	NUMBER	30	4	Y
SMAD_D_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_FBREVNET_D	NUMBER	30	4	Y
SMAD_D_FBNHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_FBREVGROSS_M	NUMBER	30	4	Y
SMAD_D_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_FBREVNET_M	NUMBER	30	4	Y
SMAD_D_FBNHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_FBREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_FBREVNET_Y	NUMBER	30	4	Y
SMAD_D_FBNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_D_MINIREVGROSS_D	NUMBER	30	4	Y
SMAD_D_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_TELEREVGROSS_D	NUMBER	30	4	Y
SMAD_D_TELENHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_MISCREVGROSS_D	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_D_MINIREVGROSS_M	NUMBER	30	4	Y
SMAD_D_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_TELEREVGROSS_M	NUMBER	30	4	Y
SMAD_D_TELENHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_MISCREVGROSS_M	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_D_MINIREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_MININHTLREVGROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_D_TELEREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_MISCREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_D_MINIREVNET_D	NUMBER	30	4	Y
SMAD_D_MININHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_TELEREVNET_D	NUMBER	30	4	Y
SMAD_D_TELENHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_MISCREVNET_D	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_NOSTATREVNET_D	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMAD_D_MINIREVNET_M	NUMBER	30	4	Y
SMAD_D_MININHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_TELEREVNET_M	NUMBER	30	4	Y
SMAD_D_TELENHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_MISCREVNET_M	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_NOSTATREVNET_M	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMAD_D_MINIREVNET_Y	NUMBER	30	4	Y
SMAD_D_MININHTLREVNET_Y	NUMBER	30	4	Y
SMAD_D_TELEREVNET_Y	NUMBER	30	4	Y
SMAD_D_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMAD_D_MISCREVNET_Y	NUMBER	30	4	Y
SMAD_D_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_D_NOSTATREVNET_Y	NUMBER	30	4	Y
SMAD_D_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_V_TOTALGROSSREV_D	NUMBER	30	4	Y
SMAD_V_TOTALGROSSREV_M	NUMBER	30	4	Y
SMAD_V_TOTALGROSSREV_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_V_TOTALNETREV_D	NUMBER	30	4	Y
SMAD_V_TOTALNETREV_M	NUMBER	30	4	Y
SMAD_V_TOTALNETREV_Y	NUMBER	30	4	Y
SMAD_V_PAYMENTS_D	NUMBER	30	4	Y
SMAD_V_PAYMENTS_M	NUMBER	30	4	Y
SMAD_V_PAYMENTS_Y	NUMBER	30	4	Y
SMAD_V_ROOMREVGROSS_D	NUMBER	30	4	Y
SMAD_V_ROOMREVGROSS_M	NUMBER	30	4	Y
SMAD_V_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_ROOMREVNET_D	NUMBER	30	4	Y
SMAD_V_ROOMREVNET_M	NUMBER	30	4	Y
SMAD_V_ROOMREVNET_Y	NUMBER	30	4	Y
SMAD_V_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMAD_V_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMAD_V_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMAD_V_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMAD_V_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMAD_V_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVNET_M	NUMBER	30	4	Y
SMAD_V_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_V_FBREVGROSS_D	NUMBER	30	4	Y
SMAD_V_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_FBREVNET_D	NUMBER	30	4	Y
SMAD_V_FBNHTLREVNET_D	NUMBER	30	4	Y
SMAD_V_FBREVGROSS_M	NUMBER	30	4	Y
SMAD_V_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_FBREVNET_M	NUMBER	30	4	Y
SMAD_V_FBNHTLREVNET_M	NUMBER	30	4	Y
SMAD_V_FBREVGROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_V_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_FBREVNET_Y	NUMBER	30	4	Y
SMAD_V_FBNHTLREVNET_Y	NUMBER	30	4	Y
SMAD_V_MINIREVGROSS_D	NUMBER	30	4	Y
SMAD_V_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_TELEREVGROSS_D	NUMBER	30	4	Y
SMAD_V_TELENHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_MISCREVGROSS_D	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMAD_V_MINIREVGROSS_M	NUMBER	30	4	Y
SMAD_V_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_TELEREVGROSS_M	NUMBER	30	4	Y
SMAD_V_TELENHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_MISCREVGROSS_M	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMAD_V_MINIREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_MININHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_TELEREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_MISCREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAD_V_MINIREVNET_D	NUMBER	30	4	Y
SMAD_V_MININHTLREVNET_D	NUMBER	30	4	Y
SMAD_V_TELEREVNET_D	NUMBER	30	4	Y
SMAD_V_TELENHTLREVNET_D	NUMBER	30	4	Y
SMAD_V_MISCREVNET_D	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVNET_D	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_V_NOSTATREVNED_D	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVNED_D	NUMBER	30	4	Y
SMAD_V_MINIREVNED_M	NUMBER	30	4	Y
SMAD_V_MININHTLREVNED_M	NUMBER	30	4	Y
SMAD_V_TELEREVNED_M	NUMBER	30	4	Y
SMAD_V_TELENHTLREVNED_M	NUMBER	30	4	Y
SMAD_V_MISCREVNED_M	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVNED_M	NUMBER	30	4	Y
SMAD_V_NOSTATREVNED_M	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVNED_M	NUMBER	30	4	Y
SMAD_V_MINIREVNED_Y	NUMBER	30	4	Y
SMAD_V_MININHTLREVNED_Y	NUMBER	30	4	Y
SMAD_V_TELEREVNED_Y	NUMBER	30	4	Y
SMAD_V_TELENHTLREVNED_Y	NUMBER	30	4	Y
SMAD_V_MISCREVNED_Y	NUMBER	30	4	Y
SMAD_V_MISCNHTLREVNED_Y	NUMBER	30	4	Y
SMAD_V_NOSTATREVNED_Y	NUMBER	30	4	Y
SMAD_V_NOSTATNHTLREVNED_Y	NUMBER	30	4	Y
SMAD_D_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_IND_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_IND_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_COMPANY_NHTLREV_GR_OSS_D	NUMBER	30	4	Y
SMAD_D_COMPANY_NHTLREV_GR_OSS_M	NUMBER	30	4	Y
SMAD_D_COMPANY_NHTLREV_GR_OSS_Y	NUMBER	30	4	Y
SMAD_D_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_D_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMAD_D_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMAD_D_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_D_MPLANER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAD_D_MPLANER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAD_D_MPLANER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_AGENT_REV_GROSS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_V_IND_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_IND_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_COMPANY_NHTLREV_GR OSS_D	NUMBER	30	4	Y
SMAD_V_COMPANY_NHTLREV_GR OSS_M	NUMBER	30	4	Y
SMAD_V_COMPANY_NHTLREV_GR OSS_Y	NUMBER	30	4	Y
SMAD_V_AGENT_NHTLREV_GROS S_D	NUMBER	30	4	Y
SMAD_V_AGENT_NHTLREV_GROS S_M	NUMBER	30	4	Y
SMAD_V_AGENT_NHTLREV_GROS S_Y	NUMBER	30	4	Y
SMAD_V_IND_NHTLREV_GROSS_ D	NUMBER	30	4	Y
SMAD_V_IND_NHTLREV_GROSS_ M	NUMBER	30	4	Y
SMAD_V_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMAD_V_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMAD_V_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_MPLANER_REV_GROSS_ D	NUMBER	30	4	Y
SMAD_V_MPLANER_REV_GROSS_ M	NUMBER	30	4	Y
SMAD_V_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMAD_V_SOURCE_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAD_V_SOURCE_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAD_V_SOURCE_NHTLREV_GRO SS_Y	NUMBER	30	4	Y
SMAD_V_BOOKER_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAD_V_BOOKER_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAD_V_BOOKER_NHTLREV_GRO SS_Y	NUMBER	30	4	Y
SMAD_V_VENDOR_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAD_V_VENDOR_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAD_V_VENDOR_NHTLREV_GRO SS_Y	NUMBER	30	4	Y

## SMAD

Field Name	Type	Length	Decimals	Not NULL
SMAD_V_MPLANER_NHTLREV_GR OSS_D	NUMBER	30	4	Y
SMAD_V_MPLANER_NHTLREV_GR OSS_M	NUMBER	30	4	Y
SMAD_V_MPLANER_NHTLREV_GR OSS_Y	NUMBER	30	4	Y
SMAD_CHILDS_G1_D	NUMBER	6		Y
SMAD_CHILDS_G1_M	NUMBER	6		Y
SMAD_CHILDS_G1_Y	NUMBER	6		Y
SMAD_CHILDS_G2_D	NUMBER	7		Y
SMAD_CHILDS_G2_M	NUMBER	7		Y
SMAD_CHILDS_G2_Y	NUMBER	7		Y
SMAD_CHILDS_G3_D	NUMBER	7		Y
SMAD_CHILDS_G3_M	NUMBER	7		Y
SMAD_CHILDS_G3_Y	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G1_D	NUMBER	6		Y
SMAD_DOMESTICCHILDS_G1_M	NUMBER	6		Y
SMAD_DOMESTICCHILDS_G1_Y	NUMBER	6		Y
SMAD_DOMESTICCHILDS_G2_D	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G2_M	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G2_Y	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G3_D	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G3_M	NUMBER	7		Y
SMAD_DOMESTICCHILDS_G3_Y	NUMBER	7		Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	Description
SMAN_ID	NUMBER	30		N	Unique Identifier for Manager Report
SMAN_DATE	DATE			N	Fidelio System Date
SMAN_ADULTS_D	NUMBER	5		Y	Adults in House DTD (v8_sys_stat_adult); select sum(ydet_adultno) value from ydet,yres where ydet_yres_id=yres_id and yres_resstatus<>3 and ydet_date=(select wgbs_datevalue from fideliodate)
SMAN_ADULTS_M	NUMBER	5		Y	Adults in House MTD
SMAN_ADULTS_Y	NUMBER	7		Y	Adults in House YTD

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_CHILDS_D	NUMBER	5		Y	Children in House DTD (v8_sys_personchild) select sum(nvl(YRGL_NUMBER,0)) child from ydet,yres,yrgl where yrgl_ydet_id(+)=ydet_id and ydet_yres_id=yres_id and yres_resstatus<>3 and ydet_date=(select d.WGBS_DATEVALUE from fideliodate d)
SMAN_CHILDS_M	NUMBER	5		Y	Children in House MTD
SMAN_CHILDS_Y	NUMBER	7		Y	Children in House YTD
SMAN_ROOMS_OCC_D	NUMBER	5		Y	Occupied Rooms DTD (v.CLEAN+v.dirty rooms_occ from v8_sys_hs_housekeep_occupied v) select nvl(sum(decode(yhks_clean,1,1,0)),0) clean, nvl(sum(decode(yhks_clean,1,0,1)),0) dirty from yrms,yhks,fideliodate d where yrms_validfrom<= d.WGBS_DATEVALUE and yrms_validuntil>= d.WGBS_DATEVALUE and yrms_yhks_id=yhks_id /*and yhks_clean=1*/ and exists (select yres_id from yres,ydet where ydet_yres_id=yres_id and yres_resstatus<>3 and ydet_date=d.WGBS_DATEVALUE and yres_actarrtime is not null and yres_actdeptime is null and ydet_yrms_id=yrms_id) and not exists (select YRST_YRMS_ID from YRST,YRSC where YRST_FROMTIME<=d.WGBS_DATEVALUE and trunc(YRST_UNTILTIME)>d.WGBS_DATEVALUE and YRST.YRST_YRSC_ID=YRSC_ID and YRSC.YRSC_AFFECTAILABILITY=1 and YRST_YRMS_ID=YRMS_ID)
SMAN_ROOMS_OCC_M	NUMBER	5		Y	Occupied Rooms MTD
SMAN_ROOMS_OCC_Y	NUMBER	7		Y	Occupied Rooms YTD
SMAN_ROOMSINHOTEL_D	NUMBER	5		Y	Rooms in Hotel DTD (select noofrooms from v8_sys_nooftotalrooms_all tot where tot.WDAT_DATE=today) select wdat_date,count(yrms_id) noofrooms from yrms,wdat where yrms_validfrom<= wdat_date and yrms_validuntil>= wdat_date and not exists (select YRST_YRMS_ID from YRST,YRSC where YRST_FROMTIME<=WDAT_DATE and trunc(YRST_UNTILTIME)>WDAT_DATE and YRST.YRST_YRSC_ID=YRSC_ID and YRSC.YRSC_AFFECTAILABILITY=1 and YRST_YRMS_ID=YRMS_ID) group by wdat_date
SMAN_ROOMSINHOTEL_M	NUMBER	5		Y	Rooms in Hotel MTD
SMAN_ROOMSINHOTEL_Y	NUMBER	7		Y	Rooms in Hotel YTD
SMAN_ROOMS_OOO_D	NUMBER	5		Y	Out of Order Rooms DTD (select OOO from v8_sys_housekeep_ooo_all v) select sum(decode(nvl(YRSC_AFFECTAILABILITY,1),1,0,1)) oos ,sum(decode(YRSC_AFFECTAILABILITY,1,1,0)) ooo from YRST,YRSC,fideliodate d where YRST_FROMTIME<=d.wgbs_datevalue and trunc(YRST_UNTILTIME)>d.wgbs_datevalue and YRST.YRST_YRSC_ID=YRSC_ID
SMAN_ROOMS_OOO_M	NUMBER	5		Y	Out of Order Rooms MTD
SMAN_ROOMS_OOO_Y	NUMBER	7		Y	Out of Order Rooms YTD

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_WALKIN_D	NUMBER	5		Y	Walkin Rooms DTD (select v.NOOFROOMS from v8_sys_hs_walkin_room v where v.WDAT_DATE=today) select wdat_date,sum(noofrooms) noofrooms from ( select wdat_date ,decode(nvl(ydet_sharenum,0),0),sum(ydet_noofrooms),avg(ydet_noofrooms)) noofrooms from yres,wdat,ydet where ydet_yres_id=yres_id and ydet_date=wdat_date and trunc(yres.YRES_ACTARRTIME)=ydet.YDET_DATE and YRES_WALKIN=1 and yres_resstatus<> 3 group by wdat_date,ydet_sharenum ) group by wdat_date
SMAN_WALKIN_M	NUMBER	5		Y	Walkin Rooms MTD
SMAN_WALKIN_Y	NUMBER	7		Y	Walkin Rooms YTD
SMAN_ARR_ROOMS_D	NUMBER	5		Y	Arrival Rooms DTD (select v.actroom from v8_sys_hs_arr_actroom v where v.wdat_date=today) select wdat_date,sum(actroom) actroom from ( select wdat_date ,decode(nvl(ydet_sharenum,0),0),sum(ydet_noofrooms),avg(ydet_noofrooms)) actroom from wdat,ydet,yres y where ydet_date=wdat_date and yres_exparitime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 and yres_actarrtime is not null and (nvl(ydet_sharenum,0)= 0 or not exists (select d.ydet_sharenum from ydet d,yres r where d.ydet_yres_id=r.yres_id and d.ydet_sharenum=ydet_sharenum and d.ydet_id<>ydet.ydet_id and y.yres_exparitime<>r.yres_exparitime and d.ydet_sharenum=ydet.ydet_sharenum ) ) group by wdat_date,ydet_sharenum ) group by wdat_date
SMAN_ARR_ROOMS_M	NUMBER	5		Y	Arrival Rooms MTD
SMAN_ARR_ROOMS_Y	NUMBER	7		Y	Arrival Rooms YTD
SMAN_DEP_ROOMS_D	NUMBER	5		Y	Departure Rooms DTD (select v.actroom from v8_sys_hs_dep_actroom v where v.wdat_date=today) select wdat_date,sum(actroom) actroom from ( select wdat_date ,decode(nvl(ydet_sharenum,0),0),sum(ydet_noofrooms),avg(ydet_noofrooms)) actroom from wdat,ydet,yres y where ydet_id=yres_last_ydet_id and yres_expdeptime=wdat_date and yres_resstatus<>3 and yres_actdeptime is not null and (nvl(ydet_sharenum,0)= 0 or not exists (select d.ydet_sharenum from ydet d,yres r where d.ydet_yres_id=r.yres_id and d.ydet_sharenum=ydet_sharenum and d.ydet_id<>ydet.ydet_id and (y.yres_expdeptime<>r.yres_expdeptime or r.yres_actdeptime is not null) and d.ydet_sharenum=ydet.ydet_sharenum ) ) group by wdat_date,ydet_sharenum ) group by wdat_date
SMAN_DEP_ROOMS_M	NUMBER	5		Y	Departure Rooms MTD
SMAN_DEP_ROOMS_Y	NUMBER	7		Y	Departure Rooms YTD

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	Description
SMAN_ARR_ADULTS_D	NUMBER	5		Y	Arrival Adults DTD (select v.actadult from v8_sys_hs_arr_actadult v where v.wdat_date=today) select wdat_date ,sum(ydet_adultno) actadult from wdat,ydet,yres where ydet_date=wdat_date and yres_exparrrtime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 and yres_actarrtime is not null group by wdat_date
SMAN_ARR_ADULTS_M	NUMBER	5		Y	Arrival Adults MTD
SMAN_ARR_ADULTS_Y	NUMBER	7		Y	Arrival Adults YTD
SMAN_ARR_CHILDS_D	NUMBER	5		Y	Arrival Children DTD (select v.actchild from v8_sys_hs_arr_actchild v where v.wdat_date=today) select wdat_date ,sum(yrgl_number) actchild from wdat,ydet,yres,yrgl where ydet_date=wdat_date and yres_exparrrtime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 and yres_actarrtime is not null and yrgl_ydet_id=ydet_id group by wdat_date
SMAN_ARR_CHILDS_M	NUMBER	5		Y	Arrival Children MTD
SMAN_ARR_CHILDS_Y	NUMBER	7		Y	Arrival Children YTD
SMAN_DEP_ADULTS_D	NUMBER	5		Y	Departure Adults DTD (select v.actadult from v8_sys_hs_dep_actadult v where v.wdat_date=today) select wdat_date ,sum(ydet_adultno) actadult from wdat,ydet,yres where ydet_id=yres_last_ydet_id and yres_expdeptime=wdat_date and yres_resstatus<>3 and yres_actdeptime is not null group by wdat_date
SMAN_DEP_ADULTS_M	NUMBER	5		Y	Departure Adults MTD
SMAN_DEP_ADULTS_Y	NUMBER	7		Y	Departure Adults YTD
SMAN_DEP_CHILDS_D	NUMBER	5		Y	Departure Childs DTD (select v.actchild from v8_sys_hs_dep_actchild v where v.wdat_date=today) select wdat_date ,sum(YRGL_NUMBER) actchild from wdat,ydet,yres,yrgl where ydet_id=yres_last_ydet_id and yrgl_ydet_id=ydet_id and yres_expdeptime=wdat_date and yres_resstatus<>3 and yres_actdeptime is not null group by wdat_date
SMAN_DEP_CHILDS_M	NUMBER	5		Y	Departure Childs MTD
SMAN_DEP_CHILDS_Y	NUMBER	7		Y	Departure Childs YTD
SMAN_TOTALGROSSREV_D	NUMBER	30	4	Y	Total Gross Revenue DTD (select amount,nhtlamount from v8_sys_stat_grossrev) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) amount ,sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlamount from zpos,zdco where zpos_zdco_id=zdco_idand nvl(zdco_nonhtlrev,0)<> 1 and trunc(zpos_postdate)=(select wgbs_datevalue from fideliodate) and zpos_cdt<> 5
SMAN_TOTALGROSSREV_M	NUMBER	30	4	Y	Total Gross Revenue MTD
SMAN_TOTALGROSSREV_Y	NUMBER	30	4	Y	Total Gross Revenue YTD
SMAN_TOTALNETREV_D	NUMBER	30	4	Y	Total Net Revenue DTD (select amount,nhtlamount from v8_sys_stat_netrev) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) amount ,sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlamount from zpos,zdco where zpos_zdco_id=zdco_idand nvl(zdco_nonhtlrev,0)<> 1 and trunc(zpos_postdate)=(select wgbs_datevalue from fideliodate) and zpos_cdt=1

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_TOTALNETREV_M	NUMBER	30	4	Y	Total Net Revenue MTD
SMAN_TOTALNETREV_Y	NUMBER	30	4	Y	Total Net Revenue YTD
SMAN_COMPROOMS_D	NUMBER	5		Y	Complimentary Rooms DTD (select value from v8_sys_stat_comprooms) select sum(ydet_noofrooms) value from yres,ydet,yrch where yres_id=ydet_yres_id and yres_resstatus<> 3 and ydet_date=(select wgbs_datevalue from fideliodate) and trunc(yres.YRES_EXPDEPTIME) -trunc(yres.YRES_EXPARRTIME)>0 and yrch_id=ydet_yrch_id and yrch_compstatus=1
SMAN_COMPROOMS_M	NUMBER	5		Y	Complimentary Rooms MTD
SMAN_COMPROOMS_Y	NUMBER	7		Y	Complimentary Rooms YTD
SMAN_HOUSEUSERROOMS_D	NUMBER	5		Y	House Use Rooms DTD (select value from v8_sys_stat_houseuserrooms) select sum(ydet_noofrooms) value from yres,ydet,yrch where yres_id=ydet_yres_id and yres_resstatus<> 3 and ydet_date=(select wgbs_datevalue from fideliodate) and yrch_id=ydet_yrch_id and trunc(yres.YRES_EXPDEPTIME) -trunc(yres.YRES_EXPARRTIME)>0 and yrch_compstatus=2
SMAN_HOUSEUSERROOMS_M	NUMBER	5		Y	House Use Rooms MTD
SMAN_HOUSEUSERROOMS_Y	NUMBER	7		Y	House Use Rooms YTD
SMAN_BEDSINHOTEL_D	NUMBER	5		Y	Beds in Hotel DTD (select bedno from v8_sys_stat_bedsinhotel) select sum(yrms_noofpersons) bedno from yrms where yrms_validfrom<= (select wgbs_datevalue from fideliodate) and yrms_validuntil>= (select wgbs_datevalue from fideliodate)
SMAN_BEDSINHOTEL_M	NUMBER	7		Y	Beds in Hotel MTD
SMAN_BEDSINHOTEL_Y	NUMBER	7		Y	Beds in Hotel YTD
SMAN_REPEATGUESTARRROOM_D	NUMBER	5		Y	Repeating Guests Arrival Rooms DTD (select noofrooms from v8_sys_stat_repeatguestroom) SELECT sum(ydet_noofrooms) noofrooms FROM yres, ydet WHERE yres_resstatus<>3 and ydet_yres_id=yres_id and trunc(yres.yres_actarrTIME)=(select trunc(wgbs_datevalue) from fideliodate) and ydet_date=(select wgbs_datevalue from fideliodate) and exists (select y.yres_id from yres y where trunc(y.yres_actarrtime)<(select wgbs_datevalue from fideliodate) and y.yres_xcms_id=yres_xcms_id)
SMAN_REPEATGUESTARRROOM_M	NUMBER	5		Y	Repeating Guests Arrival Rooms MTD
SMAN_REPEATGUESTARRROOM_Y	NUMBER	7		Y	Repeating Guests Arrival Rooms YTD
SMAN_RESMADETODAY_D	NUMBER	5		Y	Reservations created DTD (select value from v8_sys_stat_rescreatedtoday) select count(yres_id) value from yres,wmlg l where yres_resstatus<>3 and wmlg_tablename="YRES" and wmlg_table_id=yres_id and trunc(wmlg_time) =trunc(sysdate) and (trunc(wmlg_time) =trunc(sysdate-1) or trunc(wmlg_time) =trunc(sysdate-1))
SMAN_RESMADETODAY_M	NUMBER	5		Y	Reservations created MTD

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_RESMADETDAY_Y	NUMBER	7		Y	Reservations created YTD
SMAN_RESCANCELEDTDAY_D	NUMBER	5		Y	Reservations cancelled DTD (select value from v8_sys_stat_rescancelled) select count(yres_id) value from yres,ycxl c where yres_resstatus=3 and ycxl_yres_id=yres_id and trunc(ycxl_date)=(select wgb_datevalue from fideliodate) and ycxl_cancelorreinststate=1 and not exists (select cc.ycxl_id from ycxl cc where cc.ycxl_yres_id=yres_id and cc.ycxl_id>c.ycxl_id)
SMAN_RESCANCELEDTDAY_M	NUMBER	5		Y	Reservations cancelled MTD
SMAN_RESCANCELEDTDAY_Y	NUMBER	7		Y	Reservations cancelled YTD
SMAN_ARRADULTSTOMORROW_D	NUMBER	5		Y	Arrival Adults Tomorrow (def + tent) (select expadult from v8_sys_hs_arr_alladult v where v.WDAT_DATE=today+1) select wdat_date ,sum(decode(yres_ygrp_id,null,ydet_adultno,ydet_no ofrooms)) expadult from wdat,ydet,yres where ydet_date=wdat_date and yres_exparrrtime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 group by wdat_date
SMAN_DEPADULTSTOMORROW_D	NUMBER	5		Y	Departure Adults Tomorrow (select expadult from v8_sys_hs_dep_exadult v where v.WDAT_DATE=today+1) select wdat_date ,sum(decode(yres_ygrp_id,null,ydet_adultno,ydet_no ofrooms)) expadult from wdat,ydet,yres where ydet_id=yres_last_ydet_id and yres_expdeptime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 and yres_actdeptime is null group by wdat_date
SMAN_ARRROOMSTOMORROW_D	NUMBER	5		Y	Arrival Rooms Tomorrow (def + tent) (select exproom from v8_sys_hs_arr_allroom v where v.WDAT_DATE=today+1) select wdat_date,sum(exproom) exproom from ( select wdat_date,decode(nvl(ydet_sharenum,0),0,sum(ydet _noofrooms),avg(ydet_noofrooms)) exproom from wdat,ydet,yres y where ydet_date=wdat_date and yres_exparrrtime=wdat_date and ydet_yres_id=yres_id and yres_resstatus<>3 and (nvl(ydet_sharenum,0)= 0 or not exists (select d.ydet_sharenum from ydet d,yres r where d.ydet_yres_id=r.yres_id and d.ydet_sharenum=ydet_sharenum and d.ydet_id<>ydet.ydet_id and (y.yres_exparrrtime<>r.yres_exparrrtime or r.yres_actarrtime is not null) and d.ydet_sharenum=ydet.ydet_sharenum )) group by wdat_date,ydet_sharenum ) group by wdat_date

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	Description
SMAN_DEPROOMSTOMORROW_D	NUMBER	5		Y	Departure Rooms Tomorrow (select exproom from v8_sys_hs_dep_exproom v where v.WDAT_DATE=today+1) select wdat_date,sum(exproom) exproom from ( select wdat_date ,ydet_sharenum ,decode(nvl(ydet_sharenum,0),0,sum(ydet_noofrooms),avg(ydet_noofrooms)) exproom from wdat,ydet,yres y where ydet_id=yres_last_ydet_id and yres_expdeptime=wdat_date and yres_resstatus<>3 and yres_actdeptime is null and (nvl(ydet_sharenum,0)= 0 or not exists (select d.ydet_sharenum from ydet d,yres r where d.ydet_yres_id=r.yres_id and d.ydet_sharenum=ydet_sharenum and d.ydet_id<>ydet.ydet_id and y.yres_expdeptime<>r.yres_expdeptime and d.ydet_sharenum=ydet.ydet_sharenum ) ) group by wdat_date,ydet_sharenum) group by wdat_date
SMAN_COMPANY_ROOMS_D	NUMBER	5		Y	Company Rooms DTD (select value from v8_sys_stat_companyrooms) select sum(ydet_noofrooms) value from yres,ydet,ycln where yres_id=ydet_yres_id and yres_resstatus<>3 and ydet_date=(select wgbs_datevalue from fideliodate) and ycln_ydet_id=ydet_id and ycln_xcca_internalcategory=1
SMAN_COMPANY_ROOMS_M	NUMBER	5		Y	Company Rooms MTD
SMAN_COMPANY_ROOMS_Y	NUMBER	7		Y	Company Rooms YTD
SMAN_COMPANY_REV_GROSS_D	NUMBER	30	4	Y	Company Revenue Gross DTD (select value,nhtlvalue from v8_sys_stat_companyrevenue) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) value ,sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlvalue from zpos,ycln,ydet,zdco where zpos_yres_id=ydet_yres_id and ydet_id=ycln_ydet_id and ycln_xcca_internalcategory=1 and zpos_cdt in (1,2) and zpos_zdco_id=zdco_id and ydet_date=(select wgbs_datevalue from fideliodate)
SMAN_COMPANY_REV_GROSS_M	NUMBER	30	4	Y	Company Revenue Gross MTD
SMAN_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y	Company Revenue Gross YTD
SMAN_AGENT_ROOMS_D	NUMBER	5		Y	Travel Agent Rooms DTD (select value from v8_sys_stat_agentrooms) select sum(ydet_noofrooms) value from yres,ydet,ycln where yres_id=ydet_yres_id and yres_resstatus<>3 and ydet_date=(select wgbs_datevalue from fideliodate) and ycln_ydet_id=ydet_id and ycln_xcca_internalcategory=2
SMAN_AGENT_ROOMS_M	NUMBER	5		Y	Travel Agent Rooms MTD
SMAN_AGENT_ROOMS_Y	NUMBER	7		Y	Travel Agent Rooms YTD

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_AGENT_REV_GROSS_D	NUMBER	30	4	Y	Travel Agent Revenue Gross DTD (select value,nhtlvalue from v8_sys_stat_agentrevenue) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) value ,sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlvalue from zpos,ycln,ydet,zdco where zpos_yres_id=ydet_yres_id and ydet_id=ycln_ydet_id and ycln_xcca_internalcategory=2 and zpos_cdt in (1,2) and zpos_zdco_id=zdco_id and ydet_date=(select wgbs_datevalue from fideliodate)
SMAN_AGENT_REV_GROSS_M	NUMBER	30	4	Y	Travel Agent Revenue Gross MTD
SMAN_AGENT_REV_GROSS_Y	NUMBER	30	4	Y	Travel Agent Revenue Gross YTD
SMAN_IND_ROOMS_D	NUMBER	5		Y	Individual Rooms DTD (select value from v8_sys_stat_individualrooms) select sum(ydet_noofrooms) value from yres,ydet where yres_id=ydet_yres_id and yres_resstatus<> 3 and ydet_date=(select wgbs_datevalue from fideliodate) and not exists (select ycln_id from ycln where ycln_ydet_id=ydet_id and ycln_xcca_internalcategory in (1,2))
SMAN_IND_ROOMS_M	NUMBER	5		Y	Individual Rooms MTD
SMAN_IND_ROOMS_Y	NUMBER	7		Y	Individual Rooms YTD
SMAN_IND_REV_GROSS_D	NUMBER	30	4	Y	Individual Gross Revenue DTD (select value,nhtlvalue from v8_sys_stat_individualrevenue) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) value ,sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlvalue from zpos,ydet,zdco where zpos_yres_id=ydet_yres_id and zpos_cdt in (1,2) and ydet_date=(select wgbs_datevalue from fideliodate) and zpos_zdco_id=zdco_id and not exists (select ycln_id from ycln where ycln_ydet_id=ydet_id and ycln_xcca_internalcategory in (1,2))
SMAN_IND_REV_GROSS_M	NUMBER	30	4	Y	Individual Gross Revenue MTD
SMAN_IND_REV_GROSS_Y	NUMBER	30	4	Y	Individual Gross Revenue YTD
SMAN_VIPADULTS_D	NUMBER	5		Y	VIP Adults in House DTD (select value from v8_sys_stat_vipadult) SELECT sum(ydet_adultno) value FROM ydet, yres, xpal WHERE ydet_yres_id=yres_id and yres_resstatus<>3 and ydet_date=(select wgbs_datevalue from fideliodate) and xpal.XPAL_XCMS_ID=yres.YRES_XCMS_ID and xpal_xpac_id=11
SMAN_VIPADULTS_M	NUMBER	5		Y	VIP Adults in House MTD
SMAN_VIPADULTS_Y	NUMBER	7		Y	VIP Adults in House YTD
SMAN_PAYMENTS_D	NUMBER	30	4	Y	Payments DTD (select value from v8_sys_stat_payments) select sum(zpos_unitprice*zpos_quantity) value from zpos where zpos_cdt= 5 and trunc(zpos_postdate)=(select wgbs_datevalue from fideliodate)
SMAN_PAYMENTS_M	NUMBER	30	4	Y	Payments MTD
SMAN_PAYMENTS_Y	NUMBER	30	4	Y	Payments YTD

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_ROOMREVGROSS_D	NUMBER	30	4	Y	Gross Room Revenue DTD (select value,nhtlvalue from v8_sys_stat_grossroomrev) select sum(decode(zdco_nonhtlrev,1,0,t.zpos_unitprice*t.zpos_quantity)) value ,sum(decode(zdco_nonhtlrev,1,t.zpos_unitprice*t.zpos_quantity)) nhtlvalue from zpos p,zdco,zpos t where p.zpos_zdco_id=zdco_id and trunc(p.zpos_postdate)=(select wgbs_datevalue from fideliodate) and p.zpos_cdt=1 and zdco_stats_type=1 and t.ZPOS_TAXLINK_ID=p.ZPOS_TAXLINK_ID
SMAN_ROOMREVGROSS_M	NUMBER	30	4	Y	Gross Room Revenue MTD
SMAN_ROOMREVGROSS_Y	NUMBER	30	4	Y	Gross Room Revenue YTD
SMAN_ROOMREVNET_D	NUMBER	30	4	Y	Net Room Revenue DTD (select value,nhtlvalue from v8_sys_stat_netroomrev) select sum(decode(zdco_nonhtlrev,1,0,zpos_unitprice*zpos_quantity)) value, sum(decode(zdco_nonhtlrev,1,zpos_unitprice*zpos_quantity)) nhtlvalue from zpos,zdco where zpos_zdco_id=zdco_id and trunc(zpos_postdate)=(select wgbs_datevalue from fideliodate) and zpos_cdt=1 and zdco_stats_type=1
SMAN_ROOMREVNET_M	NUMBER	30	4	Y	Net Room Revenue MTD
SMAN_ROOMREVNET_Y	NUMBER	30	4	Y	Net Room Revenue YTD
SMAN_CANCFORTODAY_D	NUMBER	5		Y	Cancellations for Today DTD (select value from v8_sys_stat_rescancfortoday) select count(yres_id) value from yres where yres_resstatus=3 and yres_noavailreason=3 and yres_exparrTIME=(select wgbs_datevalue from fideliodate)
SMAN_CANCFORTODAY_M	NUMBER	5		Y	Cancellations for Today MTD
SMAN_CANCFORTODAY_Y	NUMBER	7		Y	Cancellations for Today YTD
SMAN_DEPNOTPAID_D	NUMBER	5		Y	Departure Rooms not paid DTD (select value from v8_sys_stat_depnotpaid) select count(yres_id) value from yres where yres_expdeptime=(select wgbs_datevalue from fideliodate) and yres_actdeptime is null and yres_actarrtime is not null and yres_resstatus<>3 and 0<>(select sum(decode(zpos_cdt,5,-zpos_unitprice*zpos_quantity),zpos_unitprice*zpos_quantity)) from zpos where zpos_yres_id=yres_id)
SMAN_DEPNOTPAID_M	NUMBER	5		Y	Departure Rooms not paid MTD
SMAN_DEPNOTPAID_Y	NUMBER	7		Y	Departure Rooms not paid YTD
SMAN_NOSHOWROOMS_D	NUMBER	5		Y	No Show Rooms DTD (select value from v8_sys_stat_noshowrooms) select sum(ydet_noofrooms) value from yres,ydet where ydet_date=(select wgbs_datevalue from fideliodate) and ydet_yres_id=yres_id and yres_resstatus=3 and yres_noavailreason=4
SMAN_NOSHOWROOMS_M	NUMBER	5		Y	No Show Rooms MTD
SMAN_NOSHOWROOMS_Y	NUMBER	7		Y	No Show Rooms YTD
SMAN_DAYUSERROOMS_D	NUMBER	5		Y	Day Use Rooms DTD (select value from v8_sys_stat_dayuserrooms) select sum(ydet_noofrooms) value from yres,ydet where ydet_date=(select wgbs_datevalue from fideliodate) and yres_exparrtime=yres_expdeptime and ydet_yres_id=yres_id and yres_resstatus<>3

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_DAYUSERROOMS_M	NUMBER	5		Y	Day Use Rooms MTD
SMAN_DAYUSERROOMS_Y	NUMBER	7		Y	Day Use Rooms YTD
SMAN_MAXBEDSINHOTEL_D	NUMBER	5		Y	Maximum Beds in Hotel DTD (select bedno from v8_sys_stat_maxbedsinhotel) select sum(yrms_max_beds) bedno from yrms where yrms_validfrom<= (select wgbs_datevalue from fideliodate) and yrms_validuntil>= (select wgbs_datevalue from fideliodate)
SMAN_MAXBEDSINHOTEL_M	NUMBER	7		Y	Maximum Beds in Hotel MTD
SMAN_MAXBEDSINHOTEL_Y	NUMBER	7		Y	Maximum Beds in Hotel YTD
SMAN_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y	Total Gross Non Hotel Revenue DTD
SMAN_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y	Total Gross Non Hotel Revenue MTD
SMAN_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y	Total Gross Non Hotel Revenue YTD
SMAN_TOTALNETNHTLREV_D	NUMBER	30	4	Y	Total Net Non Hotel Revenue DTD
SMAN_TOTALNETNHTLREV_M	NUMBER	30	4	Y	Total Net Non Hotel Revenue MTD
SMAN_TOTALNETNHTLREV_Y	NUMBER	30	4	Y	Total Net Non Hotel Revenue YTD
SMAN_COMPANY_NHTLREV_GROSS_D	NUMBER	30	4	Y	Company Gross Non Hotel Revenue DTD
SMAN_COMPANY_NHTLREV_GROSS_M	NUMBER	30	4	Y	Company Gross Non Hotel Revenue MTD
SMAN_COMPANY_NHTLREV_GROSS_Y	NUMBER	30	4	Y	Company Gross Non Hotel Revenue YTD
SMAN_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y	Travel Agent Gross Non Hotel Revenue DTD
SMAN_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y	Travel Agent Gross Non Hotel Revenue MTD
SMAN_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y	Travel Agent Gross Non Hotel Revenue YTD
SMAN_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y	Individual Gross Non Hotel Revenue DTD
SMAN_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y	Individual Gross Non Hotel Revenue MTD
SMAN_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y	Individual Gross Non Hotel Revenue YTD
SMAN_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y	Room Revenue Non Hotel Gross DTD
SMAN_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y	Room Revenue Non Hotel Gross MTD
SMAN_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y	Room Revenue Non Hotel Gross YTD
SMAN_ROOMNHTLREVNET_D	NUMBER	30	4	Y	Non Hotel Room Revenue Net DTD
SMAN_ROOMNHTLREVNET_M	NUMBER	30	4	Y	Non Hotel Room Revenue Net MTD
SMAN_ROOMNHTLREVNET_Y	NUMBER	30	4	Y	Non Hotel Room Revenue Net YTD
SMAN_FBREVGROSS_D	NUMBER	30	4	Y	FB Revenue Gross DTD
SMAN_FBNHTLREVGROSS_D	NUMBER	30	4	Y	Non Hotel FB Revenue Gross DTD
SMAN_FBREVNET_D	NUMBER	30	4	Y	FB Revenue Net DTD
SMAN_FBNHTLREVNET_D	NUMBER	30	4	Y	Non Hotel FB Revenue Net DTD
SMAN_FBREVGROSS_M	NUMBER	30	4	Y	FB Revenue Gross MTD

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_FBNHTLREVGROSS_M	NUMBER	30	4	Y	Non Hotel FB Revenue Gross MTD
SMAN_FBREVNEM_M	NUMBER	30	4	Y	FB Revenue Net MTD
SMAN_FBNHTLREVNEM_M	NUMBER	30	4	Y	Non Hotel FB Revenue Net MTD
SMAN_FBREVGROSS_Y	NUMBER	30	4	Y	FB Revenue Gross YTD
SMAN_FBNHTLREVGROSS_Y	NUMBER	30	4	Y	Non Hotel FB Revenue Gross YTD
SMAN_FBREVNEM_Y	NUMBER	30	4	Y	FB Revenue Net YTD
SMAN_FBNHTLREVNEM_Y	NUMBER	30	4	Y	Non Hotel FB Revenue Net YTD
SMAN_OCCNEXTFOURWEEKS	NUMBER	30	4	Y	Occupancy next 4 Weeks (Calculated from Stored Procedure SMANOCC)
SMAN_OCCTOMORROW	NUMBER	30	4	Y	Occupancy Tomorrow (Calculated from Stored Procedure SMANOCC)
SMAN_OCCNEXTSEVENDAYS	NUMBER	30	4	Y	Occupancy next 7 days (Calculated from Stored Procedure SMANOCC)
SMAN_OCCUNTILENDMONTH	NUMBER	30	4	Y	Occupancy until Month End (Calculated from Stored Procedure SMANOCC)
SMAN_OCCENDYEAR	NUMBER	30	4	Y	Occupancy until End of Year (Calculated from Stored Procedure SMANOCC)
SMAN_MINIREVGROSS_D	NUMBER	30	4	Y	SMAN_MINIREVGROSS_D is of SMAN
SMAN_MININHTLREVGROSS_D	NUMBER	30	4	Y	SMAN_MININHTLREVGROSS_D is of SMAN
SMAN_TELEREVGROSS_D	NUMBER	30	4	Y	SMAN_TELEREVGROSS_D is of SMAN
SMAN_TELENHTLREVGROSS_D	NUMBER	30	4	Y	SMAN_TELENHTLREVGROSS_D is of SMAN
SMAN_MISCREVGROSS_D	NUMBER	30	4	Y	SMAN_MISCREVGROSS_D is of SMAN
SMAN_MISCNHTLREVGROSS_D	NUMBER	30	4	Y	SMAN_MISCNHTLREVGROSS_D is of SMAN
SMAN_NOSTATREVGROSS_D	NUMBER	30	4	Y	SMAN_NOSTATREVGROSS_D is of SMAN
SMAN_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVGROSS_D is of SMAN
SMAN_MINIREVGROSS_M	NUMBER	30	4	Y	SMAN_MINIREVGROSS_M is of SMAN
SMAN_MININHTLREVGROSS_M	NUMBER	30	4	Y	SMAN_MININHTLREVGROSS_M is of SMAN
SMAN_TELEREVGROSS_M	NUMBER	30	4	Y	SMAN_TELEREVGROSS_M is of SMAN
SMAN_TELENHTLREVGROSS_M	NUMBER	30	4	Y	SMAN_TELENHTLREVGROSS_M is of SMAN
SMAN_MISCREVGROSS_M	NUMBER	30	4	Y	SMAN_MISCREVGROSS_M is of SMAN
SMAN_MISCNHTLREVGROSS_M	NUMBER	30	4	Y	SMAN_MISCNHTLREVGROSS_M is of SMAN
SMAN_NOSTATREVGROSS_M	NUMBER	30	4	Y	SMAN_NOSTATREVGROSS_M is of SMAN
SMAN_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVGROSS_M is of SMAN
SMAN_MINIREVGROSS_Y	NUMBER	30	4	Y	SMAN_MINIREVGROSS_Y is of SMAN
SMAN_MININHTLREVGROSS_Y	NUMBER	30	4	Y	SMAN_MININHTLREVGROSS_Y is of SMAN
SMAN_TELEREVGROSS_Y	NUMBER	30	4	Y	SMAN_TELEREVGROSS_Y is of SMAN
SMAN_TELENHTLREVGROSS_Y	NUMBER	30	4	Y	SMAN_TELENHTLREVGROSS_Y is of SMAN
SMAN_MISCREVGROSS_Y	NUMBER	30	4	Y	SMAN_MISCREVGROSS_Y is of SMAN

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y	SMAN_MISCNHTLREVGROSS_Y is of SMAN
SMAN_NOSTATREVGROSS_Y	NUMBER	30	4	Y	SMAN_NOSTATREVGROSS_Y is of SMAN
SMAN_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVGROSS_Y is of SMAN
SMAN_MINIREVNET_D	NUMBER	30	4	Y	SMAN_MINIREVNET_D is of SMAN
SMAN_MININHTLREVNET_D	NUMBER	30	4	Y	SMAN_MININHTLREVNET_D is of SMAN
SMAN_TELEREVNET_D	NUMBER	30	4	Y	SMAN_TELEREVNET_D is of SMAN
SMAN_TELENHTLREVNET_D	NUMBER	30	4	Y	SMAN_TELENHTLREVNET_D is of SMAN
SMAN_MISCREVNET_D	NUMBER	30	4	Y	SMAN_MISCREVNET_D is of SMAN
SMAN_MISCNHTLREVNET_D	NUMBER	30	4	Y	SMAN_MISCNHTLREVNET_D is of SMAN
SMAN_NOSTATREVNET_D	NUMBER	30	4	Y	SMAN_NOSTATREVNET_D is of SMAN
SMAN_NOSTATNHTLREVNET_D	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVNET_D is of SMAN
SMAN_MINIREVNET_M	NUMBER	30	4	Y	SMAN_MINIREVNET_M is of SMAN
SMAN_MININHTLREVNET_M	NUMBER	30	4	Y	SMAN_MININHTLREVNET_M is of SMAN
SMAN_TELEREVNET_M	NUMBER	30	4	Y	SMAN_TELEREVNET_M is of SMAN
SMAN_TELENHTLREVNET_M	NUMBER	30	4	Y	SMAN_TELENHTLREVNET_M is of SMAN
SMAN_MISCREVNET_M	NUMBER	30	4	Y	SMAN_MISCREVNET_M is of SMAN
SMAN_MISCNHTLREVNET_M	NUMBER	30	4	Y	SMAN_MISCNHTLREVNET_M is of SMAN
SMAN_NOSTATREVNET_M	NUMBER	30	4	Y	SMAN_NOSTATREVNET_M is of SMAN
SMAN_NOSTATNHTLREVNET_M	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVNET_M is of SMAN
SMAN_MINIREVNET_Y	NUMBER	30	4	Y	SMAN_MINIREVNET_Y is of SMAN
SMAN_MININHTLREVNET_Y	NUMBER	30	4	Y	SMAN_MININHTLREVNET_Y is of SMAN
SMAN_TELEREVNET_Y	NUMBER	30	4	Y	SMAN_TELEREVNET_Y is of SMAN
SMAN_TELENHTLREVNET_Y	NUMBER	30	4	Y	SMAN_TELENHTLREVNET_Y is of SMAN
SMAN_MISCREVNET_Y	NUMBER	30	4	Y	SMAN_MISCREVNET_Y is of SMAN
SMAN_MISCNHTLREVNET_Y	NUMBER	30	4	Y	SMAN_MISCNHTLREVNET_Y is of SMAN
SMAN_NOSTATREVNET_Y	NUMBER	30	4	Y	SMAN_NOSTATREVNET_Y is of SMAN
SMAN_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y	SMAN_NOSTATNHTLREVNET_Y is of SMAN
SMAN_OCCNEXTFOURWEEKS_D	NUMBER	30	4	Y	SMAN_OCCNEXTFOURWEEKS_D is of SMAN
SMAN_OCCTOMORROW_D	NUMBER	30	4	Y	SMAN_OCCTOMORROW_D is of SMAN
SMAN_OCCNEXTSEVENDAYS_D	NUMBER	30	4	Y	SMAN_OCCNEXTSEVENDAYS_D is of SMAN
SMAN_OCCUNTILENDMONTH_D	NUMBER	30	4	Y	SMAN_OCCUNTILENDMONTH_D is of SMAN
SMAN_OCCENDYEAR_D	NUMBER	30	4	Y	SMAN_OCCENDYEAR_D is of SMAN
SMAN_OCCNEXTFOURWEEKS_T	NUMBER	30	4	Y	SMAN_OCCNEXTFOURWEEKS_T is of SMAN

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_OCCTOMORROW_T	NUMBER	30	4	Y	SMAN_OCCTOMORROW_T is of SMAN
SMAN_OCCNEXTSEVENDAYS_T	NUMBER	30	4	Y	SMAN_OCCNEXTSEVENDAYS_T is of SMAN
SMAN_OCCUNTILENDMONTH_T	NUMBER	30	4	Y	SMAN_OCCUNTILENDMONTH_T is of SMAN
SMAN_OCCENDYEAR_T	NUMBER	30	4	Y	SMAN_OCCENDYEAR_T is of SMAN
SMAN_SOURCE_ROOMS_D	NUMBER	5		Y	SMAN_SOURCE_ROOMS_D is of SMAN
SMAN_SOURCE_ROOMS_M	NUMBER	5		Y	SMAN_SOURCE_ROOMS_M is of SMAN
SMAN_SOURCE_ROOMS_Y	NUMBER	7		Y	SMAN_SOURCE_ROOMS_Y is of SMAN
SMAN_SOURCE_REV_GROSS_D	NUMBER	30	4	Y	SMAN_SOURCE_REV_GROSS_D is of SMAN
SMAN_SOURCE_REV_GROSS_M	NUMBER	30	4	Y	SMAN_SOURCE_REV_GROSS_M is of SMAN
SMAN_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y	SMAN_SOURCE_REV_GROSS_Y is of SMAN
SMAN_BOOKER_ROOMS_D	NUMBER	5		Y	SMAN_BOOKER_ROOMS_D is of SMAN
SMAN_BOOKER_ROOMS_M	NUMBER	5		Y	SMAN_BOOKER_ROOMS_M is of SMAN
SMAN_BOOKER_ROOMS_Y	NUMBER	7		Y	SMAN_BOOKER_ROOMS_Y is of SMAN
SMAN_BOOKER_REV_GROSS_D	NUMBER	30	4	Y	SMAN_BOOKER_REV_GROSS_D is of SMAN
SMAN_BOOKER_REV_GROSS_M	NUMBER	30	4	Y	SMAN_BOOKER_REV_GROSS_M is of SMAN
SMAN_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y	SMAN_BOOKER_REV_GROSS_Y is of SMAN
SMAN_VENDOR_ROOMS_D	NUMBER	5		Y	SMAN_VENDOR_ROOMS_D is of SMAN
SMAN_VENDOR_ROOMS_M	NUMBER	5		Y	SMAN_VENDOR_ROOMS_M is of SMAN
SMAN_VENDOR_ROOMS_Y	NUMBER	7		Y	SMAN_VENDOR_ROOMS_Y is of SMAN
SMAN_VENDOR_REV_GROSS_D	NUMBER	30	4	Y	SMAN_VENDOR_REV_GROSS_D is of SMAN
SMAN_VENDOR_REV_GROSS_M	NUMBER	30	4	Y	SMAN_VENDOR_REV_GROSS_M is of SMAN
SMAN_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y	SMAN_VENDOR_REV_GROSS_Y is of SMAN
SMAN_MPLANER_ROOMS_D	NUMBER	5		Y	SMAN_MPLANER_ROOMS_D is of SMAN
SMAN_MPLANER_ROOMS_M	NUMBER	5		Y	SMAN_MPLANER_ROOMS_M is of SMAN
SMAN_MPLANER_ROOMS_Y	NUMBER	7		Y	SMAN_MPLANER_ROOMS_Y is of SMAN
SMAN_MPLANER_REV_GROSS_D	NUMBER	30	4	Y	SMAN_MPLANER_REV_GROSS_D is of SMAN
SMAN_MPLANER_REV_GROSS_M	NUMBER	30	4	Y	SMAN_MPLANER_REV_GROSS_M is of SMAN
SMAN_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y	SMAN_MPLANER_REV_GROSS_Y is of SMAN
SMAN_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y	SMAN_SOURCE_NHTLREV_GROSS_D is of SMAN
SMAN_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y	SMAN_SOURCE_NHTLREV_GROSS_M is of SMAN
SMAN_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y	SMAN_SOURCE_NHTLREV_GROSS_Y is of SMAN
SMAN_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y	SMAN_BOOKER_NHTLREV_GROSS_D is of SMAN
SMAN_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y	SMAN_BOOKER_NHTLREV_GROSS_M is of SMAN

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	Description
SMAN_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y	SMAN_BOOKER_NHTLREV_GROSS_Y is of SMAN
SMAN_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y	SMAN_VENDOR_NHTLREV_GROSS_D is of SMAN
SMAN_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y	SMAN_VENDOR_NHTLREV_GROSS_M is of SMAN
SMAN_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y	SMAN_VENDOR_NHTLREV_GROSS_Y is of SMAN
SMAN_MPLANER_NHTLREV_GROSS_D	NUMBER	30	4	Y	SMAN_MPLANER_NHTLREV_GROSS_D is of SMAN
SMAN_MPLANER_NHTLREV_GROSS_M	NUMBER	30	4	Y	SMAN_MPLANER_NHTLREV_GROSS_M is of SMAN
SMAN_MPLANER_NHTLREV_GROSS_Y	NUMBER	30	4	Y	SMAN_MPLANER_NHTLREV_GROSS_Y is of SMAN
SMAN_WALKEDFORTODAY_D	NUMBER	5		Y	Walked Reservations for Today
SMAN_WALKEDFORTODAY_M	NUMBER	6		Y	Walked Reservations for this Month
SMAN_WALKEDFORTODAY_Y	NUMBER	7		Y	Walked Reservations for this Year
SMAN_RESWALKEDTODAY_D	NUMBER	5		Y	Reservation Walked Today
SMAN_RESWALKEDTODAY_M	NUMBER	6		Y	Reservation Walked this Month
SMAN_RESWALKEDTODAY_Y	NUMBER	7		Y	Reservation Walked this Year
SMAN_DOMESTICCHILDS_D	NUMBER	5		Y	Domestic Children for Switzerland
SMAN_DOMESTICCHILDS_M	NUMBER	5		Y	Domestic Children for Switzerland
SMAN_DOMESTICCHILDS_Y	NUMBER	5		Y	Domestic Children for Switzerland
SMAN_ARR_DOMESTICCHILDS_D	NUMBER	5		Y	
SMAN_ARR_DOMESTICCHILDS_M	NUMBER	5		Y	
SMAN_ARR_DOMESTICCHILDS_Y	NUMBER	5		Y	
SMAN_DEP_DOMESTICCHILDS_D	NUMBER	5		Y	
SMAN_DEP_DOMESTICCHILDS_M	NUMBER	5		Y	
SMAN_DEP_DOMESTICCHILDS_Y	NUMBER	5		Y	
SMAN_DAYCOUNT	NUMBER	5		Y	
SMAN_ROOMS_OOS_D	NUMBER	5		Y	OOS Rooms Today
SMAN_ROOMS_OOS_M	NUMBER	5		Y	OOS Rooms this Month
SMAN_ROOMS_OOS_Y	NUMBER	7		Y	OOS Rooms Year
SMAN_ROOMS_OCC_DFS_D	NUMBER	5		Y	Single Occupied Double Rooms Today
SMAN_ROOMS_OCC_DFS_M	NUMBER	5		Y	Single Occupied Double Rooms this Month
SMAN_ROOMS_OCC_DFS_Y	NUMBER	7		Y	Single Occupied Double Rooms this Year
SMAN_COMP_ADULTS_D	NUMBER	5		Y	Complimentary Adults Today
SMAN_COMP_ADULTS_M	NUMBER	5		Y	Complimentary Adults this Month
SMAN_COMP_ADULTS_Y	NUMBER	7		Y	Complimentary Adults Year
SMAN_COMP_CHILDS_D	NUMBER	5		Y	Complimentary Children Today

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_COMP_CHILDS_M	NUMBER	5		Y	Complimentary Children this Month
SMAN_COMP_CHILDS_Y	NUMBER	7		Y	Complimentary Children Year
SMAN_PARTNER_ID	NUMBER	30		Y	
SMAN_IMPORTED	NUMBER	1		N	
SMAN_WPHS_ID	NUMBER	30		Y	
SMAN_REMOTE	NUMBER	1		Y	
SMAN_CHILDS_G1_D	NUMBER	6		Y	
SMAN_CHILDS_G2_D	NUMBER	7		Y	
SMAN_CHILDS_G3_D	NUMBER	7		Y	
SMAN_CHILDS_G1_M	NUMBER	6		Y	
SMAN_CHILDS_G2_M	NUMBER	7		Y	
SMAN_CHILDS_G3_M	NUMBER	7		Y	
SMAN_CHILDS_G1_Y	NUMBER	6		Y	
SMAN_CHILDS_G2_Y	NUMBER	7		Y	
SMAN_CHILDS_G3_Y	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G1_D	NUMBER	6		Y	
SMAN_DOMESTICCHILDS_G2_D	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G3_D	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G1_M	NUMBER	6		Y	
SMAN_DOMESTICCHILDS_G2_M	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G3_M	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G1_Y	NUMBER	6		Y	
SMAN_DOMESTICCHILDS_G2_Y	NUMBER	7		Y	
SMAN_DOMESTICCHILDS_G3_Y	NUMBER	7		Y	
SMAN_ARRCHILDSTOMORROW_D	NUMBER	5		Y	
SMAN_DEPCHILDSTOMORROW_D	NUMBER	5		Y	
SMAN_HOUSEUSE_ADULTS_D	NUMBER	5		Y	
SMAN_HOUSEUSE_ADULTS_M	NUMBER	5		Y	
SMAN_HOUSEUSE_ADULTS_Y	NUMBER	7		Y	
SMAN_WALKIN_ADULTS_D	NUMBER	5		Y	
SMAN_WALKIN_ADULTS_M	NUMBER	5		Y	
SMAN_WALKIN_ADULTS_Y	NUMBER	7		Y	
SMAN_DAYUSE_ADULTS_D	NUMBER	5		Y	

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_DAYUSE_ADULTS_M	NUMBER	5		Y
SMAN_DAYUSE_ADULTS_Y	NUMBER	7		Y
SMAN_RESCANCELEDTODAYDEF_D	NUMBER	5		Y
SMAN_RESCANCELEDTODAYDEF_M	NUMBER	5		Y
SMAN_RESCANCELEDTODAYDEF_Y	NUMBER	7		Y
SMAN_CANCFORTODAYDEF_D	NUMBER	5		Y
SMAN_CANCFORTODAYDEF_M	NUMBER	5		Y
SMAN_CANCFORTODAYDEF_Y	NUMBER	5		Y
SMAN_D_TOTALGROSSREV_D	NUMBER	30	4	Y
SMAN_D_TOTALGROSSREV_M	NUMBER	30	4	Y
SMAN_D_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMAN_D_TOTALNETREV_D	NUMBER	30	4	Y
SMAN_D_TOTALNETREV_M	NUMBER	30	4	Y
SMAN_D_TOTALNETREV_Y	NUMBER	30	4	Y
SMAN_D_PAYMENTS_D	NUMBER	30	4	Y
SMAN_D_PAYMENTS_M	NUMBER	30	4	Y
SMAN_D_PAYMENTS_Y	NUMBER	30	4	Y
SMAN_D_ROOMREVGROSS_D	NUMBER	30	4	Y
SMAN_D_ROOMREVGROSS_M	NUMBER	30	4	Y
SMAN_D_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_ROOMREVNET_D	NUMBER	30	4	Y
SMAN_D_ROOMREVNET_M	NUMBER	30	4	Y
SMAN_D_ROOMREVNET_Y	NUMBER	30	4	Y
SMAN_D_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMAN_D_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMAN_D_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMAN_D_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMAN_D_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMAN_D_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMAN_D_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_ROOMNHTLREVNET_D	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_D_ROOMNHTLREVN_M	NUMBER	30	4	Y
SMAN_D_ROOMNHTLREVN_Y	NUMBER	30	4	Y
SMAN_D_FBREVGROSS_D	NUMBER	30	4	Y
SMAN_D_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_FBREVN_D	NUMBER	30	4	Y
SMAN_D_FBNHTLREVN_D	NUMBER	30	4	Y
SMAN_D_FBREVGROSS_M	NUMBER	30	4	Y
SMAN_D_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_FBREVN_M	NUMBER	30	4	Y
SMAN_D_FBNHTLREVN_M	NUMBER	30	4	Y
SMAN_D_FBREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_FBREVN_Y	NUMBER	30	4	Y
SMAN_D_FBNHTLREVN_Y	NUMBER	30	4	Y
SMAN_D_MINIREVGROSS_D	NUMBER	30	4	Y
SMAN_D_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_TELEREGROSS_D	NUMBER	30	4	Y
SMAN_D_TELNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_MISCREVGROSS_D	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_D_MINIREVGROSS_M	NUMBER	30	4	Y
SMAN_D_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_TELEREGROSS_M	NUMBER	30	4	Y
SMAN_D_TELNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_MISCREVGROSS_M	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_D_MINIREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_MININHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_TELEREGROSS_Y	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_D_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_MISCREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_D_MINIREVNET_D	NUMBER	30	4	Y
SMAN_D_MININHTLREVNET_D	NUMBER	30	4	Y
SMAN_D_TELEREVNET_D	NUMBER	30	4	Y
SMAN_D_TELENHTLREVNET_D	NUMBER	30	4	Y
SMAN_D_MISCREVNET_D	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMAN_D_NOSTATREVNET_D	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMAN_D_MINIREVNET_M	NUMBER	30	4	Y
SMAN_D_MININHTLREVNET_M	NUMBER	30	4	Y
SMAN_D_TELEREVNET_M	NUMBER	30	4	Y
SMAN_D_TELENHTLREVNET_M	NUMBER	30	4	Y
SMAN_D_MISCREVNET_M	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMAN_D_NOSTATREVNET_M	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMAN_D_MINIREVNET_Y	NUMBER	30	4	Y
SMAN_D_MININHTLREVNET_Y	NUMBER	30	4	Y
SMAN_D_TELEREVNET_Y	NUMBER	30	4	Y
SMAN_D_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMAN_D_MISCREVNET_Y	NUMBER	30	4	Y
SMAN_D_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_D_NOSTATREVNET_Y	NUMBER	30	4	Y
SMAN_D_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_TOTALGROSSREV_D	NUMBER	30	4	Y
SMAN_V_TOTALGROSSREV_M	NUMBER	30	4	Y
SMAN_V_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMAN_V_TOTALNETREV_D	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_V_TOTALNETREV_M	NUMBER	30	4	Y
SMAN_V_TOTALNETREV_Y	NUMBER	30	4	Y
SMAN_V_PAYMENTS_D	NUMBER	30	4	Y
SMAN_V_PAYMENTS_M	NUMBER	30	4	Y
SMAN_V_PAYMENTS_Y	NUMBER	30	4	Y
SMAN_V_ROOMREVGROSS_D	NUMBER	30	4	Y
SMAN_V_ROOMREVGROSS_M	NUMBER	30	4	Y
SMAN_V_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_ROOMREVNET_D	NUMBER	30	4	Y
SMAN_V_ROOMREVNET_M	NUMBER	30	4	Y
SMAN_V_ROOMREVNET_Y	NUMBER	30	4	Y
SMAN_V_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMAN_V_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMAN_V_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMAN_V_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMAN_V_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMAN_V_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_FBREVGROSS_D	NUMBER	30	4	Y
SMAN_V_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_FBREVNET_D	NUMBER	30	4	Y
SMAN_V_FBNHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_FBREVGROSS_M	NUMBER	30	4	Y
SMAN_V_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_FBREVNET_M	NUMBER	30	4	Y
SMAN_V_FBNHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_FBREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_FBNHTLREVGROSS_Y	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_V_FBREVNET_Y	NUMBER	30	4	Y
SMAN_V_FBNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_MINIREVGROSS_D	NUMBER	30	4	Y
SMAN_V_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_TELEREVGROSS_D	NUMBER	30	4	Y
SMAN_V_TELENHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_MISCREVGROSS_D	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMAN_V_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMAN_V_MINIREVGROSS_M	NUMBER	30	4	Y
SMAN_V_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_TELEREVGROSS_M	NUMBER	30	4	Y
SMAN_V_TELENHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_MISCREVGROSS_M	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMAN_V_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMAN_V_MINIREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_MININHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_TELEREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_MISCREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMAN_V_MINIREVNET_D	NUMBER	30	4	Y
SMAN_V_MININHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_TELEREVNET_D	NUMBER	30	4	Y
SMAN_V_TELENHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_MISCREVNET_D	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_NOSTATREVNET_D	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_V_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMAN_V_MINIREVNET_M	NUMBER	30	4	Y
SMAN_V_MININHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_TELEREVNET_M	NUMBER	30	4	Y
SMAN_V_TELENHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_MISCREVNET_M	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_NOSTATREVNET_M	NUMBER	30	4	Y
SMAN_V_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMAN_V_MINIREVNET_Y	NUMBER	30	4	Y
SMAN_V_MININHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_TELEREVNET_Y	NUMBER	30	4	Y
SMAN_V_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_MISCREVNET_Y	NUMBER	30	4	Y
SMAN_V_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_V_NOSTATREVNET_Y	NUMBER	30	4	Y
SMAN_V_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMAN_D_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_IND_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_IND_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_COMPANY_NHTLREV_GR_OSS_D	NUMBER	30	4	Y
SMAN_D_COMPANY_NHTLREV_GR_OSS_M	NUMBER	30	4	Y
SMAN_D_COMPANY_NHTLREV_GR_OSS_Y	NUMBER	30	4	Y
SMAN_D_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_D_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_D_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMAN_D_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMAN_D_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_D_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_D_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_D_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_D_MPLANER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_D_MPLANER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_D_MPLANER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_IND_REV_GROSS_D	NUMBER	30	4	Y

## SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL
SMAN_V_IND_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_COMPANY_NHTLREV_GR OSS_D	NUMBER	30	4	Y
SMAN_V_COMPANY_NHTLREV_GR OSS_M	NUMBER	30	4	Y
SMAN_V_COMPANY_NHTLREV_GR OSS_Y	NUMBER	30	4	Y
SMAN_V_AGENT_NHTLREV_GROS S_D	NUMBER	30	4	Y
SMAN_V_AGENT_NHTLREV_GROS S_M	NUMBER	30	4	Y
SMAN_V_AGENT_NHTLREV_GROS S_Y	NUMBER	30	4	Y
SMAN_V_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMAN_V_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMAN_V_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMAN_V_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMAN_V_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMAN_V_SOURCE_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAN_V_SOURCE_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAN_V_SOURCE_NHTLREV_GRO SS_Y	NUMBER	30	4	Y
SMAN_V_BOOKER_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAN_V_BOOKER_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAN_V_BOOKER_NHTLREV_GRO SS_Y	NUMBER	30	4	Y
SMAN_V_VENDOR_NHTLREV_GRO SS_D	NUMBER	30	4	Y
SMAN_V_VENDOR_NHTLREV_GRO SS_M	NUMBER	30	4	Y
SMAN_V_VENDOR_NHTLREV_GRO SS_Y	NUMBER	30	4	Y
SMAN_V_MPLANER_NHTLREV_GRO SS_D	NUMBER	30	4	Y

### SMAN

Statistic File Manager Report Allows to continue with former manager report.Calculated by stored procedure during Night Audit.

Field Name	Type	Length	Decimals	Not NULL	
SMAN_V_MPLANER_NHTLREV_GRONUMBER SS_M		30	4	Y	
SMAN_V_MPLANER_NHTLREV_GRONUMBER SS_Y		30	4	Y	
SMAN_DAYUSEONDEPARTURE_D	NUMBER	5		Y	
SMAN_DAYUSEONDEPARTURE_M	NUMBER	5		Y	
SMAN_DAYUSEONDEPARTURE_Y	NUMBER	7		Y	
SMAN_DAYUSEONDEP_ADULTS_D	NUMBER	5		Y	
SMAN_DAYUSEONDEP_ADULTS_M	NUMBER	5		Y	
SMAN_DAYUSEONDEP_ADULTS_Y	NUMBER	7		Y	
SMAN_ROOMS_OCC_E1P_D	NUMBER	5		Y	
SMAN_ROOMS_OCC_E1P_M	NUMBER	5		Y	
SMAN_ROOMS_OCC_E1P_Y	NUMBER	7		Y	
SMAN_ROOMS_OCC_M1P_D	NUMBER	5		Y	
SMAN_ROOMS_OCC_M1P_M	NUMBER	5		Y	
SMAN_ROOMS_OCC_M1P_Y	NUMBER	7		Y	
SMAN_EARLY_DEP_ROOMS_D	NUMBER	5		Y	early departures Rooms day
SMAN_EARLY_DEP_ROOMS_M	NUMBER	5		Y	early departures Rooms month
SMAN_EARLY_DEP_ROOMS_Y	NUMBER	7		Y	early departures Rooms year
SMAN_EARLY_DEP_ADULTS_D	NUMBER	5		Y	early departures adults day
SMAN_EARLY_DEP_ADULTS_M	NUMBER	5		Y	early departures adults month
SMAN_EARLY_DEP_ADULTS_Y	NUMBER	7		Y	early departures adults year
SMAN_EARLY_DEP_CHILDS_D	NUMBER	5		Y	early departures children day
SMAN_EARLY_DEP_CHILDS_M	NUMBER	5		Y	early departures children month
SMAN_EARLY_DEP_CHILDS_Y	NUMBER	7		Y	early departures children year

### SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_ID	NUMBER	30		N
SMBD_DATE	DATE			N
SMBD_SECTION	NUMBER	2		Y
SMBD_ADULTS_D	NUMBER	5		Y
SMBD_ADULTS_M	NUMBER	5		Y
SMBD_ADULTS_Y	NUMBER	7		Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_CHILDS_D	NUMBER	5		Y
SMBD_CHILDS_M	NUMBER	5		Y
SMBD_CHILDS_Y	NUMBER	7		Y
SMBD_ROOMS_OCC_D	NUMBER	5		Y
SMBD_ROOMS_OCC_M	NUMBER	5		Y
SMBD_ROOMS_OCC_Y	NUMBER	7		Y
SMBD_ROOMSINHOTEL_D	NUMBER	5		Y
SMBD_ROOMSINHOTEL_M	NUMBER	5		Y
SMBD_ROOMSINHOTEL_Y	NUMBER	7		Y
SMBD_ROOMS_OOO_D	NUMBER	5		Y
SMBD_ROOMS_OOO_M	NUMBER	5		Y
SMBD_ROOMS_OOO_Y	NUMBER	7		Y
SMBD_WALKIN_D	NUMBER	5		Y
SMBD_WALKIN_M	NUMBER	5		Y
SMBD_WALKIN_Y	NUMBER	7		Y
SMBD_ARR_ROOMS_D	NUMBER	5		Y
SMBD_ARR_ROOMS_M	NUMBER	5		Y
SMBD_ARR_ROOMS_Y	NUMBER	7		Y
SMBD_DEP_ROOMS_D	NUMBER	5		Y
SMBD_DEP_ROOMS_M	NUMBER	5		Y
SMBD_DEP_ROOMS_Y	NUMBER	7		Y
SMBD_ARR_ADULTS_D	NUMBER	5		Y
SMBD_ARR_ADULTS_M	NUMBER	5		Y
SMBD_ARR_ADULTS_Y	NUMBER	7		Y
SMBD_ARR_CHILDS_D	NUMBER	5		Y
SMBD_ARR_CHILDS_M	NUMBER	5		Y
SMBD_ARR_CHILDS_Y	NUMBER	7		Y
SMBD_DEP_ADULTS_D	NUMBER	5		Y
SMBD_DEP_ADULTS_M	NUMBER	5		Y
SMBD_DEP_ADULTS_Y	NUMBER	7		Y
SMBD_DEP_CHILDS_D	NUMBER	5		Y
SMBD_DEP_CHILDS_M	NUMBER	5		Y
SMBD_DEP_CHILDS_Y	NUMBER	7		Y

### SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_TOTALGROSSREV_D	NUMBER	30	4	Y
SMBD_TOTALGROSSREV_M	NUMBER	30	4	Y
SMBD_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMBD_TOTALNETREV_D	NUMBER	30	4	Y
SMBD_TOTALNETREV_M	NUMBER	30	4	Y
SMBD_TOTALNETREV_Y	NUMBER	30	4	Y
SMBD_COMPROOMS_D	NUMBER	5		Y
SMBD_COMPROOMS_M	NUMBER	5		Y
SMBD_COMPROOMS_Y	NUMBER	7		Y
SMBD_HOUSEUSERROOMS_D	NUMBER	5		Y
SMBD_HOUSEUSERROOMS_M	NUMBER	5		Y
SMBD_HOUSEUSERROOMS_Y	NUMBER	7		Y
SMBD_BEDSINHOTEL_D	NUMBER	5		Y
SMBD_BEDSINHOTEL_M	NUMBER	5		Y
SMBD_BEDSINHOTEL_Y	NUMBER	7		Y
SMBD_REPEATGUESTARRROOM_D	NUMBER	5		Y
SMBD_REPEATGUESTARRROOM_M	NUMBER	5		Y
SMBD_REPEATGUESTARRROOM_Y	NUMBER	7		Y
SMBD_RESMADEtoday_D	NUMBER	5		Y
SMBD_RESMADEtoday_M	NUMBER	5		Y
SMBD_RESMADEtoday_Y	NUMBER	7		Y
SMBD_RESCANCELEDtoday_D	NUMBER	5		Y
SMBD_RESCANCELEDtoday_M	NUMBER	5		Y
SMBD_RESCANCELEDtoday_Y	NUMBER	7		Y
SMBD_ARRADULTSTOMORROW_D	NUMBER	5		Y
SMBD_DEPADULTSTOMORROW_D	NUMBER	5		Y
SMBD_ARRROOMSTOMORROW_D	NUMBER	5		Y
SMBD_DEPROOMSTOMORROW_D	NUMBER	5		Y
SMBD_COMPANY_ROOMS_D	NUMBER	5		Y
SMBD_COMPANY_ROOMS_M	NUMBER	5		Y
SMBD_COMPANY_ROOMS_Y	NUMBER	7		Y
SMBD_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMBD_COMPANY_REV_GROSS_M	NUMBER	30	4	Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_AGENT_ROOMS_D	NUMBER	5		Y
SMBD_AGENT_ROOMS_M	NUMBER	5		Y
SMBD_AGENT_ROOMS_Y	NUMBER	7		Y
SMBD_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMBD_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMBD_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_IND_ROOMS_D	NUMBER	5		Y
SMBD_IND_ROOMS_M	NUMBER	5		Y
SMBD_IND_ROOMS_Y	NUMBER	7		Y
SMBD_IND_REV_GROSS_D	NUMBER	30	4	Y
SMBD_IND_REV_GROSS_M	NUMBER	30	4	Y
SMBD_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_VIPADULTS_D	NUMBER	5		Y
SMBD_VIPADULTS_M	NUMBER	5		Y
SMBD_VIPADULTS_Y	NUMBER	7		Y
SMBD_PAYMENTS_D	NUMBER	30	4	Y
SMBD_PAYMENTS_M	NUMBER	30	4	Y
SMBD_PAYMENTS_Y	NUMBER	30	4	Y
SMBD_ROOMREVGROSS_D	NUMBER	30	4	Y
SMBD_ROOMREVGROSS_M	NUMBER	30	4	Y
SMBD_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMBD_ROOMREVNET_D	NUMBER	30	4	Y
SMBD_ROOMREVNET_M	NUMBER	30	4	Y
SMBD_ROOMREVNET_Y	NUMBER	30	4	Y
SMBD_CANCFORTODAY_D	NUMBER	5		Y
SMBD_CANCFORTODAY_M	NUMBER	5		Y
SMBD_CANCFORTODAY_Y	NUMBER	7		Y
SMBD_DEPNOTPAID_D	NUMBER	5		Y
SMBD_DEPNOTPAID_M	NUMBER	5		Y
SMBD_DEPNOTPAID_Y	NUMBER	7		Y
SMBD_NOSHOWROOMS_D	NUMBER	5		Y
SMBD_NOSHOWROOMS_M	NUMBER	5		Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_NOSHOWROOMS_Y	NUMBER	7		Y
SMBD_DAYUSERROOMS_D	NUMBER	5		Y
SMBD_DAYUSERROOMS_M	NUMBER	5		Y
SMBD_DAYUSERROOMS_Y	NUMBER	7		Y
SMBD_MAXBEDSINHOTEL_D	NUMBER	5		Y
SMBD_MAXBEDSINHOTEL_M	NUMBER	5		Y
SMBD_MAXBEDSINHOTEL_Y	NUMBER	7		Y
SMBD_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMBD_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMBD_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMBD_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMBD_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMBD_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMBD_COMPANY_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_COMPANY_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_COMPANY_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMBD_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMBD_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMBD_ROOMNHTLREVNET_M	NUMBER	30	4	Y
SMBD_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMBD_FBREVGROSS_D	NUMBER	30	4	Y
SMBD_FBREVGROSS_M	NUMBER	30	4	Y
SMBD_FBREVGROSS_Y	NUMBER	30	4	Y
SMBD_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_FBNHTLREVGROSS_M	NUMBER	30	4	Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMBD_FBREVNED_D	NUMBER	30	4	Y
SMBD_FBREVNED_M	NUMBER	30	4	Y
SMBD_FBREVNED_Y	NUMBER	30	4	Y
SMBD_FBNHTLREVNED_D	NUMBER	30	4	Y
SMBD_FBNHTLREVNED_M	NUMBER	30	4	Y
SMBD_FBNHTLREVNED_Y	NUMBER	30	4	Y
SMBD_OCCTOMORROW	NUMBER	30	4	Y
SMBD_OCCNEXTSEVENDAYS	NUMBER	30	4	Y
SMBD_OCCUNTILENDMONTH	NUMBER	30	4	Y
SMBD_OCCENDYEAR	NUMBER	30	4	Y
SMBD_OCCNEXTFOURWEEKS	NUMBER	30	4	Y
SMBD_SOURCE_ROOMS_D	NUMBER	5		Y
SMBD_SOURCE_ROOMS_M	NUMBER	5		Y
SMBD_SOURCE_ROOMS_Y	NUMBER	7		Y
SMBD_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMBD_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMBD_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_BOOKER_ROOMS_D	NUMBER	5		Y
SMBD_BOOKER_ROOMS_M	NUMBER	5		Y
SMBD_BOOKER_ROOMS_Y	NUMBER	7		Y
SMBD_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMBD_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMBD_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_VENDOR_ROOMS_D	NUMBER	5		Y
SMBD_VENDOR_ROOMS_M	NUMBER	5		Y
SMBD_VENDOR_ROOMS_Y	NUMBER	7		Y
SMBD_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMBD_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMBD_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_MPLANER_ROOMS_D	NUMBER	5		Y
SMBD_MPLANER_ROOMS_M	NUMBER	5		Y
SMBD_MPLANER_ROOMS_Y	NUMBER	7		Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMBD_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMBD_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMBD_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_MPLANER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMBD_MPLANER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMBD_MPLANER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMBD_MINIREVGROSS_D	NUMBER	30	4	Y
SMBD_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_TELEREVGROSS_D	NUMBER	30	4	Y
SMBD_TELENHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_MISCREVGROSS_D	NUMBER	30	4	Y
SMBD_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMBD_MINIREVGROSS_M	NUMBER	30	4	Y
SMBD_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMBD_TELEREVGROSS_M	NUMBER	30	4	Y
SMBD_TELENHTLREVGROSS_M	NUMBER	30	4	Y
SMBD_MISCREVGROSS_M	NUMBER	30	4	Y
SMBD_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMBD_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMBD_MINIREVGROSS_Y	NUMBER	30	4	Y
SMBD_MININHTLREVGROSS_Y	NUMBER	30	4	Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_TELEREVGROSS_Y	NUMBER	30	4	Y
SMBD_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMBD_MISCREVGROSS_Y	NUMBER	30	4	Y
SMBD_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMBD_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMBD_MINIREVNET_D	NUMBER	30	4	Y
SMBD_MININHTLREVNET_D	NUMBER	30	4	Y
SMBD_TELEREVNET_D	NUMBER	30	4	Y
SMBD_TELENHTLREVNET_D	NUMBER	30	4	Y
SMBD_MISCREVNET_D	NUMBER	30	4	Y
SMBD_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMBD_NOSTATREVNET_D	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMBD_MINIREVNET_M	NUMBER	30	4	Y
SMBD_MININHTLREVNET_M	NUMBER	30	4	Y
SMBD_TELEREVNET_M	NUMBER	30	4	Y
SMBD_TELENHTLREVNET_M	NUMBER	30	4	Y
SMBD_MISCREVNET_M	NUMBER	30	4	Y
SMBD_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMBD_NOSTATREVNET_M	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMBD_MINIREVNET_Y	NUMBER	30	4	Y
SMBD_MININHTLREVNET_Y	NUMBER	30	4	Y
SMBD_TELEREVNET_Y	NUMBER	30	4	Y
SMBD_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMBD_MISCREVNET_Y	NUMBER	30	4	Y
SMBD_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMBD_NOSTATREVNET_Y	NUMBER	30	4	Y
SMBD_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMBD_DOMESTICCHILDS_D	NUMBER	5		Y
SMBD_DOMESTICCHILDS_M	NUMBER	5		Y
SMBD_DOMESTICCHILDS_Y	NUMBER	5		Y

## SMBD

Field Name	Type	Length	Decimals	Not NULL
SMBD_ARR_DOMESTICCHILDS_D	NUMBER	5		Y
SMBD_ARR_DOMESTICCHILDS_M	NUMBER	5		Y
SMBD_ARR_DOMESTICCHILDS_Y	NUMBER	5		Y
SMBD_DEP_DOMESTICCHILDS_D	NUMBER	5		Y
SMBD_DEP_DOMESTICCHILDS_M	NUMBER	5		Y
SMBD_DEP_DOMESTICCHILDS_Y	NUMBER	5		Y
SMBD_ROOMS_OOS_D	NUMBER	5		Y
SMBD_ROOMS_OOS_M	NUMBER	5		Y
SMBD_ROOMS_OOS_Y	NUMBER	7		Y
SMBD_ROOMS_OCC_DFS_D	NUMBER	5		Y
SMBD_ROOMS_OCC_DFS_M	NUMBER	5		Y
SMBD_ROOMS_OCC_DFS_Y	NUMBER	7		Y
SMBD_COMP_ADULTS_D	NUMBER	5		Y
SMBD_COMP_ADULTS_M	NUMBER	5		Y
SMBD_COMP_ADULTS_Y	NUMBER	7		Y
SMBD_COMP_CHILDS_D	NUMBER	5		Y
SMBD_COMP_CHILDS_M	NUMBER	5		Y
SMBD_COMP_CHILDS_Y	NUMBER	7		Y
SMBD_OCCTOMORROW_D	NUMBER	30	4	Y
SMBD_OCCTOMORROW_T	NUMBER	30	4	Y
SMBD_OCCNEXTSEVENDAYS_D	NUMBER	30	4	Y
SMBD_OCCNEXTSEVENDAYS_T	NUMBER	30	4	Y
SMBD_OCCUNTILENDMONTH_D	NUMBER	30	4	Y
SMBD_OCCUNTILENDMONTH_T	NUMBER	30	4	Y
SMBD_OCCENDYEAR_D	NUMBER	30	4	Y
SMBD_OCCENDYEAR_T	NUMBER	30	4	Y
SMBD_OCCNEXTFOURWEEKS_D	NUMBER	30	4	Y
SMBD_OCCNEXTFOURWEEKS_T	NUMBER	30	4	Y
SMBD_WPHS_ID	NUMBER	30		Y
SMBD_PARTNER_ID	NUMBER	30		Y
SMBD_IMPORTED	NUMBER	1		N

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_ID	NUMBER	30		N
SMRT_DATE	DATE			N
SMRT_YCAT_ID	NUMBER	30		N
SMRT_ADULTS_D	NUMBER	5		Y
SMRT_ADULTS_M	NUMBER	5		Y
SMRT_ADULTS_Y	NUMBER	7		Y
SMRT_CHILDS_D	NUMBER	5		Y
SMRT_CHILDS_M	NUMBER	5		Y
SMRT_CHILDS_Y	NUMBER	7		Y
SMRT_ROOMS_OCC_D	NUMBER	5		Y
SMRT_ROOMS_OCC_M	NUMBER	5		Y
SMRT_ROOMS_OCC_Y	NUMBER	7		Y
SMRT_ROOMSINHOTEL_D	NUMBER	5		Y
SMRT_ROOMSINHOTEL_M	NUMBER	5		Y
SMRT_ROOMSINHOTEL_Y	NUMBER	7		Y
SMRT_ROOMS_OOO_D	NUMBER	5		Y
SMRT_ROOMS_OOO_M	NUMBER	5		Y
SMRT_ROOMS_OOO_Y	NUMBER	7		Y
SMRT_WALKIN_D	NUMBER	5		Y
SMRT_WALKIN_M	NUMBER	5		Y
SMRT_WALKIN_Y	NUMBER	7		Y
SMRT_ARR_ROOMS_D	NUMBER	5		Y
SMRT_ARR_ROOMS_M	NUMBER	5		Y
SMRT_ARR_ROOMS_Y	NUMBER	7		Y
SMRT_DEP_ROOMS_D	NUMBER	5		Y
SMRT_DEP_ROOMS_M	NUMBER	5		Y
SMRT_DEP_ROOMS_Y	NUMBER	7		Y
SMRT_ARR_ADULTS_D	NUMBER	5		Y
SMRT_ARR_ADULTS_M	NUMBER	5		Y
SMRT_ARR_ADULTS_Y	NUMBER	7		Y
SMRT_ARR_CHILDS_D	NUMBER	5		Y
SMRT_ARR_CHILDS_M	NUMBER	5		Y
SMRT_ARR_CHILDS_Y	NUMBER	7		Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_DEP_ADULTS_D	NUMBER	5		Y
SMRT_DEP_ADULTS_M	NUMBER	5		Y
SMRT_DEP_ADULTS_Y	NUMBER	7		Y
SMRT_DEP_CHILDS_D	NUMBER	5		Y
SMRT_DEP_CHILDS_M	NUMBER	5		Y
SMRT_DEP_CHILDS_Y	NUMBER	7		Y
SMRT_TOTALGROSSREV_D	NUMBER	30	4	Y
SMRT_TOTALGROSSREV_M	NUMBER	30	4	Y
SMRT_TOTALGROSSREV_Y	NUMBER	30	4	Y
SMRT_TOTALNETREV_D	NUMBER	30	4	Y
SMRT_TOTALNETREV_M	NUMBER	30	4	Y
SMRT_TOTALNETREV_Y	NUMBER	30	4	Y
SMRT_COMPROOMS_D	NUMBER	5		Y
SMRT_COMPROOMS_M	NUMBER	5		Y
SMRT_COMPROOMS_Y	NUMBER	7		Y
SMRT_HOUSEUSERROOMS_D	NUMBER	5		Y
SMRT_HOUSEUSERROOMS_M	NUMBER	5		Y
SMRT_HOUSEUSERROOMS_Y	NUMBER	7		Y
SMRT_BEDSINHOTEL_D	NUMBER	5		Y
SMRT_BEDSINHOTEL_M	NUMBER	5		Y
SMRT_BEDSINHOTEL_Y	NUMBER	7		Y
SMRT_REPEATGUESTARRROOM_D	NUMBER	5		Y
SMRT_REPEATGUESTARRROOM_M	NUMBER	5		Y
SMRT_REPEATGUESTARRROOM_Y	NUMBER	7		Y
SMRT_RESMADETDODAY_D	NUMBER	5		Y
SMRT_RESMADETDODAY_M	NUMBER	5		Y
SMRT_RESMADETDODAY_Y	NUMBER	7		Y
SMRT_RESCANCELEDTDODAY_D	NUMBER	5		Y
SMRT_RESCANCELEDTDODAY_M	NUMBER	5		Y
SMRT_RESCANCELEDTDODAY_Y	NUMBER	7		Y
SMRT_ARRADULTSTOMORROW_D	NUMBER	5		Y
SMRT_DEPADULTSTOMORROW_D	NUMBER	5		Y
SMRT_ARRROOMSTOMORROW_D	NUMBER	5		Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_DEPROOMSTOMORROW_D	NUMBER	5		Y
SMRT_COMPANY_ROOMS_D	NUMBER	5		Y
SMRT_COMPANY_ROOMS_M	NUMBER	5		Y
SMRT_COMPANY_ROOMS_Y	NUMBER	7		Y
SMRT_COMPANY_REV_GROSS_D	NUMBER	30	4	Y
SMRT_COMPANY_REV_GROSS_M	NUMBER	30	4	Y
SMRT_COMPANY_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_AGENT_ROOMS_D	NUMBER	5		Y
SMRT_AGENT_ROOMS_M	NUMBER	5		Y
SMRT_AGENT_ROOMS_Y	NUMBER	7		Y
SMRT_AGENT_REV_GROSS_D	NUMBER	30	4	Y
SMRT_AGENT_REV_GROSS_M	NUMBER	30	4	Y
SMRT_AGENT_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_IND_ROOMS_D	NUMBER	5		Y
SMRT_IND_ROOMS_M	NUMBER	5		Y
SMRT_IND_ROOMS_Y	NUMBER	7		Y
SMRT_IND_REV_GROSS_D	NUMBER	30	4	Y
SMRT_IND_REV_GROSS_M	NUMBER	30	4	Y
SMRT_IND_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_VIPADULTS_D	NUMBER	5		Y
SMRT_VIPADULTS_M	NUMBER	5		Y
SMRT_VIPADULTS_Y	NUMBER	7		Y
SMRT_PAYMENTS_D	NUMBER	30	4	Y
SMRT_PAYMENTS_M	NUMBER	30	4	Y
SMRT_PAYMENTS_Y	NUMBER	30	4	Y
SMRT_ROOMREVGROSS_D	NUMBER	30	4	Y
SMRT_ROOMREVGROSS_M	NUMBER	30	4	Y
SMRT_ROOMREVGROSS_Y	NUMBER	30	4	Y
SMRT_ROOMREVNET_D	NUMBER	30	4	Y
SMRT_ROOMREVNET_M	NUMBER	30	4	Y
SMRT_ROOMREVNET_Y	NUMBER	30	4	Y
SMRT_CANCFORTODAY_D	NUMBER	5		Y
SMRT_CANCFORTODAY_M	NUMBER	5		Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_CANCFORTODAY_Y	NUMBER	7		Y
SMRT_DEPNOTPAID_D	NUMBER	5		Y
SMRT_DEPNOTPAID_M	NUMBER	5		Y
SMRT_DEPNOTPAID_Y	NUMBER	7		Y
SMRT_NOSHOWROOMS_D	NUMBER	5		Y
SMRT_NOSHOWROOMS_M	NUMBER	5		Y
SMRT_NOSHOWROOMS_Y	NUMBER	7		Y
SMRT_DAYUSERROOMS_D	NUMBER	5		Y
SMRT_DAYUSERROOMS_M	NUMBER	5		Y
SMRT_DAYUSERROOMS_Y	NUMBER	7		Y
SMRT_MAXBEDSINHOTEL_D	NUMBER	5		Y
SMRT_MAXBEDSINHOTEL_M	NUMBER	5		Y
SMRT_MAXBEDSINHOTEL_Y	NUMBER	7		Y
SMRT_TOTALGROSSNHTLREV_D	NUMBER	30	4	Y
SMRT_TOTALGROSSNHTLREV_M	NUMBER	30	4	Y
SMRT_TOTALGROSSNHTLREV_Y	NUMBER	30	4	Y
SMRT_TOTALNETNHTLREV_D	NUMBER	30	4	Y
SMRT_TOTALNETNHTLREV_M	NUMBER	30	4	Y
SMRT_TOTALNETNHTLREV_Y	NUMBER	30	4	Y
SMRT_COMPANY_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_COMPANY_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_COMPANY_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_AGENT_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_AGENT_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_AGENT_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_IND_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_IND_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_IND_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_ROOMNHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_ROOMNHTLREVGROSS_M	NUMBER	30	4	Y
SMRT_ROOMNHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_ROOMNHTLREVNET_D	NUMBER	30	4	Y
SMRT_ROOMNHTLREVNET_M	NUMBER	30	4	Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_ROOMNHTLREVNET_Y	NUMBER	30	4	Y
SMRT_FBREVGROSS_D	NUMBER	30	4	Y
SMRT_FBREVGROSS_M	NUMBER	30	4	Y
SMRT_FBREVGROSS_Y	NUMBER	30	4	Y
SMRT_FBNHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_FBNHTLREVGROSS_M	NUMBER	30	4	Y
SMRT_FBNHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_FBREVNET_D	NUMBER	30	4	Y
SMRT_FBREVNET_M	NUMBER	30	4	Y
SMRT_FBREVNET_Y	NUMBER	30	4	Y
SMRT_FBNHTLREVNET_D	NUMBER	30	4	Y
SMRT_FBNHTLREVNET_M	NUMBER	30	4	Y
SMRT_FBNHTLREVNET_Y	NUMBER	30	4	Y
SMRT_OCCTOMORROW	NUMBER	30	4	Y
SMRT_OCCNEXTSEVENDAYS	NUMBER	30	4	Y
SMRT_OCCUNTILENDMONTH	NUMBER	30	4	Y
SMRT_OCCENDYEAR	NUMBER	30	4	Y
SMRT_OCCNEXTFOURWEEKS	NUMBER	30	4	Y
SMRT_SOURCE_ROOMS_D	NUMBER	5		Y
SMRT_SOURCE_ROOMS_M	NUMBER	5		Y
SMRT_SOURCE_ROOMS_Y	NUMBER	7		Y
SMRT_SOURCE_REV_GROSS_D	NUMBER	30	4	Y
SMRT_SOURCE_REV_GROSS_M	NUMBER	30	4	Y
SMRT_SOURCE_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_BOOKER_ROOMS_D	NUMBER	5		Y
SMRT_BOOKER_ROOMS_M	NUMBER	5		Y
SMRT_BOOKER_ROOMS_Y	NUMBER	7		Y
SMRT_BOOKER_REV_GROSS_D	NUMBER	30	4	Y
SMRT_BOOKER_REV_GROSS_M	NUMBER	30	4	Y
SMRT_BOOKER_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_VENDOR_ROOMS_D	NUMBER	5		Y
SMRT_VENDOR_ROOMS_M	NUMBER	5		Y
SMRT_VENDOR_ROOMS_Y	NUMBER	7		Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_VENDOR_REV_GROSS_D	NUMBER	30	4	Y
SMRT_VENDOR_REV_GROSS_M	NUMBER	30	4	Y
SMRT_VENDOR_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_MPLANER_ROOMS_D	NUMBER	5		Y
SMRT_MPLANER_ROOMS_M	NUMBER	5		Y
SMRT_MPLANER_ROOMS_Y	NUMBER	7		Y
SMRT_MPLANER_REV_GROSS_D	NUMBER	30	4	Y
SMRT_MPLANER_REV_GROSS_M	NUMBER	30	4	Y
SMRT_MPLANER_REV_GROSS_Y	NUMBER	30	4	Y
SMRT_SOURCE_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_SOURCE_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_SOURCE_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_BOOKER_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_BOOKER_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_BOOKER_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_VENDOR_NHTLREV_GROSS_D	NUMBER	30	4	Y
SMRT_VENDOR_NHTLREV_GROSS_M	NUMBER	30	4	Y
SMRT_VENDOR_NHTLREV_GROSS_Y	NUMBER	30	4	Y
SMRT_MPLANER_NHTLREV_GROSSNUMBER_D	NUMBER	30	4	Y
SMRT_MPLANER_NHTLREV_GROSSNUMBER_M	NUMBER	30	4	Y
SMRT_MPLANER_NHTLREV_GROSSNUMBER_Y	NUMBER	30	4	Y
SMRT_MINIREVGROSS_D	NUMBER	30	4	Y
SMRT_MININHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_TELEREVGROSS_D	NUMBER	30	4	Y
SMRT_TELENHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_MISCREVGROSS_D	NUMBER	30	4	Y
SMRT_MISCNHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_NOSTATREVGROSS_D	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVGROSS_D	NUMBER	30	4	Y
SMRT_MINIREVGROSS_M	NUMBER	30	4	Y
SMRT_MININHTLREVGROSS_M	NUMBER	30	4	Y
SMRT_TELEREVGROSS_M	NUMBER	30	4	Y
SMRT_TELENHTLREVGROSS_M	NUMBER	30	4	Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_MISCREVGROSS_M	NUMBER	30	4	Y
SMRT_MISCNHTLREVGROSS_M	NUMBER	30	4	Y
SMRT_NOSTATREVGROSS_M	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVGROSS_M	NUMBER	30	4	Y
SMRT_MINIREVGROSS_Y	NUMBER	30	4	Y
SMRT_MININHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_TELEREVGROSS_Y	NUMBER	30	4	Y
SMRT_TELENHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_MISCREVGROSS_Y	NUMBER	30	4	Y
SMRT_MISCNHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_NOSTATREVGROSS_Y	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVGROSS_Y	NUMBER	30	4	Y
SMRT_MINIREVNET_D	NUMBER	30	4	Y
SMRT_MININHTLREVNET_D	NUMBER	30	4	Y
SMRT_TELEREVNET_D	NUMBER	30	4	Y
SMRT_TELENHTLREVNET_D	NUMBER	30	4	Y
SMRT_MISCREVNET_D	NUMBER	30	4	Y
SMRT_MISCNHTLREVNET_D	NUMBER	30	4	Y
SMRT_NOSTATREVNET_D	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVNET_D	NUMBER	30	4	Y
SMRT_MINIREVNET_M	NUMBER	30	4	Y
SMRT_MININHTLREVNET_M	NUMBER	30	4	Y
SMRT_TELEREVNET_M	NUMBER	30	4	Y
SMRT_TELENHTLREVNET_M	NUMBER	30	4	Y
SMRT_MISCREVNET_M	NUMBER	30	4	Y
SMRT_MISCNHTLREVNET_M	NUMBER	30	4	Y
SMRT_NOSTATREVNET_M	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVNET_M	NUMBER	30	4	Y
SMRT_MINIREVNET_Y	NUMBER	30	4	Y
SMRT_MININHTLREVNET_Y	NUMBER	30	4	Y
SMRT_TELEREVNET_Y	NUMBER	30	4	Y
SMRT_TELENHTLREVNET_Y	NUMBER	30	4	Y
SMRT_MISCREVNET_Y	NUMBER	30	4	Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_MISCNHTLREVNET_Y	NUMBER	30	4	Y
SMRT_NOSTATREVNET_Y	NUMBER	30	4	Y
SMRT_NOSTATNHTLREVNET_Y	NUMBER	30	4	Y
SMRT_WALKEDFORTODAY_D	NUMBER	5		Y
SMRT_WALKEDFORTODAY_M	NUMBER	6		Y
SMRT_WALKEDFORTODAY_Y	NUMBER	7		Y
SMRT_RESWALKEDTODAY_D	NUMBER	5		Y
SMRT_RESWALKEDTODAY_M	NUMBER	6		Y
SMRT_RESWALKEDTODAY_Y	NUMBER	7		Y
SMRT_DOMESTICCHILDS_D	NUMBER	5		Y
SMRT_DOMESTICCHILDS_M	NUMBER	5		Y
SMRT_DOMESTICCHILDS_Y	NUMBER	5		Y
SMRT_ARR_DOMESTICCHILDS_D	NUMBER	5		Y
SMRT_ARR_DOMESTICCHILDS_M	NUMBER	5		Y
SMRT_ARR_DOMESTICCHILDS_Y	NUMBER	5		Y
SMRT_DEP_DOMESTICCHILDS_D	NUMBER	5		Y
SMRT_DEP_DOMESTICCHILDS_M	NUMBER	5		Y
SMRT_DEP_DOMESTICCHILDS_Y	NUMBER	5		Y
SMRT_OCCNEXTFOURWEEKS_D	NUMBER	30	4	Y
SMRT_OCCTOMORROW_D	NUMBER	30	4	Y
SMRT_OCCNEXTSEVENDAYS_D	NUMBER	30	4	Y
SMRT_OCCUNTILENDMONTH_D	NUMBER	30	4	Y
SMRT_OCCENDYEAR_D	NUMBER	30	4	Y
SMRT_OCCNEXTFOURWEEKS_T	NUMBER	30	4	Y
SMRT_OCCTOMORROW_T	NUMBER	30	4	Y
SMRT_OCCNEXTSEVENDAYS_T	NUMBER	30	4	Y
SMRT_OCCUNTILENDMONTH_T	NUMBER	30	4	Y
SMRT_OCCENDYEAR_T	NUMBER	30	4	Y
SMRT_DAYCOUNT	NUMBER	5		Y
SMRT_PARTNER_ID	NUMBER	30		Y
SMRT_IMPORTED	NUMBER	1		Y
SMRT_WPHS_ID	NUMBER	30		Y
SMRT_ROOMS_OOS_D	NUMBER	5		Y

## SMRT

Field Name	Type	Length	Decimals	Not NULL
SMRT_ROOMS_OOS_M	NUMBER	5		Y
SMRT_ROOMS_OOS_Y	NUMBER	7		Y
SMRT_ROOMS_OCC_DFS_D	NUMBER	5		Y
SMRT_ROOMS_OCC_DFS_M	NUMBER	5		Y
SMRT_ROOMS_OCC_DFS_Y	NUMBER	7		Y
SMRT_COMP_ADULTS_D	NUMBER	5		Y
SMRT_COMP_ADULTS_M	NUMBER	5		Y
SMRT_COMP_ADULTS_Y	NUMBER	7		Y
SMRT_COMP_CHILDS_D	NUMBER	5		Y
SMRT_COMP_CHILDS_M	NUMBER	5		Y
SMRT_COMP_CHILDS_Y	NUMBER	7		Y
SMRT_ARRCHILDSTOMORROW_D	NUMBER	5		Y
SMRT_DEPCHILDSTOMORROW_D	NUMBER	5		Y
SMRT_HOUSEUSE_ADULTS_D	NUMBER	5		Y
SMRT_HOUSEUSE_ADULTS_M	NUMBER	5		Y
SMRT_HOUSEUSE_ADULTS_Y	NUMBER	7		Y
SMRT_WALKIN_ADULTS_D	NUMBER	5		Y
SMRT_WALKIN_ADULTS_M	NUMBER	5		Y
SMRT_WALKIN_ADULTS_Y	NUMBER	7		Y
SMRT_DAYUSE_ADULTS_D	NUMBER	5		Y
SMRT_DAYUSE_ADULTS_M	NUMBER	5		Y
SMRT_DAYUSE_ADULTS_Y	NUMBER	7		Y

## SPRS

Field Name	Type	Length	Decimals	Not NULL
SPRS_XCMS_NAME1	VARCHAR2	35		N
SPRS_NAMECOUNT	NUMBER	10		N

## SRD2

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

## SRD2

Field Name	Type	Length	Decimals	Not NULL	
SRD2_ID	NUMBER	30		N	
SRD2_DATE	DATE			N	
SRD2_ZDCO_ID	NUMBER	30		N	
SRD2_YCAD_ID	NUMBER	30		N	
SRD2_NETREV_D	NUMBER	30	4	Y	
SRD2_GROSSREV_D	NUMBER	30	4	Y	
SRD2_NETREV_M	NUMBER	30	4	Y	
SRD2_GROSSREV_M	NUMBER	30	4	Y	
SRD2_NETREV_Y	NUMBER	30	4	Y	
SRD2_GROSSREV_Y	NUMBER	30	4	Y	
SRD2_PARTNER_ID	NUMBER	30		Y	
SRD2_IMPORTED	NUMBER	1		Y	
SRD2_WPHS_ID	NUMBER	30		Y	
SRD2_ZDCO_LONGDESC	VARCHAR2	30		Y	
SRD2_ZDCO_NUMERICDESC	NUMBER	5		Y	
SRD2_ZDCG_LONGDESC	VARCHAR2	30		Y	
SRD2_ZDCO_CDT	NUMBER	1		Y	
SRD2_TYPE	NUMBER	30		Y	0 Standard (all revenue), 1 Hotel, 2 Deposit, 3 Voucher

## SRDS

Revenue Statistic per Day and per Hotel Segment

Field Name	Type	Length	Decimals	Not NULL	Description
SRDS_ID	NUMBER	30		N	Unique identifier
SRDS_DATE	DATE			N	Date
SRDS_ZDCO_ID	NUMBER	30		N	Link to department code
SRDS_YCAD_ID	NUMBER	30		N	Link to hotel segment
SRDS_NETREV_D	NUMBER	30	4	Y	Net revenue daily
SRDS_GROSSREV_D	NUMBER	30	4	Y	Gross revenue daily
SRDS_NETREV_M	NUMBER	30	4	Y	Net revenue monthly
SRDS_GROSSREV_M	NUMBER	30	4	Y	Gross revenue monthly
SRDS_NETREV_Y	NUMBER	30	4	Y	Net revenue yearly
SRDS_GROSSREV_Y	NUMBER	30	4	Y	Gross revenue yearly
SRDS_PARTNER_ID	NUMBER	30		Y	ID of Partner Hotel (spare field for Hotel Connector)

## SRDS

Revenue Statistic per Day and per Hotel Segment

Field Name	Type	Length	Decimals	Not NULL	
SRDS_IMPORTED	NUMBER	1		Y	Import control flag
SRDS_WPHS_ID	NUMBER	30		Y	Link to Partner Hotel (Hotel Connector)
SRDS_ZDCO_LONGDESC	VARCHAR2	30		Y	ZDCO_LONGDESC from Partner Hotel (Hotel Connector)
SRDS_ZDCO_NUMERICDESC	NUMBER	5		Y	ZDCO_NUMERICDESC from Partner Hotel (Hotel Connector)
SRDS_ZDCG_LONGDESC	VARCHAR2	30		Y	ZDCG_LONGDESC from Partner Hotel (Hotel Connector)
SRDS_ZDCO_CDT	NUMBER	1		Y	ZDCO_CDT from Partner Hotel (Hotel Connector)
SRDS_TYPE	NUMBER	30		Y	Obsolete column, new table SRD2 used instead to differentiate

## SRP2

Field Name	Type	Length	Decimals	Not NULL	
SRP2_ID	NUMBER	30		N	
SRP2_DATE	DATE			N	
SRP2_ZDCO_ID	NUMBER	30		N	
SRP2_NETREV_D	NUMBER	30	4	Y	
SRP2_GROSSREV_D	NUMBER	30	4	Y	
SRP2_NETREV_M	NUMBER	30	4	Y	
SRP2_GROSSREV_M	NUMBER	30	4	Y	
SRP2_NETREV_Y	NUMBER	30	4	Y	
SRP2_GROSSREV_Y	NUMBER	30	4	Y	
SRP2_PARTNER_ID	NUMBER	30		Y	
SRP2_IMPORTED	NUMBER	1		Y	
SRP2_WPHS_ID	NUMBER	30		Y	
SRP2_ZDCO_LONGDESC	VARCHAR2	30		Y	
SRP2_ZDCO_NUMERICDESC	NUMBER	5		Y	
SRP2_ZDCG_LONGDESC	VARCHAR2	30		Y	
SRP2_ZDCO_CDT	NUMBER	1		Y	
SRP2_TYPE	NUMBER	30		Y	0 Standard (all revenue), 1 Hotel, 2 Deposit, 3 Voucher

## SRPD

Revenue Statistic per Day

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

## SRPD

Revenue Statistic per Day

Field Name	Type	Length	Decimals	Not NULL	
SRPD_ID	NUMBER	30		N	Primary Key
SRPD_DATE	DATE			N	Date
SRPD_ZDCO_ID	NUMBER	30		N	Link to Department Code
SRPD_NETREV_D	NUMBER	30	4	Y	net revenue
SRPD_GROSSREV_D	NUMBER	30	4	Y	gross revenue
SRPD_NETREV_M	NUMBER	30	4	Y	net revenue MTD
SRPD_GROSSREV_M	NUMBER	30	4	Y	gross revenue MTD
SRPD_NETREV_Y	NUMBER	30	4	Y	net revenue YTD
SRPD_GROSSREV_Y	NUMBER	30	4	Y	gross revenue YTD
SRPD_PARTNER_ID	NUMBER	30		Y	ID of Partner Hotel (spare field for Hotel Connector)
SRPD_IMPORTED	NUMBER	1		N	Import control flag
SRPD_WPHS_ID	NUMBER	30		Y	Link to Partner Hotel (Hotel Connector)
SRPD_ZDCO_LONGDESC	VARCHAR2	30		Y	ZDCO_LONGDESC from partner hotel
SRPD_ZDCO_NUMERICDESC	NUMBER	5		Y	ZDCO_NUMERICDESC from partner hotel
SRPD_ZDCG_LONGDESC	VARCHAR2	30		Y	ZDCG_LONGDESC from partner hotel
SRPD_ZDCO_CDT	NUMBER	1		Y	ZDCO_CDT from partner hotel
SRPD_TYPE	NUMBER	30		Y	Obsolete column, new table SRP2 used instead to differentiate

## STAB

Field Name	Type	Length	Decimals	Not NULL	
STAB_SNAPSHOTTIME	DATE			Y	
STAB_TABLE_NAME	VARCHAR2	40		Y	
STAB_ROW_NUMBER	NUMBER	30		Y	
STAB_MAX_ID	NUMBER	30		Y	
STAB_BATCH_NUMBER	NUMBER	30		Y	

## SUPL

track of the statistic tables records to be updated in master hotel

Field Name	Type	Length	Decimals	Not NULL	
SUPL_ID	NUMBER	30		N	
SUPL_TABLE_ID	NUMBER	30		N	

### SUPL

track of the statistic tables records to be updated in master hotel

Field Name	Type	Length	Decimals	Not NULL
SUPL_TABLENAME	VARCHAR2	4		Y

### TACC

TAP Commission Accounts

Field Name	Type	Length	Decimals	Not NULL	
TACC_ID	NUMBER	30		N	Unique Identifier
TACC_LONGDESC	VARCHAR2	30		N	TAP Account Name
TACC_NUMBER	VARCHAR2	30		N	TAP Account Number
TACC_ZCUR_ID	NUMBER	30		N	TAP Account Currency Link
TACC_PAIDOFF_METHOD	NUMBER	1		N	Payment type: 1=check, 2=bank draft 3=ascii export
TACC_MINIMUM_PROCESS_AMOUNT	NUMBER	30	4	N	Minimum Process Amount
TACC_MINIMUM_PROCESS_AGE	NUMBER	3		Y	Minimum Age of Commission before processed
TACC_HOLD	NUMBER	1		Y	Hold = 1 , all commissions are on hold for the bank account, we do have on hold level as well for agents and commissions. The higher level always has higher priority.
TACC_DEFAULT	NUMBER	1		Y	1 = means if no tacc can be retrieved via currency link to xccd we assign the travelagent to this account
TACC_WRPT_ID	NUMBER	30		Y	ACCOUNT CHEQUE REPORT

### TACD

TAP Commission Details (links from ZPOS to TACO) here we store separate record for tax and net revenue figures.

Field Name	Type	Length	Decimals	Not NULL	
TACD_ID	NUMBER	30		N	Unique Identifier
TACD_ZPOS_ID	NUMBER	30		Y	Link to Main zpos Record which resulted in commission created
TACD_TACO_ID	NUMBER	30		Y	Link to Commission Record
TACD_COMABLEAMOUNT	NUMBER	30	4	N	Commissionable Amount
TACD_COMM_AMOUNT	NUMBER	30	4	N	Calculated Commission Amount
TACD_DT	NUMBER	30	4	Y	TACD_DT is of TACD
TACD_DELETED	NUMBER	1		Y	1 = deleted
TACD_PROCESSEDATECHECK	NUMBER	1		Y	Obsolete column, not used anymore
TACD_TACM_ID	NUMBER	30		Y	TACD_TACM_ID is of TACD
TACD_COMMTYPE	NUMBER	1		Y	null,0 = per department code, 1= per night, 2= per stay, 3>manual, 4=Prepaid
TACD_TCCR_ID	NUMBER	30		Y	if commission is per night or per stay,commission rule is stored in order to avoid duplications
TACD_YDET_ID	NUMBER	30		Y	, Commission is created based on linked reservation night, if comm_rule=per Night

## TACD

TAP Commission Details (links from ZPOS to TACO) here we store separate record for tax and net revenue figures.

Field Name	Type	Length	Decimals	Not NULL	
TACD_TCOD_ID	NUMBER	30		Y	Id of TAP commission code calculation based on
TACD_CALC_ORIGIN	NUMBER	1		Y	Origin of calculation 1=RATE CODE, 2=TRAVEL AGENT, 3=SOURCE
TACD_YRCH_ID	NUMBER	30		Y	
TACD_NOTE	VARCHAR2	200		Y	REASON OF MANUAL COMMISSION AMOUNT
TACD_DELETEDATE	DATE			Y	Datetime of TACD deletion flag
TACD_CALCDATE	DATE			Y	Datetime of TACD record insertion
TACD_FR_COMABLEAMOUNT	NUMBER	30	4	Y	foreign currency comable amount
TACD_FR_COMM_AMOUNT	NUMBER	30	4	Y	foreign currency commission NET amount
TACD_FR_DT	NUMBER	30	4	Y	foreign currency VAT of comable amount

## TACM

Memo with deletion reason

Field Name	Type	Length	Decimals	Not NULL	
TACM_ID	NUMBER	30		N	TACM_ID identifies TACM
TACM_DELETEMEMO	VARCHAR2	400		N	TACM_DELETEMEMO partly identifies TACM

## TACO

TAP Commissions

Field Name	Type	Length	Decimals	Not NULL	
TACO_ID	NUMBER	30		N	Unique Identifier
TACO_TACR_ID	NUMBER	30		N	Link to Travel Agent or Source
TACO_YRES_ID	NUMBER	30		Y	Commission reservation link
TACO_HOLD	NUMBER	1		Y	1 = commission on hold
TACO_MANUAL	NUMBER	1		Y	1 = Manual entered or adjusted
TACO_ZFAC_ID	NUMBER	30		Y	Commissions calculated for FA

## TACR

TAP Commission Receptients

Field Name	Type	Length	Decimals	Not NULL	
TACR_ID	NUMBER	30		N	Unique Identifier
TACR_TACC_ID	NUMBER	30		N	Link to TAP Account
TACR_XCMS_ID	NUMBER	30		N	Link to Travel Agent or Source Profile

## TACR

TAP Commission Receptients

Field Name	Type	Length	Decimals	Not NULL	
TACR_HOLD	NUMBER	1		Y	Hold =1, all commissions for this agent are on hold

## TAPD

TAP PROCESS LINK TABLE TO TAP COMMISSION DETAILS TO PROCESS TABLE

Field Name	Type	Length	Decimals	Not NULL	
TAPD_ID	NUMBER	30		N	
TAPD_TAPR_ID	NUMBER	30		Y	
TAPD_TACD_ID	NUMBER	30		Y	
TAPD_VOID	NUMBER	1		Y	Rollback flag
TAPD_VOID_SYSDATE	DATE			Y	Rollback systemdate
TAPD_VOID_DATETIME	DATE			Y	Rollback date and time

## TAPR

Field Name	Type	Length	Decimals	Not NULL	
TAPR_ID	NUMBER	30		N	
TAPR_PRC_SYSDATE	DATE			N	Process systemdate
TAPR_PRC_DATETIME	DATE			Y	Process date and time
TAPR_BILLING	NUMBER	1		Y	Process is created by Billing Screen TAP Posting

## TCCL

TAP Calculations rules link to TAP Commission Codes. If no date range is entered, this link is always valid, if entered this allows to change as per contracts the cacluation methods.

Field Name	Type	Length	Decimals	Not NULL	
TCCL_ID	NUMBER	30		N	Unique Identifier
TCCL_TCOD_ID	NUMBER	30		N	Link to TAP Commission Code
TCCL_TCCR_ID	NUMBER	30		N	Link to TAP Commission Calculation rule
TCCL_FROMDATE	DATE			Y	Valid for calculation from
TCCL_TODATE	DATE			Y	Valid for calculation until this date

## TCCR

TAP Commission Calculation Rules, the rules apply to the department codes linked through TCCZ.

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

## TCCR

TAP Commission Calculation Rules, the rules apply to the department codes linked through TCCZ.

Field Name	Type	Length	Decimals	Not NULL	
TCCR_ID	NUMBER	30		N	Unique Identifier
TCCR_SHORTDESC	VARCHAR2	3		N	TAP Commission Code Short Description
TCCR_LONGDESC	VARCHAR2	30		N	TAP Commission Code Long Description
TCCR_CALC_ON_NETREV	NUMBER	1		Y	1 = Calculate on net revenue
TCCR_VAT_ON_COMMISSION	NUMBER	30	4	Y	VAT percentage amount to be added on to commission
TCCR_INACTIVE	NUMBER	1		Y	1 = Inactive
TCCR_DISPLORDER	NUMBER	3		Y	Display Order
TCCR_ADDITIONTYPE	NUMBER	1		Y	null,0 = per department code, 1= per night, 2= per stay
TCCR_RULE	NUMBER	1		Y	null,0 = addition, 1= multiplier
TCCR_VALUE	NUMBER	30	4	Y	TCCR_VALUE is of TCCR

## TCCZ

Table of TCCZ

Field Name	Type	Length	Decimals	Not NULL	
TCCZ_ID	NUMBER	30		N	Unique Identifier
TCCZ_ZDCO_ID	NUMBER	30		N	Department Code Link
TCCZ_TCCR_ID	NUMBER	30		N	Link to Tap Commission Calculation Rules

## TCOD

Travel Agent Processing Commission Codes

Field Name	Type	Length	Decimals	Not NULL	
TCOD_ID	NUMBER	30		N	Unique Identifier
TCOD_SHORTDESC	VARCHAR2	3		N	Commission Code
TCOD_LONGDESC	VARCHAR2	30		N	Commission Code Description
TCOD_DISPLORDER	NUMBER	3		N	Display Order
TCOD_MULTIPLIER	VARCHAR2	200		Y	Obsolete
TCOD_ADDITIONS	VARCHAR2	200		Y	Obsolete
TCOD_DEFAULT	NUMBER	1		Y	Default Commission Code
TCOD_INACTIVE	NUMBER	1		Y	1 = Inactive

### TCRT

TAP Commission Route, for each Travel agent or source allows to define another travel agent or source where the commission in tap is routed to. No hops are allowed. Maybe later we add from and to date range for that functionality.

Field Name	Type	Length	Decimals	Not NULL	
TCRT_ID	NUMBER	30		N	Unique Identifier
TCRT_FROM_XCMS_ID	NUMBER	30		N	Source Travel Agents XCMS_ID
TCRT_TO_XCMS_ID	NUMBER	30		N	Target Travel Agents XCMS_ID

### ULAT

User Setting for activity/task types to be displayed in Profile Tree

Field Name	Type	Length	Decimals	Not NULL	
ULAT_ID	NUMBER	30		N	Unique ID
ULAT_XCMS_ID	NUMBER	30		Y	User ID
ULAT_WATY_ID	NUMBER	30		Y	Act/Task Type ID

### VBGL

Booking - Guest link

Field Name	Type	Length	Decimals	Not NULL	
VBGL_ID	NUMBER	30		N	
VBGL_VBOK_ID	NUMBER	30		N	
VBGL_XCMS_ID	NUMBER	30		Y	
VBGL_XCAC_ID	NUMBER	30		Y	
VBGL_XCAC_INDEX	NUMBER	2		Y	

### VBOA

Attribute link to Service Plan

Field Name	Type	Length	Decimals	Not NULL	
VBOA_ID	NUMBER	30		N	
VBOA_VBOK_ID	NUMBER	30		N	
VBOA_XPDA_ID	NUMBER	30		N	

### VBOK

Booking. Collects room reservations and service reservations

Field Name	Type	Length	Decimals	Not NULL	
VBOK_ID	NUMBER	30		N	
VBOK_XCMS_ID	NUMBER	30		N	

## VBOK

Booking. Collects room reservations and service reservations

Field Name	Type	Length	Decimals	Not NULL
VBOK_YGCO_ID	NUMBER	30		Y
VBOK_STATUS	NUMBER	1		N 0=tentative 1=definitive 2=offer 3=cancelled
VBOK_WCOL_ID	NUMBER	30		Y
VBOK_ZCUR_ID	NUMBER	30		Y
VBOK_YCDP_ID	NUMBER	30		Y
VBOK_BONUS_XMNR_ID	NUMBER	30		Y
VBOK_CONFIRMATIONNO	VARCHAR2	10		N
VBOK_NOOFPERSONS	NUMBER	4		N
VBOK_STARTDATE	DATE			Y
VBOK_ENDDATE	DATE			Y
VBOK_FREETEXT1	VARCHAR2	100		Y
VBOK_FREETEXT2	VARCHAR2	100		Y
VBOK_XCMA_ID	NUMBER	30		Y
VBOK_CHANNEL_YRAS_ID	NUMBER	30		Y
VBOK_SOURCE_YRAS_ID	NUMBER	30		Y
VBOK_READONLY	DATE			Y
VBOK_OPTIONDATE	DATE			Y

## VBOP

Service Plan - Person number

Field Name	Type	Length	Decimals	Not NULL
VBOP_ID	NUMBER	30		N
VBOP_VBOK_ID	NUMBER	30		N
VBOP_XCAC_ID	NUMBER	30		N
VBOP_NUMBER	NUMBER	3		N

## VBPL

Booking - Profile link (guests, travel agent, booker etc)

Field Name	Type	Length	Decimals	Not NULL
VBPL_ID	NUMBER	30		N
VBPL_VBOK_ID	NUMBER	30		N
VBPL_XCMS_ID	NUMBER	30		Y

## VCAS

Available service list for hotels

Field Name	Type	Length	Decimals	Not NULL
VCAS_ID	NUMBER	30		N
VCAS_VCTY_ID	NUMBER	30		N
VCAS_VSTS_ID	NUMBER	30		N
VCAS_NUMBER	NUMBER	3		Y

## VCTY

City

Field Name	Type	Length	Decimals	Not NULL
VCTY_ID	NUMBER	30		N
VCTY_SHORTDESC	VARCHAR2	12		N
VCTY_LONGDESC	VARCHAR2	30		N
VCTY_DISPLORDER	NUMBER	3		Y
VCTY_XCOU_ID	VARCHAR2	30		Y
VCTY_INACTIVE	NUMBER	1		N

## VLAS

Available service list for locations

Field Name	Type	Length	Decimals	Not NULL
VLAS_ID	NUMBER	30		N
VLAS_VLOC_ID	NUMBER	30		N
VLAS_VSTS_ID	NUMBER	30		N
VLAS_NUMBER	NUMBER	3		Y

## VLOC

Location

Field Name	Type	Length	Decimals	Not NULL
VLOC_ID	NUMBER	30		N
VLOC_SHORTDESC	VARCHAR2	12		N
VLOC_LONGDESC	VARCHAR2	30		N
VLOC_DISPLORDER	NUMBER	3		Y
VLOC_INACTIVE	NUMBER	1		N
VLOC_VCTY_ID	VARCHAR2	30		Y

### VLOC

Location

Field Name	Type	Length	Decimals	Not NULL	
VLOC_WPHS_ID	VARCHAR2	30		Y	
VLOC_WPHSREPR	NUMBER	1		N	Hotel representation type: 0=hotel 1=location inside hotel 2=location near hotel
VLOC_GPS	VARCHAR2	50		Y	

### VPOS

Service charges (later transferred to zpos in central, or to partner, or to third party system)

Field Name	Type	Length	Decimals	Not NULL	
VPOS_ID	NUMBER	30		N	
VPOS_VSRV_ID	NUMBER	30		N	
VPOS_XCMS_ID	NUMBER	30		N	
VPOS_DATE	DATE			N	
VPOS_POSTINGDATE	DATE			N	
VPOS_ZDCO_ID	NUMBER	30		N	
VPOS_UNITPRICE	NUMBER	30	4	N	
VPOS_QUANTITY	NUMBER	10		N	
VPOS_TAXLINK_ID	NUMBER	30		N	
VPOS_INERNALSPLIT_ID	NUMBER	30		N	
VPOS_DT	NUMBER	1		N	
VPOS_GROSSUNITPRICE	NUMBER	30		N	
VPOS_TRANSFERRED	NUMBER	1		N	0=not transferred 1=transferred
VPOS_POSTED	NUMBER	1		N	
VPOS_ZPOS_ID	NUMBER	30		Y	In central postings only. Empty if transferred to partner. (Partner stores vpos_id for reference)
VPOS_WPHS_ID	NUMBER	30		Y	Empty for central postings. Filled for items to be transferred
VPOS_FOREIGNUNITPRICE	NUMBER	30	4	Y	
VPOS_FOREIGNGROSSUNITPRICE	NUMBER	30	4	Y	
VPOS_ZCUR_ID	NUMBER	30		N	
VPOS_TYPE	NUMBER	1		N	0=price 1=cost 2=tax
VPOS_YPOS_TYPE	NUMBER	1		Y	Same as ypos_type. Data is copied from ypos
VPOS_M_ZCUR_ID	NUMBER	30		Y	Mirror home currency
VPOS_M_UNITPRICE	NUMBER	30		Y	Mirror unit price in mirror home currency
VPOS_M_GROSSUNITPRICE	NUMBER	30		Y	Mirror gross unit price in mirror home currency

## VRST

Regular service timetable (transport timetable. ie: flights)

Field Name	Type	Length	Decimals	Not NULL
VRST_ID	NUMBER	30		N
VRST_SHORTDESC	VARCHAR2	10		Y
VRST_LONGDESC	VARCHAR2	50		Y
VRST_VSTS_ID	NUMBER	30		N
VRST_FROMDATE	DATE			N
VRST_TODATE	DATE			N
VRST_STARTTIME	DATE			Y
VRST_ENDTIME	DATE			Y
VRST_FROM_VLOC_ID	NUMBER	30		Y
VRST_TO_VLOC_ID	NUMBER	30		Y
VRST_WEEKLYSCHEDULE	CHAR			N
VRST_INACTIVE	NUMBER	1		N
VRST_WCOL_ID	NUMBER	30		Y

## VSAA

Attribute link to Service Allocation

Field Name	Type	Length	Decimals	Not NULL
VSAA_ID	NUMBER	30		N
VSAA_VSAH_ID	NUMBER	30		N
VSAA_XPDA_ID	NUMBER	30		N

## VSAD

Service allocation detail

Field Name	Type	Length	Decimals	Not NULL
VSAD_ID	NUMBER	30		N
VSAD_VSAH_ID	NUMBER	30		N
VSAD_VSSV_ID	NUMBER	30		Y
VSAD_VSCL_ID	NUMBER	30		Y
VSAD_NOOFPERSONS	NUMBER	30		N
VSAD_PRICE	NUMBER	30	4	Y
VSAD_COST	NUMBER	30	4	Y
VSAD_TAX	NUMBER	30	4	Y

## VSAD

Service allocation detail

Field Name	Type	Length	Decimals	Not NULL
VSAD_PRICE_MANUAL	NUMBER	30	4	Y
VSAD_COST_MANUAL	NUMBER	30	4	Y
VSAD_TAX_MANUAL	NUMBER	30	4	Y
VSAD_PRICE_FOREIGN	NUMBER	30	4	Y
VSAD_COST_FOREIGN	NUMBER	30	4	Y
VSAD_TAX_FOREIGN	NUMBER	30	4	Y
VSAD_PRICE_FOREIGN_MANUAL	NUMBER	30	4	Y
VSAD_COST_FOREIGN_MANUAL	NUMBER	30	4	Y
VSAD_TAX_FOREIGN_MANUAL	NUMBER	30	4	Y
VSAD_PRICE_ZDCO_ID	NUMBER	30		Y
VSAD_COST_ZDCO_ID	NUMBER	30		Y
VSAD_TAX_ZDCO_ID	NUMBER	30		Y
VSAD_PRICE_ZCUR_ID	NUMBER	30		Y
VSAD_COST_ZCUR_ID	NUMBER	30		Y
VSAD_TAX_ZCUR_ID	NUMBER	30		Y
VSAD_PRICE_EXCHRATE	NUMBER	38	18	Y
VSAD_COST_EXCHRATE	NUMBER	38	18	Y
VSAD_TAX_EXCHRATE	NUMBER	38	18	Y
VSAD_PRICE_REVERSEEXCHRATE	NUMBER	1		Y
VSAD_COST_REVERSEEXCHRATE	NUMBER	1		Y
VSAD_TAX_REVERSEEXCHRATE	NUMBER	1		Y
VSAD_PRICE_FINALAMOUNT	NUMBER	30	4	Y
VSAD_PRICE_FOREIGNFINALAMOUNT	NUMBER	30	4	Y
VSAD_COST_FINALAMOUNT	NUMBER	30	4	Y
VSAD_COST_FOREIGNFINALAMOUNT	NUMBER	30	4	Y
VSAD_TAX_FINALAMOUNT	NUMBER	30	4	Y
VSAD_TAX_FOREIGNFINALAMOUNT	NUMBER	30	4	Y
VSAD_PRICE_PERCENTAGE	NUMBER	1		N
VSAD_PRICE_PERCENTAGEVALUE	NUMBER	30	4	Y

## VSAH

Service Allocation header

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

## VSAH

Service Allocation header

Field Name	Type	Length	Decimals	Not NULL	
VSAH_ID	NUMBER	30		N	
VSAH_SHORTDESC	VARCHAR2	10		Y	
VSAH_LONGDESC	VARCHAR2	60		Y	
VSAH_STATUS	NUMBER	1		N	0=definitive 1=tentative 2=cancelled
VSAH_FROMDATE	DATE			Y	
VSAH_TODATE	DATE			Y	
VSAH_CUTOFFDATE	DATE			Y	
VSAH_CUTOFFDAYS	NUMBER	3		Y	
VSAH_PRICE	NUMBER	30	4	Y	
VSAH_COST	NUMBER	30	4	Y	
VSAH_TAX	NUMBER	30	4	Y	
VSAH_PRICE_MANUAL	NUMBER	30	4	Y	
VSAH_COST_MANUAL	NUMBER	30	4	Y	
VSAH_TAX_MANUAL	NUMBER	30	4	Y	
VSAH_PRICE_FOREIGN	NUMBER	30	4	Y	
VSAH_COST_FOREIGN	NUMBER	30	4	Y	
VSAH_TAX_FOREIGN	NUMBER	30	4	Y	
VSAH_PRICE_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSAH_COST_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSAH_TAX_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSAH_PRICE_ZDCO_ID	NUMBER	30		Y	
VSAH_COST_ZDCO_ID	NUMBER	30		Y	
VSAH_TAX_ZDCO_ID	NUMBER	30		Y	
VSAH_PRICE_ZCUR_ID	NUMBER	30		Y	
VSAH_COST_ZCUR_ID	NUMBER	30		Y	
VSAH_TAX_ZCUR_ID	NUMBER	30		Y	
VSAH_PRICE_EXCHRATE	NUMBER	38	18	Y	
VSAH_COST_EXCHRATE	NUMBER	38	18	Y	
VSAH_TAX_EXCHRATE	NUMBER	38	18	Y	
VSAH_PRICE_REVERSEEXCHRATE	NUMBER	1		Y	
VSAH_COST_REVERSEEXCHRATE	NUMBER	1		Y	
VSAH_TAX_REVERSEEXCHRATE	NUMBER	1		Y	
VSAH_PRICE_FINALAMOUNT	NUMBER	30	4	Y	

## VSAH

Service Allocation header

Field Name	Type	Length	Decimals	Not NULL
VSAH_PRICE_FOREIGNFINALAMOUNT NT	NUMBER	30	4	Y
VSAH_COST_FINALAMOUNT	NUMBER	30	4	Y
VSAH_COST_FOREIGNFINALAMOU NT	NUMBER	30	4	Y
VSAH_TAX_FINALAMOUNT	NUMBER	30	4	Y
VSAH_TAX_FOREIGNFINALAMOUN T	NUMBER	30	4	Y
VSAH_PRICE_PERCENTAGE	NUMBER	1		N
VSAH_PRICE_PERCENTAGEVALUE	NUMBER	30	4	Y

## VSAV

Service availability

Field Name	Type	Length	Decimals	Not NULL
VSAV_ID	NUMBER	30		N
VSAV_VSTS_ID	NUMBER	30		N
VSAV_FROMDATE	DATE			N
VSAV_TODATE	DATE			N
VSAV_FROMHOUR	DATE			Y
VSAV_TOHOUR	DATE			Y
VSAV_MON	NUMBER	1		Y
VSAV_TUE	NUMBER	1		Y
VSAV_WED	NUMBER	1		Y
VSAV_THU	NUMBER	1		Y
VSAV_FRI	NUMBER	1		Y
VSAV_SAT	NUMBER	1		Y
VSAV_SUN	NUMBER	1		Y
VSAV_STATUS	NUMBER	1		N

0=not available 1=available

## VSCC

Service Class - Cost Package link

Field Name	Type	Length	Decimals	Not NULL
VSCC_ID	NUMBER	30		N
VSCC_VSCL_ID	NUMBER	30		N
VSCC_YPAC_ID	NUMBER	30		N

## VSCL

Service class

Field Name	Type	Length	Decimals	Not NULL
VSCL_ID	NUMBER	30		N
VSCL_SHORTDESC	VARCHAR2	12		N
VSCL_LONGDESC	VARCHAR2	30		N
VSCL_DISPLORDER	NUMBER	3		Y
VSCL_VSTS_ID	NUMBER	30		N
VSCL_INACTIVE	NUMBER	1		N
VSCL_SIMPLEPRICESETUP	NUMBER	1		N
VSCL_PRICE	NUMBER	30	4	Y
VSCL_PRICE_ZCUR_ID	NUMBER	30		Y
VSCL_PRICE_ZDCO_ID	NUMBER	30		Y
VSCL_PRICEFLAT	NUMBER	1		N
VSCL_PRICEPERCENTAGE	NUMBER	1		N
VSCL_PRICE_YRCH_ID	NUMBER	30		Y
VSCL_SIMPLECOSTSETUP	NUMBER	1		N
VSCL_COST	NUMBER	30	4	Y
VSCL_COST_ZCUR_ID	NUMBER	30		Y
VSCL_COST_ZDCO_ID	NUMBER	30		Y
VSCL_COSTFLAT	NUMBER	1		N
VSCL_COST_YRCH_ID	NUMBER	30		Y
VSCL_SIMPLETAXSETUP	NUMBER	1		N
VSCL_TAX	NUMBER	30	4	Y
VSCL_TAX_ZCUR_ID	NUMBER	30		Y
VSCL_TAX_ZDCO_ID	NUMBER	30		Y
VSCL_TAXFLAT	NUMBER	1		N
VSCL_TAX_YRCH_ID	NUMBER	30		Y

## VSCP

Service Class - Price Package link

Field Name	Type	Length	Decimals	Not NULL
VSCP_ID	NUMBER	30		N
VSCP_VSCL_ID	NUMBER	30		N
VSCP_YPAC_ID	NUMBER	30		N

## VSCT

Service Class - Cost Package link

Field Name	Type	Length	Decimals Not NULL
VSCT_ID	NUMBER	30	N
VSCT_VSCL_ID	NUMBER	30	N
VSCT_YPAC_ID	NUMBER	30	N

## VSPC

Service - Cost Package link

Field Name	Type	Length	Decimals Not NULL
VSPC_ID	NUMBER	30	N
VSPC_VSTS_ID	NUMBER	30	N
VSPC_YPAC_ID	NUMBER	30	N

## VSPL

Service - Price Package link

Field Name	Type	Length	Decimals Not NULL
VSPL_ID	NUMBER	30	N
VSPL_VSTS_ID	NUMBER	30	N
VSPL_YPAC_ID	NUMBER	30	N

## VSPT

Service - Tax Package link

Field Name	Type	Length	Decimals Not NULL
VSPT_ID	NUMBER	30	N
VSPT_VSTS_ID	NUMBER	30	N
VSPT_YPAC_ID	NUMBER	30	N

## VSRA

Attribute link to Service Booking

Field Name	Type	Length	Decimals Not NULL
VSRA_ID	NUMBER	30	N
VSRA_VSRV_ID	NUMBER	30	N
VSRA_XPDA_ID	NUMBER	30	N

## VSRE

Service reservation - Employee link (ie: drivers)

Field Name	Type	Length	Decimals	Not NULL
VSRE_ID	NUMBER	30		N
VSRE_VSRV_ID	NUMBER	30		N
VSRE_XCED_ID	NUMBER	30		N

## VSRG

Service reservation - Guest link

Field Name	Type	Length	Decimals	Not NULL	
VSRG_ID	NUMBER	30		N	
VSRG_VSRV_ID	NUMBER	30		N	
VSRG_ROLE	NUMBER	1		N	0=guest 1=linked for internalcategory
VSRG_XCMS_ID	NUMBER	30		Y	
VSRG_XCAC_ID	NUMBER	30		Y	
VSRG_XCAC_INDEX	NUMBER	2		Y	

## VSRP

Service reservation - Person number

Field Name	Type	Length	Decimals	Not NULL
VSRP_ID	NUMBER	30		N
VSRP_VSRV_ID	NUMBER	30		N
VSRP_XCAC_ID	NUMBER	30		N
VSRP_NUMBER	NUMBER	3		N
VSRP_VSCL_ID	NUMBER	30		Y
VSRP_VSAD_ID	NUMBER	30		Y

## VSRV

Service reservation (leg)

Field Name	Type	Length	Decimals	Not NULL	
VSRV_ID	NUMBER	30		N	
VSRV_TYPE	NUMBER	1		N	0=service 1=room reservation 2=third party service
VSRV_NOOFPERSONS	NUMBER	30		Y	
VSRV_VBOK_ID	NUMBER	30		Y	
VSRV_NUMBER	VARCHAR2	30		Y	

## VSRV

Service reservation (leg)

Field Name	Type	Length	Decimals	Not NULL	
VSRV_INVOICEDINCENTRAL	NUMBER	1		N	
VSRV_SYSTEMNAME	VARCHAR2	10		Y	Third party related service. Empty=fidelio
VSRV_LINKID	VARCHAR2	50		Y	Id in third party system
VSRV_START_WPHS_ID	NUMBER	30		Y	
VSRV_END_WPHS_ID	NUMBER	30		Y	
VSRV_INVOICE_WPHS_ID	NUMBER	30		Y	
VSRV_FROMDATE	DATE			Y	
VSRV_TODATE	DATE			Y	
VSRV_FROMTIME	DATE			Y	
VSRV_TOTIME	DATE			Y	
VSRV_CONFIRMATIONNO	VARCHAR2	30		Y	
VSRV_VSCL_ID	NUMBER	30		Y	
VSRV_PRICE_ZCUR_ID	NUMBER	30		Y	
VSRV_PRICE	NUMBER	30	4	Y	
VSRV_PRICE_FOREIGN	NUMBER	30	4	Y	
VSRV_PRICE_MANUAL	NUMBER	30	4	Y	
VSRV_PRICE_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSRV_PRICE_EXCHRATE	NUMBER	38	18	Y	
VSRV_PRICE_REVERSEEXCHRATE	NUMBER	1		Y	
VSRV_PRICE_FINALAMOUNT	NUMBER	30	4	Y	
VSRV_PRICE_FOREIGNFINALAMOUNT	NUMBER	30	4	Y	
VSRV_PRICE_PERCENTAGE	NUMBER	1		N	
VSRV_PRICE_PERCENTAGEVALUE	NUMBER	30	4	Y	
VSRV_COST_ZCUR_ID	NUMBER	30		Y	
VSRV_COST	NUMBER	30	4	Y	
VSRV_COST_FOREIGN	NUMBER	30	4	Y	
VSRV_COST_MANUAL	NUMBER	30	4	Y	
VSRV_COST_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSRV_COST_EXCHRATE	NUMBER	38	18	Y	
VSRV_COST_REVERSEEXCHRATE	NUMBER	1		Y	
VSRV_COST_FINALAMOUNT	NUMBER	30	4	Y	
VSRV_COST_FOREIGNFINALAMOUNT	NUMBER	30	4	Y	
VSRV_TAX_ZCUR_ID	NUMBER	30		Y	

### VSRV

Service reservation (leg)

Field Name	Type	Length	Decimals	Not NULL	
VSRV_TAX	NUMBER	30	4	Y	
VSRV_TAX_FOREIGN	NUMBER	30	4	Y	
VSRV_TAX_MANUAL	NUMBER	30	4	Y	
VSRV_TAX_FOREIGN_MANUAL	NUMBER	30	4	Y	
VSRV_TAX_EXCHRATE	NUMBER	38	18	Y	
VSRV_TAX_REVERSEEXCHRATE	NUMBER	1		Y	
VSRV_TAX_FINALAMOUNT	NUMBER	30	4	Y	
VSRV_TAX_FOREIGNFINALAMOUNT	NUMBER	30	4	Y	
VSRV_STATUS	NUMBER	1		N	0=tentative 1=definitive 2=cancelled
VSRV_POSTTIME	DATE			Y	
VSRV_DESC	VARCHAR2	200		Y	
VSRV_FROM_VLOC_ID	NUMBER	30		Y	Location info for non scheduled services (vssv) ie reservations and third party services
VSRV_TO_VLOC_ID	NUMBER	30		Y	Location info for non scheduled services (vssv) ie reservations and third party services
VSRV_VSAH_ID	NUMBER	30		Y	
VSRV_AFFECTSAVAILABILITY	NUMBER	1		N	

### VSSA

Attribute link to Scheduled Service

Field Name	Type	Length	Decimals	Not NULL
VSSA_ID	NUMBER	30		N
VSSA_VSSV_ID	NUMBER	30		N
VSSA_XPDA_ID	NUMBER	30		N

### VSSV

Scheduled service (ie: taxi or flight)

Field Name	Type	Length	Decimals	Not NULL	
VSSV_ID	NUMBER	30		N	
VSSV_SHORTDESC	VARCHAR2	10		Y	
VSSV_LONGDESC	VARCHAR2	50		Y	
VSSV_VSTG_ID	NUMBER	30		N	for drafts without vsts id
VSSV_VSTS_ID	NUMBER	30		Y	
VSSV_VRST_ID	NUMBER	30		Y	

### VSSV

Scheduled service (ie: taxi or flight)

Field Name	Type	Length	Decimals	Not NULL	
VSSV_FROM_VLOC_ID	NUMBER	30		Y	
VSSV_TO_VLOC_ID	NUMBER	30		Y	
VSSV_FROM	DATE			N	
VSSV_TO	DATE			Y	
VSSV_FROMTIME	DATE			Y	
VSSV_TOTIME	DATE			Y	
VSSV_ORIGINALFROMTIME	DATE			Y	
VSSV_ORIGINALTOTIME	DATE			Y	
VSSV_DURATIONMINUTES	NUMBER	4		Y	
VSSV_WCOL_ID	NUMBER	30		Y	
VSSV_VALIDATIONTIME	DATE			Y	1=Resquest is validated for availability 0=Request/promise only
VSSV_ORGANISEDTIME	DATE			Y	1=Service is organised and booked to happen
VSSV_STATUS	NUMBER	1		N	0=active 1=cancelled
VSSV_CLOSEDFORINDEPENDENT	DATE			Y	1=closed for independent booking. Allocation only

### VSTG

Service type group

Field Name	Type	Length	Decimals	Not NULL
VSTG_ID	NUMBER	30		N
VSTG_SHORTDESC	VARCHAR2	12		N
VSTG_LONGDESC	VARCHAR2	30		N
VSTG_INACTIVE	NUMBER	1		N
VSTG_DISPLORDER	NUMBER	3		Y

### VSTS

Service type

Field Name	Type	Length	Decimals	Not NULL
VSTS_ID	NUMBER	30		N
VSTS_SHORTDESC	VARCHAR2	12		N
VSTS_LONGDESC	VARCHAR2	30		N
VSTS_DISPLORDER	NUMBER	3		Y
VSTS_VSTG_ID	NUMBER	30		N

### VSTS

Service type

Field Name	Type	Length	Decimals	Not NULL	
VSTS_PROVIDER_XCMS_ID	NUMBER	30		Y	
VSTS_THIRDPARTY	NUMBER	1		N	
VSTS_ALLOCATIONS	NUMBER	1		N	
VSTS_MAXNUMBER	NUMBER	3		Y	For example: for hotel owned vehicles have a maximum number
VSTS_CHARGETYPE	NUMBER	1		N	0=once 1=per hour 2=per day
VSTS_INACTIVE	NUMBER	1		N	
VSTS_WCOL_ID	NUMBER	30		Y	
VSTS_SCHEDULED	NUMBER	1		N	0=service is available on demand. ie: taxi 1=available at prescheduled times
VSTS_FROMTIME	DATE			Y	For non scheduled services this defines availability of service during the day
VSTS_UNTILTIME	DATE			Y	For non scheduled services this defines availability of service during the day
VSTS_PICKUPNEEDED	NUMBER	1		N	
VSTS_MINPERSON	NUMBER	3		Y	
VSTS_MAXPERSON	NUMBER	3		Y	
VSTS_TODATEALLOWED	NUMBER	1		N	
VSTS_TOTIMEALLOWED	NUMBER	1		N	
VSTS_DESCRIPTIONALLOWED	NUMBER	1		N	0=disabled 1=enabled 2=mandatory
VSTS_SIMPLEPRICESETUP	NUMBER	1		N	
VSTS_PRICE	NUMBER	30	4	Y	
VSTS_PRICE_ZCUR_ID	NUMBER	30		Y	
VSTS_PRICE_ZDCO_ID	NUMBER	30		Y	
VSTS_PRICEFLAT	NUMBER	1		N	
VSTS_PRICEPERCENTAGE	NUMBER	1		N	
VSTS_PRICE_YRCH_ID	NUMBER	30		Y	
VSTS_SIMPLECOSTSETUP	NUMBER	1		N	
VSTS_COST	NUMBER	30	4	Y	
VSTS_COST_ZCUR_ID	NUMBER	30		Y	
VSTS_COST_ZDCO_ID	NUMBER	30		Y	
VSTS_COSTFLAT	NUMBER	1		N	
VSTS_COST_YRCH_ID	NUMBER	30		Y	
VSTS_SIMPLETAXSETUP	NUMBER	1		N	
VSTS_TAX	NUMBER	30	4	Y	
VSTS_TAX_ZCUR_ID	NUMBER	30		Y	
VSTS_TAX_ZDCO_ID	NUMBER	30		Y	

### VSTS

Service type

Field Name	Type	Length	Decimals	Not NULL	
VSTS_TAX_YRCH_ID	NUMBER	30		Y	
VSTS_PRICEDESCALLOWED	NUMBER	1		N	0=disabled 1=enabled 2=mandatory
VSTS_TAXFLAT	NUMBER	1		N	
VSTS_ALLOWWITHOUTCLASS	NUMBER	1		N	

### W8HP

Suite 8 Home page configuration table

Field Name	Type	Length	Decimals	Not NULL	
W8HP_ID	NUMBER	30		N	
W8HP_URLTEXT	VARCHAR2	200		Y	
W8HP_QUESTIONNAIRETEXT	VARCHAR2	2000		Y	Introduction text as shown on Questionnaire web page
W8HP_TABRESMAXPAX	NUMBER	2		Y	
W8HP_XPDA_ID	NUMBER	30		Y	
W8HP_CCM_WRPT_ID	NUMBER	30		Y	
W8HP_CCM_MS_XCMA_ID	NUMBER	30		Y	CCM Web Booking Market Segment
W8HP_CCM_SC_YRAS_ID	NUMBER	30		Y	CCM Web Booking Source Code
W8HP_CCM_CC_YRAS_ID	NUMBER	30		Y	CCM Web Booking Channel Code
W8HP_CCM_NC_XCNC_ID	NUMBER	30		Y	CCM Web Booking Notes Category
W8HP_CCM_CM_XCMS_ID	NUMBER	30		Y	CCM Web Booking Conference Manager
W8HP_XML_MWRD	DATE			Y	XML Max Web Reservation Date
W8HP_XML_S8HPAVLLIMIT_YALG_ID	NUMBER	30		Y	XML S8HP Avl. Limit
W8HP_FACEBOOKBUTTON	NUMBER	1		Y	
W8HP_TWITTERBUTTON	NUMBER	1		Y	
W8HP_GOOGLEPLUS	NUMBER	1		Y	
W8HP_BOOKWITHOUTREGISTRATION	NUMBER	1		Y	
W8HP_USERATEMARKET	NUMBER	1		Y	S8HP should user rate market code if it is defined
W8HP_MYSTAYCHECKIN	NUMBER	1		Y	
W8HP_PAYDIRECT	NUMBER	1		Y	if 1, it is not necessary to enter a credit card and and the customer is routed to the defined pay system before reservation is confirmed.
W8HP_QNR_SENDFNOTIFICATION	NUMBER	1		Y	Send email notification, when guest fills out questionnaire
W8HP_QNR_WRPT_ID	NUMBER	30		Y	Email Subject Report id
W8HP_QNR_EMAILID	VARCHAR2	300		Y	Email id of the receiver
W8HP_QNR_SUBJECT_WRPT_ID	NUMBER	30		Y	

## W8HP

Suite 8 Home page configuration table

Field Name	Type	Length	Decimals	Not NULL
W8HP_ONLIENEPAYMENTIFRAME	NUMBER	1		Y
W8HP_MAXPAX	NUMBER	2		Y
W8HP_MAXADULT	NUMBER	2		Y
W8HP_MAXCHILDREN	NUMBER	2		Y
W8HP_DEPOSIT_ZDCO_ID	NUMBER	30		Y
W8HP_LOGIN_WITH_RESID	NUMBER	1		Y
W8HP_PROFILEPICTURE	NUMBER	1		Y
W8HP_MAXIMGHEIGHT	NUMBER	6		Y
W8HP_MAXIMGWIDTH	NUMBER	6		Y
W8HP_MINLOS	NUMBER	3		Y
W8HP_MAXLOS	NUMBER	3		Y
W8HP_BASKET_WRPT_ID	NUMBER	30		Y
W8HP_REG_SHOWPREFERENCES	NUMBER	1		Y
W8HP_REG_SHOWOTHERPREFE NCES	NUMBER	1		Y
W8HP_REG_SHOWTABLERESERVA TIONS	NUMBER	1		Y
W8HP_REG_SHOWBONUSPOINTS	NUMBER	1		Y
W8HP_REG_SHOWREGISTEREDEV ENTS	NUMBER	1		Y
W8HP_REG_SHOWRESERVATIONS	NUMBER	1		Y
W8HP_REG_SHOWALLOTTMENTS	NUMBER	1		Y
W8HP_CALENDAREVENT_FILTERD AYS	NUMBER	3		Y
W8HP_SHOWEVENTLOCATIONS	NUMBER	1		Y
W8HP_REG_SHOWCUSTOMPAGE	NUMBER	1		Y
W8HP_CONFIRMATIONASPDF	NUMBER	1		Y
W8HP_HOTELSEGMENTCOMBO	NUMBER	1		Y
W8HP_CALENDAREVENT_CONF_W RPTID	NUMBER	30		Y
W8HP_MYHOTELSHOPTRACKINGPI XEL	NUMBER	1		Y
W8HP_MYHOTELSHOPID	VARCHAR2	20		Y

## WAAL

Maintenance Attribute Links

Field Name	Type	Length	Decimals	Not NULL	
WAAL_ID	NUMBER	30		N	
WAAL_WACT_ID	NUMBER	30		Y	Linked Maintenance Type Id

## WAAL

Maintenance Attribute Links

Field Name	Type	Length	Decimals	Not NULL	
WAAL_XPDA_ID	NUMBER	30		Y	Linked Maintenance Attribute Item Id
WAAL_XPAC_ID	NUMBER	30		Y	Linked Maintenance Attribute Categories Id

## WACT

Activities and Tasks

Field Name	Type	Length	Decimals	Not NULL	
WACT_ID	NUMBER	30		N	Unique internal ID
WACT_WATY_ID	NUMBER	30		N	Link to activity type
WACT_XXOPPORTUNITYID	NUMBER	30		Y	Link to opportunity
WACT_DESCRIPTION	VARCHAR2	60		Y	Description of activity
WACT_STARTTIME	DATE			Y	Activity start date and time
WACT_ENDTIME	DATE			Y	End date and time of activity
WACT_ALLDAY	NUMBER	1		Y	All day event (1) or not (0 or null)
WACT_TODO	NUMBER	1		Y	Defines if it is an -1 = todo item or -not(0 or null) if not, it will appear in the calendar -2 = Traces (former Front office known feature)
WACT_WASC_ID	NUMBER	30		Y	Link to 'show as' categories
WACT_PRIVATE	NUMBER	1		Y	Private(1) or not (0 or null)
WACT_WART_ID	NUMBER	30		Y	Link to reminder category
WACT_PRIORITY	NUMBER	2		Y	0 = Normal   1 = Low   2 = High
WACT_COMPLPERC	NUMBER	3		Y	Completion percentage
WACT_COMPLTIME	DATE			Y	Date and time of completion
WACT_WANT_ID	NUMBER	30		Y	Link to activity notes
WACT_COST	NUMBER	30	4	Y	Cost
WACT_STATUS	NUMBER	1		Y	Status of the task 0= not started 1= in progress 2= completed 3= waiting on someone else 4= deferred
WACT_REPEATTIME	DATE			Y	Date/time for activity to be repeated if snoozed
WACT_DISMISS	NUMBER	1		Y	Dismiss Yes(1), No (0)
WACT_XCOM_ID	NUMBER	30		Y	Here we store selected communication method for this particular activity.
WACT_YBOM_ID	NUMBER	30		Y	Activity Link to Booking Master
WACT_YRES_ID	NUMBER	30		Y	Link to Reservations
WACT_YBLH_ID	NUMBER	30		Y	Link to Blocks
WACT_AACC_ID	NUMBER	30		Y	Link to A/R Accounts
WACT_AVAILCHK	NUMBER	1		Y	0 = No 1 = Yes
WACT_WPHS_ID	NUMBER	30		Y	Remote Hotel Id

## WACT

Activities and Tasks

Field Name	Type	Length	Decimals	Not NULL	
WACT_PLACE_TYPE	NUMBER	1		Y	0=none, 1=room, 2=functionspace, 3=location, 4=public places
WACT_PLACE_ID	NUMBER	30		Y	ID of place_type=1: yrms_id, place_type=2: yfsc_id, place_type=3: waty_id, palce_type=4: ypub_id
WACT_GLOBALID	NUMBER	30		Y	In Partner Hotels used to store WACT_ID of the Master (Hotel Connector)
WACT_FROMMASTER	NUMBER	1		N	1= Downloaded from Master Hotel (Hotel Connencor)
WACT_POPUP	NUMBER	1		Y	1= Logbook entry will pop up
WACT_HC_EXTRAINFO	VARCHAR2	2000		Y	hotel connector extra information
WACT_REMINDTIME	DATE			Y	Time when reminder before due time has been sent
WACT_REMINDTIMEAFTER	DATE			Y	Time when reminder after due time has been sent
WACT_YGRP_ID	NUMBER	30		Y	Linked to group
WACT_XCMS_ID	NUMBER	30		Y	locator link to non hotel guests
WACT_WMSL_ID	NUMBER	30		Y	Referenced Activity Status Level Id
WACT_ESTIMATED_DURATION_MIN	NUMBER	12		Y	estimated time that it takes in minutes
WACT_ACTUAL_DURATION_MIN	NUMBER	12		Y	actual time it took in minutes
WACT_FIDCRSID	VARCHAR2	20		Y	
WACT_WORJ_ID	NUMBER	30		Y	Maintenance Orgin ID
WACT_YCMP_ID	NUMBER	30		Y	Guest Comments ID
WACT_REMINDERSTATE	NUMBER	3		Y	1-Reminder, 2-Level1, 3-Reminder+Level1, 4-Level2, 5-Reminder+Level2, 6-Level1+Level2, 7-Reminder+Level1+Level2, 15-Not Processed, Old records
WACT_ZFAC_ID	NUMBER	30		Y	for Financial Accounts
WACT_REQUESTLINKED_ID	NUMBER	30		Y	Request Employee
WACT_RRES_ID	NUMBER	30		Y	
WACT_RESOLVEDNOTE_WANT_ID	NUMBER	30		Y	Resolved note id
WACT_YDEP_ID	NUMBER	30		Y	Trace linked to deposit
WACT_FROM_COPY_WACT_ID	NUMBER	30		Y	from copy wact_id

## WADV

Web booking advertisements

Field Name	Type	Length	Decimals	Not NULL	
WADV_ID	NUMBER	30		N	
WADV_NAME	VARCHAR2	60		Y	
WADV_HTML	VARCHAR2	1000		Y	
WADV_ADV_START	DATE			Y	
WADV_ADV_END	DATE			Y	

### WADV

Web booking advertisements

Field Name	Type	Length	Decimals	Not NULL
WADV_BOOK_START	DATE			Y
WADV_BOOK_END	DATE			Y
WADV_WIMG_ID	NUMBER	30		Y
WADV_DISPLORDER	NUMBER	4		Y
WADV_INACTIVE	NUMBER	1		Y
WADV_WEBENABLED	NUMBER	1		Y
WADV_RATEQUERY	NUMBER	1		Y
WADV_KIOSKENABLED	NUMBER	1		Y

### WAGR

Maintenance Group

Field Name	Type	Length	Decimals	Not NULL	
WAGR_ID	NUMBER	30		N	
WAGR_WHDE_ID	NUMBER	30		N	Linked to Resp. Departments
WAGR_LONGDESC	VARCHAR2	30		Y	
WAGR_SHORTDESC	VARCHAR2	3		Y	
WAGR_DISPLORDER	NUMBER	3		Y	
WAGR_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
WAGR_DEFAULT	NUMBER	1		Y	
WAGR_NOTIFYHKSCREEN	NUMBER	1		Y	Notify in HK Screen

### WALA

Activity link to companies, individuals and employees

Field Name	Type	Length	Decimals	Not NULL	
WALA_ID	NUMBER	30		N	Unique internal ID
WALA_WACT_ID	NUMBER	30		N	Link to activity types
WALA_XCMS_ID	NUMBER	30		N	Link to customer table
WALA_PRIMARY	NUMBER	1		Y	primary(1) or not(0 or null) there can be more than one primaries but only one for each xcms_type
WALA_XCMS_TYPE	NUMBER	1		Y	Profile type. 1=Company, 2=Contact, 3=Manager 4=Partner Hotel (only for Hotel Connector)
WALA_READ	NUMBER	1		Y	1= Logbook entry has been read

### WAMT

Field Name	Type	Length	Decimals	Not NULL	
WAMT_ID	NUMBER	30		N	Id
WAMT_WATY_ID	NUMBER	30		Y	Maintenance type
WAMT_PLACE_TYPE	NUMBER	1		Y	1-Room, 2-Function Space, 3-Location, 4-Public Places
WAMT_XCED_ID	NUMBER	30		Y	Responsible department
WAMT_NOTES	VARCHAR2	2000		Y	Notes
WAMT_INACTIVE	NUMBER	1		Y	0-Active, 1-Inactive
WAMT_CONDITION	VARCHAR2	2000		Y	Sql condition
WAMT_WORJ_ID	NUMBER	30		Y	Maintenance Origin

### WANT

Field Name	Type	Length	Decimals	Not NULL	
WANT_ID	NUMBER	30		N	
WANT_NOTES	LONG			Y	Actual note
WANT_NOTES_CLOB	CLOB			Y	Obsolete field, not used anymore
WANT_NOTES_VC	VARCHAR2	2000		Y	
WANT_PREVIOUS_ID	NUMBER	30		Y	Previous Want_id
WANT_CREATEDON	DATE			Y	Record insert datetime
WANT_CREATEDBY_XCED_ID	NUMBER	30		Y	Employee Id Who inserted record

### WAPP

Applications used by the system.

Field Name	Type	Length	Decimals	Not NULL	
WAPP_ID	NUMBER	30		N	Unique Identifier
WAPP_LONGDESC	VARCHAR2	30		N	Application Description
WAPP_EXECUTABLENAME	VARCHAR2	60		N	Name of Executable
WAPP_EXTENSION	VARCHAR2	3		Y	Extension

### WAPS

Application link to Worstation and Path of installation on this workstation.

Field Name	Type	Length	Decimals	Not NULL	
WAPS_ID	NUMBER	30		N	Unique Identifier

## WAPS

Application link to Worstation and Path of installation on this workstation.

Field Name	Type	Length	Decimals	Not NULL	
WAPS_WAPP_ID	NUMBER	30		N	Application Link
WAPS_WPCA_ID	NUMBER	30		N	Workstation Link
WAPS_PATH	VARCHAR2	200		N	Path on this Workstation for selected Application

## WART

Activity reminder Time Categories

Field Name	Type	Length	Decimals	Not NULL	
WART_ID	NUMBER	30		N	Unique internal ID
WART_SHORTDESC	VARCHAR2	3		N	Short description of reminder values
WART_LONGDESC	VARCHAR2	30		N	Long description of reminder values
WART_DISPLORDER	NUMBER	3		Y	Display order of reminder values
WART_TYPE	NUMBER	1		Y	Reminder Type 1=minutes, 2=days, 3=week, 4=month
WART_CATEGORY	NUMBER	1		Y	Reminder category (1=activity reminder, 2=snooze reminder)

## WASC

Activity 'show as' categories (free,busy,tentative, etc)

Field Name	Type	Length	Decimals	Not NULL	
WASC_ID	NUMBER	30		N	Unique internal ID
WASC_SHORTDESC	VARCHAR2	3		N	Short description of 'show as' categories
WASC_LONGDESC	VARCHAR2	30		N	Long description of 'show as' categories
WASC_DISPLORDER	NUMBER	3		Y	Display order of 'show as' categories
WASC_WCOL_ID	NUMBER	30		N	Color for display in Activity Screen. We do not plan to have a manual override of this color on the activity level itself.

## WATG

Activity Groups for the types from WATY, used for FO Trace Groups and may be for categorizing activities and tasks as well.

Field Name	Type	Length	Decimals	Not NULL	
WATG_ID	NUMBER	30		N	Unique Identifier
WATG_SHORTDESC	VARCHAR2	3		N	Short Description
WATG_LONGDESC	VARCHAR2	30		N	Description
WATG_DISPLORDER	NUMBER	3		Y	Display Order
WATG_ROLE	NUMBER	1		N	0 = Task and Activity, 2 = Trace, 3 = Billing Authorization, 4 = Locator, 5 = Automatic Traces, 6 = Hotel Maintenance, 7 = Logbook

## WATG

Activity Groups for the types from WATY, used for FO Trace Groups and may be for categorizing activities and tasks as well.

Field Name	Type	Length	Decimals	Not NULL	
WATG_RES	NUMBER	1		Y	1 = for trace groups appearing in reservations
WATG_BLOCK	NUMBER	1		Y	1 = for trace groups appearing in Room Blocks
WATG_AR	NUMBER	1		Y	1 = for trace groups appearing in Accounts receivable
WATG_FA	NUMBER	1		Y	Is Link to Financial Accounts
WATG_TABRES	NUMBER	1		Y	
WATG_ZFAC	NUMBER	1		Y	Is Link to Financial Accounts

## WATI

automatic translation import configuration

Field Name	Type	Length	Decimals	Not NULL	
WATI_ID	NUMBER	30		N	Unique ID
WATI_WLAN_ID	NUMBER	30		N	Link to language table
WATI_AUTOMATIC	NUMBER	1		N	1= night audit runs import
WATI_FTPFILE	VARCHAR2	1000		N	Path and file name on FTP
WATI_USR	VARCHAR2	60		Y	Login name
WATI_PW	VARCHAR2	30		Y	Login password
WATI_PORT	NUMBER	6		Y	Port for FTP connection
WATI_LASTIMPORT	DATE			Y	Date of last import
WATI_WFTP_ID	NUMBER	30		Y	link to ftp account used for download
WATI_FTPFOLDER	VARCHAR2	100		Y	remote ftp folder, where files are stored for download

## WATL

automatic translation import log

Field Name	Type	Length	Decimals	Not NULL	
WATL_ID	NUMBER	30		N	Unique ID
WATL_DATE	DATE			N	Date of import
WATL_XCED_ID	NUMBER	30		N	ID of user that performed the import
WATL_LOG	LONG			N	Log information

## WATR

Table of WATR

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### WATR

Table of WATR

Field Name	Type	Length	Decimals	Not NULL	
WATR_ID	NUMBER	30		N	unique code
WATR_WATY_ID	NUMBER	30		Y	task type
WATR_PARENT_ID	NUMBER	30		Y	parent id
WATR_INTERNAL_ID	NUMBER	5		Y	hard coded interna id
WATR_VALUE	VARCHAR2	60		Y	values
WATR_FOR	NUMBER	1		Y	1=bookings,2=profiles,..
WATR_OPERATER	NUMBER	3		Y	hard coded values for operators
WATR_LOGICALOPERATER	NUMBER	1		Y	WATR_LOGICALOPERATER is of WATR
WATR_CONDITION_DATEVALUE	DATE			Y	date values for extraconditions
WATR_CONDITION_VALUE	VARCHAR2	60		Y	values for extraconditions

### WATY

Activity Types

Field Name	Type	Length	Decimals	Not NULL	
WATY_ID	NUMBER	30		N	Unique internal ID
WATY_SHORTDESC	VARCHAR2	3		N	Short description of activity types
WATY_LONGDESC	VARCHAR2	30		N	Long description of activity types
WATY_DISPLORDER	NUMBER	3		Y	Display order of activity types
WATY_WATG_ID	NUMBER	30		Y	WATY_WATG_ID is of WATY
WATY_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
WATY_OOO	NUMBER	1		Y	Ask for room ooo on maintenance edit
WATY_AUTOSMS	NUMBER	1		Y	SMS Should be sent when task is created
WATY_REMINDERSMS	NUMBER	1		Y	SMS Should be sent when is not resolved within configured time
WATY_DUEMIN	NUMBER	5		Y	The task should be resolved within configured time
WATY_REMIND	NUMBER	5		Y	Number of minutes after due time, when reminder SMS has to be send
WATY_REMINDAFTER	NUMBER	5		Y	
WATY_WEBGUESTENABLED	NUMBER	1		Y	
WATY_XCED_ID	NUMBER	30		Y	
WATY_PRIORITY	NUMBER	1		Y	0 = Normal   1 = low   2 = High
WATY_ASKDURATION	NUMBER	1		Y	Flag for Ask Duration on maintenance completion
WATY_DURATION_MIN	NUMBER	8		Y	required time to complete task
WATY_REMINDAFTER2	NUMBER	10		Y	RemindAfter 2
WATY_WAGR_ID	NUMBER	30		Y	Linked to Maintenance Group

## WATY

Activity Types

Field Name	Type	Length	Decimals	Not NULL	
WATY_ISRESOLVEDNOTE	NUMBER	1		Y	Resolved Note
WATY_DUEDAYS	NUMBER	3		Y	Due Days to resolve this task
WATY_WEBINFO	VARCHAR2	1000		Y	Web Short Information
WATY_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information

## WAVL

Avaiability colors for Suite 8 Homepage availability calendar

Field Name	Type	Length	Decimals	Not NULL	
WAVL_ID	NUMBER	30		N	
WAVL_RANGE1	NUMBER	3		Y	
WAVL_COLOR1	NUMBER	10		Y	
WAVL_RANGE2	NUMBER	3		Y	
WAVL_COLOR2	NUMBER	10		Y	
WAVL_RANGE3	NUMBER	3		Y	
WAVL_COLOR3	NUMBER	10		Y	
WAVL_COLOR4	NUMBER	10		Y	
WAVL_FULLYOCCUPIED_COLOR	NUMBER	10		Y	
WAVL_NAME1	VARCHAR2	30		Y	
WAVL_NAME2	VARCHAR2	30		Y	
WAVL_NAME3	VARCHAR2	30		Y	
WAVL_NAME4	VARCHAR2	30		Y	
WAVL_NAME_FULLYOCCUPIED	VARCHAR2	30		Y	
WAVL_WCOL1	NUMBER	30		Y	
WAVL_WCOL2	NUMBER	30		Y	
WAVL_WCOL3	NUMBER	30		Y	
WAVL_WCOL4	NUMBER	30		Y	
WAVL_FULLYOCCUPIED_WCOL	NUMBER	30		Y	

## WBCF

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### WBCF

Field Name	Type	Length	Decimals	Not NULL	
WBCF_CATEGORY	NUMBER	2		N	0,null=bcNone, 1=bcBillingHistory, 2=bcGuestChecks, 3=bcUserlog, 4=bcCorrespondence, 5=bcCashierClosure, 6=bcMoveLog, 7=bcINvoiceLink, 8=bcPostingComment
WBCF_BACKUP_TYPE	NUMBER	1		N	1=MOVE TO BACKUP USER, 2=DELETE FROM DB
WBCF_BACKUP_DAYS	NUMBER	4		Y	OLDER THAN (SYSTEMDATE - DAY) WILL BE PROCESSED
WBCF_DELETE	NUMBER	1		Y	DELETE FROM BACKUP USER
WBCF_DELETE_DAYS	NUMBER	4		Y	OLDER THAN (SYSTEMDATE - DAY) WILL BE PROCESSED
WBCF_INACTIVE	NUMBER	1		Y	
WBCF_COMMITCOUNT	NUMBER	4		Y	db commit after number of processed records
WBCF_DELAYMSEC	NUMBER	4		Y	break after db commit

### WCCK

Stores components of the key, used for CC crypting

Field Name	Type	Length	Decimals	Not NULL	
WCCK_ID	NUMBER	30		N	Unique ID
WCCK_LICNAME	VARCHAR2	60		N	Licence name
WCCK_DBID	VARCHAR2	60		N	Unique database ID
WCCK_HDEFKEY	VARCHAR2	60		Y	Hotel defined key

### WCCS

Central Configuration Transfer Subscription

Field Name	Type	Length	Decimals	Not NULL	
WCCS_ID	NUMBER	30		N	
WCCS_TABLENAME	VARCHAR2	4		N	
WCCS_TABLEID	NUMBER	30		N	
WCCS_WPHS_ID	NUMBER	30		N	

### WCID

Suite 8 Kiosk Date config

Field Name	Type	Length	Decimals	Not NULL	
WCID_ID	NUMBER	30		N	
WCID_DATE	DATE			Y	
WCID_ONLYSELECTEDROOMS	NUMBER	1		Y	if 1, only rooms configured in WCIR can be assigned on the WCID_DATE

### WCIP

Check In Point configuration

Field Name	Type	Length	Decimals	Not NULL	
WCIP_ID	NUMBER	30		N	
WCIP_MAXNIGHTS	NUMBER	3		Y	Maximum number of nights wich can be booked from the Check In Point
WCIP_PAYMENT	NUMBER	1		Y	Advanced payment rules for the Check In Point. 0 - nothing has to be paid in advance / 1 - First night price / 2 - All has to be paid
WCIP_POSTCHARGES	NUMBER	1		Y	Advanced posting rules for the Check In Point. 0 - nothing has to be posted / 1 - First night price / 2 - All stay has to be posted
WCIP_WALKINONLY	NUMBER	1		Y	
WCIP_OOO	NUMBER	1		Y	Kiosk is out of order
WCIP_SHOWBANNER	NUMBER	1		Y	flag to show/hide Banner
WCIP_PACKAGES	VARCHAR2	100		Y	List of Kiosk enabled packages
WCIP_CHECKINFORPAIDONLY	NUMBER	1		Y	

### WCIR

Check In Point room assigment config per day

Field Name	Type	Length	Decimals	Not NULL	
WCIR_ID	NUMBER	30		N	
WCIR_DATE	DATE			Y	
WCIR_YRMS_ID	NUMBER	30		Y	
WCIR_DISPLORDER	NUMBER	4		Y	

### WCOL

colors

Field Name	Type	Length	Decimals	Not NULL	
WCOL_ID	NUMBER	30		N	Unique internal ID
WCOL_SHORTDESC	VARCHAR2	3		N	short description
WCOL_LONGDESC	VARCHAR2	30		N	description/name
WCOL_DISPLORDER	NUMBER	3		Y	Display order
WCOL_COLOR	NUMBER	30		Y	colour coordinates
WCOL_FONTCOLOR	NUMBER	30		Y	

## WCOR

Correspondence link table

Field Name	Type	Length	Decimals	Not NULL	
WCOR_ID	NUMBER	30		N	
WCOR_WACT_ID	NUMBER	30		N	Activity link
WCOR_WMAI_ID	NUMBER	30		N	Email/SMS link

## WCRN

column rename in grids

Field Name	Type	Length	Decimals	Not NULL	
WCRN_ID	NUMBER	30		N	
WCRN_WLAN_ID	NUMBER	30		N	
WCRN_GRIDNAME	VARCHAR2	200		N	
WCRN_ORIGINALCOLUMNNAME	VARCHAR2	60		N	
WCRN_NEWCOLUMNNAME	VARCHAR2	60		N	

## WCSP

Correspondence Sending Preferences for Bonus Points etc.

Field Name	Type	Length	Decimals	Not NULL	
WCSP_ID	NUMBER	30		N	
WCSP_ROLE	NUMBER	2		N	1 - Bonus Points
WCSP_SENDING	NUMBER	1		N	0 = dont send, 1 = Letter, 2 = EMAIL
WCSP_LETTER_XADR_ID	NUMBER	30		Y	
WCSP_EMAIL_XCOM_ID	NUMBER	30		Y	
WCSP_XMNR_ID	NUMBER	30		Y	

## WDAT

list of dates

Field Name	Type	Length	Decimals	Not NULL	
WDAT_DATE	DATE			N	Date

## WDBF

User Dashboard files

Field Name	Type	Length	Decimals	Not NULL	
WDBF_ID	NUMBER	30		N	

### WDBF

User Dashboard files

Field Name	Type	Length	Decimals	Not NULL	
WDBF_FILENAME	VARCHAR2	200		N	File Name
WDBF_TYPE	NUMBER	1		N	1=HTML 2=RTF
WDBF_DISPLORDER	NUMBER	3		Y	Display Order

### WDBG

Field Name	Type	Length	Decimals	Not NULL	
WDBG_ID	NUMBER	30		N	
WDBG_TIMESTAMP	DATE			N	
WDBG_WPCA_ID	NUMBER	30		Y	
WDBG_SMALLTEXT	VARCHAR2	200		Y	
WDBG_BIGTEXT	CLOB			Y	

### WDCG

Document Groups

Field Name	Type	Length	Decimals	Not NULL	
WDCG_ID	NUMBER	30		N	Unique Identifier
WDCG_SHORTDESC	VARCHAR2	3		N	Short Description for Document Group
WDCG_LONGDESC	VARCHAR2	30		N	Long Description for Document Group
WDCG_DISPLORDER	NUMBER	3		N	Display Order
WDCG_DIRECTORIES	LONG			N	Directories allowed to search and Store, like:
WDCG_DEFAULTTEXTENSION	VARCHAR2	80		Y	Default Filter, like *.TXT or *.*
WDCG_ROLE	NUMBER	1		Y	wdcg_role = 1 : Linked document is for telephone Book
WDCG_UPLOAD	NUMBER	1		Y	1 if should be uploaded to master hotel
WDCG_STORAGETYPE	NUMBER	1		Y	Storage type; 1 - to directory; 2 - to DB
WDCG_DEFWIDTH	NUMBER	10		Y	Default image width
WDCG_DEFHEIGHT	NUMBER	10		Y	Default image height

### WDCL

Documents attached to Profiles

Field Name	Type	Length	Decimals	Not NULL	
WDCL_ID	NUMBER	30		N	Unique Identifier

### WDCL

Documents attached to Profiles

Field Name	Type	Length	Decimals	Not NULL	
WDCL_WDCG_ID	NUMBER	30		N	Link to Document Group
WDCL_TABLENAME	VARCHAR2	4		N	Table name linked to
WDCL_TABLE_ID	NUMBER	30		N	Table ID linked to
WDCL_DOC_TYPE	NUMBER	1		N	0 - Attached document; 1- Picture
WDCL_FILENAME	VARCHAR2	400		N	WDCL_FILENAME is of WDCL
WDCL_DATETIME	DATE			Y	WDCL_DATETIME is of WDCL
WDCL_XCMS_ID	NUMBER	30		Y	WDCL_XCMS_ID is of WDCL
WDCL_WPHS_ID	NUMBER	30		Y	Hotel where document was created
WDCL_WIMG_ID	NUMBER	30		Y	Link to image

### WDEC

Calendar ICS reports setup

Field Name	Type	Length	Decimals	Not NULL	
WDEC_ID	NUMBER	30		N	
WDEC_REPORT_ROLE	NUMBER	2		N	Report role
WDEC_WRPT_ID	NUMBER	30		N	Reference to the report

### WDES

Default email subjects per report type

Field Name	Type	Length	Decimals	Not NULL	
WDES_ID	NUMBER	30		N	
WDES_REPORT_ROLE	NUMBER	2		N	Report role
WDES_WRPT_ID	NUMBER	30		N	Reference to the report

### WDTC

Data translation cache (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WDTC_ID	NUMBER	30		N	Unique ID
WDTC_WPHS_ID	NUMBER	30		N	WDTC_WPHS_ID is of WDTC
WDTC_TIMESTAMP	DATE			N	WDTC_TIMESTAMP is of WDTC
WDTC_CONFIG	LONG			Y	WDTC_CONFIG is of WDTC

### WDWI

Dashboard widgets

Field Name	Type	Length	Decimals	Not NULL	
WDWI_ID	NUMBER	30		N	
WDWI_NAME	VARCHAR2	50		N	
WDWI_DESCRIPTION	VARCHAR2	200		Y	
WDWI_INACTIVE	NUMBER	1		Y	
WDWI_LEFT	NUMBER	30		Y	
WDWI_TOP	NUMBER	30		Y	
WDWI_HEIGHT	NUMBER	30		Y	
WDWI_WIDTH	NUMBER	30		Y	
WDWI_URL	VARCHAR2	250		N	
WDWI_DISPLORDER	NUMBER	10		Y	
WDWI_HIDDEN	NUMBER	1		Y	1=TRUE, 0 or NULL =FALSE; Hidden Widgets will not be visible in the Widget config screen, field will only be accessible via table.
WDWI_CONTENT	NCLOB			Y	

### WDWU

Table for storing the widgets data for user

Field Name	Type	Length	Decimals	Not NULL	
WDWU_ID	NUMBER	30		N	ID
WDWU_XCED_ID	NUMBER	30		N	User ID
WDWU_NAME	VARCHAR2	100		Y	Widget Name
WDWU_WDWI_ID	NUMBER	30		N	Widget Type
WDWU_TOP	NUMBER	30		N	Top
WDWU_LEFT	NUMBER	30		N	Left
WDWU_HEIGHT	NUMBER	30		N	Height
WDWU_WIDTH	NUMBER	30		N	Width

### WEAD

Easy Letter departments

Field Name	Type	Length	Decimals	Not NULL	
WEAD_ID	NUMBER	30		N	Unique ID
WEAD_DESCRIPTION	VARCHAR2	60		Y	Department
WEAD_WEAS_ROLE	NUMBER	1		Y	0-General letter 1-Profile Letter   2-Reservation (confirmation) letter   3-Booking (confirmation) letter   4-Task+Activity

### WEAD

Easy Letter departments

Field Name	Type	Length	Decimals	Not NULL	
WEAD_INACTIVE	NUMBER	1		Y	1=Inactive
WEAD_DISPLORDER	NUMBER	3		Y	Display order

### WEAL

Link Easy letter templates to departments

Field Name	Type	Length	Decimals	Not NULL	
WEAL_ID	NUMBER	30		N	Unique ID
WEAL_WEAS_ID	NUMBER	30		N	Link to Easy letter template
WEAL_WEAD_ID	NUMBER	30		N	Link to Easy letter department

### WEAP

External Application configuration

Field Name	Type	Length	Decimals	Not NULL	
WEAP_ID	NUMBER	30		N	Unique Identifier
WEAP_DISPNAME	VARCHAR2	30		N	Name displayed in menu
WEAP_COMMANDLINE	VARCHAR2	255		N	Command line to run
WEAP_PARAMETERS	VARCHAR2	255		Y	Parameter for current command line
WEAP_DISPORDER	NUMBER	3		N	Display Order
WEAP_SHORTCUT	NUMBER	5		Y	User definable Short Cut Key

### WEAS

Easy letter setup

Field Name	Type	Length	Decimals	Not NULL	
WEAS_ID	NUMBER	30		N	Unique ID
WEAS_DESCRIPTION	VARCHAR2	30		N	Description
WEAS_DISPLORDER	NUMBER	3		N	Dispaly order
WEAS_WRPB_ID	NUMBER	30		N	Reference to template
WEAS_DEFAULT	NUMBER	1		Y	1 = default
WEAS_ROLE	NUMBER	1		Y	0-General letter 1-Profile Letter   2-Reservation (confirmation) letter   3-Booking (confirmation) letter   4-Task+Activity

### WECF

Email defaults setup for CC/BCC

Field Name	Type	Length	Decimals	Not NULL	
WECF_ID	NUMBER	30		N	ID
WECF_AREA	NUMBER	3		N	Area of Suite8 to which applies; 1 -Reservation; 2-Conference Booking; 3-Correspondence
WECF_CC	VARCHAR2	60		Y	Defaults for CC; list of values allowed; 1-Hotel email Address; 2- User Email Address
WECF_BCC	VARCHAR2	60		Y	Defaults for BCC; list of values allowed; 1-Hotel email Address; 2- User Email Address

### WEDA

Email Default attachments per role

Field Name	Type	Length	Decimals	Not NULL	
WEDA_ID	NUMBER	30		N	
WEDA_ROLE	NUMBER	2		N	1=Profiles 2=Tasks+Activities 3=PMS 4=CCM 5=A/R 6=Maintenance 7=Table Reservations
WEDA_FILEPATH	VARCHAR2	400		N	
WEDA_WTXT_ID	NUMBER	30		Y	

### WEGR

System wide employee groups

Field Name	Type	Length	Decimals	Not NULL	
WEGR_ID	NUMBER	30		N	Unique internal ID
WEGR_SHORTDESC	VARCHAR2	3		N	Short description for employee groups
WEGR_LONGDESC	VARCHAR2	30		N	Long description for employee groups
WEGR_DISPLORDER	NUMBER	3		Y	Display order of employee groups
WEGR_RPSL_ID	NUMBER	30		Y	User Group Report Permission Level

### WERR

Application error log

Field Name	Type	Length	Decimals	Not NULL	
WERR_ID	NUMBER	30		N	
WERR_HOTELID	VARCHAR2	100		N	Identifies the hotel
WERR_TIMESTAMP	DATE			N	
WERR_HOTELDATE	DATE			N	
WERR_APPNAME	VARCHAR2	3		N	FV8=fidleiov8.exe FS=fidelioserver etc
WERR_APPVERSION	VARCHAR2	20		N	
WERR_EXCEPTIONNAME	VARCHAR2	50		N	Internal name of he exception (for programmers only)

### WERR

Application error log

Field Name	Type	Length	Decimals	Not NULL	
WERR_EXCEPTIONTEXT	VARCHAR2	2000		Y	Text of the error message appearing on screen for the user
WERR_SESSIONERRORCOUNT	NUMBER	4		Y	Number of errors logged since application startup
WERR_SESSIONTIMESINCELASTERROR				Y	Time elapsed since last logged error of the same application session
WERR_ELFLOG	CLOB			Y	Generated eureka elf log file
WERR_SHORTAPPLOG	VARCHAR2	2000		Y	short version of applog to be able to use in simple sql queries
WERR_FULLAPPLOG	CLOB			Y	Application execution log. Focused controls, parent control, parent forms etc + any other program execution info logged by the programmer
WERR_ORIGIN	NUMBER	1		N	0=error in the hotel 1=error imported from other hotel
WERR_TRANSFERRED	NUMBER	1		Y	1=transferred to central database
WERR_TRANSFERTIME	DATE			Y	time of exporting or importing
WERR_SESSION	VARCHAR2	32		N	unique id of each program session
WERR_MACHINENAME	VARCHAR2	30		Y	
WERR_FORM	VARCHAR2	100		Y	
WERR_CONTROL	VARCHAR2	100		Y	
WERR_DBID	VARCHAR2	100		Y	string to identify db instances of the same hotel database. ie: live/training/testing
WERR_SOURCEFILE	VARCHAR2	100		Y	source file on top of call stack
WERR_PROCEDURE	VARCHAR2	100		Y	procedure on top of call stack
WERR_COMMENT	VARCHAR2	2000		Y	
WERR_UNIQUEID	VARCHAR2	32		Y	
WERR_COMMENTTIMESTAMP	DATE			Y	
WERR_COMMENTUSER	VARCHAR2	60		Y	
WERR_STATUSTEXT	VARCHAR2	60		Y	
WERR_SYSINFO	CLOB			Y	
WERR_USER	VARCHAR2	60		Y	

### WERS

Field Name	Type	Length	Decimals	Not NULL
WERS_ID	NUMBER	30		N
WERS_TEXT	VARCHAR2	60		N
WERS_DISPLORDER	NUMBER	3		Y

## WFAQ

Table for storing documents in database

Field Name	Type	Length	Decimals	Not NULL	
WFAQ_ID	NUMBER	30		N	Id in table
WFAQ_DATA	LONG RAW			Y	Document in database
WFAQ_TYPE	NUMBER	2		Y	0= for html   1 = for rtf   2 = mhtml   3 = doc   4 = txt
WFAQ_DESCRIPTION	VARCHAR2	200		Y	Description of document
WFAQ_PATH	VARCHAR2	200		Y	Path for the template document used for mailing
WFAQ_DOCUMENT_TYPE	NUMBER	1		Y	1: body document; 2: attachment document

## WFFD

Fields from views/tables for mailing (setup)

Field Name	Type	Length	Decimals	Not NULL	
WFFD_ID	NUMBER	30		N	WFFD_ID partly identifies WFFQ
WFFD_WVFD_ID	NUMBER	30		N	ID of linked view
WFFD_FIELDNAME	VARCHAR2	100		Y	Field Name (table field name)
WFFD_DESCRIPTION	VARCHAR2	100		Y	Field Description (for users)
WFFD_SELECTED	NUMBER	1		Y	Not used
WFFD_FIELDTYPE	VARCHAR2	10		Y	Field Type
WFFD_RELATEDFIELD	NUMBER	30		Y	ID of related field (link field)
WFFD_RELATEDDESCRIPTION	NUMBER	30		Y	ID of related display field
WFFD_DISPLORDER	NUMBER	10		Y	Field for display order
WFFD_MEANING	NUMBER	1		Y	Represent a description of field
WFFD_BLANKIFPARENT	NUMBER	1		Y	Option for leaving blank the field if company has linked profiles
WFFD_SEPARATION	NUMBER	1		Y	Show or not the separation between profiles types - 0 = None 1=Company 2=Individual 3=Both
WFFD_USERDEFINEDFIELD	NUMBER	1		Y	1-Specify if the field is an user defined
WFFD_FORMULA	VARCHAR2	256		Y	Formula if the field is user defined
WFFD_SYSTEM	NUMBER	1		Y	1 = V8 system field

## WFFL

Fields for list

Field Name	Type	Length	Decimals	Not NULL	
WFFL_ID	NUMBER	30		N	Unique Identifier
WFFL_WLOF_ID	NUMBER	30		Y	Link to WLOF
WFFL_WFFD_ID	NUMBER	30		Y	Link to WFFD

## WFFL

Fields for list

Field Name	Type	Length	Decimals	Not NULL	
WFFL_DISPLAYORDER	NUMBER	30		Y	Display Order
WFFL_FIELDTYPE	NUMBER	1		Y	0=database; 1=hardcoded xpac records ;2=customized xpac records

## WFGL

FORM CUSTOMIZATION LINK TO USER GROUP

Field Name	Type	Length	Decimals	Not NULL	
WFGL_ID	NUMBER	30		N	WFGL_ID identifies WFGL
WFGL_WFMC_ID	NUMBER	30		N	WFGL_WFMC_ID is of WFGL
WFGL_WEGR_ID	NUMBER	30		N	WFGL_WEGR_ID is of WFGL
WFGL_WFMC_FORMID	VARCHAR2	255		Y	wfgl_wfmc_formid is of wfgl

## WFLS

Bed and Breakfasts feature list configuration

Field Name	Type	Length	Decimals	Not NULL	
WFLS_ID	NUMBER	30		N	WFLS_ID identifies WFLS
WFLS_NAME	VARCHAR2	50		N	Feature Name
WFLS_ENABLED	NUMBER	1		N	Is feature enabled

## WFLT

Flights

Field Name	Type	Length	Decimals	Not NULL	
WFLT_ID	NUMBER	30		N	WFLT_ID identifies WFLT
WFLT_XAIL_ID	NUMBER	30		N	WFLT_XAIL_ID is of WFLT
WFLT_CODE	VARCHAR2	10		N	WFLT_CODE is of WFLT
WFLT_ORIGINALTIME	DATE			N	WFLT_ORIGINALTIME is of WFLT
WFLT_CHANGEDTIME	DATE			Y	in case of a delay
WFLT_DEFAULT_WGPT_ID	NUMBER	30		Y	BY DEFAULT IT IS FILLED FROM XAIL_DEFAULT_WGPT_ID
WFLT_ARRDEP	NUMBER	1		N	0=ARRIVAL 1=DEPARTURE
WFLT_DESTINATION	VARCHAR2	30		Y	ESTINATION CITY / AIRPORT FOR DEPARTING FLIGHTS AND THE OTHER WAY ROUND FOR ARRIVALS

## WFMC

form customization (future purpose for screen painter)

Field Name	Type	Length	Decimals	Not NULL	
WFMC_ID	NUMBER	30		N	Unique Identifier
WFMC_FORMID	VARCHAR2	255		N	Name of Form of the modified Screen
WFMC_VERSIONID	VARCHAR2	30		Y	Version information
WFMC_DATA	LONG			Y	Screen Data
WFMC_COMMENT	VARCHAR2	2000		Y	WFMC_COMMENT is of WFMC
WFMC_WLAN_ID	NUMBER	30		Y	language the customization is based on. for errorfree results, it should be used for this language only. otherwise translations may get los
WFMC_SYSTEMVERSION	NUMBER	1		N	0=dream from designer 1=greatis from designer
WFMC_ANCESTOR_VERSIONID	VARCHAR2	30		Y	

## WFMS

from customization scripts

Field Name	Type	Length	Decimals	Not NULL	
WFMS_ID	NUMBER	30		N	
WFMS_WFMC_ID	NUMBER	30		N	
WFMS_SCRIPT	LONG			Y	

## WFPP

FLOOR PLAN TABLE

Field Name	Type	Length	Decimals	Not NULL	
WFPP_ID	NUMBER	30		N	WFPP_ID
WFPP_DISPLAY	NUMBER	3		Y	Display order
WFPP_FLOOR	VARCHAR2	3		N	FLOOR code
WFPP_FLOORNAME	VARCHAR2	30		Y	FLOOR Name
WFPP_PICTURE	LONG RAW			Y	Floor Plan screen detail
WFPP_PICTURE_C	VARCHAR2	2000		Y	Floor Plan room no
WFPP_SHORTDESC	VARCHAR2	3		Y	Shortdescription of Floor
WFPP_PICTURE_C_CLOB	CLOB			Y	Floor Plan room no Clob Type

## WFPR

Fidelio Printer Setup (Linking Workstation from WPCA to Print Job Configuration in WPJC)

Field Name	Type	Length	Decimals	Not NULL	
WFPR_ID	NUMBER	30		N	Unique Identifier

### WFPR

Fidelio Printer Setup (Linking Workstation from WPCA to Print Job Configuration in WPJC)

Field Name	Type	Length	Decimals	Not NULL	
WFPR_WPCA_ID	NUMBER	30		N	Link to Workstation
WFPR_WPJC_ID	NUMBER	30		N	Link to Print Job Category
WFPR_WPPP_ID	NUMBER	30		N	Link to Printer
WFPR_COPY_WPPP_ID	NUMBER	30		Y	Printer for copies

### WFTP

Field Name	Type	Length	Decimals	Not NULL	
WFTP_ID	NUMBER	30		N	Unique Id
WFTP_SERVER	VARCHAR2	100		Y	ftp url
WFTP_USERNAME	VARCHAR2	30		Y	username of ftp account
WFTP_PASSWORD	VARCHAR2	30		Y	password of ftp account
WFTP_PORT	NUMBER	5		Y	port, standard = 21
WFTP_MODE	NUMBER	1		Y	0 = Default of used protocol, 1 = Active, 2 = Passive
WFTP_PROTOCOL	NUMBER	1		Y	0 = FTP/FTPS, 1 SFTP
WFTP_ENCRYPTION	NUMBER	1		Y	0 = explicit FTP over TLS, 1 = implicit FTP over TLS, 2 = Plain FTP (no encryption)
WFTP_LOGON_TYPE	NUMBER	1		Y	0 = Anonymous, 1 = Normal
WFTP_CERTIFICATE	VARCHAR2	100		Y	file name and path of certificate file
WFTP_CERTIFICATE_PWD	VARCHAR2	1024		Y	certificate password
WFTP_COMPRESSION	NUMBER	1		Y	0 = No, 1 = Yes
WFTP_ENCRYPT_DATACHANNEL	NUMBER	1		Y	0 = No, 1 = Yes
WFTP_CERTIFICATE_FORMAT	NUMBER	1		Y	0 = DER, 1 = PEM, 2 = PFX, 3 = SPC
WFTP_USE_SSL	NUMBER	1		Y	0 = No, 1 = Yes
WFTP_SSL_SESSION_RESUMPTION	NUMBER	1		Y	0 = No, 1 = Yes
WFTP_DESCRIPTION	VARCHAR2	100		Y	Name of the FTP Account
WFTP_DEBUG	NUMBER	1		Y	Debug level for FTP 0 = No Logging, 1 = Command Logging
WFTP_USE_MLIS	NUMBER	1		Y	indicates the use of MLST/MLSD to list directories
WFTP_USE_TLS	NUMBER	1		Y	indicates use of TLS 0 = No, 1 = Explicit TLS, 2 = Implicit TLS, 3 = Require TLS
WFTP_TRANSFER_TYPE	NUMBER	1		Y	ftp transfer type 0 = ASCII, 1 = Binary (default)

### WFTR

Table of WFTR

Field Name	Type	Length	Decimals	Not NULL	
WFTR_ID	NUMBER	30		N	WFTR_ID identifies WFTR
WFTR_WLAN_ID	NUMBER	30		N	WFTR_WLAN_ID is of WFTR
WFTR_FORM	VARCHAR2	200		Y	WFTR_FORM is of WFTR
WFTR_COMPONENT	VARCHAR2	200		Y	WFTR_COMPONENT is of WFTR
WFTR_PROPERTY	VARCHAR2	60		Y	WFTR_PROPERTY is of WFTR
WFTR_VALUE	VARCHAR2	2000		Y	WFTR_VALUE is of WFTR
WFTR_IGNORE	NUMBER	1		Y	1 = ignore for translation filters

### WFUL

FORM CUSTOMIZATION LINK TO USER

Field Name	Type	Length	Decimals	Not NULL	
WFUL_ID	NUMBER	30		N	WFUL_ID identifies WFUL
WFUL_WFMC_ID	NUMBER	30		N	WFUL_WFMC_ID is of WFUL
WFUL_XCMS_ID	NUMBER	30		N	WFUL_XCMS_ID is of WFUL
WFUL_WFMC_FORMID	VARCHAR2	255		Y	wful_wfmc_formid is of wful

### WGBS

global settings

Field Name	Type	Length	Decimals	Not NULL	
WGBS_ID	NUMBER	30		N	WGBS_ID identifies WGBS
WGBS_NAME	VARCHAR2	60		N	WGBS_NAME is of WGBS
WGBS_CHARVALUE	VARCHAR2	60		Y	WGBS_CHARVALUE is of WGBS
WGBS_NUMERICVALUE	NUMBER	30	4	Y	WGBS_NUMERICVALUE is of WGBS
WGBS_DATEVALUE	DATE			Y	WGBS_DATEVALUE is of WGBS
WGBS_NIGHTAUDIT	NUMBER	1		Y	Indicator: 1 if night audit is running, null if not
WGBS_ACCESSDENY	NUMBER	1		Y	

### WGPT

GUEST PICK UP TYPE (FROM AIRPORT BY BUS BY CAR ETC)

Field Name	Type	Length	Decimals	Not NULL	
WGPT_ID	NUMBER	30		N	Unique Identifier
WGPT_SHORTDESC	VARCHAR2	3		N	WGPT_SHORTDESC is of WGPT

### WGPT

GUEST PICK UP TYPE (FROM AIRPORT BY BUS BY CAR ETC)

Field Name	Type	Length	Decimals	Not NULL	
WGPT_LONGDESC	VARCHAR2	200		N	WGPT_LONGDESC is of WGPT
WGPT_DISPLORDER	NUMBER	3		N	WGPT_DISPLORDER is of WGPT
WGPT_TIMENEEEDED	DATE			Y	TIME NEEDED FOR THE TRANSPORT

### WGSS

grid setting storage

Field Name	Type	Length	Decimals	Not NULL	
WGSS_ID	NUMBER	30		N	
WGSS_XCED_ID	NUMBER	30		N	
WGSS_NAME	VARCHAR2	200		N	
WGSS_DATA	BLOB			N	

### WHDE

hotel departments (like reservation,conference,kitchen...)

Field Name	Type	Length	Decimals	Not NULL	
WHDE_ID	NUMBER	30		N	WHDE_ID identifies WHDE
WHDE_SHORTDESC	VARCHAR2	3		N	WHDE_SHORTDESC is of WHDE
WHDE_LONGDESC	VARCHAR2	30		N	WHDE_LONGDESC is of WHDE
WHDE_DISPLORDER	NUMBER	3		Y	WHDE_DISPLORDER is of WHDE
WHDE_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
WHDE_ROLE	NUMBER	1		Y	1 - Housekeeping, 2 - Maintenance, 3 - Kitchen, 4 = Restaurants

### WHFU

Remote Hotel Field Update Configuration

Field Name	Type	Length	Decimals	Not NULL	
WHFU_ID	NUMBER	30		N	Unique ID
WHFU_WPHS_ID	NUMBER	30		N	Link to Partner Hotel Setup
WHFU_FIELDNAME	VARCHAR2	60		N	Fieldname
WHFU_READ	NUMBER	1		Y	Right to read
WHFU_WRITE	NUMBER	1		Y	Right to write

### WHIN

Hints

Field Name	Type	Length	Decimals	Not NULL	
WHIN_ID	NUMBER	30		N	unique id of whin
WHIN_SHORTDESC	VARCHAR2	3		N	Short Description
WHIN_DISPLORDER	NUMBER	3		N	Display Order
WHIN_CONDITION	LONG			Y	WHIN_CONDITION is of WHIN
WHIN_TEXTMESSAGE	VARCHAR2	100		Y	WHIN_TEXTMESSAGE is of WHIN
WHIN_PROGRAMSTATE	NUMBER	2		N	Defined where this hint is called. 1 = after departure date (PMS)   2 = after rate code (PMS)   3 = at Check In   4 = at Check Out   5 = CheckOutBeforePayment   6 = CheckOutAfterPayment   7 = Room Move   8 = after arrival date (CCM)   9 = after departure date (CCM)   10 = after conference status (CCM)   11 = after rooms status (CCM)   12 = when editing booking (CCM)   13 = when closing booking (CCM)   14 = after event status (CCM)   15 = after event type (CCM)   16 = after event type (CCM)   17 = when editing event (CCM)   18 = when closing event (CCM)   19 = when editing profile (CRM)   20 = when closing profile (CRM)
WHIN_HTMLNAME	VARCHAR2	60		Y	if textmessage is filled this is shown else we display the html.
WHIN_ACTIVE	NUMBER	1		Y	1 = active

### WHLP

RoboHelp LinkFile

Field Name	Type	Length	Decimals	Not NULL	
WHLP_ID	NUMBER	30		N	INTERNAL ID
WHLP_COMPONENTNAMES	VARCHAR2	200		N	NAME OF COMPONENT (FORMNAME OR FORMNAME.COMPONENTNAME). WILL BE DETERMINED BY PROGRAM. IF FORMNAME.COMPONENTNAME NOT FOUND IN THE TABLE, FORMNAME WILL BE USED.
WHLP_TOPICID	VARCHAR2	500		N	TOPIC ID USED BY ROBOHELP. SO ONE TOPIC ID COULD BE MAPPED TO DIFFERENT CONTROLS/FORMS

### WICC

Internal Communication Config

Field Name	Type	Length	Decimals	Not NULL	
WICC_ID	NUMBER	30		N	WICC_ID identifies WICC
WICC_WPCA_ID	NUMBER	30		N	WICC_WPCA_ID is of WICC
WICC_ONLINE	NUMBER	1		N	WICC_ONLINE is of WICC
WICC_ADDRESS	VARCHAR2	60		Y	WICC_ADDRESS is of WICC
WICC_PORT	NUMBER	6		Y	WICC_PORT is of WICC
WICC_OFFLINE	NUMBER	1		N	WICC_OFFLINE is of WICC

## WICC

Internal Communication Config

Field Name	Type	Length	Decimals	Not NULL	
WICC_POLLINTERVAL	NUMBER	10		Y	WICC_POLLINTERVAL is of WICC

## WICL

Internal Communication Log Table

Field Name	Type	Length	Decimals	Not NULL	
WICL_ID	NUMBER	30		N	WICL_ID identifies WICL
WICL_TIMESTAMP	DATE			N	WICL_TIMESTAMP is of WICL
WICL_MSGNAME	VARCHAR2	60		Y	WICL_MSGNAME is of WICL
WICL_WPCA_ID	NUMBER	30		N	WICL_WPCA_ID is of WICL
WICL_MSG	VARCHAR2	2000		Y	

## WICM

Internal Communication

Field Name	Type	Length	Decimals	Not NULL	
WICM_ID	NUMBER	30		N	WICM_ID identifies WICM
WICM_ADDRESS	VARCHAR2	15		N	WICM_ADDRESS is of WICM
WICM_PORT	NUMBER	6		N	WICM_PORT is of WICM
WICM_TIMESTAMP	DATE			Y	WICM_TIMESTAMP is of WICM
WICM_WPCA_ID	NUMBER	30		Y	WICM_WPCA_ID is of WICM
WICM_UNIQUEIDPERCLIENT	VARCHAR2	60		N	WICM_UNIQUEIDPERCLIENT is of WICM

## WIDT

IFC Data through commands

Field Name	Type	Length	Decimals	Not NULL	
WIDT_ID	NUMBER	30		N	
WIDT_DESCRIPTION	VARCHAR2	30		N	
WIDT_PRECONFIG_TEXT	VARCHAR2	30		Y	
WIDT_TYPE	NUMBER	1		Y	
WIDT_DATATYPE	VARCHAR2	1		Y	0 - pre configured text , 1 - user input value
WIDT_LINKID	NUMBER	30		Y	
WIDT_LEVEL	NUMBER	2		Y	

### WILG

Interface Log

Field Name	Type	Length	Decimals	Not NULL	
WILG_ID	NUMBER	30		N	WILG_ID identifies WILG
WILG_ERRORDESC	LONG			Y	WILG_ERRORDESC is of WILG
WILG_PCDATE	DATE			N	WILG_PCDATE is of WILG
WILG_XCMS_ID	NUMBER	30		Y	WILG_XCMS_ID is of WILG
WILG_WPCA_ID	NUMBER	30		Y	WILG_WPCA_ID is of WILG
WILG_READ	NUMBER	1		N	WILG_READ is of WILG
WILG_READBY_XCMS_ID	NUMBER	30		Y	WILG_READBY_XCMS_ID is of WILG
WILG_READBY_WPCA_ID	NUMBER	30		Y	WILG_READBY_WPCA_ID is of WILG
WILG_IFC_TYPE	VARCHAR2	3		Y	Interface Family from ICFG_IFC_TYPE. Just used for Reporting.
WILG_ERRORDESC_VC	VARCHAR2	2000		Y	Store first 2000 characters from wilg_errordesc

### WIMG

Web booking images (rooms, advertisements etc.)

Field Name	Type	Length	Decimals	Not NULL	
WIMG_ID	NUMBER	30		N	
WIMG_IMAGE	LONG RAW			Y	
WIMG_IMPORTDATE	DATE			Y	
WIMG_COMPRESSED	NUMBER	1		Y	1 - Compressed
WIMG_PRIMARY	NUMBER	1		Y	Primary flag, used on profile html, to identify the picture to display

### WIML

Tables and Images Link Table

Field Name	Type	Length	Decimals	Not NULL	
WIML_ID	NUMBER	30		N	WIML ID
WIML_TABLENAME	CHAR			N	Linked Table Name
WIML_TABLEID	NUMBER	30		N	Record id from the linked table
WIML_DESCRIPTION	VARCHAR2	60		Y	
WIML_IMAGETYPE	NUMBER	1		N	0.Web Picture, 1.Mobile Device Picture, 2.Thumbnail
WIML_WIMG_ID	NUMBER	30		N	Linked image id
WIML_WEBENABLED	NUMBER	1		Y	1. available in web

### WINT

interval table for table reservations

Field Name	Type	Length	Decimals	Not NULL	
WINT_ID	NUMBER	30		N	ID
WINT_INTERVAL	NUMBER	3		N	interval
WINT_INTERVALTYPE	NUMBER	1		N	interval type; 0 - minutes; 1 - hours; 2 - days; 3 - weeks; 4 - months
WINT_SNAP	NUMBER	1		N	used as snap also

### WLAF

Lost and Found

Field Name	Type	Length	Decimals	Not NULL	
WLAF_ID	NUMBER	30		N	WLAF_ID identifies WLAF
WLAF_WLFG_ID	NUMBER	30		N	Link to Lost and Found Group
WLAF_XCMS_ID	NUMBER	30		N	if WLAF_TYPE=1 this is the person which lost the item if WLAF_TYPE=2 this is the person which foundt the item
WLAF_USER_XCMS_ID	NUMBER	30		N	User entering this L and F information
WLAF_YRMS_ID	NUMBER	30		Y	Lost or found in that room
WLAF_YFSC_ID	NUMBER	30		Y	Lost or found in that function space
WLAF_TYPE	NUMBER	1		N	1 = Lost, 2 = Found
WLAF_LONGDESC	VARCHAR2	60		N	WLAF_LONGDESC is of WLAF
WLAF_WHEN	DATE			N	if WLAF_TYPE=1 this is the date when the item was lost if WLAF_TYPE=2 this is the date when the item was foundt
WLAF_WHERE	VARCHAR2	30		Y	Where the item was found or lost (if this was not clearly in a room or a functino space)
WLAF_DATE	DATE			N	Date when this L and F Information was entered
WLAF_KEEPUNTILDATE	DATE			Y	if WLAF_TYPE = 2 this is the date until when the found item should be kept (defaults to sysdate + global setting)
WLAF_FREETEXT	VARCHAR2	1000		Y	free text to describe the L and F items
WLAF_PICTURE	LONG RAW			Y	Picture of the found item
WLAF_FOUND_WLAF_ID	NUMBER	30		Y	when the item was connected between lost and found record this is filled with the record id of the found item
WLAF_NUMBERCYCLE	NUMBER	30		Y	Automatically generated number for found items
WLAF_RESOLVEDATE	DATE			Y	When the case was resolved
WLAF_RESOLVED_USER_XCMS_ID	NUMBER	30		Y	User which entered case resolution
WLAF_YPUB_ID	NUMBER	30		Y	Link to public places
WLAF_PICTURE_FORMAT	NUMBER	1		Y	0 - JPEG, 1 - BMP

### WLAN

languages in the system

Field Name	Type	Length	Decimals	Not NULL	
WLAN_ID	NUMBER	30		N	WLAN_ID identifies WLAN
WLAN_SHORTDESC	VARCHAR2	3		N	WLAN_SHORTDESC is of WLAN
WLAN_LONGDESC	VARCHAR2	30		N	WLAN_LONGDESC is of WLAN
WLAN_DISPLORDER	NUMBER	3		Y	WLAN_DISPLORDER is of WLAN
WLAN_SYSTEM	NUMBER	1		Y	WLAN_SYSTEM is of WLAN
WLAN_DATABASE	NUMBER	1		Y	WLAN_DATABASE is of WLAN
WLAN_GUEST	NUMBER	1		Y	WLAN_GUEST is of WLAN
WLAN_INACTIVE	NUMBER	1		Y	1 = Inactive
WLAN_ISO2	VARCHAR2	2		Y	Iso 2 Standard Code
WLAN_ISO3	VARCHAR2	3		Y	Iso 3 Standard Code
WLAN_DEFAULT	NUMBER	1		Y	WLAN_DEFAULT is of WLAN
WLAN_WEBCULTURE	VARCHAR2	10		Y	Web Culture for Suite 8 Web and Suite 8 Homepage

### WLCK

record locks

Field Name	Type	Length	Decimals	Not NULL	
WLCK_TYPE	NUMBER	2		N	WLCK_TYPE identifies WLCK
WLCK_ID	NUMBER	30		N	WLCK_ID partly identifies WLCK
WLCK_WPCA_ID	NUMBER	30		N	WLCK_WPCA_ID is of WLCK
WLCK_TIMESTAMP	DATE			N	WLCK_TIMESTAMP is of WLCK
WLCK_WSES_ID	NUMBER	30		Y	
WLCK_TABLENAME	VARCHAR2	4		Y	

### WLFA

Activities with Lost and Found items, such as 'Moved to Housekeeping' or 'Handed out personally' or 'Sent per post'

Field Name	Type	Length	Decimals	Not NULL	
WLFA_ID	NUMBER	30		N	Unique Identifier
WLFA_USER_XCMS_ID	NUMBER	30		N	User which entered this action
WLFA_DATE	DATE			N	when this action was performed
WLFA_WLAF_ID	NUMBER	30		N	the action was performed on the linked WLFA record
WLFA_FREETEXT	VARCHAR2	200		Y	free text edit to describe the action
WLFA_WLFC_ID	NUMBER	30		N	L and F Action category link

## WLFC

Lost and Found Action Categories

Field Name	Type	Length	Decimals	Not NULL	
WLFC_ID	NUMBER	30		N	WLFC_ID identifies WLFC
WLFC_LOST	NUMBER	1		Y	1 = if this is an action code for lost items
WLFC_FOUND	NUMBER	1		Y	1 = if this is an action code for found items
WLFC_SHORTDESC	VARCHAR2	3		N	Short description
WLFC_LONGDESC	VARCHAR2	30		N	Long description
WLFC_DISPLORDER	NUMBER	3		N	WLFC_DISPLORDER is of WLFC
WLFC_FINAL	NUMBER	1		Y	If value is 1, the lost and found process return is over.
WLFC_INACTIVE	NUMBER	1		Y	1 = Inactive

## WLFG

Lost and Found Item Categories, such like 'Cosmetics, Laundry etc'

Field Name	Type	Length	Decimals	Not NULL	
WLFG_ID	NUMBER	30		N	WLFG_ID identifies WLFG
WLFG_LONGDESC	VARCHAR2	30		N	Long description of L and F Group
WLFG_DISPLORDER	NUMBER	3		N	Display Order
WLFG_INACTIVE	NUMBER	1		Y	1 = Inactive
WLFG_NOOFDAYS	NUMBER	3		Y	Default number of days

## WLHC

Holiday Check Interface review Posting Log

Field Name	Type	Length	Decimals	Not NULL	
WLHC_ID	NUMBER	30		N	Id
WLHC_DATE	DATE			N	Review Date
WLHC_YRES_ID	NUMBER	30		N	Reservation id
WLHC_REVIEW	VARCHAR2	4000		N	Review Text
WLHC_REPLY	VARCHAR2	2000		Y	Reply from HolidayCheck
WLHC_SUCCESS	NUMBER	1		Y	1. Successful

## WLIB

Field Name	Type	Length	Decimals	Not NULL	
WLIB_ID	NUMBER	30		N	

### WLIB

Field Name	Type	Length	Decimals	Not NULL
WLIB_TIMESTAMP	DATE			N
WLIB_HASH	VARCHAR2	32		Y
WLIB_DATA	CLOB			N

### WLIC

License Table

Field Name	Type	Length	Decimals	Not NULL	
WLIC_ID	NUMBER	30		N	WLIC_ID identifies WLIC
WLIC_LONGDESC	VARCHAR2	200		N	license code description
WLIC_ACTIVE	NUMBER	1		N	1 = active License
WLIC_CODE	VARCHAR2	30		Y	license code.
WLIC_GROUP	NUMBER	2		N	1 - General 2 - Front Office 3 - CCM 4 - Interfaces 5 - IFC FKT LOGO
WLIC_LICENSENAME	VARCHAR2	200		Y	Identifier for license (like fkt logo and function for ifc)

### WLLC

Luggage Locations (like reception, luggage room etc)

Field Name	Type	Length	Decimals	Not NULL	
WLLC_ID	NUMBER	30		N	Unique Identifier
WLLC_SHORTDESC	VARCHAR2	3		N	Short Description of Luggage Location
WLLC_LONGDESC	VARCHAR2	30		N	Long Description of Luggage Location
WLLC_DISPLORDER	NUMBER	3		Y	WLLC_DISPLORDER is of WLLC
WLLC_INACTIVE	NUMBER	1		Y	1 = Inactive

### WLNR

Sequence for automatic Luggage numbersr

Field Name	Type	Length	Decimals	Not NULL	
WLNR_NUMBER	NUMBER	30		N	WLNR_NUMBER identifies WLNR

### WLOF

List of fields used for display for merge

Field Name	Type	Length	Decimals	Not NULL	
WLOF_ID	NUMBER	30		N	WLOF_ID identifies WLOF

### WLOF

List of fields used for display for merge

Field Name	Type	Length	Decimals	Not NULL	
WLOF_WVFD_ID	NUMBER	30		Y	WLOF_WVFD_ID is of WLOF
WLOF_DESCRIPTION	VARCHAR2	100		Y	WLOF_DESCRIPTION is of WLOF
WLOF_DISPLORDER	NUMBER	3		Y	Display order

### WLOG

User Log

Field Name	Type	Length	Decimals	Not NULL	
WLOG_ID	NUMBER	30		N	WLOG_ID identifies WLOG
WLOG_TIME	DATE			N	WLOG_TIME is of WLOG
WLOG_XCED_ID	NUMBER	30		N	WLOG_XCED_ID is of WLOG
WLOG_TYPE	NUMBER	3		N	WLOG_TYPE is of WLOG
WLOG_TABLE_ID	NUMBER	30		N	WLOG_TABLE_ID is of WLOG
WLOG_TEXT	VARCHAR2	400		N	WLOG_TEXT is of WLOG
WLOG_WPCA_ID	NUMBER	30		N	WLOG_WPCA_ID is of WLOG
WLOG_SYSDAT	DATE			N	WLOG_SYSDAT is of WLOG
WLOG_TABLENAME	CHAR			N	WLOG_TABLENAME is of WLOG
WLOG_TERMINAL	VARCHAR2	60		Y	Terminal Name/Ip Address
WLOG_WPHS_ID	NUMBER	30		Y	In central db this shows which hotel made changes using xml interface

### WLOL

linking the lower hirarchy ids with higher hirarchy ids

Field Name	Type	Length	Decimals	Not NULL	
WLOL_ID	NUMBER	30		N	wlol id
WLOL_WLOG_ID	NUMBER	30		N	wlog table id
WLOL_TABLE_ID	NUMBER	30		N	link table id in higher hirarchy
WLOL_TYPE	NUMBER	1		N	1=ybom, 2=yevm, 3=yebes, 4=yebr, 5=yemn, 5=yemi

### WLOP

Online payments log

Field Name	Type	Length	Decimals	Not NULL	
WLOP_ID	NUMBER	30		N	
WLOP_DATE	DATE			N	

### WLOP

Online payments log

Field Name	Type	Length	Decimals	Not NULL	
WLOP_TYPE	NUMBER	2		N	Payment system type. 1 = Telecash 2 = Paypal
WLOP_SUCCESS	NUMBER	1		N	1 = success 0 = failure
WLOP_APPROVALNUMBER	VARCHAR2	100		Y	Approval number from online payment system
WLOP_MESSAGE	VARCHAR2	3000		Y	

### WLOR

Online payments log link table for the reservations

Field Name	Type	Length	Decimals	Not NULL	
WLOR_ID	NUMBER	30		N	
WLOR_WLOP_ID	NUMBER	30		N	
WLOR_YRES_ID	NUMBER	30		Y	
WLOR_COUP_ID	NUMBER	30		Y	

### WLUG

Luggage Handling

Field Name	Type	Length	Decimals	Not NULL	
WLUG_ID	NUMBER	30		N	WLUG_ID identifies WLUG
WLUG_CUSTOMDATA	VARCHAR2	50		Y	CAN BE ENTERED MANUALLY OR AUTOMATICALLY DEPENDING ON GLOBAL SETTINGS. USER INTERFACE MIGHT ACCEPT NUMERIC CHARACTERS ONLY DEPENDING ON SETTINGS
WLUG_QUANTITY	NUMBER	3		N	number of luggage pieces
WLUG_YRES_ID	NUMBER	30		N	Luggage Link to Reservation
WLUG_PRINTED	NUMBER	3		N	HOW MANY TIMES IT WAS PRINTED
WLUG_COMMENTS	VARCHAR2	200		Y	Comments user could add if needed
WLUG_WLLC_ID	NUMBER	30		Y	Location of Luggage
WLUG_STATUS	NUMBER	1		Y	1=PICKED UP BY GUEST 0=STILL IN HOTEL
WLUG_XCED_ID	NUMBER	30		N	2=DELIVERED TO ROOM user who created this record
WLUG_CREATIONTIME	DATE			N	when created

### WLUS

Assigned User Rights

Field Name	Type	Length	Decimals	Not NULL	
WLUS_ID	NUMBER	30		N	Unique ID

### WLUS

Assigned User Rights

Field Name	Type	Length	Decimals	Not NULL	
WLUS_WUSR_XCMS_ID	NUMBER	30		Y	Link to User Rights
WLUS_XCMS_ID	NUMBER	30		Y	Link to Users
WLUS_NAME	VARCHAR2	100		N	Right Name
WLUS_VALUE	NUMBER	1		N	0= Not assigned 1=Enabled 2= Denied

### WMAA

Email attachments

Field Name	Type	Length	Decimals	Not NULL	
WMAA_ID	NUMBER	30		N	WMAA PK
WMAA_WMAI_ID	NUMBER	30		N	Attachment link to the email
WMAA_FILENAME	VARCHAR2	128		N	Attachment file name
WMAA_ATTACHMENT_WTXT_ID	NUMBER	30		N	link to the binary storage

### WMAI

Emails for sending

Field Name	Type	Length	Decimals	Not NULL	
WMAI_ID	NUMBER	30		N	Unique Identifier
WMAI_BODY_WTXT_ID	NUMBER	30		N	Reference to record in WTXT containing body
WMAI_ATTACHMENT_WTXT_ID	NUMBER	30		Y	Reference to record in WTXT containing attachment
WMAI_ATTACHMENT_FILE_NAME	VARCHAR2	256		Y	Physical file name
WMAI_FIDELIODATE	DATE			N	Date of sending
WMAI_SENT	NUMBER	1		N	0 - Not yet sent; 1 - sent
WMAI_NO_OF_ATTEMPTS	NUMBER	3		N	No of sending attempts
WMAI_LAST_ATTEMPT	DATE			Y	Timestamp of last attempt
WMAI_TO	VARCHAR2	2000		Y	Recipient address
WMAI_SUBJECT	VARCHAR2	256		Y	Email subject
WMAI_SENDER	VARCHAR2	128		N	Sender address
WMAI_ATTACHMENT_RTF_WTXT_ID	NUMBER	30		Y	RTF source for PDF attachments
WMAI_CC	VARCHAR2	2000		Y	
WMAI_BCC	VARCHAR2	2000		Y	
WMAI_BLOCKSEND	NUMBER	1		Y	if user has no right to send letters or denied the send request then blocksend=1 otherwise 0 or null
WMAI_READONLY	NUMBER	1		Y	

### WMAI

Emails for sending

Field Name	Type	Length	Decimals	Not NULL	
WMAI_SMS	NUMBER	1		Y	The record is SMS message
WMAI_SMSCONFIRMCODE	VARCHAR2	100		Y	Gateway confirmation code or error message in case of failure
WMAI_DRAFT	NUMBER	1		Y	The email saved for future editing
WMAI_BODY_SRC_WTXT_ID	NUMBER	30		Y	
WMAI_ERROR	VARCHAR2	2000		Y	Error while sending

### WMAS

manual statistic values table

Field Name	Type	Length	Decimals	Not NULL	
WMAS_ID	NUMBER	30		N	Unique ID
WMAS_WMST_ID	NUMBER	30		N	Link to statistic type
WMAS_DATE	DATE			Y	Statistic date
WMAS_VALUE	NUMBER	30	4	Y	Statistic value
WMAS_FREETEXT	VARCHAR2	1000		Y	Free definable text

### WMAT

Mailing Translation

Field Name	Type	Length	Decimals	Not NULL	
WMAT_ID	NUMBER	30		N	Unique ID
WMAT_WLAN_ID	NUMBER	30		N	Link to Languages
WMAT_STRING	VARCHAR2	200		N	String to be translated
WMAT_VALUE	VARCHAR2	200		N	Translated string

### WMLG

table modification log

Field Name	Type	Length	Decimals	Not NULL	
WMLG_ID	NUMBER	30		N	WMLG_ID identifies WMLG
WMLG_TABLENAME	VARCHAR2	4		N	WMLG_TABLENAME is of WMLG
WMLG_TABLE_ID	NUMBER	30		N	WMLG_TABLE_ID is of WMLG
WMLG_FIDELIODATE	DATE			N	Fidelio System Date
WMLG_TIME_CREATION	DATE			Y	WMLG_TIME_CREATION is of WMLG
WMLG_TIME_UPDATE	DATE			Y	WMLG_TIME_UPDATE is of WMLG

### WMLG

table modification log

Field Name	Type	Length	Decimals	Not NULL	
WMLG_XCMS_CREATION	NUMBER	30		Y	WMLG_XCMS_CREATION is of WMLG
WMLG_XCMS_UPDATE	NUMBER	30		Y	WMLG_XCMS_UPDATE is of WMLG
WMLG_CREAPRGVERSION	VARCHAR2	15		Y	Created by Program Version
WMLG_CREADBVERSION	VARCHAR2	15		Y	Created by DB Version
WMLG_UPDPRGVERSION	VARCHAR2	15		Y	Updated by Program Version
WMLG_UPDDBVERSION	VARCHAR2	15		Y	Updated by DB Version

### WMSL

Maintenance status level

Field Name	Type	Length	Decimals	Not NULL	
WMSL_ID	NUMBER	30		N	
WMSL_SHORTDESC	VARCHAR2	3		N	
WMSL_LONGDESC	VARCHAR2	30		N	
WMSL_DISPLORDER	NUMBER	3		N	
WMSL_WEBENABLED	NUMBER	1		N	
WMSL_INACTIVE	NUMBER	1		N	
WMSL_FORRESOLVE	NUMBER	1		Y	Flag for maintenance Resolution status
WMSL_DEFAULT	NUMBER	1		Y	1 = Default Maintenance Status Level
WMSL_DEFAULTFOR SOLVE	NUMBER	1		Y	Default for solved

### WMSO

Query Wizard History

Field Name	Type	Length	Decimals	Not NULL	
WMSO_ID	NUMBER	30		N	Unique identifier
WMSO_WQFD_ID	NUMBER	30		N	Link to Mailing Query
WMSO_CREATIONDATE	DATE			Y	Date of saving history
WMSO_DESCRIPTION	VARCHAR2	60		Y	History Name
WMSO_WLOF_ID	NUMBER	30		Y	Link to a selected list of fields
WMSO_DICS	NUMBER	1		Y	Display individual if company selected
WMSO_DIWL	NUMBER	1		Y	Display individual without link
WMSO_DCCS	NUMBER	1		Y	Display company if contact selected
WMSO_CPI	NUMBER	1		Y	Contact preference individual

## WMSO

Query Wizard History

Field Name	Type	Length	Decimals	Not NULL	
WMSO_CPC	NUMBER	1		Y	Contact preference company
WMSO_DMC	NUMBER	1		Y	Display mailing contact
WMSO_DPC	NUMBER	1		Y	Display primary contact
WMSO_DOC	NUMBER	1		Y	Display other contact
WMSO_EFM	NUMBER	1		Y	Exclude family members
WMSO_AC	NUMBER	1		Y	Address check
WMSO_EC	NUMBER	1		Y	Email check
WMSO_MIICS	NUMBER	1		Y	Matched individuals if company selected
WMSO_BODY_WFAQ_ID	NUMBER	30		Y	Link to body document id
WMSO_ATTACHMENT_WFAQ_ID	NUMBER	30		Y	Link to attachment document id
WMSO_SUBJECT	VARCHAR2	60		Y	Email Subject
WMSO_ATTACHMENT	VARCHAR2	200		Y	Email Attachment

## WMST

manual statistic types table

Field Name	Type	Length	Decimals	Not NULL	
WMST_ID	NUMBER	30		N	Unique ID
WMST_SHORTDESC	VARCHAR2	3		Y	Short description
WMST_LONGDESC	VARCHAR2	30		Y	Long description
WMST_UNIT	VARCHAR2	10		Y	Unit
WMST_DISPLORDER	NUMBER	6		Y	Display order
WMST_INACTIVE	NUMBER	1		Y	1 = Inactive

## WMWC

Mailing Wizard Configuration for execution

Field Name	Type	Length	Decimals	Not NULL	
WMWC_ID	NUMBER	30		N	
WMWC_SHORTDESC	VARCHAR2	3		Y	
WMWC_LONGDESC	VARCHAR2	100		Y	
WMWC_WSQG_ID	NUMBER	30		Y	
WMWC_WSQL_ID	NUMBER	30		Y	
WMWC_CREATED_XCED_ID	NUMBER	30		Y	

## WMWC

Mailing Wizard Configuration for execution

Field Name	Type	Length	Decimals	Not NULL	
WMWC_TIME_CREATED	DATE			Y	
WMWC_FIXED	NUMBER	1		Y	1=SQL Statement is fixed, parameter are stored in WSQL with parameter in SQL, 0= SQL Statement is not fixed, Parameters are used during execution, Parameter in WSQP are used
WMWC_DISPLORDER	NUMBER	4		Y	
WMWC_REMARKS	VARCHAR2	2000		Y	
WMWC_TECHNICAL_INFO	VARCHAR2	2000		Y	

## WMWD

Mailing Wizard Details Sql Statements

Field Name	Type	Length	Decimals	Not NULL	
WMWD_ID	NUMBER	30		N	
WMWD_SHORTDESC	VARCHAR2	3		Y	
WMWD_LONGDESC	VARCHAR2	60		Y	
WMWD_WMWM_ID	NUMBER	30		N	
WMWD_SQL_SETUP	LONG			Y	
WMWD_DISPLORDER	NUMBER	4		Y	
WMWD_REMARKS	VARCHAR2	2000		Y	

## WMWE

Mailing Wizard Execution Log

Field Name	Type	Length	Decimals	Not NULL	
WMWE_ID	NUMBER	30		N	
WMWE_SHORTDESC	VARCHAR2	3		Y	
WMWE_LONGDESC	VARCHAR2	100		Y	
WMWE_TIME	DATE			Y	
WMWE_XCED_ID	NUMBER	30		N	
WMWE_WSQG_ID	NUMBER	30		Y	
WMWE_WSQL_ID	NUMBER	30		Y	
WMWE_RESULTCOUNT	NUMBER	10		Y	Store the number of records found here
WMWE_RESULTXCMS	LONG			Y	Store the XCMS_IS in the same format as we store XCMS in XML when exporting from Profile Grid
WMWE_REMARKS	VARCHAR2	2000		Y	
WMWE_TECHNICAL_INFO	VARCHAR2	2000		Y	

## WMWE

Mailing Wizard Execution Log

Field Name	Type	Length	Decimals	Not NULL
WMWE_WACT_TYPE	NUMBER	1		Y
WMWE_WMWS_ID	NUMBER	30		Y

## WMWF

Mailing Wizard Field List

Field Name	Type	Length	Decimals	Not NULL	
WMWF_ID	NUMBER	30		N	
WMWF_SHORTDESC	VARCHAR2	3		Y	
WMWF_LONGDESC	VARCHAR2	100		Y	
WMWF_TYPE	NUMBER	1		Y	1=Profile, 2= Address, 3= Communication, 0=Misc
WMWF_TABLE_NAME	VARCHAR2	4		Y	
WMWF_TABLE_LINK_FIELD	VARCHAR2	30		Y	
WMWF_DISPLORDER	NUMBER	4		Y	
WMWF_REMARKS	VARCHAR2	2000		Y	
WMWF_SQL_SETUP	LONG			Y	

## WMWG

Mailing Wizard Global Exclusion

Field Name	Type	Length	Decimals	Not NULL
WMWG_ID	NUMBER	30		N
WMWG_SHORTDESC	VARCHAR2	3		Y
WMWG_LONGDESC	VARCHAR2	100		Y
WMWG_DISPLORDER	NUMBER	4		Y
WMWG_REMARKS	VARCHAR2	2000		Y
WMWG_SQL_SETUP	LONG			Y

## WMWL

Mailing Wizard SQL Log

Field Name	Type	Length	Decimals	Not NULL
WMWL_ID	NUMBER	30		N
WMWL_WMWD_ID	NUMBER	30		Y
WMWL_WMWD_EXCL	NUMBER	1		Y

### WMWL

Mailing Wizard SQL Log

Field Name	Type	Length	Decimals	Not NULL
WMWL_WMWF_ID	NUMBER	30		Y
WMWL_WMWG_ID	NUMBER	30		Y
WMWL_WSQL_ID	NUMBER	30		Y
WMWL_TIMESTAMP	DATE			Y

### WMWM

Mailing Wizard Main Sql Groups

Field Name	Type	Length	Decimals	Not NULL
WMWM_ID	NUMBER	30		N
WMWM_SHORTDESC	VARCHAR2	3		Y
WMWM_LONGDESC	VARCHAR2	60		Y
WMWM_DISPLORDER	NUMBER	4		Y
WMWM_REMARKS	VARCHAR2	2000		Y

### WMWP

Mailing Wizard Parameter for Details Sql Statements

Field Name	Type	Length	Decimals	Not NULL
WMWP_ID	NUMBER	30		N
WMWP_TYP	NUMBER	1		Y
WMWP_WMWD_ID	NUMBER	30		N
WMWP_MULTIPLE	NUMBER	1		Y
WMWP_TABLE_NAME	VARCHAR2	4		Y
WMWP_TABLE_FIELD	VARCHAR2	30		Y
WMWP_PARAMETERNAME	VARCHAR2	30		Y
WMWP_INTERNAL_SQL	VARCHAR2	2000		Y
WMWP_FIELD1	VARCHAR2	30		Y
WMWP_FIELD2	VARCHAR2	30		Y
WMWP_FIELD3	VARCHAR2	30		Y
WMWP_DISPLORDER	NUMBER	4		Y
WMWP_REMARKS	VARCHAR2	2000		Y

0=STRING 1=INTEGER 2=FLOAT 3=BOOLEAN  
4=DATE 5=DATETIME 6=STRING with data selection  
7=INTEGER with data selection

## WMWS

Saved Mailing Wizard Settings

Field Name	Type	Length	Decimals	Not NULL
WMWS_ID	NUMBER	30		N
WMWS_SHORTDESC	VARCHAR2	3		Y
WMWS_LONGDESC	VARCHAR2	60		Y
WMWS_REMARKS	VARCHAR2	2000		Y
WMWS_XCED_ID	NUMBER	30		Y
WMWS_WSQL_ID	NUMBER	30		Y
WMWS_TIMESTAMP	DATE			Y

## WMWX

Mailing Wizard SQL execution detail Log

Field Name	Type	Length	Decimals	Not NULL
WMWX_ID	NUMBER	30		N
WMWX_WMWP_ID	NUMBER	30		Y
WMWX_WMWP_INCL	NUMBER	1		Y
WMWX_WMWE_ID	NUMBER	30		Y
WMWX_TIMESTAMP	DATE			Y
WMWX_PARAMCONTENT	VARCHAR2	2000		Y

## WMWZ

Saved Mailing Wizard Settings link table

Field Name	Type	Length	Decimals	Not NULL
WMWZ_ID	NUMBER	30		N
WMWZ_WMWS_ID	NUMBER	30		Y
WMWZ_WMWD_ID	NUMBER	30		Y
WMWZ_WMWD_INCL	NUMBER	1		Y
WMWZ_WMWG_ID	NUMBER	30		Y
WMWZ_WMWF_ID	NUMBER	30		Y

## WNAE

Night Audit Exports (Back office interface)

Field Name	Type	Length	Decimals	Not NULL
WNAE_ID	NUMBER	30		N

WNAE\_ID identifies WNAE

### WNAE

Night Audit Exports (Back office interface)

Field Name	Type	Length	Decimals	Not NULL	
WNAE_LONGDESC	VARCHAR2	30		N	WNAE_LONGDESC is of WNAE
WNAE_AUTOMATIC	NUMBER	1		N	WNAE_AUTOMATIC is of WNAE
WNAE_EXPORTFILENAME	VARCHAR2	200		N	WNAE_EXPORTFILENAME is of WNAE
WNAE_HEADER_SQL	VARCHAR2	2000		Y	WNAE_HEADER_SQL is of WNAE
WNAE_DATA_SQL	VARCHAR2	4000		Y	WNAE_DATA_SQL is of WNAE
WNAE_FOOTER_SQL	VARCHAR2	2000		Y	WNAE_FOOTER_SQL is of WNAE
WNAE_APPEND	NUMBER	1		Y	WNAE_APPEND is of WNAE
WNAE_WHEN	NUMBER	1		Y	1 = daily 2 = last day of month ... to be continued on demand
WNAE_AFTERDATECHANGE	NUMBER	1		Y	1=run after na has changed fideliodate. 0 or null= run before date change
WNAE_BATCHFILENAME	VARCHAR2	60		Y	
WNAE_DELETEAFTERMOVEDTOBAT CH	NUMBER	1		Y	
WNAE_DISPLORDER	NUMBER	3		Y	
WNAE_DEFTYPE	NUMBER	1		Y	
WNAE_WRPT_ID	NUMBER	30		Y	
WNAE_EXPORTTYPE	NUMBER	1		Y	
WNAE_PARAMETERS	VARCHAR2	1000		Y	
WNAE_REPORT_TYPE	NUMBER	2		Y	Indicates the report type for ideas 1 = CurrentTotal, 2 = CurrentTotalRT, 3 = CurrentSegRT, 4 = PastTotal, 5 = PastTotalRT, 6 = PastSegRT

### WNAL

Night Audit Log

Field Name	Type	Length	Decimals	Not NULL	
WNAL_ID	NUMBER	30		N	WNAL_ID identifies WNAL
WNAL_TIME	DATE			N	WNAL_TIME is of WNAL
WNAL_USER_XCMS_ID	NUMBER	30		N	WNAL_USER_XCMS_ID is of WNAL
WNAL_TERMINAL_WPCA_ID	NUMBER	30		N	WNAL_TERMINAL_WPCA_ID is of WNAL
WNAL_LOG	LONG			Y	
WNAL_FIDELIODATE	DATE			Y	WNAL_LOG is of WNAL

### WNAR

ASP Night Audit reports

Field Name	Type	Length	Decimals	Not NULL	
WNAR_ID	NUMBER	30		N	

### WNAR

ASP Night Audit reports

Field Name	Type	Length	Decimals	Not NULL	
WNAR_WRPT_ID	NUMBER	30		Y	
WNAR_TIMESTAMP	DATE			N	
WNAR_SYSDATE	DATE			N	
WNAR_REPORT	LONG RAW			Y	
WNAR_TYPE	NUMBER	2		N	0 - Night Audit report, 1 - Text Exports, 2 - Remote printing reports
WNAR_NAME	VARCHAR2	200		Y	used if the report is not specified (for example for exports)
WNAR_HANDLED	NUMBER	1		Y	
WNAR_WPJC_ID	NUMBER	30		Y	
WNAR_WPCA_ID	NUMBER	30		Y	
WNAR_PRINTERNAME	VARCHAR2	300		Y	

### WNAS

Night Audit Setup Table

Field Name	Type	Length	Decimals	Not NULL	
WNAS_ID	NUMBER	30		N	WNAS_ID identifies WNAS
WNAS_NAME	VARCHAR2	30		N	WNAS_NAME is of WNAS
WNAS_SQL	LONG			N	WNAS_SQL is of WNAS
WNAS_ORDER	NUMBER	4		Y	WNAS_ORDER is of WNAS
WNAS_NAPOSITION	NUMBER	2		Y	WNAS_NAPOSITION is of WNAS
WNAS_INACTIVE	NUMBER	1		Y	

### WNEB

night audit text export batch timestamps

Field Name	Type	Length	Decimals	Not NULL	
WNEB_TIMESTAMP	DATE			N	
WNEB_HOTELDATE	DATE			Y	

### WNEL

Night audit Export log

Field Name	Type	Length	Decimals	Not NULL	
WNEL_ID	NUMBER	30		N	WNEL_ID identifies WNEL
WNEL_WNAE_ID	NUMBER	30		N	WNEL_WNAE_ID is of WNEL

### WNEL

Night audit Export log

Field Name	Type	Length	Decimals	Not NULL	
WNEL_TIME	DATE			N	WNEL_TIME is of WNEL
WNEL_USER_XCMS_ID	NUMBER	30		N	WNEL_USER_XCMS_ID is of WNEL
WNEL_WPCA_ID	NUMBER	30		Y	WNEL_WPCA_ID is of WNEL
WNEL_AUTOMATIC	NUMBER	1		N	1 = ran automatically 0 = run manually
WNEL_FIDELIodate	DATE			Y	WNEL_FIDELIodate is of WNEL

### WNUM

List of Numbers, for Reporting

Field Name	Type	Length	Decimals	Not NULL	
WNUM_VALUE	NUMBER	30		N	Value

### WOIP

object data import plan. identifies records to be imported

Field Name	Type	Length	Decimals	Not NULL	
WOIP_ID	NUMBER	30		N	
WOIP_SOURCETABLENAME	VARCHAR2	20		N	
WOIP_SOURCEID	NUMBER	30		N	
WOIP_STATUS	NUMBER	1		N	0=to be imported 1=success 2=failure 3=disabled(not to be imported)
WOIP_LASTSTATUSCHANGE	DATE			N	
WOIP_TAG	VARCHAR2	30		N	short identifier for record. ie in case of reservations: future/history/inhouse or anything else entered by some conversion tool
WOIP_DESCRIPTION	VARCHAR2	500		N	information that may help users to identify records in user interface of other programs we are importing from
WOIP_COMMENT	VARCHAR2	200		Y	user comment that helps identify records. should be entered by some conversion tool
WOIP_ERRORLOG	VARCHAR2	2000		Y	
WOIP_V8ID	NUMBER	30		Y	

### WORJ

Maintenance Origins

Field Name	Type	Length	Decimals	Not NULL	
WORJ_ID	NUMBER	30		N	
WORJ_SHORTDESCRIPTION	VARCHAR2	60		Y	
WORJ_LONGDESCRIPTION	VARCHAR2	200		Y	

### WORJ

Maintenance Origins

Field Name	Type	Length	Decimals	Not NULL	
WORJ_DISPLAYORDER	NUMBER	4		Y	
WORJ_INACTIVE	NUMBER	1		Y	
WORJ_ROLE	NUMBER	1		Y	where role = 1 means guest generated and makes wact_xcms_id mandatory when entering the maintenance task; 2 = Automatic
WORJ_DEFAULT	NUMBER	1		Y	1 = Default Maintenance Origin

### WPCA

Workstation Identification

Field Name	Type	Length	Decimals	Not NULL	
WPCA_ID	NUMBER	30		N	Unique identifier of the workstation
WPCA_NETBIOSNAME	VARCHAR2	60		N	Set variable COMPUTERNAME
WPCA_LONGDESC	VARCHAR2	30		N	user definable description of the workstation
WPCA_SWIPER	NUMBER	1		Y	WPCA_SWIPER is of WPCA
WPCA_WSWC_ID	NUMBER	30		Y	Link to swipe type
WPCA_WAKE_RESPONSE	NUMBER	1		Y	0 = do not show, 1 = show pop-ups
WPCA_CASH_DRAWER_PORT	NUMBER	1		Y	COM port number of Cash Drawer
WPCA_LOGOFFTIME	NUMBER	4		Y	
WPCA_BARCODEREADERBAUD	NUMBER	6		Y	Barcode Reader Baud, 1=300 2=1200 3=2400 4=4800 5=9600 6=19200 7=38400 8=57600
WPCA_BARCODEREADERPORT	NUMBER	2		Y	Barcode Reader COM Port number
WPCA_IFCBUSI_LAST_TIME	DATE			Y	Timestamp, when ifcbusi loaded last time in this workstation
WPCA_IFCBUSI_LAST_VERSION	VARCHAR2	10		Y	Version Number of the last IfcBusi dll
WPCA_ENABLETELEPHONY	NUMBER	1		Y	1 - enable telephony for this workstation
WPCA_TAIPREDIAL	NUMBER	1		Y	predial number for outgoing calls
WPCA_DEFAULTTAPIADDRESS	VARCHAR2	100		Y	default tapi address to use for outgoing calls
WPCA_ENABLESKYPE	NUMBER	1		Y	1 - enable skype support on this workstation
WPCA_SILENTSKYPE	NUMBER	1		Y	1 - set silent mode for skype
WPCA_PASSSCANNER	NUMBER	3		Y	Obsolete using table linked devices to terminal
WPCA_CASH_DRAWER_BAUD	NUMBER	5		Y	Cash Drawer baud rate
WPCA_CASH_DRAWER_NULLS	NUMBER	2		Y	Cash Drawer. Amount of nulls to init
WPCA_CASH_DRAWER_STRING	VARCHAR2	20		Y	Cash Drawer. Sleep time
WPCA_CASH_DRAWER_SLEEP	NUMBER	2		Y	
WPCA_PMS_LAST_VERSION	VARCHAR2	15		Y	last PMS Version used in this workstation
WPCA_SKIPMAKEKEYFORTRANSPONDER	NUMBER	1		Y	1. Makekey during Transponder check-in will be skipped in this workstation

## WPCA

Workstation Identification

Field Name	Type	Length	Decimals	Not NULL	
WPCA_HASEIDREADER	NUMBER	1		Y	Obsolete using table linked devices to terminal
WPCA_REFRESHLEVEL	NUMBER	3		Y	OBSOLETE COLUMN, NOT USED ANYMORE
WPCA_WSET_ID	NUMBER	30		Y	linked Swedish E Tax Control Unit
WPCA_ETAX_REGISTERID	VARCHAR2	16		Y	ETAX cash register id of the terminal
WPCA_THAIRDNUMBER	VARCHAR2	100		Y	
WPCA_IS_S8_KIOSK	NUMBER	1		Y	1 = for KIOSK
WPCA_KIOSK_ZFST_ID	NUMBER	30		Y	Custom folio styles per Kiosk terminal

## WPCL

workstation activity log

Field Name	Type	Length	Decimals	Not NULL	
WPCL_ID	NUMBER	30		N	WPCL_ID identifies WPCL
WPCL_WPCA_ID	NUMBER	30		N	WPCL_WPCA_ID is of WPCL
WPCL_TIME	DATE			N	WPCL_TIME is of WPCL
WPCL_ACTIVITY	NUMBER	2		N	0 login 1 logout
WPCL_XCED_ID	NUMBER	30		N	WPCL_XCED_ID is of WPCL

## WPDT

Data translation for partner hotels (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WPDT_ID	NUMBER	30		N	Unique ID
WPDT_WPHS_ID	NUMBER	30		N	WPDT_WPHS_ID is of WPDT
WPDT_TABLENAME	VARCHAR2	4		N	WPDT_TABLENAME is of WPDT
WPDT_TOFROM	NUMBER	1		N	0 = DATA IS MOVED TOWARD PARTNER HOTEL 1 = DATA IS MOVED FROM PARTNERHOTEL
WPDT_FROMID	NUMBER	30		N	WPDT_FROMID is of WPDT
WPDT_TOID	NUMBER	30		N	WPDT_TOID is of WPDT

## WPER

Homepage Persistent storage

Field Name	Type	Length	Decimals	Not NULL	
WPER_ID	NUMBER	30		N	
WPER_USER_IDENTIFIER	VARCHAR2	300		N	

## WPER

Homepage Persistent storage

Field Name	Type	Length	Decimals	Not NULL
WPER_DATA	CLOB			Y
WPER_TIMESTAMP	DATE			Y
WPER_EXPIRED	DATE			Y

## WPHL

connection to remote schemas table

Field Name	Type	Length	Decimals	Not NULL	
WPHL_ID	NUMBER	30		N	ID
WPHL_WPHS_ID	NUMBER	30		N	linked wphs_id
WPHL_LINK	VARCHAR2	30		N	target schema
HOTEL_ID	NUMBER	30		N	hotel id

## WPHS

Partner Hotels (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WPHS_ID	NUMBER	30		N	Unique ID
WPHS_CODE	VARCHAR2	5		N	WPHS_CODE is of WPHS
WPHS_NAME	VARCHAR2	200		N	WPHS_NAME is of WPHS
WPHS_URL	VARCHAR2	200		Y	WPHS_URL is of WPHS
WPHS_ACTIVE	NUMBER	1		Y	WPHS_ACTIVE is of WPHS
WPHS_USERNAME	VARCHAR2	60		Y	WPHS_USERNAME is of WPHS
WPHS_PASSWORD	VARCHAR2	60		Y	WPHS_PASSWORD is of WPHS
WPHS_ALLOWPROFILELOOKUP	NUMBER	10		Y	WPHS_ALLOWPROFILELOOKUP is of WPHS
WPHS_TRANSLCONFTIME	DATE			Y	IN MASTER IT STORES WHEN TRANSLATION CONFIG WAS CHANGED. IN PARTNERS WE DONT USE IT
WPHS_RESERVATION	NUMBER	1		Y	Allow create remote reservation
WPHS_AVAILABILITY	NUMBER	1		Y	Allow send remote availability request
WPHS_DISPLORDER	NUMBER	3		Y	Display order
WPHS_DBUSER	VARCHAR2	30		Y	Database user name of remote hotels. Used if hotels are hosted in same oracle instance.
WPHS_CONFERENCECDIARY	NUMBER	1		Y	Display in conference diary
WPHS_ALTERNATEURL	VARCHAR2	200		Y	Alternate hotel URL
WPHS_MULTIV8USER	VARCHAR2	30		Y	this is checked against multi hotel wusr passwords. if empty, current logged in user data is used
WPHS_MULTIV8PW	VARCHAR2	30		Y	

### WPHS

Partner Hotels (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WPHS_DBPW	VARCHAR2	50		Y	
WPHS_DBALIAS	VARCHAR2	50		Y	
WPHS_MULTIHOTEL	NUMBER	1		Y	
WPHS_WCOL_ID	NUMBER	30		Y	
WPHS_TASKANDACTIVITY	NUMBER	1		Y	Task and Activity
WPHS_VPDID	VARCHAR2	30		Y	virtual private database id. this value needs to be set for the context variable in oracle to activate security policy that restricts queries to data of that hotel.
WPHS_CRS_ROLE	NUMBER	1		Y	1=central 2=mirror 3=partner 4=direct partner null=no crs functionality
WPHS_CRSPAIRCODE	VARCHAR2	5		Y	
WPHS_MULTIHOTELCONFIG	NUMBER	1		N	
WPHS_SYSTEMTYPE	NUMBER	1		N	0=fidelio pms 1=third party system
WPHS_PROPERTYTYPE	NUMBER	1		N	0=hotel 1=restaurant 2=spa
WPHS_VLOC_ID	NUMBER	30		Y	

### WPJC

Print Job Configuration

Field Name	Type	Length	Decimals	Not NULL	
WPJC_ID	NUMBER	30		N	WPJC_ID identifies WPJC
WPJC_LONGDESC	VARCHAR2	30		N	Print Jobs, like, Confirmation letters, Folio Print, Message Print
WPJC_DISPLORDER	NUMBER	3		Y	WPJC_DISPLORDER is of WPJC
WPJC_WAPP_ID	NUMBER	30		Y	Application which edits / opens the elemnts of this report group section.
WPJC_ADVANCED	NUMBER	1		Y	
WPJC_PRIM_PAGES	NUMBER	1		Y	
WPJC_SEC_PAGES	NUMBER	1		Y	
WPJC_PRIM_FIRST_TO	NUMBER	5		Y	
WPJC_PRIM_FROM_TO	NUMBER	5		Y	
WPJC_PRIM_FROM_TO_END	NUMBER	5		Y	
WPJC_SEC_FIRST_TO	NUMBER	5		Y	
WPJC_SEC_FROM_TO	NUMBER	5		Y	
WPJC_SEC_FROM_TO_END	NUMBER	5		Y	
WPJC_PRIM_COPIES	NUMBER	2		Y	
WPJC_SEC_COPIES	NUMBER	1		Y	

### WPML

Auto profile merge log (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WPML_ID	NUMBER	30		N	Unique ID
WPML_TIMESTAMP	DATE			N	WPML_TIMESTAMP is of WPML
WPML_FROMLOCALTOSEVER	NUMBER	1		N	0 = FROMSERVERTOLOCAL 1 = FROMLOCALTOSEVER
WPML_XCMS_ID	NUMBER	30		N	WPML_XCMS_ID is of WPML
WPML_LOG	LONG			N	WPML_LOG is of WPML
WPML_XCED_ID	NUMBER	30		N	WPML_XCED_ID is of WPML
WPML_PROFILESYNC	NUMBER	1		N	1 = merge performed by profile sync

### WPPP

Printer per PC

Field Name	Type	Length	Decimals	Not NULL	
WPPP_ID	NUMBER	30		N	WPPP_ID identifies WPPP
WPPP_LONGDESC	VARCHAR2	60		N	WPPP_LONGDESC is of WPPP
WPPP_PRINTER	VARCHAR2	120		N	Physical Printer name, joseph calls that driver
WPPP_WPCA_ID	NUMBER	30		N	WPPP_WPCA_ID is of WPPP

### WPSD

Profile Search Setting Details

Field Name	Type	Length	Decimals	Not NULL	
WPSD_ID	NUMBER	30		N	Unique Identifier
WPSD_WPSS_ID	NUMBER	30		N	WPSD_WPSS_ID is of WPSD
WPSD_ROLE	NUMBER	2		N	WPSD_ROLE is of WPSD
WPSD_NAME	VARCHAR2	30		N	WPSD_NAME is of WPSD
WPSD_VALUE	NUMBER	5		N	WPSD_VALUE is of WPSD
WPSD_COMPANY	NUMBER	1		N	

### WPSF

Profile match points for certain values in fields

Field Name	Type	Length	Decimals	Not NULL	
WPSF_ID	NUMBER	30		N	Unique ID
WPSF_WPSS_ID	NUMBER	30		N	Link to WPSS
WPSF_FIELDNAME	VARCHAR2	60		N	Fieldname

### WPSF

Profile match points for certain values in fields

Field Name	Type	Length	Decimals	Not NULL	
WPSF_VALUE	VARCHAR2	200		N	Value
WPSF_SIMILARITYPERCENTAGE	NUMBER	3		N	Percentage of similarity
WPSF_POINT	NUMBER	5		N	Points
WPSF_COMPANY	NUMBER	1		N	

### WPSL

Auto Profile Sync Log (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
WPSL_ID	NUMBER	30		N	WPSL_ID identifies WPSL
WPSL_TIME	DATE			N	WPSL_TIME is of WPSL
WPSL_LOG	LONG			Y	WPSL_LOG is of WPSL

### WPSS

Profile Search Settings

Field Name	Type	Length	Decimals	Not NULL	
WPSS_ID	NUMBER	30		N	Unique Identifier
WPSS_SHORTDESC	VARCHAR2	5		N	Short Description
WPSS_LONGDESC	VARCHAR2	30		N	Long Description
WPSS_TYPE	NUMBER	1		N	0 = local profile match 1 = remote profile match 2 = profile upload 3 = interface
WPSS_COMPANYRULES	NUMBER	1		N	0=All profiles use the same rule set. 1=Companies use separate ruleset

### WPTS

Field Name	Type	Length	Decimals	Not NULL	
WPTS_ID	NUMBER	30		N	
WPTS_TIMESTAMP	DATE			N	
WPTS_GLOBALID	NUMBER	30		Y	
WPTS_REMOTETIMESTAMP	DATE			Y	

### WQAN

ANSWERS

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### WQAN

ANSWERS

Field Name	Type	Length	Decimals	Not NULL	
WQAN_ID	NUMBER	30		N	
WQAN_WQUE_ID	NUMBER	30		N	
WQAN_SHORTDESC	VARCHAR2	60		Y	
WQAN_LONGDESC	VARCHAR2	200		Y	
WQAN_VALUE	NUMBER	10		Y	THE MEASURE OF THE ANSWER
WQAN_DISPLORDER	NUMBER	4		Y	

### WQFD

Activity start time

Field Name	Type	Length	Decimals	Not NULL	
WQFD_ID	NUMBER	30		N	WQFD_ID identifies WFFQ
WQFD_DESCRIPTION	VARCHAR2	100		Y	Description of standard mailing
WQFD_TYPE	NUMBER	1		Y	1=advanced mailing, 0=standard mailing
WQFD_COMP1	VARCHAR2	30		Y	Company from
WQFD_COMP2	VARCHAR2	30		Y	Company to
WQFD_INDI1	VARCHAR2	30		Y	Individual from
WQFD_INDI2	VARCHAR2	30		Y	Individual to
WQFD_ZIPC1	VARCHAR2	30		Y	Zip Code selection from
WQFD_ZIPC2	VARCHAR2	30		Y	Zip Code selection to
WQFD_CITY	VARCHAR2	30		Y	City
WQFD_ACTI_XCMS_ACTIVE	NUMBER	1		Y	1=active, 0=all (inactive and active)
WQFD_NOMA_XCMS_NOMAILING	NUMBER	1		Y	No mailing flag
WQFD_INH1	DATE			Y	WQFD_INH1 is of WQFD
WQFD_INH2	DATE			Y	WQFD_INH2 is of WQFD
WQFD_ARR1	DATE			Y	WQFD_ARR1 is of WQFD
WQFD_ARR2	DATE			Y	WQFD_ARR2 is of WQFD
WQFD_DEP1	DATE			Y	WQFD_DEP1 is of WQFD
WQFD_DEP2	DATE			Y	WQFD_DEP2 is of WQFD
WQFD_NIG1	NUMBER	30		Y	WQFD_NIG1 is of WQFD
WQFD_NIG2	NUMBER	30		Y	WQFD_NIG2 is of WQFD
WQFD_STA1	NUMBER	30		Y	WQFD_STA1 is of WQFD
WQFD_STA2	NUMBER	30		Y	WQFD_STA2 is of WQFD
WQFD_REV1	NUMBER	30	4	Y	WQFD_REV1 is of WQFD

## WQFD

Activity start time

Field Name	Type	Length	Decimals	Not NULL	
WQFD_REV2	NUMBER	30	4	Y	WQFD_REV2 is of WQFD
WQFD_BARR1	DATE			Y	WQFD_BARR1 is of WQFD
WQFD_BARR2	DATE			Y	WQFD_BARR2 is of WQFD
WQFD_BDEP1	DATE			Y	WQFD_BDEP1 is of WQFD
WQFD_BDEP2	DATE			Y	WQFD_BDEP2 is of WQFD
WQFD_CORE1	NUMBER	30		Y	WQFD_CORE1 is of WQFD
WQFD_CORE2	NUMBER	30		Y	WQFD_CORE2 is of WQFD
WQFD_RORE1	NUMBER	30		Y	WQFD_RORE1 is of WQFD
WQFD_RORE2	NUMBER	30		Y	WQFD_RORE2 is of WQFD
WQFD_RETO1	NUMBER	30		Y	WQFD_RETO1 is of WQFD
WQFD_RETO2	NUMBER	30		Y	WQFD_RETO2 is of WQFD
WQFD_SORT	NUMBER	30		Y	WQFD_SORT is of WQFD
WQFD_ASTD1	DATE			Y	WQFD_ASTD1 is of WQFD
WQFD_ASTD2	DATE			Y	Activity start time
WQFD_ACD1	DATE			Y	Activity end time
WQFD_ACD2	DATE			Y	Activity end time
WQFD_BINH1	DATE			Y	Booking inhouse start date
WQFD_BINH2	DATE			Y	Booking inhouse end date
WQFD_RPAY1	NUMBER	30	4	Y	Contain the customer payment limit for query
WQFD_RPAY2	NUMBER	30	4	Y	Contain the customer payment limit for query
WQFD_PCREATED1	DATE			Y	Profile created date
WQFD_PCREATED2	DATE			Y	Profile created date
WQFD_AIND	NUMBER	1		Y	Specify if should display only individuals linked to activity not all linked to a company if the company has activities conditions
WQFD_BIND	NUMBER	1		Y	Specify if should display only individuals linked to booking not all linked to a company if the company has booking conditions
WQFD_FSTA	NUMBER	1		Y	Future stays flag
WQFD_FNIG	NUMBER	1		Y	Future nights flag
WQFD_RIND	NUMBER	1		Y	Only linked to reservation flag
WQFD_ROPT	NUMBER	1		Y	Options for birthdare field 1- inhouse reservations; 2- not inhouse reservations
WQFD_DISPLORDER	NUMBER	3		Y	Display order
WQFD_NOEMAILING	NUMBER	1		Y	Standard mailing no emailing flag

## WQNL

QUESTIONNAIRE FORM LINKTABLE TO QUESTIONS

Field Name	Type	Length	Decimals	Not NULL	
WQNL_ID	NUMBER	30		N	
WQNL_WQNR_ID	NUMBER	30		Y	LINK TO QUESTIONNAIRE FORM
WQNL_WQUE_ID	NUMBER	30		Y	LINK TO QUESTIONS
WQNL_MULTICHOICE	NUMBER	1		Y	USER CAN SELECT MULTIPLE ANSWERS
WQNL_DISPLORDER	NUMBER	4		Y	
WQNL_WQUG_ID	NUMBER	30		Y	
WQNL_GROUPORDER	NUMBER	4		Y	Displayorder of the Question groups
WQNL_COLUMNCOUNT	NUMBER	3		Y	Answer options Column Count

## WQNR

QUESTIONNAIRE FORM

Field Name	Type	Length	Decimals	Not NULL	
WQNR_ID	NUMBER	30		N	
WQNR_SHORTDESC	VARCHAR2	10		Y	
WQNR_LONGDESC	VARCHAR2	60		Y	
WQNR_INACTIVE	NUMBER	1		Y	
WQNR_DISPLORDER	NUMBER	4		Y	
WQNR_WEBINTRODUCTIONTEXT	VARCHAR2	2000		Y	Introduction text as shown on Questionnaire web page
WQNR_COLUMNCOUNT	NUMBER	3		Y	Default Answer options Column Count
WQNR_HOLIDAYCHECK	NUMBER	1		Y	Use this form holidaycheck questionnaire

## WQUE

QUESTIONS

Field Name	Type	Length	Decimals	Not NULL	
WQUE_ID	NUMBER	30		N	
WQUE_QUESTIONTEXT	VARCHAR2	2000		Y	
WQUE_DESCRIPTION	VARCHAR2	2000		Y	
WQUE_INACTIVE	NUMBER	1		Y	
WQUE_DISPLORDER	NUMBER	4		Y	
WQUE_QUESTIONKIND	NUMBER	3		Y	Type Question. 0=Undefined, 1=YesNo, 2=Multiple, 3=Rating
WQUE_ANSWERMAXLENGTH	NUMBER	4		Y	maximum number of characters allowed in answer text

### WQUG

Question Groups

Field Name	Type	Length	Decimals	Not NULL
WQUG_ID	NUMBER	30		N
WQUG_SHORTDESC	VARCHAR2	10		Y
WQUG_LONGDESC	VARCHAR2	30		Y
WQUG_DISPLORDER	NUMBER	3		Y
WQUG_INACTIVE	NUMBER	1		Y

### WRCF

custom fields for internal editor

Field Name	Type	Length	Decimals	Not NULL	
WRCF_ID	NUMBER	30		N	wrcf_id
WRCF_CAPTION	VARCHAR2	64		N	custom field caption
WRCF_CODE	VARCHAR2	4000		N	code template to be inserted into the report
WRCF_HELP	LONG			Y	help for field usage
WRCF_EDIT_BEFORE_INSERT	NUMBER	1		N	is field should be edited before insert

### WRCG

Field Name	Type	Length	Decimals	Not NULL
WRCG_ID	NUMBER	30		N
WRCG_NAME	VARCHAR2	50		N

### WRCT

Field Name	Type	Length	Decimals	Not NULL
WRCT_ID	NUMBER	30		N
WRCT_TASK	NUMBER	3		N
WRCT_WRCG_ID	NUMBER	30		N

### WRDQ

Default queries for Internal Editor reports by report role

Field Name	Type	Length	Decimals	Not NULL	
WRDQ_ID	NUMBER	30		N	Unique ID

### WRDQ

Default queries for Internal Editor reports by report role

Field Name	Type	Length	Decimals	Not NULL	
WRDQ_ROLE	NUMBER	2		N	Report Role
WRDQ_QUERY	LONG			N	QUERY TEXT
WRDQ_ALIAS	VARCHAR2	32		N	ALIAS NAME
WRDQ_RUNORDER	NUMBER	4		N	RUN ORDER

### WRED

Table of related entities and the type of relation. Fields for joining or fields for values

Field Name	Type	Length	Decimals	Not NULL	
WRED_ID	NUMBER	30		N	Unique Id of record
WRED_WVFD_ID1	NUMBER	30		Y	First's view ID
WRED_WFFD_ID1	NUMBER	30		Y	First's field ID
WRED_WVFD_ID2	NUMBER	30		Y	Second view's ID
WRED_WFFD_ID2	NUMBER	30		Y	Second's field Id
WRED_RELATIONTYPE	NUMBER	1		Y	WRED_RELATIONTYPE is of WRED
WRED_TOBEDISPLAY	VARCHAR2	100		Y	WRED_TOBEDISPLAY is of WRED

### WREX

Configuration for report exports

Field Name	Type	Length	Decimals	Not NULL	
WREX_ID	NUMBER	30		N	
WREX_ROLE	NUMBER	3		N	Role of report = wrps_role
WREX_TYPE	NUMBER	1		N	Type of report = wrps_type
WREX_PATH	VARCHAR2	500		N	Path where reports will be saved
WREX_FILENAME	VARCHAR2	30		Y	Filename to which _timestamp will be appended
WREX_FORMAT	NUMBER	2		Y	Export format, this should be correlated with wrps_role
WREX_INACTIVE	NUMBER	1		Y	0 - execute; 1- do not execute

### WRFQ

Relations for the views from query at query level.

Field Name	Type	Length	Decimals	Not NULL	
WRFQ_ID	NUMBER	30		N	Unique identifier
WRFQ_WQFD_ID	NUMBER	30		Y	Identify the query to which is attached this relationships

### WRFQ

Relations for the views from query at query level.

Field Name	Type	Length	Decimals	Not NULL	
WRFQ_WLOF_ID	NUMBER	30		Y	Identifies the list of fields with which is build the relationships
WRFQ_WRED_ID	NUMBER	30		Y	Identify the global relationships between views from database. Wred must be pre-build
WRFQ_TYPE	NUMBER	1		Y	Identify the type of join - inner, outer. Implicit is inner join
WRFQ_WVFD_ID	NUMBER	30		Y	When outer join to which view is refering this outer join
WRFQ_WFFD_ID	NUMBER	30		Y	Field of previous view

### WRPB

binary report storage, this binary report can be linked to multiple WRPT report records. Different Parameter settings can use same binary report different ways.

Field Name	Type	Length	Decimals	Not NULL	
WRPB_ID	NUMBER	30		N	WRPB_ID identifies WRPB
WRPB_LONGDESC	VARCHAR2	120		N	User definable report name, can be different from crystal file name
WRPB_REPORTPATH	VARCHAR2	120		Y	WRPB_REPORTPATH is of WRPB
WRPB_REPORTNAME	VARCHAR2	120		Y	file name of crystal report
WRPB_BINARY	LONG RAW			Y	Binary storage of the report file (rpt)
WRPB_DISPLORDER	NUMBER	6		Y	WRPB_DISPLORDER is of WRPB
WRPB_FILETIMESTAMP	DATE			Y	last modification time of the file
WRPB_FILESIZE	NUMBER	30		Y	WRPB_FILESIZE is of WRPB
WRPB_SUBPATH	VARCHAR2	50		Y	WRPB_SUBPATH is of WRPB
WRPB_REPORTTYPE	NUMBER	1		N	0 - Crystal Binary 1 - RTF 2 - OLAP Cube
WRPB_FEATURE	VARCHAR2	100		Y	Feature for which the report is available for
WRPB_MANUALSETLOCATION	NUMBER	1		Y	No automatic set location on demand when running report every time
WRPB_NONBINARYREPORTID	NUMBER	30		Y	Reference to id for a non binary report. For example custom sql in WSQL

### WRPD

report parameter defaults

Field Name	Type	Length	Decimals	Not NULL	
WRPD_ID	NUMBER	30		N	WRPD_ID identifies WRPD
WRPD_WRPT_ID	NUMBER	30		N	WRPD_WRPT_ID is of WRPD
WRPD_NAME	VARCHAR2	60		N	does not reference to wrpp_id to allow defaults for non configured parameters read directly from the report
WRPD_VALUE	VARCHAR2	3000		Y	WRPD_VALUE is of WRPD
WRPD_INVISIBLE	NUMBER	1		Y	if the parameter is invisible it is passed automatically with default value
WRPD_SHOWSYSTEMPARAM	NUMBER	1		Y	Showing SP- parameters on screen

### WRPE

Police and Tourist Export

Field Name	Type	Length	Decimals	Not NULL	
WRPE_ID	NUMBER	30		N	Unique ID
WRPE_YRES_ID	NUMBER	30		N	Link to YRES
WRPE_XCMS_ID	NUMBER	30		N	Link to XCMS
WRPE_POLICENUMBER	NUMBER	30		Y	Police Number
WRPE_TOURISTNUMBER	NUMBER	30		Y	Tourist Number
WRPE_TIMESTAMP	DATE			N	Timestamp
WRPE_HOTELDATE	DATE			N	Hoteldate
WRPE_CICO	NUMBER	1		N	0 = Check in, 1 = Check out
WRPE_DEPARTURE	DATE			Y	Departure Date

### WRPL

Report Print Log

Field Name	Type	Length	Decimals	Not NULL	
WRPL_ID	NUMBER	30		N	WRPL_ID identifies WRPL
WRPL_PRINTEDTIME	DATE			N	WRPL_PRINTEDTIME is of WRPL
WRPL_XCMS_ID	NUMBER	30		N	WRPL_XCMS_ID is of WRPL
WRPL_WRPT_ID	NUMBER	30		N	WRPL_WRPT_ID is of WRPL
WRPL_PRINTFINISHEDTIME	DATE			Y	

### WRPM

Multiple Reports

Field Name	Type	Length	Decimals	Not NULL	
WRPM_ID	NUMBER	30		N	id
WRPM_WRPT_ID	NUMBER	30		N	linked report
WRPM_PARENT_WRPM_ID	NUMBER	30		N	the parent report record
WRPM_LONGDESC	VARCHAR2	30		Y	longdesc
WRPM_OPEN	NUMBER	1		Y	0=print, 1= show report on screen first
WRPM_ROLE	NUMBER	3		Y	1=confirmation, 2=folio, 3=message

### WRPP

report parameters

Field Name	Type	Length	Decimals	Not NULL	
WRPP_ID	NUMBER	30		N	WRPP_ID identifies WRPP
WRPP_WRPB_ID	NUMBER	30		N	WRPP_WRPB_ID is of WRPP
WRPP_NAME	VARCHAR2	30		N	internal name in the crystal reports file
WRPP_LONGDESC	VARCHAR2	30		N	WRPP_LONGDESC is of WRPP
WRPP_TYPE	NUMBER	1		N	0 = string 1 = integer 2 = date 3 = time 4 = Date type 5 = Combo Box 6 = Multi Select Box 7 = Boolean
WRPP_LOOKUPQUERY	VARCHAR2	2000		Y	WRPP_LOOKUPQUERY is of WRPP
WRPP_LOOKUPIDFIELD	VARCHAR2	60		Y	WRPP_LOOKUPIDFIELD is of WRPP
WRPP_DISPLORDER	NUMBER	8		Y	WRPP_DISPLORDER is of WRPP
WRPP_LOOKUPSHOWFIELD	VARCHAR2	60		Y	WRPP_LOOKUPSHOWFIELD is of WRPP
WRPP_LOOKUPSHOWFIELD2	VARCHAR2	60		Y	WRPP_LOOKUPSHOWFIELD2 is of WRPP
WRPP_MANDATORY	NUMBER	1		Y	It is mandatory to pass value to parameter

### WRPQ

queries by bands for text editor

Field Name	Type	Length	Decimals	Not NULL	
WRPQ_ID	NUMBER	30		N	Primary key
WRPQ_WRPB_ID	NUMBER	30		N	reference to binary report
WRPQ_QUERY	LONG			N	query text
WRPQ_ALIAS	VARCHAR2	32		N	alias name
WRPQ_RUNORDER	NUMBER	4		N	run order

### WRPS

User definable Report Sections

Field Name	Type	Length	Decimals	Not NULL	
WRPS_ID	NUMBER	30		N	WRPS_ID identifies WRPS
WRPS_SHORTDESC	VARCHAR2	3		N	WRPS_SHORTDESC is of WRPS
WRPS_LONGDESC	VARCHAR2	30		N	WRPS_LONGDESC is of WRPS
WRPS_DISPLORDER	NUMBER	3		N	WRPS_DISPLORDER is of WRPS
WRPS_MASTER_WRPS_ID	NUMBER	30		Y	WRPS_MASTER_WRPS_ID is of WRPS
WRPS_TYPE	NUMBER	1		Y	0 = report 1 = text format template 2 = Cube Reports templates 3 = Html templates 4= FastReport templates 5 = Word Merge templates
WRPS_WPJC_ID	NUMBER	30		Y	Default Print Job Section for this report or text template section. Maybe we support later on as well the configuration per WRPT record.

### WRPS

User definable Report Sections

Field Name	Type	Length	Decimals	Not NULL	
WRPS_ROLE	NUMBER	3		Y	1=Confirmation Letter  2=Folio Layout  3=Message Print  4=Shift report  5=Conference Confirmation  6=Registration Card  7=Currency Exchange  8=AR Reminders  9=Paid Outs  10=Activities  11=Deposit Receipts  12=Group Confirmation  13=Special Reports  14=AR Statements  15=Mailing Hitlists  16=CCM Participant Lists  17=AR Compression  18=Petty Cash   19=Profile Letters (Correspondence)   20=ProfileStatistic   21=TableReservation   22=TableReservationList   23=TAP   24=NotaCorrection   25=EmailTemplate   26=RoomKeyLabel   27=Logbook   28=AREgyptianInvoice   29=menucards   30=ar payment receipt   31=Barcode Ticket  ... (stCertificate, stMaintenance)...   34=Payment Receipt
WRPS_SECURITYLEVEL	NUMBER	2		Y	1 = highest 99 = lowest if not filled V8 will automatically fill with 99
WRPS_RPSL_ID	NUMBER	30		Y	Report security level for executing
WRPS_YCAD_ID	NUMBER	30		Y	Link report section to the hotel segment

### WRPT

Reports Table (former Berichte.DBF)

Field Name	Type	Length	Decimals	Not NULL	
WRPT_ID	NUMBER	30		N	WRPT_ID identifies WRPT
WRPT_WRPS_ID	NUMBER	30		N	Link to report section
WRPT_LONGDESC	VARCHAR2	60		N	name
WRPT_WRPB_ID	NUMBER	30		N	WRPT_WRPB_ID is of WRPT
WRPT_DISPLORDER	NUMBER	6		Y	WRPT_DISPLORDER is of WRPT
WRPT_SECURITYLEVEL	NUMBER	2		Y	WRPT_SECURITYLEVEL is of WRPT
WRPT_WPPP_ID	NUMBER	30		Y	Overwrites default printer setting for this single report.
WRPT_COPIES	NUMBER	1		Y	Number of Copies
WRPT_TITLE	VARCHAR2	60		Y	Title to be printed on the report.
WRPT_NA_EXPORT	NUMBER	1		Y	0: none, 1: export and print 2: only export
WRPT_ZINN_ID	NUMBER	30		Y	link to registration card number cycle in zinn
WRPT_SECONDARY_COPIES	NUMBER	1		Y	WRPT_SECONDARY_COPIES is of WRPT
WRPT_WLAN_ID	NUMBER	30		Y	Language for this report, this vlue is overwriting global report language setting
WRPT_CONFIRM_WLAN_ID	NUMBER	1		Y	1 = Report comes up on runtime with language selection 0 = no language dialogue
WRPT_SUFIXNUMBER	NUMBER	1		Y	CCM use this field for reports that are defined to increase the suffix number of the printed reports
WRPT_SAVEREPORT	NUMBER	1		Y	Obsolete
WRPT_REPORTLEVEL	NUMBER	1		Y	ccm use this field to specify that the report belonging to a section can be visible in different parts: ex report from section confirmation are visible for booking level or event level

### WRPT

Reports Table (former Berichte.DBF)

Field Name	Type	Length	Decimals	Not NULL	
WRPT_EXTERNAL_ID	VARCHAR2	10		Y	Third party systems can retrieve reports based on third party ID
WRPT_RPSL_ID	NUMBER	30		Y	Report security level for executing
WRPT_AUTOICS	NUMBER	1		Y	
WRPT_EMAILSENDPREF	NUMBER	1		Y	Email sending preference; 0- attachment(default); 1-body

### WRPX

Report Parameter search type link

Field Name	Type	Length	Decimals	Not NULL	
WRPX_ID	NUMBER	30		N	
WRPX_SEARCHTYPE	NUMBER	1		N	1=Reservation search, 2=Profile search
WRPX_INTERNALCATEGORY	NUMBER	1		Y	in case Profile search the default profile type
WRPX_RESSTATUS	NUMBER	1		Y	in case Reservation search the default Reservation status

### WRTR

Report and HTML Translation Loading all static strings from Reports and HTMLs.

Field Name	Type	Length	Decimals	Not NULL	
WRTR_ID	NUMBER	30		N	Unique Identifier
WRTR_WLAN_ID	NUMBER	30		N	Language Id of this translated String
WRTR_STRING	VARCHAR2	2000		N	String to be translated
WRTR_VALUE	VARCHAR2	2000		Y	Translated String
WRTR_IGNORE	NUMBER	1		Y	Ignored by Translation Studio Filter for not translated strings (no one wants to translate this)

### WRVD

internal editor functions and variables definition

Field Name	Type	Length	Decimals	Not NULL	
WRVD_ID	NUMBER			N	wrvd id
WRVD_WRPB_ID	NUMBER			N	reference to the report
WRVD_FUNCTIONS	CLOB			Y	functions
WRVD_MACROS	CLOB			Y	macros
WRVD_VARIABLES	CLOB			Y	variables

## WRWM

Word Merge components table

Field Name	Type	Length	Decimals	Not NULL	
WRWM_ID	NUMBER	30		N	Id
WRWM_WRPT_ID	NUMBER	30		N	Id of main report
WRWM_PART_WRPT_ID	NUMBER	30		N	
WRWM_FILENAME	VARCHAR2	60		N	Subreport filename, as specified in word merge document
WRWM_EXECUTIONSTEP	NUMBER	3		N	Execution Step

## WRXP

Regular Expression setup

Field Name	Type	Length	Decimals	Not NULL	
WRXP_ID	NUMBER	30		N	Unique ID
WRXP_SHORTDESC	VARCHAR2	3		N	Regular Expression Code
WRXP_LONGDESC	VARCHAR2	30		N	Regular Expression Description
WRXP_REGEXP	VARCHAR2	1000		N	Regular Expression Definition
WRXP_EXAMPLE	VARCHAR2	50		Y	

## WSAL

Server activity log

Field Name	Type	Length	Decimals	Not NULL	
WSAL_ID	NUMBER	30		N	
WSAL_APP	VARCHAR2	30		N	
WSAL_SERVERACTIVITY	VARCHAR2	30		N	
WSAL_TIMESTAMP	DATE			N	
WSAL_COMPLETIONTIMESTAMP	DATE			Y	
WSAL_WPCA_ID	NUMBER	30		Y	
WSAL_XCED_ID	NUMBER	30		Y	
WSAL_FIDELIODATE	DATE			N	
WSAL_AUTOMATIC	NUMBER	1		N	
WSAL_TEXT	VARCHAR2	2000		Y	
WSAL_FULLLOG	CLOB			Y	

### WSCM

modules used by email body template

Field Name	Type	Length	Decimals	Not NULL	
WSCM_ID	NUMBER	30		N	
WSCM_WSCT_ID	NUMBER	30		N	
WSCM_MODULE	NUMBER	2		Y	1=CRM 2=Tasks+Activities 3=PMS 4=CCM 5=A/R 6=Maintenance 7=Table Reservations

### WSCR

Field Name	Type	Length	Decimals	Not NULL	
WSCR_ID	NUMBER	30		N	
WSCR_NAME	VARCHAR2	20		N	
WSCR_SCRIPT	LONG			N	

### WSCT

Simple Custom Text

Field Name	Type	Length	Decimals	Not NULL	
WSCT_ID	NUMBER	30		N	Unique Identifier
WSCT_WLAN_ID	NUMBER	30		N	Language Link
WSCT_ROLE	NUMBER	1		N	1 Folio supplement, 2 Email Body Default, 3 City Ledger invoice supplement
WSCT_TEXT	LONG			Y	Text
WSCT_DEFAULT	NUMBER	1		Y	Default= 1
WSCT_XCED_ID	NUMBER	30		Y	If filled, means that this template is private for the selected user
WSCT_DISPLORDER	NUMBER	4		Y	
WSCT_DESCRIPTION	VARCHAR2	30		Y	

### WSEQ

dummy table to get values from sequences. nobody should modify structure or data

Field Name	Type	Length	Decimals	Not NULL	
WSEQ_DUMMY	CHAR			N	WSEQ_DUMMY identifies WSEQ

### WSES

Holding information about logged in users

Field Name	Type	Length	Decimals	Not NULL	
WSES_ID	NUMBER	30		N	WSES Primary Key

### WSES

Holding information about logged in users

Field Name	Type	Length	Decimals	Not NULL	
WSES_WPCA_ID	NUMBER	30		N	Terminal Name where user have been logged in
WSES_XCED_ID	NUMBER	30		N	ID Of user logged in
WSES_LOGIN_TIME	DATE			N	Login Time
WSES_SID	NUMBER	30		N	Oracle Session ID
WSES_INSTANCEID	NUMBER	3		Y	

### WSET

Swedish E Tax Control Units

Field Name	Type	Length	Decimals	Not NULL	
WSET_ID	NUMBER	30		N	
WSET_NAME	VARCHAR2	60		Y	Unique Name
WSET_SERIALNUMBER	VARCHAR2	20		Y	Control Unit Serial Number
WSET_PORT	NUMBER	1		Y	
WSET_PARITY	NUMBER	1		Y	Parity 0.None, 1.ODD, 2.EVEN
WSET_BAUDRATE	NUMBER	30		Y	Baud Rate
WSET_TYPE	VARCHAR2	1		Y	TYPE A or TYPE B
WSET_TIMEOUT	NUMBER	4		Y	Time out in Seconds
WSET_MINDELAY	NUMBER	4		Y	Maximum Delay (seconds) between two consecutive Bytes
WSET_MAXDELAY	NUMBER	4		Y	
WSET_SWVERSION	VARCHAR2	10		Y	ETax Software version

### WSFH

Scanned Files history

Field Name	Type	Length	Decimals	Not NULL	
WSFH_ID	NUMBER	30		N	
WSFH_DESCRIPTION	VARCHAR2	50		N	
WSFH_DATA	LONG RAW			Y	
WSFH_ISPROCESSED	NUMBER	1		N	
WSFH_CREATEDON	DATE			N	
WSFH_PROCESSEDON	DATE			Y	
WSCH_ATTACHED_XCMS_ID	NUMBER	30		Y	
WSFH_CREATEDBY_XCMS_ID	NUMBER	30		N	

### WSFH

Scanned Files history

Field Name	Type	Length	Decimals	Not NULL	
WSFH_PROCESSEDBY_XCMS_ID	NUMBER	30		Y	
WSFH_FILENAME	VARCHAR2	150		Y	
WSFH_FILENAME2	VARCHAR2	150		Y	
WSFH_FACEFILENAME	VARCHAR2	150		Y	
WSFH_LINKED_YRES_ID	NUMBER	30		Y	
WSFH_LINKED_XCMS_ID	NUMBER	30		Y	
WSFH_XPDG_ID	NUMBER	30		Y	Document type as recognized for later assigning to profile
WSFH_XDEV_ID	NUMBER	30		Y	Link to device that scanned the document

### WSFS

Sales Force Synchronisation Log

Field Name	Type	Length	Decimals	Not NULL	
WSFS_ID	NUMBER	30		N	
WSFS_TABLE_NAME	VARCHAR2	4		N	
WSFS_TABLE_ID	NUMBER	30		N	
WSFS_SYNC_DATE	DATE			Y	
WSFS_SF_ID	VARCHAR2	30		Y	

### WSIG

Signed documents

Field Name	Type	Length	Decimals	Not NULL	
WSIG_ID	NUMBER	30		N	Signed document id
WSIG_YRES_ID	NUMBER	30		Y	Linked reservation id
WSIG_XCMS_ID	NUMBER	30		Y	Linked profile id
WSIG_DOCUMENT	LONG RAW			Y	Body of pdf signed document

### WSKL

Maintenance tasks, skills

Field Name	Type	Length	Decimals	Not NULL	
WSKL_ID	NUMBER	30		N	
WSKL_XCMS_ID	NUMBER	30		N	
WSKL_WATY_ID	NUMBER	30		N	

### WSKL

Maintenance tasks, skills

Field Name	Type	Length	Decimals	Not NULL	
WSKL_DISPLORDER	NUMBER	4		Y	
WSKL_SW_ASSIGN	NUMBER	1		Y	1 = send message when assigned
WSKL_ASN_SMS	NUMBER	1		Y	1 = send sms for assign
WSKL_ASN_EMAIL	NUMBER	1		Y	1 = send email for assing
WSKL_SW_REMOVE	NUMBER	1		Y	1 = send message when removed
WSKL_RMV_SMS	NUMBER	1		Y	1 = send sms for remove
WSKL_RMV_EMAIL	NUMBER	1		Y	1 = send email for remove
WSKL_DML1_SMS	NUMBER	1		Y	1 = send sms for DueMin L1
WSKL_DML1_EMAIL	NUMBER	1		Y	1 = send email for Due Min L1
WSKL_DML2_SMS	NUMBER	1		Y	1 = send sms for DueMin L2
WSKL_DML2_EMAIL	NUMBER	1		Y	1 = send email for Due Min L2
WSKL_RMD_SMS	NUMBER	1		Y	1 = send sms for Reminder Min
WSKL_RMD_EMAIL	NUMBER	1		Y	1 = send email for Reminder Min
WSKL_SKILLED	NUMBER	1		Y	Skilled
WSKL_SW_UPDATE	NUMBER	1		Y	1 = send message when updated
WSKL_UPDT_SMS	NUMBER	1		Y	1 = send sms for update
WSKL_UPDT_EMAIL	NUMBER	1		Y	1 = send email for update
WSKL_SW_NEWTASK	NUMBER	1		Y	1 = send message when added new Task
WSKL_NEW_SMS	NUMBER	1		Y	1 = send sms for new
WSKL_NEW_EMAIL	NUMBER	1		Y	1 = send email for new

### WSMC

System monitor configuration

Field Name	Type	Length	Decimals	Not NULL
WSMC_ID	NUMBER	30		N
WSMC_WPCA_ID	NUMBER	30		N
WSMC_TIMESTAMP	DATE			N
WSMC_CONFIGXML	CLOB			N

### WSML

System monitor log

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

## WSML

System monitor log

Field Name	Type	Length	Decimals	Not NULL
WSML_ID	NUMBER	30		N
WSML_WPCA_ID	NUMBER	30		Y
WSML_TERMINALNAME	VARCHAR2	60		Y
WSML_TIMESTAMP	DATE			N
WSML_TEXT	CLOB			N

## WSOQ

Sort order for fields used in mailing

Field Name	Type	Length	Decimals	Not NULL	
WSOQ_ID	NUMBER	30		N	Unique id
WSOQ_WQFD_ID	NUMBER	30		Y	Link with query id
WSOQ_WFFD_ID	NUMBER	30		Y	Link with field id from database
WSOQ_POSITION	NUMBER	30		Y	Position of field in sort order
WSOQ_SORTTYPE	NUMBER	1		Y	Sort type; ascend or descend
WSOQ_WMISO_ID	NUMBER	30		Y	Link to wizard history

## WSPD

Table to store the results for speed test functionality in webSuite

Field Name	Type	Length	Decimals	Not NULL	
WSPD_ID	NUMBER	30		N	unique id
WSPD_DATE	DATE			Y	Date and time of speed test start
WSPD_DOWNLOAD	VARCHAR2	60		Y	Result of download speed
WSPD_UPLOAD	VARCHAR2	60		Y	Result of upload speed
WSPD_XCED_ID	NUMBER	30		Y	User ID of user who started speed test

## WSPS

Synchronization service database setup

Field Name	Type	Length	Decimals	Not NULL	
WSPS_ID	NUMBER	30		N	Unique ID
WSPS_DESCRIPTION	VARCHAR2	30		Y	DB description
WSPS_SERVICE	VARCHAR2	30		Y	TNS service name
WSPS_USERNAME	VARCHAR2	30		Y	Username

## WSPS

Synchronization service database setup

Field Name	Type	Length	Decimals	Not NULL	
WSPS_PASSWORD	VARCHAR2	30		Y	Password
WSPS_DISABLED	NUMBER	1		Y	
WSPS_VPDID	VARCHAR2	30		Y	

## WSQC

custom sql columns on screen

Field Name	Type	Length	Decimals	Not NULL	
WSQC_ID	NUMBER	30		N	
WSQC_WSQL_ID	NUMBER	30		N	
WSQC_FIELDNAME	VARCHAR2	60		N	
WSQC_SCREENNAME	VARCHAR2	60		N	
WSQC_DISPLORDER	NUMBER	3		N	

## WSQG

CUSTOM SQL STATEMENTS CONFIGURED TO BE RUN BY THE USER. TO RUN MAINTENANCE SQL STATEMENTS LIKE STARTING A PROCEDURE AND SUCH

Field Name	Type	Length	Decimals	Not NULL	
WSQG_ID	NUMBER	30		N	Unique Identifier
WSQG_SHORTDESC	VARCHAR2	5		N	Short description
WSQG_LONGDESC	VARCHAR2	2000		N	Long Description
WSQG_DISPLORDER	NUMBER	3		Y	Display Order

## WSQL

SQL STATEMENT

Field Name	Type	Length	Decimals	Not NULL	
WSQL_ID	NUMBER	30		N	WSQL_ID identifies WSQL
WSQL_SHORTDESC	VARCHAR2	5		N	WSQL_SHORTDESC is of WSQL
WSQL_LONGDESC	VARCHAR2	2000		N	WSQL_LONGDESC is of WSQL
WSQL_DISPLORDER	NUMBER	3		Y	WSQL_DISPLORDER is of WSQL
WSQL_WSQG_ID	NUMBER	30		Y	WSQL_WSQG_ID is of WSQL
WSQL_STATEMENT	LONG			Y	WSQL_STATEMENT is of WSQL
WSQL_HTMLFILE	VARCHAR2	200		Y	
WSQL_HTMLIDFIELD	VARCHAR2	60		Y	

## WSQL

SQL STATEMENT

Field Name	Type	Length	Decimals	Not NULL	
WSQL_ROWLIMIT	NUMBER	30		Y	Rowlimit

## WSQP

SQL STATEMENT PARAMETERS

Field Name	Type	Length	Decimals	Not NULL	
WSQP_ID	NUMBER	30		N	WSQP_ID identifies WSQP
WSQP_SHORTDESC	VARCHAR2	20		N	WSQP_SHORTDESC is of WSQP
WSQP_LONGDESC	VARCHAR2	200		N	WSQP_LONGDESC is of WSQP
WSQP_DISPLORDER	NUMBER	3		Y	WSQP_DISPLORDER is of WSQP
WSQP_TYPE	NUMBER	1		Y	0=STRING 1=INTEGER 2=FLOAT 3=BOOLEAN 4=DATE WILL HAVE TO ADD FUNCTIONALITY IF SELECTION LIST WILL EVER BE NEEDED
WSQP_WSQL_ID	NUMBER	30		Y	WSQP_WSQL_ID is of WSQP
WSQP_DEF_VALUE	VARCHAR2	2000		Y	Used in Mailing Wizard to store the last default value
WSQP_TABLE_NAME	VARCHAR2	4		Y	
WSQP_PARAMFIELD	VARCHAR2	30		Y	
WSQP_SHOWFIELD1	VARCHAR2	30		Y	
WSQP_SHOWFIELD2	VARCHAR2	30		Y	
WSQP_INTERNAL_SQL	VARCHAR2	2000		Y	
WSQP_INCLUDEPARAM	NUMBER	1		Y	1 = Parameter is included, 0 = excluded
WSQP_MULTISELECT	NUMBER	1		N	
WSQP_WMWP_ID	NUMBER	30		Y	Link to the parameters of the mailing that generated the sql with this parameter

## WSTR

Table of WSTR

Field Name	Type	Length	Decimals	Not NULL	
WSTR_ID	NUMBER	30		N	Unique identifier
WSTR_WLAN_ID	NUMBER	30		N	Link to language table
WSTR_STRING	VARCHAR2	2000		N	String to be translated
WSTR_VALUE	VARCHAR2	2000		Y	Translated Text for string
WSTR_IGNORE	NUMBER	1		Y	1 = ignore for translation filters

### WSVQ

Table for storing the multiple selections made for standard query

Field Name	Type	Length	Decimals	Not NULL	
WSVQ_ID	NUMBER	30		N	Id in WSVQ
WSVQ_WQFD_ID	NUMBER	30		Y	Relation with queries from database
WSVQ_TABLE	VARCHAR2	4		Y	Table from wich selection is made
WSVQ_TABLE_ID	NUMBER	30		Y	Id in destination table
WSVQ_TABLE_CAT_ID	NUMBER	30		Y	Additional categories id
WSVQ_COMPANY	NUMBER	1		Y	Value considered for company
WSVQ_INDIVIDUAL	NUMBER	1		Y	Value considered for individual
WSVQ_WWFQ_ID	NUMBER	30		Y	Linked values are linked to advanced mailing detail definition

### WSWC

Swiper Configuration

Field Name	Type	Length	Decimals	Not NULL	
WSWC_ID	NUMBER	30		N	Internal Id
WSWC_LONGDESC	VARCHAR2	30		N	Description of Swiping Configuration
WSWC_DISPLORDER	NUMBER	3		N	Display Order
WSWC_NAME_SEP	VARCHAR2	1		Y	Name Separator
WSWC_ENDOFTRACK_SEP	VARCHAR2	1		Y	End of Track Separator
WSWC_TRACK2START_SEP	VARCHAR2	1		Y	Track 2 Start Separator
WSWC_EXPYDATE_SEP	VARCHAR2	1		Y	Expiry Date Separator
WSWC_COURTESY_SEP	VARCHAR2	1		Y	Courtesy Card Separator
WSWC_SWIPESPEED	NUMBER	4		Y	Swipe Speed in MS

### WSYB

batch operations for user

Field Name	Type	Length	Decimals	Not NULL	
WSYB_ID	NUMBER	30		N	unique identifier
WSYB_WSYF_ID	NUMBER	30		N	link with folder definition
WSYB_DESCRIPTION	VARCHAR2	100		N	user description of batch operation
WSYB_DIRECTION	NUMBER	1		N	direction of sincronization v8 to outlook or outlook to v8

### WSYC

conditions for synchronization folder

Field Name	Type	Length	Decimals	Not NULL	
WSYC_ID	NUMBER	30		N	unique identifier
WSYC_WSYB_ID	NUMBER	30		Y	condition is linked to operation id
WSYC_INTERNAL_ID	NUMBER	3		Y	internal condition id
WSYC_LINK_ID	NUMBER	30		Y	linked id for conditions with multiple values
WSYC_OPERATOR_ID	NUMBER	3		Y	equal, not equal, greater..
WSYC_NUMBER	NUMBER	30	2	Y	number value
WSYC_STRING	VARCHAR2	100		Y	string value
WSYC_DATE	DATE			Y	date value
WSYC_LOGICLINK	NUMBER	1		Y	and / or between conditions

### WSYD

v8 items id that are transposed in outlook without having an id in outlook

Field Name	Type	Length	Decimals	Not NULL	
WSYD_ID	NUMBER	30		N	unique identifier
WSYD_WSYM_ID	NUMBER	30		Y	link to mapped item
WSYD_TABLENAME	VARCHAR2	4		Y	tables from which records are mapped to outlook items: xadr, xcom
WSYD_TABLE_ID	NUMBER	30		Y	id from mapped table
WSYD_DATABASEMODIFICATIONTIME	DATE			Y	database modification time of records
WSYD_SERVERCATEGORY	VARCHAR2	100		Y	mapped server category

### WSYF

synchronization folders

Field Name	Type	Length	Decimals	Not NULL	
WSYF_ID	NUMBER	30		N	unique identifier
WSYF_WPCA_ID	NUMBER	30		N	machine from which synchronization was runned
WSYF_OSUSERNAME	VARCHAR2	60		N	operating system user name which run the synchronization
WSYF_DESCRIPTION	VARCHAR2	100		Y	user description for folder
WSYF_FOLDER_ID	VARCHAR2	200		N	entry id from outlook; unique identifier
WSYF_FOLDER_TYPE	NUMBER	3		Y	folder type 0-contacts; 1-tasks
WSYF_XCMS_ID	NUMBER	30		N	user of v8 application
WSYF_LINKED_WSYF_ID	NUMBER	30		Y	linked folder; ex: notes folder attached to the current one

### WSYM

table which store the corellation between v8 id's and outlook id's

Field Name	Type	Length	Decimals	Not NULL	
WSYM_ID	NUMBER	30		N	unique identifier
WSYM_WSYF_ID	NUMBER	30		Y	link to the folder of item
WSYM_DATABASEID	NUMBER	30		Y	v8 database id; like xcms_id, wact_id
WSYM_OUTLOOKID	VARCHAR2	200		Y	outlook internal id
WSYM_DATABASEMODIFICATIONTIME	DATE			Y	v8 item wmlg time creation or update
WSYM_OUTLOOKMODIFICATIONTIME	DATE			Y	outlook item creation time or update

### WSYT

synchronization table for v8 types like address types, communications types

Field Name	Type	Length	Decimals	Not NULL	
WSYT_ID	NUMBER	30		N	unique identifier
WSYT_APPLICATION_ID	NUMBER	3		N	application id: outlook, etc
WSYT_TABLENAME	VARCHAR2	4		N	table that store the type, xaty, xcmt
WSYT_TABLEID	NUMBER	30		N	type id
WSYT_MAPPEDTO	VARCHAR2	100		N	type in sincronized application to which v8 type is mapped
WSYT_PRIORITY	NUMBER	2		Y	Priority for mapping V8 address types or communication types with Outlook

### WTBC

Telephone Book Categories

Field Name	Type	Length	Decimals	Not NULL	
WTBC_ID	NUMBER	30		N	WTBC_ID identifies WTBC
WTBC_SHORTDESC	VARCHAR2	3		N	WTBC_SHORTDESC is of WTBC
WTBC_LONGDESC	VARCHAR2	30		N	WTBC_LONGDESC is of WTBC
WTBC_DISPLORDER	NUMBER	3		Y	WTBC_DISPLORDER is of WTBC

### WTBE

Telephone Book Entries

Field Name	Type	Length	Decimals	Not NULL	
WTBE_ID	NUMBER	30		N	WTBE_ID identifies WTBE
WTBE_WTBC_ID	NUMBER	30		N	WTBE_WTBC_ID is of WTBE
WTBE_NAME	VARCHAR2	30		N	WTBE_NAME is of WTBE
WTBE_TEXT	LONG			Y	WTBE_TEXT is of WTBE

### WTRL

translation strings

Field Name	Type	Length	Decimals	Not NULL	
WTRL_ID	NUMBER	30		N	WTRL_ID identifies WTRL
WTRL_WLAN_ID	NUMBER	30		N	WTRL_WLAN_ID is of WTRL
WTRL_TABLENAME	CHAR			N	WTRL_TABLENAME is of WTRL
WTRL_TABLEID	NUMBER	30		N	WTRL_TABLEID is of WTRL
WTRL_FIELDNAME	VARCHAR2	30		N	WTRL_FIELDNAME is of WTRL
WTRL_VALUE	VARCHAR2	2000		N	WTRL_VALUE is of WTRL

### WTWN

contains town and code for italian police export

Field Name	Type	Length	Decimals	Not NULL	
WTWN_ID	NUMBER	30		N	wtwn_id identifies wtwn
WTWN_CODE	VARCHAR2	9		N	wtwn_code is the standard police code
WTWN_TOWN	VARCHAR2	40		N	wtwn_town is the name of the town
WTWN_XCOU_ID	NUMBER	30		Y	Link to Country id
WTWN_XSTA_ID	NUMBER	30		Y	Link to State id

### WTXT

Text binary storage

Field Name	Type	Length	Decimals	Not NULL	
WTXT_ID	NUMBER	30		N	WTXT_ID identifies WTXT
WTXT_DATA	LONG RAW			Y	
WTXT_DOCFORMAT	NUMBER	1		Y	0/null - Ms Word Format; 1-Text; 2-Acrobat PDF; 3-HTML; 4-RTF; 5-MHTML; 6-Unknown. Currently used to store any email attachment; 7 - Outlook attachments
WTXT_SIZE	NUMBER	30		Y	Size of the stored data
WTXT_COMPRESSED	NUMBER	1		Y	0/null - Ms Word Format; 1-Text; 2-Acrobat PDF; 3-HTML; 4-RTF; 5-MHTML; 6-Unknown. Currently used to store any email attachment

### WUNO

User Notes

Field Name	Type	Length	Decimals	Not NULL	
WUNO_ID	NUMBER	30		N	
WUNO_NOTES	VARCHAR2	2000		N	

### WUNO

User Notes

Field Name	Type	Length	Decimals	Not NULL
WUNO_XCED_ID	NUMBER	30		N
WUNO_DATE	DATE			Y

### WURS

Table for user right listing

Field Name	Type	Length	Decimals	Not NULL	
WURS_DBNAME	VARCHAR2	200		N	Unique ID
WURS_DESC	VARCHAR2	200		N	Description
WURS_1	VARCHAR2	200		Y	WURS_1 is of WURS
WURS_2	VARCHAR2	200		Y	WURS_2 is of WURS
WURS_3	VARCHAR2	200		Y	WURS_3 is of WURS
WURS_4	VARCHAR2	200		Y	WURS_4 is of WURS
WURS_5	VARCHAR2	200		Y	WURS_5 is of WURS
WURS_6	VARCHAR2	200		Y	WURS_6 is of WURS
WURS_7	VARCHAR2	200		Y	WURS_7 is of WURS
WURS_8	VARCHAR2	200		Y	WURS_8 is of WURS
WURS_9	VARCHAR2	200		Y	WURS_9 is of WURS

### WUSR

User Right Configuration

Field Name	Type	Length	Decimals	Not NULL	
WUSR_ID	NUMBER	30		N	WUSR_ID identifies WUSR
WUSR_XCMS_ID	NUMBER	30		Y	WUSR_XCMS_ID is of WUSR
WUSR_WEGR_ID	NUMBER	30		Y	WUSR_WEGR_ID is of WUSR
WUSR_NAME	VARCHAR2	200		N	WUSR_NAME is of WUSR
WUSR_VALUE	NUMBER	1		N	WUSR_VALUE is of WUSR

### WUSS

user settings

Field Name	Type	Length	Decimals	Not NULL	
WUSS_ID	NUMBER	30		N	WUSS_ID identifies WUSS
WUSS_XCMS_ID	NUMBER	30		N	WUSS_XCMS_ID is of WUSS

### WUSS

user settings

Field Name	Type	Length	Decimals	Not NULL	
WUSS_NAME	VARCHAR2	200		N	WUSS_NAME is of WUSS
WUSS_VALUE	VARCHAR2	60		Y	WUSS_VALUE is of WUSS

### WVAR

system wide variables

Field Name	Type	Length	Decimals	Not NULL	
WVAR_ID	NUMBER	30		N	WVAR_ID identifies WVAR
WVAR_NAME	VARCHAR2	30		N	WVAR_NAME is of WVAR
WVAR_FORMULA	LONG			N	WVAR_FORMULA is of WVAR

### WVFD

Views and Tables from Database for Mailing (setup)

Field Name	Type	Length	Decimals	Not NULL	
WVFD_ID	NUMBER	30		N	Unique internal ID
WVFD_VIEWNAME	VARCHAR2	100		Y	Name of view
WVFD_DESCRIPTION	VARCHAR2	100		Y	Description of view
WVFD_OBJECT_TYPE	VARCHAR2	10		Y	Object type (view, table)
WVFD_TYPE_ID	NUMBER	1		Y	1=Customer information   2=Customer Addresses   3=Activities   4= Booking   5= Reservation
WVFD_SYSTEM	NUMBER	1		Y	1 = V8 system view

### WVFF

Pre-defined field values (setup)

Field Name	Type	Length	Decimals	Not NULL	
WVFF_ID	NUMBER	30		N	Unique internal ID
WVFF_WFFD_ID	NUMBER	30		Y	ID of linked field
WVFF_PREDEFVALUE	VARCHAR2	100		Y	Pre-defined values of field
WVFF_DESCRIPTION	VARCHAR2	100		Y	Description of pre-defined values

### WVNM

Virtual Numbers

Field Name	Type	Length	Decimals	Not NULL	
WVNM_ID	NUMBER	30		N	Unique ID

## WVNM

Virtual Numbers

Field Name	Type	Length	Decimals	Not NULL	
WVNM_WVNP_ID	NUMBER	30		N	Link to WVNP
WVNM_NUMBER	VARCHAR2	10		N	number
WVNM_YRMS_ID	NUMBER	30		Y	Last room assigned to
WVNM_XCMS_ID	NUMBER	30		Y	last guest assigned to
WVNM_YRES_ID	NUMBER	30		Y	last resevation assigned to
WVNM_LAST_USED	DATE			Y	last used on
WVNM_STATISTICS	NUMBER	4		Y	WVNM_STATISTICS is of WVNM
WVNM_INACTIVE	NUMBER	1		Y	1 = inactive
WVNM_ASSIGN_DATE	DATE			Y	Assigned on
WVNM_XCED_ID	NUMBER	30		Y	Hotel User , who assigned the number
WVNM_PIN	VARCHAR2	10		Y	pin
WVNM_PERMANENT	NUMBER	1		Y	Paramanent Assignment
WVNM_INUSE	NUMBER	1		Y	WVNM_INUSE is of WVNM
WVNM_ZFAC_ID	NUMBER	30		Y	zfac id
WVNM_WSNAME	VARCHAR2	60		Y	Workstation name
WVNM_IFC_COMMENT	VARCHAR2	100		Y	Comments by IFC
WVNM_EXT_NUM	VARCHAR2	20		Y	WVNM_EXT_NUM is of WVNM
WVNM_IFC_STATUS	VARCHAR2	2		Y	current status in IFC
WVNM_PERMANENT_XCMS_ID	NUMBER	30		Y	Xcms_id , if this number is this is blocked by this XCMS permanently
WVNM_LAST_IFC_ACTION_TYPE	VARCHAR2	1		Y	WVNM_LAST_IFC_ACTION_TYPE is of WVNM
WVNM_ZFAN_ID	NUMBER	30		Y	WVNM_ZFAN_ID is of WVNM

## WVNP

Virtual Number pools

Field Name	Type	Length	Decimals	Not NULL	
WVNP_ID	NUMBER	30		N	Unique ID
WVNP_POOL_ID	NUMBER	2		N	Pool identification Number
WVNP_POOL_TYPE	VARCHAR2	1		Y	Pool type R. Room based G. GuestBased
WVNP_ASSIGNMENT_TYPE	NUMBER	1		Y	assignment type 1.Do not assign, 2.Automatic assign 3. prompt to assign
WVNP_DESCRIPTION	VARCHAR2	50		Y	Description
WVNP_REQUIRED	NUMBER	1		Y	Mandatory flag
WVNP_INACTIVE	NUMBER	1		Y	Inactive flag
WVNP_ICFG_ID	NUMBER	30		Y	Link to IFC setup table

### WVNP

Virtual Number pools

Field Name	Type	Length	Decimals	Not NULL	
WVNP_PIN_REQUIRED	NUMBER	1		Y	1. if the pool required guest PIN
WVNP_ALLOW_PERMANENT	NUMBER	1		Y	0. Do not allow / 1. Allow Permanent Assignments
WVNP_PRIORITY_ORDER	NUMBER	1		Y	Alcatel Priority order

### WWFQ

Clauses for query (where)

Field Name	Type	Length	Decimals	Not NULL	
WWFQ_ID	NUMBER	30		N	WWFQ_ID identifies WWFQ
WWFQ_WQFD_ID	NUMBER	30		N	WWFQ_WQFD_ID is of WWFQ
WWFQ_BS	VARCHAR2	10		Y	WWFQ_BS is of WWFQ
WWFQ_WFFD_ID	NUMBER	30		Y	WWFQ_WFFD_ID is of WWFQ
WWFQ_OPERATOR	VARCHAR2	30		Y	WWFQ_OPERATOR is of WWFQ
WWFQ_VALUE	VARCHAR2	300		Y	WWFQ_VALUE is of WWFQ
WWFQ_BF	VARCHAR2	10		Y	WWFQ_BF is of WWFQ
WWFQ_OPERAND	VARCHAR2	10		Y	WWFQ_OPERAND is of WWFQ
WWFQ_WVFD_ID	NUMBER	30		Y	WWFQ_WVFD_ID is of WWFQ
WWFQ_COMPANY	NUMBER	1		Y	0-condition not applicable to companies; 1-company have the condition
WWFQ_INDIVIDUAL	NUMBER	1		Y	0-condition not applicable to individuals; 1-individuals have the condition
WWFQ_XPAC_ID	NUMBER	30		Y	Link with Attribute Categories
WWFQ_OPERATOR_ID	NUMBER	2		Y	Internal Id for operators
WWFQ_LOPERATOR_ID	NUMBER	1		Y	Internal Id for logic operators
WWFQ_VALUE2	VARCHAR2	300		Y	Interval value for operator [between]

### WWSC

Suite 8 Homepage "Web Selling Categories"

Field Name	Type	Length	Decimals	Not NULL	
WWSC_ID	NUMBER	30		N	
WWSC_SHORTDESC	VARCHAR2	3		N	
WWSC_LONGDESC	VARCHAR2	30		N	
WWSC_START	DATE			Y	
WWSC_DEF_NIGHTS	NUMBER	2		Y	
WWSC_MIN_NIGHTS	NUMBER	2		Y	

### WWSC

Suite 8 Homepage "Web Selling Categories"

Field Name	Type	Length	Decimals	Not NULL	
WWSC_ROLE	NUMBER	1		N	1 = Room only, 2 = Arrangement, 3 = Last Minute
WWSC_DISPLORDER	NUMBER	4		Y	
WWSC_INACTIVE	NUMBER	1		Y	

### WWSP

Suite 8 Homepage "Web Selling Categories" link to packages

Field Name	Type	Length	Decimals	Not NULL	
WWSP_ID	NUMBER	30		N	
WWSP_WWSC_ID	NUMBER	30		N	
WWSP_YPAC_ID	NUMBER	30		N	

### WWSR

Suite 8 Homepage "Web Selling Categories" link to rate codes

Field Name	Type	Length	Decimals	Not NULL	
WWSR_ID	NUMBER	30		N	
WWSR_WWSC_ID	NUMBER	30		N	
WWSR_YRCH_ID	NUMBER	30		N	

### WZIP

Contains Zip, Towns Name and Country - Link

Field Name	Type	Length	Decimals	Not NULL	
WZIP_ID	NUMBER	30		N	WZIP_ID identifies WZIP
WZIP_XCOU_ID	NUMBER	30		N	WZIP_XCOU_ID is of WZIP
WZIP_ZIP	VARCHAR2	10		N	WZIP_ZIP is of WZIP
WZIP_TOWN	VARCHAR2	60		N	WZIP_TOWN is of WZIP
WZIP_XSST_ID	NUMBER	30		Y	

### XAAL

Linked Attributes to Addresses Table

Field Name	Type	Length	Decimals	Not NULL	
XAAL_ID	NUMBER	30		N	Id of xaal
XAAL_XADR_ID	NUMBER	30		N	Address id

### XAAL

Linked Attributes to Addresses Table

Field Name	Type	Length	Decimals	Not NULL	
XAAL_XPDA_ID	NUMBER	30		N	Attribute value id
XAAL_XPAC_ID	NUMBER	30		N	Linked Attribute Category Id

### XADR

Address

Field Name	Type	Length	Decimals	Not NULL	
XADR_ID	NUMBER	30		N	Unique internal ID
XADR_XATY_ID	NUMBER	30		N	Link to address type
XADR_PRIMARY	NUMBER	1		Y	Defines if address is primary address(1) or not(0)
XADR_ZIP	VARCHAR2	15		Y	Zip code
XADR_STREET1	VARCHAR2	60		Y	Street 1
XADR_STREET2	VARCHAR2	60		Y	Street 2
XADR_STREET3	VARCHAR2	60		Y	Street 3
XADR_CITY	VARCHAR2	60		Y	City
XADR_XCOU_ID	NUMBER	30		Y	Link to country table
XADR_XCMS_ID	NUMBER	30		N	Link to customer table
XADR_XSTA_ID	NUMBER	30		Y	Link to state table
XADR_GLOBALID	NUMBER	30		Y	In Partner Hotels used to store XADR_ID of the Master (Hotel Connector)
XADR_VERIFIED	NUMBER	1		Y	1 - if this address was verified by address doctor
XADR_WTWN_ID	NUMBER	30		Y	
XADR_FIDCRSID	VARCHAR2	20		Y	

### XAIL

Airlines

Field Name	Type	Length	Decimals	Not NULL	
XAIL_ID	NUMBER	30		N	internal id
XAIL_SHORTDESC	VARCHAR2	5		N	Airlines ShortCode like LH etc.
XAIL_LONGDESC	VARCHAR2	60		N	name of the airline
XAIL_DEFAULT_WGPT_ID	NUMBER	30		Y	default pickup type

### XATY

Address Types

Field Name	Type	Length	Decimals	Not NULL	
XATY_ID	NUMBER	30		N	Unique internal ID
XATY_SHORTDESC	VARCHAR2	3		N	Address Type short description
XATY_LONGDESC	VARCHAR2	30		N	Address type long description
XATY_DISPLORDER	NUMBER	3		Y	Display of address types
XATY_ROLE	NUMBER	1		Y	1 = Billing Address 2 = Mailing Address
XATY_INACTIVE	NUMBER	1		Y	0=active, 1= inactive

### XBIL

customer billing instruction link

Field Name	Type	Length	Decimals	Not NULL	
XBIL_ID	NUMBER	30		N	Unique internal ID
XBIL_XCMS_ID	NUMBER	30		N	Link to customer
XBIL_ZDCO_ID	NUMBER	30		Y	Link to department(1) or to billing instruction(0)
XBIL_ZBIC_ID	NUMBER	30		Y	link to billing instruction code or to revenue department code
XBIL_TYPE	NUMBER	1		N	1 = include, 2 = exclude

### XCAC

Child Age Category

Field Name	Type	Length	Decimals	Not NULL	
XCAC_ID	NUMBER	30		N	XCAC_ID identifies XCAC
XCAC_SHORTDESC	VARCHAR2	3		N	XCAC_SHORTDESC is of XCAC
XCAC_LONGDESC	VARCHAR2	30		N	XCAC_LONGDESC is of XCAC
XCAC_FROMAGE	NUMBER	3		N	XCAC_FROMAGE is of XCAC
XCAC_TOAGE	NUMBER	3		N	XCAC_TOAGE is of XCAC
XCAC_DISPLORDER	NUMBER	3		Y	XCAC_DISPLORDER is of XCAC
XCAC_TAXFREE	NUMBER	1		Y	used for swiss to identify childs which do not pay 'Kurtaxe', former rkz6
XCAC_INACTIVE	NUMBER	1		Y	XCAC_INACTIVE is of XCAC
XCAC_COUNTINMEALPLAN	NUMBER	1		Y	1 = this child age is counted in mealplan
XCAC_DOMESTIC	NUMBER	1		Y	1 = Domestic Children ( in Switzerland are somehow two different kind of children)
XCAC_FREEOFCHARGE	NUMBER	1		Y	1 = this child age category is free of charge (no rate defined) - will be used for specific statistics/forecasts
XCAC_REPORT_GROUP	NUMBER	1		Y	Field is used to sum up categories in Reports, possible values are 1, 2 or 3
XCAC_WEBENABLED	NUMBER	1		Y	Is available for WEB Booking engine

### XCAC

Child Age Category

Field Name	Type	Length	Decimals	Not NULL	
XCAC_XGCA_ID	NUMBER	30		N	childage category group
XCAC_COUNTFOROCCUPANCY	NUMBER	1		Y	1=count as adult for occupancy when checking maximum number of perosns of room and roomtype

### XCAG

customer address greeting predefined helper (mr, mrs,prof etc) this table helps to fill a freely entered text field in xcms (or one of its detail tables)

Field Name	Type	Length	Decimals	Not NULL	
XCAG_ID	NUMBER	30		N	Unique internal ID
XCAG_SHORTDESC	VARCHAR2	2		Y	Short description for address greetings
XCAG_LONGDESC	VARCHAR2	30		N	Long description for address greetings
XCAG_GREETCAT	NUMBER	1		N	Greeting category 0 = address 1 = letter
XCAG_DISPLORDER	NUMBER	3		Y	Display order of customer address greetings
XCAG_WLAN_ID	NUMBER	30		N	Indicates for which language this greeting is used
XCAG_TRANSLATION_ID	NUMBER	30		Y	Facility to link from greetings to other languages, as for instance from Mr. (emglish) to Herr (german)
XCAG_GREETING_ID	NUMBER	30		Y	Links corresponding address and letter greetings together, as for instance: Mr. and Dear Mr. will have the same ID and if Mr. is selected and letter greeting is empty we will automatically fill letter greeting with the linked string
XCAG_SEX	NUMBER	1		Y	Male (1) Female (2) Unknown (3)
XCAG_FAMILY	NUMBER	1		Y	1= Family Greeting

### XCAP

credit card approvals

Field Name	Type	Length	Decimals	Not NULL	
XCAP_ID	NUMBER	30		N	XCAP_ID identifies XCAP
XCAP_XCCS_ID	NUMBER	30		Y	link to credit card
XCAP_CODE	VARCHAR2	30		Y	APPROVAL Code
XCAP_AMOUNT	NUMBER	30	4	N	XCAP_AMOUNT is of XCAP
XCAP_TIME	DATE			Y	Time stamp of the Approval Transaction
XCAP_TRANSID	VARCHAR2	30		Y	Transaction ID of EFT system. (Approval Code is more bank related)
XCAP_ACTUAL	NUMBER	1		Y	1 = This approval is actual 0 = This approval is obsolete, might be due to new approval for higher approval amount. Additional Approvals are handled by IFC (IAPP)should we really do? we can calculate the newest approval, TF
XCAP_YRES_ID	NUMBER	30		Y	Link to Reservation
XCAP_ZWIN_ID	NUMBER	30		Y	Link to ZWIN

## XCAP

credit card approvals

Field Name	Type	Length	Decimals	Not NULL	
XCAP_YRCL_ID	NUMBER	30		Y	Link to Reservation - Creditcard Link table
XCAP_ROLE	NUMBER	1		Y	0 = Authorization 1 = Settlement
XCAP_ZFAC_ID	NUMBER	30		Y	Link to Financial Account
XCAP_CRYPTOGAM	VARCHAR2	1000		Y	Cryptogram Information for chip cards
XCAP_VALIDUNTIL	DATE			Y	The Validity End date
XCAP_AUDIT_TRAILNUM	VARCHAR2	15		Y	
XCAP_CURRENCY	VARCHAR2	6		Y	
XCAP_ZCUC_ID	NUMBER	30		Y	
XCAP_AUTH_TYPE	NUMBER	1		Y	0. Authorization done via EFT 1. Manual Authorization done via Telephone
XCAP_INSTALLMENTS	NUMBER	2		Y	Credit card payment installments

## XCBS

Table to store the CC Batch Settlement records

Field Name	Type	Length	Decimals	Not NULL	
XCBS_ID	NUMBER	30		N	unique code
XCBS_XCCS_ID	NUMBER	30		N	link to xccs
XCBS_YRCL_ID	NUMBER	30		Y	link to yrcl
XCBS_YRES_ID	NUMBER	30		Y	link to yres
XCBS_ZFAC_ID	NUMBER	30		Y	link to zfac
XCBS_ZWIN_ID	NUMBER	30		Y	link to zwin
XCBS_XCMS_ID	NUMBER	30		Y	link to xcms
XCBS_DATE	DATE			N	folio/transaction date
XCBS_POST_DATE	DATE			N	entry date timestamp
XCBS_AMOUNT	NUMBER	30	4	N	amount to be settled
XCBS_APPR_CODE	VARCHAR2	30		Y	approval code
XCBS_XCAP_ID	NUMBER	30		Y	link settlement xcap record
XCBS_ZBAT_ID	NUMBER	30		Y	link to zbat
XCBS_FLAG	NUMBER	1		Y	0/null not processed, 1 - successful, 2- failed
XCBS_REMARKS	VARCHAR2	100		Y	remarks/reason for the failure

### XCCA

Customer Categories

Field Name	Type	Length	Decimals	Not NULL	
XCCA_ID	NUMBER	30		N	Unique internal ID
XCCA_INTERNALCATEGORY	NUMBER	2		N	internal category that defines the role of the new category to be able to handle differently by hardcoded business logic 1=Company 2=Travel Agent 3=Source 4=Individual 5=Vendors 6=Meeting Planner
XCCA_SHORTDESC	VARCHAR2	3		N	Short description for customer categories
XCCA_LONGDESC	VARCHAR2	30		N	Long description for customer categories
XCCA_XCMSTYPE	NUMBER	1		N	Defines if customer category applies to companies or individuals
XCCA_DISPLORDER	NUMBER	3		Y	Display order of customer categories
XCCA_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XCCA_TO_INVOICE	NUMBER	1		Y	1 = Available on Tour Operator Invoice Selection

### XCCD

Customer Company Details

Field Name	Type	Length	Decimals	Not NULL	
XCCD_ID	NUMBER	30		N	Unique Internal ID
XCCD_DIVISION	VARCHAR2	30		Y	Division
XCCD_PRIMSLSOFF	VARCHAR2	30		Y	Primary Sales Office
XCCD_EMPNUM	NUMBER	5		Y	Number of employees
XCCD_TAP_ZCUR_ID	NUMBER	30		Y	Travel Agent Commission Currency
XCCD_TCOD_ID	NUMBER	30		Y	Commission Code Link for Travel Agents and Sources

### XCCL

customer customer link

Field Name	Type	Length	Decimals	Not NULL	
XCCL_ID	NUMBER	30		N	Unique internal ID
XCCL_FROM_XCMS_ID	NUMBER	30		N	customer to whom the other is linked
XCCL_TO_XCMS_ID	NUMBER	30		N	the linked customer

### XCCM

Field Name	Type	Length	Decimals	Not NULL	
XCCM_ID	NUMBER	30		N	
XCCM_XCMS_ID	NUMBER	30		N	

## XCCM

Field Name	Type	Length	Decimals	Not NULL
XCCM_ACTIVE	NUMBER	1		N
XCCM_DATE	DATE			N

## XCCS

Credit cards with link to Guest Profiles.

Field Name	Type	Length	Decimals	Not NULL	
XCCS_ID	NUMBER	30		N	Unique internal ID
XCCS_ZCCA_ID	NUMBER	30		N	Link to credit card type in ZCCA
XCCS_NUMBER	VARCHAR2	60		N	Credit card number
XCCS_EXPIRYDATE	DATE			N	Credit card expiry date
XCCS_XCMS_ID	NUMBER	30		Y	Link to customer
XCCS_HOLDERNAME	VARCHAR2	30		Y	The cardholder name as it appears on the credit/debit card. This name could differ from Fidelio Guest Name.
XCCS_ORDER	NUMBER	10		Y	Order of Credit Cards per Guest.
XCCS_ISSUE_NUMBER	VARCHAR2	2		Y	Issue number as entered by the user
XCCS_ISSUE_DATE	VARCHAR2	6		Y	Issue date as entered by the user, stored in YYYYMM format
XCCS_EFT_USAGEVALUE	NUMBER	2		Y	
XCCS_FIDCRSID	VARCHAR2	60		Y	
XCCS_CARD_ID	VARCHAR2	100		Y	CC token used by Best Western
XCCS_CARD_ID_TYPE	NUMBER	1		Y	Source of Token 1 = local interface, 2 = CRS

## XCEA

Sales Manager Activity Goals

Field Name	Type	Length	Decimals	Not NULL	
XCEA_ID	NUMBER	30		N	Unique ID
XCEA_XCED_ID	NUMBER	30		N	Link to Sales Manager
XCEA_WATY_ID	NUMBER	30		N	Link to Activity Type
XCEA_STARTDATE	DATE			Y	Goal Start Date
XCEA_ENDDATE	DATE			Y	Goal End Date
XCEA_GOAL	NUMBER	30	4	Y	Goal
XCEA_UNCOMPLETED	NUMBER	5		Y	Uncompleted
XCEA_COMPLETED	NUMBER	5		Y	Completed

## XCED

employee details (detail of xcms)

Field Name	Type	Length	Decimals	Not NULL	
XCED_ID	NUMBER	30		N	Unique internal ID
XCED_INITIALS	VARCHAR2	3		N	Employee initials, as for instance 'BB'
XCED_WEGR_ID	NUMBER	30		N	Link to employee group
XCED_TITLE	VARCHAR2	60		Y	Title of employee, job description
XCED_LANGID	NUMBER	30		N	XCED_LANGID partly identifies XCED
XCED_CITY	VARCHAR2	30		Y	City where the employee (manager) is based
XCED_LOGINNAME	VARCHAR2	30		Y	login name for employee
XCED_PASSWORD	VARCHAR2	30		Y	Encrypted password of the employee.
XCED_VALIDFROM	DATE			N	Date login name is valid from
XCED_EXPIRY	DATE			Y	XCED_EXPIRY is the expiry date of the valid employee account. Also used if a employee is terminated to stop access to employee account.
XCED_EMPLOYEEENR	VARCHAR2	30		Y	Hotel internal employee number
XCED_MAXSESSIONS	NUMBER	3		Y	number of sessions that are allowed for user
XCED_LASTLOGIN	DATE			Y	tracks date and time user has last logged in
XCED_SEX	NUMBER	1		Y	Male(1) Female(2) Unknown (3)
XCED_HIRED	DATE			Y	date when employee was hired
XCED_BIRTHTIME	DATE			Y	Birthday
XCED_FULLTIME	NUMBER	1		Y	1 = Full time 2 = Part time
XCED_STATUS	NUMBER	1		Y	XCED_STATUS is 1 = active 2 = inactive (date selection for inactive period optional) 3 = terminated (XCED_TERMINATEDATE defaulting to system date)
XCED_INACTIVEFROM	DATE			Y	Start date for the time period employee is inactive
XCED_INACTIVETO	DATE			Y	End date of period where employee is inactive
XCED_INACTIVEREASON	VARCHAR2	60		Y	Inactive reason
XCED_TERMINATEDATE	DATE			Y	Date of termination
XCED_TERMINATEREASON	LONG			Y	If xcms_active = 3 the reason for the termination of the employee must be entered here.
XCED_REHIRE	NUMBER	1		Y	1 = can be rehired again 2 = can not be rehired again
XCED_WHDE_ID	NUMBER	30		Y	Link to Hotel Departments, like FO, Sales Department or Kitchen.
XCED_PW_EXPIREDAYS	NUMBER	3		Y	XCED_PW_EXPIREDAYS is of XCED
XCED_PW_LASTCHANGED	DATE			Y	XCED_PW_LASTCHANGED is of XCED
XCED_ZCAS_ID	NUMBER	30		Y	The Link to the Cashier number if the system is set up to have Cashiers per User.
XCED_TRACEFREQ	NUMBER	2		Y	number of weeks in which activities should be automatically created (trace frequency)
XCED_SALESMGR	NUMBER	1		Y	0 = No 1 = Yes
XCED_FORCE_PW_CHANGE	NUMBER	1		Y	1 if user must change the password on next login
XCED_BADLOGIN	NUMBER	5		Y	amount of unsuccessful login trial

### XCED

employee details (detail of xcms)

Field Name	Type	Length	Decimals	Not NULL	
XCED_LEISUREUSERNAME	VARCHAR2	30		Y	username to login to leisure system
XCED_LEISUREPASSWORD	VARCHAR2	30		Y	
XCED_LEISURELANG	NUMBER	1		Y	
XCED_RPSL_ID	NUMBER	30		Y	User permission LLevel for report executing
XCED_TICKETCREATIONLEVEL	NUMBER	3		Y	Ticket Creation Level, will be compared to the ticket's level on creating a new transponder
XCED_IFONLY	NUMBER	1		Y	Not allowed to login to Suite8
XCED_TRANSPORTATION	NUMBER	1		Y	Responsible for Transportation
XCED_SALESFORCE_ID	VARCHAR2	30		Y	mapped userid from salesforce
XCED_ADSLOGINNAME	VARCHAR2	30		Y	active directory login name
XCED_IGNORE_NA_CHECK	NUMBER	1		Y	1. Ignore from Night audit expiry check routine
XCED_MOD	NUMBER	1		Y	Manager on Duty
XCED_CENTRAL	NUMBER	1		N	0=normal user 1=central user
XCED_INCENTIVECODE	VARCHAR2	5		Y	User incentive code
XCED_WAITER_ID	CHAR			Y	

### XCEE

default email bodies per user / role

Field Name	Type	Length	Decimals	Not NULL	
XCEE_ID	NUMBER	30		N	
XCEE_XCED_ID	NUMBER	30		N	
XCEE_WSCT_ID	NUMBER	30		N	
XCEE_WLAN_ID	NUMBER	30		N	
XCEE_MODULE	NUMBER	2		Y	See description of wscm_module

### XCEG

Sales Manager Revenue Goals

Field Name	Type	Length	Decimals	Not NULL	
XCEG_ID	NUMBER	30		N	Unique ID
XCEG_XCED_ID	NUMBER	30		N	Link to Sales Manager
XCEG_ZDCO_ID	NUMBER	30		N	Link to Department Code
XCEG_STARTDATE	DATE			Y	Goal Start Date
XCEG_ENDDATE	DATE			Y	Goal End Date

### XCEG

Sales Manager Revenue Goals

Field Name	Type	Length	Decimals	Not NULL	
XCEG_GOAL	NUMBER	30	4	N	Goal
XCEG_FORECAST	NUMBER	30	4	Y	Forecast
XCEG_REVENUE	NUMBER	30	4	Y	Revenue
XCEG_GOAL_NOOFNIGHTS	NUMBER	5		Y	Goal No. of nights
XCEG_FC_NOOFNIGHTS	NUMBER	5		Y	Forecast No. of nights
XCEG_NOOFNIGHTS	NUMBER	5		Y	Actual No. of Nights

### XCES

email signatures per user

Field Name	Type	Length	Decimals	Not NULL	
XCES_ID	NUMBER	30		N	
XCES_XCED_ID	NUMBER	30		N	
XCES_SIGNATURE	LONG			Y	

### XCHD

Hotel Data

Field Name	Type	Length	Decimals	Not NULL	
XCHD_ID	NUMBER	30		N	Unique internal ID
XCHD_TOTROOMS	NUMBER	4		Y	Total number of rooms

### XCHS

Hotel connector. Profile subscription per hotel

Field Name	Type	Length	Decimals	Not NULL	
XCHS_ID	NUMBER	30		N	
XCHS_XCMS_ID	NUMBER	30		N	
XCHS_WPHS_ID	NUMBER	30		N	
XCHS_INSERT_DATE	DATE			Y	
XCHS_LASTUPDATE_DATE	DATE			Y	

### XCID

Customer Individual Details

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### XCID

Customer Individual Details

Field Name	Type	Length	Decimals	Not NULL	
XCID_ID	NUMBER	30		N	Unique internal ID
XCID_MAILNAME	VARCHAR2	30		Y	Name used in mailings (Jimmy instead of Jim)
XCID_POSITION	VARCHAR2	60		Y	Position within the company
XCID_DEPARTMENT	VARCHAR2	60		Y	Department (company can be unknown)
XCID_TITLE	VARCHAR2	30		Y	Aristocratic title (Lord, Prince)
XCID_ADDRGREET	VARCHAR2	30		Y	Address greeting (Mr, Mrs etc. we have a table for predefined, but this is not a link
XCID_LETTGREET	VARCHAR2	60		Y	Letter greeting (Dear Ms, Dear Tom )
XCID_BIRTHTIME	DATE			Y	Birthday
XCID_SEX	NUMBER	1		Y	Male(1) Female(2) Unknown (3)
XCID_MANAGER_XCMS_ID	NUMBER	30		Y	Manager assigned to this individual (for organizational chart)
XCID_TAXFREE	NUMBER	1		Y	For Swiss Diplomat Handling 1 = Diplomat, these guests dont pay special tax
XCID_BIRTHPLACE	VARCHAR2	50		Y	Place of Birth
XCID_WEDDINGDAY	DATE			Y	Weddingday
XCID_FAMILY	NUMBER	1		Y	1 = If Family Profile Guest, this profile is excluded from normal Profile Searches
XCID_FAM_NAME	VARCHAR2	100		Y	Family Name
XCID_FAM_ADDRGREET	VARCHAR2	30		Y	Family Address Greeting
XCID_FAM_LETTGREET	VARCHAR2	60		Y	Family Letter Greeting
XCID_FAMILYMAILING	NUMBER	1		Y	1= Family mailing contact. More than one family member can be a mailing contact.
XCID_COPYADDRESS	NUMBER	1		Y	Copy Family Address Info Flag
XCID_COPYCOMM	NUMBER	1		Y	Copy Family Communication Flag
XCID_COPYFAMILY	NUMBER	1		Y	Copy Family Info Flag
XCID_ALT_LETTGREET	VARCHAR2	60		Y	Alternative letter greeting
XCID_WTWN_ID	NUMBER	30		Y	Link to birth town
XCID_BIRTHCOUNTRY_XCOU_ID	NUMBER	30		Y	Birth country of profile
XCID_BIRTHSTATE_XSTA_ID	NUMBER	30		Y	Birth State of profile

### XCIL

company individual link

Field Name	Type	Length	Decimals	Not NULL	
XCIL_ID	NUMBER	30		N	Unique internal ID
XCIL_COMPANY_XCMS_ID	NUMBER	30		N	XCIL_COMPANY_XCMS_ID is of XCIL
XCIL_INDIVIDUAL_XCMS_ID	NUMBER	30		N	XCIL_INDIVIDUAL_XCMS_ID is of XCIL
XCIL_ROLE	VARCHAR2	30		Y	Description of role

### XCIL

company individual link

Field Name	Type	Length	Decimals	Not NULL	
XCIL_PRIMARY	NUMBER	1		Y	primary(1) not primary(0 or null) only one can be primary for the company at the same time
XCIL_MAILING	NUMBER	1		Y	Mailing contact (1) or not mailing contact (0). More than one linked contact/individual can be a mailing contact per company.
XCIL_POSITION	VARCHAR2	60		Y	Position of linked individual
XCIL_DEPARTMENT	VARCHAR2	60		Y	Department of linked individual

### XCLR

customer customer link roles (maybe we use it only for individuals) We define different roles depending on the XCLR\_INTERNALROLE.

Field Name	Type	Length	Decimals	Not NULL	
XCLR_ID	NUMBER	30		N	XCLR_ID identifies XCLR
XCLR_SHORTDESC	VARCHAR2	3		N	XCLR_SHORTDESC is of XCLR
XCLR_LONGDESC	VARCHAR2	30		N	XCLR_LONGDESC is of XCLR
XCLR_DISPLORDER	NUMBER	3		Y	XCLR_DISPLORDER is of XCLR
XCLR_REVERSELINKID	NUMBER	30		Y	XCLR_REVERSELINKID is the reverse link. If an Offspring Record is written, we store the Parent Record as well.
XCLR_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XCLR_TYPE	NUMBER	3		Y	1-Spouse, 2-next generation (descendant), 3-prev gen (predecessor), 4-siblings, 5-partners   for parents should be 3, for children 2

### XCMA

Customer Market Segment

Field Name	Type	Length	Decimals	Not NULL	
XCMA_ID	NUMBER	30		N	Unique internal ID
XCMA_XCMM_ID	NUMBER	30		N	Link to main market table
XCMA_SHORTDESC	VARCHAR2	3		N	Short description of customer market segment
XCMA_LONGDESC	VARCHAR2	30		N	Long description of customer market segment
XCMA_DISPLORDER	NUMBER	3		Y	Display order of customer market segments
XCMA_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XCMA_CCM_DISPLORDER	NUMBER	3		Y	Display Order for CCM

### XCMG

Third party XCMS GlobalIDs / external IDs

Field Name	Type	Length	Decimals	Not NULL	
XCMG_ID	NUMBER	30		N	Primary key

### XCMG

Third party XCMS GlobalIDs / external IDs

Field Name	Type	Length	Decimals	Not NULL	
XCMG_XCMS_ID	NUMBER	30		N	Link to the profile
XCMG_CRSTYPE	VARCHAR2	30		N	Third party system name
XCMG_INACTIVE	NUMBER	1		Y	
XCMG_INACTIVE_TIMESTAMP	DATE			Y	
XCMG_DOWNLOADTIMESTAMP	DATE			Y	Time when profile was downloaded in Suite8
XCMG_GLOBALID	VARCHAR2	100		Y	

### XCMH

third party global id for any table

Field Name	Type	Length	Decimals	Not NULL	
XCMH_ID	NUMBER	30		N	
XCMH_CRSTYPE	VARCHAR2	30		N	
XCMH_TABLENAME	VARCHAR2	4		N	
XCMH_TABLEID	NUMBER	30		N	
XCMH_GID	VARCHAR2	100		N	

### XCML

Customer Market Link Table

Field Name	Type	Length	Decimals	Not NULL	
XCML_ID	NUMBER	30		N	internal id
XCML_XCMA_ID	NUMBER	30		N	link to market code
XCML_XCMS_ID	NUMBER	30		N	link to customer

### XCMM

Customer Main Market

Field Name	Type	Length	Decimals	Not NULL	
XCMM_ID	NUMBER	30	4	N	Unique internal ID
XCMM_SHORTDESC	VARCHAR2	3		N	Short description of customer main market
XCMM_LONGDESC	VARCHAR2	30		N	Long description of customer main market codes
XCMM_DISPLORDER	NUMBER	3		Y	Display order of customer main market codes
XCMM_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XCMM_CCM_DISPLORDER	NUMBER	3		Y	Display Order for CCM

### XCMM

Customer Main Market

Field Name	Type	Length	Decimals	Not NULL	
XCMM_REPORT_GROUP	NUMBER	1		Y	Field is used to sum up categories in reports, possible values are 1, 2, 3 or 4

### XCMS

Profile table. Used also for storing the nationality. For statistic reason it is stored in XCMS not XCID.

Field Name	Type	Length	Decimals	Not NULL	
XCMS_ID	NUMBER	20		N	Unique customer ID (generated by system)
XCMS_NAME1	VARCHAR2	35		N	Customer Name 1
XCMS_NAME2	VARCHAR2	35		Y	Customer Name 2
XCMS_NAME3	VARCHAR2	35		Y	Customer Name 3
XCMS_KEYNAME	VARCHAR2	30		Y	Customer Key Name
XCMS_TYPE	NUMBER	1		N	Customer Type: Company(1) Individual(2) Employee(3)
XCMS_XCCA_ID	NUMBER	30		N	Link to customer category
XCMS_SEARCHNAME	VARCHAR2	35		Y	Customer Search Name (automatically generated search phrase)
XCMS_ACTIVE	NUMBER	1		N	1 = Yes   0 = No   3 = Terminated (employees)   4 = Merged
XCMS_INACTREASON	LONG			Y	Reason for inactivation of customer profile
XCMS_INACTTIME	DATE			Y	Date and time of inactivation
XCMS_INACTUSER	NUMBER	30		Y	Link to Employee who inactivated customer Profile
XCMS_CUSTNUM	VARCHAR2	30		Y	Manually entered unique identifier (must be unique)
XCMS_CREDITSTAT	CHAR			Y	Credit status (empty=normal C=cash only B=blacklist A=City ledger authorization)
XCMS_CREDREASON	VARCHAR2	60		Y	Credit Status Change Reason
XCMS_CREDTIME	DATE			Y	Date/time of Credit Status change
XCMS_CREDUSER	NUMBER	30		Y	User Name that changed the credit status
XCMS_REVPOTCAT	NUMBER	30	4	Y	Revenue Potential Catering
XCMS_REVPOTRMS	NUMBER	30	4	Y	Revenue Potential Rooms
XCMS_VIEWFO	NUMBER	1		Y	Customer profile visible in FO(1) or not(0)
XCMS_VIEWSC	NUMBER	1		Y	Customer Profile visible in SC(1) or not(0)
XCMS_PREF_ZCUR_ID	NUMBER	30		Y	Preferred Currency
XCMS_CANDELETE	NUMBER	1		Y	Profile can be deleted (1) or not(0 or null)
XCMS_WLAN_ID	NUMBER	30		Y	language of guest
XCMS_XCOU_ID_NATION	NUMBER	30		Y	XCMS_XCOU_ID_NATION is of XCMS
XCMS_NOMAILING	NUMBER	1		Y	No mailing. 1 = True, anything else = false
XCMS_TRACEFREQ	NUMBER	3		Y	Trace frequency for ccm automated traces
XCMS_SAVEGUEST	NUMBER	1		Y	if 1, profile should be automatically deleted after a period of time.

### XCMS

Profile table. Used also for storing the nationality. For statistic reason it is stored in XCMS not XCID.

Field Name	Type	Length	Decimals	Not NULL	
XCMS_YCDP_ID	NUMBER	30		Y	Policy used for this guest
XCMS_WEBLOGIN	VARCHAR2	60		Y	Username for web bookings
XCMS_WEBPASSWORD	VARCHAR2	30		Y	Password for web bookings
XCMS_GLOBALID	NUMBER	30		Y	Global ID if Hotel Connector is installed
XCMS_CENTRALSYNCTIMESTAMP	DATE			Y	XCMS_CENTRALSYNCTIMESTAMP is of XCMS
XCMS_CENTRALSYNCTIMELOCAL	DATE			Y	XCMS_CENTRALSYNCTIMELOCAL is of XCMS
XCMS_LINKEDPROFILESYNCDONE	NUMBER	1		Y	1 = indicates that linked profiles have been synchronized with the server during initialization process (Hotel Connector)
XCMS_AUTOMERGEERROR	DATE			Y	Auto profile match error flag
XCMS_ORG_WPHS_ID	NUMBER	30		Y	Original Partner Hotel ID (Hotel Connector)
XCMS_ZTXX_ID	NUMBER	30		Y	Tax exemption link
XCMS_MERGEDTO_XCMS_ID	NUMBER	30		Y	System profile merge log - ID of merged profile
XCMS_MERGETIME	DATE			Y	System profile merge log - date/time of profile merge
XCMS_AUTOMERGEERRORID	NUMBER	1		Y	0=error 1=merged to other profile remotely 2=profile was not uploaded because it has a match point higher than configured max match point 3=unique xmnr conflict 4=manual merge needed
XCMS_EXTERNALID	NUMBER	30		Y	External ID in case profile has been inserted from external program
XCMS_NO_HC_TRANSFER	NUMBER	1		Y	0=profile can be transferred 1=profile cannot be transferred
XCMS_CONTACTPREF	NUMBER	30		Y	Contact Preference value >0 = company has been selected
XCMS_HC_TOUCHED	DATE			Y	Timestamp so that hotel connector knows an activity or something got unlinked from a certain profile
XCMS_NOEMAILING	NUMBER	1		Y	No E-Mail Mailing   1= True
XCMS_BATCHID	NUMBER	30		Y	Used for grouping profiles for batch processing. ie for duplicate search
XCMS_SYNCFAILCOUNT	NUMBER	3		Y	Counts repeated profile synchronization failures
XCMS_NOTINACTIVEBEFORE	DATE			Y	
XCMS_CENTRALCORRESPONDENC E	NUMBER	1		N	

### XCMT

Communication types, such as fax, email and phones.

Field Name	Type	Length	Decimals	Not NULL	
XCMT_ID	NUMBER	30		N	Unique internal ID
XCMT_SHORTDESC	VARCHAR2	3		N	Short description for communication types
XCMT_LONGDESC	VARCHAR2	30		N	Long description for communication types
XCMT_DISPLORDER	NUMBER	3		Y	Display order for communication types
XCMT_TYPE	NUMBER	1		Y	1=EMAIL 2=HOMEPAGE 3=TELEFAX 4=TELEPHONE

### XCMT

Communication types, such as fax, email and phones.

Field Name	Type	Length	Decimals	Not NULL	
XCMT_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XCMT_WRXP_ID	NUMBER	30		Y	
XCMT_PHONEROLE	NUMBER	1		Y	1 = Mobile phone

### XCNC

0 = active 1= inactive

Field Name	Type	Length	Decimals	Not NULL	
XCNC_ID	NUMBER	30		N	Unique internal ID
XCNC_SHORTDESC	VARCHAR2	3		N	Short description of notes categories
XCNC_LONGDESC	VARCHAR2	30		N	Long description of notes categories
XCNC_TABLELINKEDTO	NUMBER	2		Y	table linked to (0=xcms 1=ybom 2=yres 3=yevm 4=all resource notes 5=aacc)
XCNC_DISPLORDER	NUMBER	3		Y	Display order of notes categories
XCNC_INACTIVE	NUMBER	1		Y	0 = active 1= inactive
XCNC_RESTRICTION	NUMBER	1		Y	1=yes, user rights apply, 0=No
XCNC_UPLOAD	NUMBER	1		Y	1 if this category should be synchronized with master
XCNC_POPUP_PROFILE	NUMBER	1		N	popup message on profile edit
XCNC_POPUP_RESERVATION	NUMBER	1		N	popup message on reservation edit
XCNC_POPUP_CCM	NUMBER	1		N	popup message on ccm edit
XCNC_POPUP_BILLINGOPEN	NUMBER	1		N	popup message on billing open
XCNC_POPUP_TABLERESERVATIONNUMBER	NUMBER	1		Y	

### XCNL

Note Category Link to Responsible Departments

Field Name	Type	Length	Decimals	Not NULL	
XCNL_ID	NUMBER	30		N	
XCNL_XCNC_ID	NUMBER	30		N	
XCNL_WHDE_ID	NUMBER	30		N	

### XCNO

Customer Notes

Field Name	Type	Length	Decimals	Not NULL	
XCNO_ID	NUMBER	30		N	Unique internal ID

### XCNO

Customer Notes

Field Name	Type	Length	Decimals	Not NULL	
XCNO_XCNC_ID	NUMBER	30		N	Link to notes category
XCNO_TABLE_ID	NUMBER	30		N	Link to table the notes belongs to
XCNO_NOTES	LONG			N	Notes
XCNO_TABLELINKEDTO	VARCHAR2	4		N	name of table linked to
XCNO_GUESTVIEWABLE	NUMBER	1		N	Whether or not this comment should be shown to the guest. Viewable = 1 Not Viewable = 0
XCNO_INTERNALCODE	NUMBER	3		Y	meaning depends on which table the record is linked to
XCNO_GLOBALID	NUMBER	30		Y	Global ID
XCNO_NOTESVARCHAR	VARCHAR2	2000		Y	Varchar notes to make it manageable from SQL
XCNO_FIDCRSID	VARCHAR2	20		Y	

### XCOL

Company organization link table

Field Name	Type	Length	Decimals	Not NULL	
XCOL_ID	NUMBER	30		N	XCOL_ID identifies XCOL
XCOL_COMPANY_ID	NUMBER	30		N	XCOL_COMPANY_ID is of XCOL
XCOL_INDIVIDUAL_ID	NUMBER	30		N	XCOL_INDIVIDUAL_ID is of XCOL
XCOL_MANAGER_ID	NUMBER	30		N	XCOL_MANAGER_ID is of XCOL

### XCOM

Communication Table

Field Name	Type	Length	Decimals	Not NULL	
XCOM_ID	NUMBER	30		N	Unique internal ID
XCOM_XCMT_ID	NUMBER	30		Y	Link to communication type
XCOM_XADR_ID	NUMBER	30		Y	Link to an address
XCOM_XCMS_ID	NUMBER	30		Y	Link from communication to customer
XCOM_WTBE_ID	NUMBER	30		Y	link to telephone book
XCOM_VALUE	VARCHAR2	60		N	Communication value
XCOM_PRIMARY	NUMBER	1		Y	primary(1) or not(0)
XCOM_XECT_ID	NUMBER	30		Y	Link to Employee Communication Types
XCOM_GLOBALID	NUMBER	30		Y	In Partner Hotels used to store XCOM_ID of the Master (Hotel Connector)
XCOM_VERIFIED	NUMBER	1		Y	0 - not validated, 1 - valid, 2 - not valid
XCOM_MAILID	VARCHAR2	100		Y	outlook sends its own id instead of email address. i store it here

### XCOM

Communication Table

Field Name	Type	Length	Decimals	Not NULL
XCOM_FIDCRSID	VARCHAR2	20		Y

### XCOU

Contains official government ID for each country

Field Name	Type	Length	Decimals	Not NULL	
XCOU_ID	NUMBER	30		N	Unique internal id
XCOU_ISO2	VARCHAR2	2		N	ISO code (2 characters)
XCOU_ISO3	VARCHAR2	3		N	ISO code (3 characters)
XCOU_CUSTSHORTDESC	VARCHAR2	3		N	Custom short description for countries
XCOU_LONGDESC	VARCHAR2	50		N	Country long description
XCOU_ZCUR_ID	NUMBER	30		Y	Link to currency table
XCOU_GVMNT_ID	NUMBER	30		Y	Gouvernement ID, to be entered, used for country statistics
XCOU_NATIONALITY	VARCHAR2	30		Y	Nationality, like 'dutch'
XCOU_CONTINENT	NUMBER	1		Y	1 = Europe 2 = Asia 3 = Africa 4 = Australia 5 = America
XCOU_ADDR_TYPE	NUMBER	2		Y	used for full address view.
XCOU_DISPLORDER	NUMBER	3		Y	Display Order
XCOU_INACTIVE	NUMBER	1		Y	1 = inactive
XCOU_XREG_ID	NUMBER	30		Y	Link to Region
XCOU_DOMESTIC	NUMBER	1		Y	Domestic Flag
XCOU_TOURIST_ZINN_ID	NUMBER	30		Y	Link to defined Number Cycle

### XCRL

Customer rate linkage.

Field Name	Type	Length	Decimals	Not NULL	
XCRL_ID	NUMBER	30		N	Unique internal ID
XCRL_ORDER	NUMBER	3		Y	Display order of rate codes per XCMS_ID
XCRL_XCMS_ID	NUMBER	30		N	Link to customer
XCRL_YRCH_ID	NUMBER	30		N	Link to rate code
XCRL_VALIDFROM	DATE			Y	Date rate code is valid from
XCRL_VALIDTO	DATE			Y	Date rate code is valid to

### XCTH

contracts

Field Name	Type	Length	Decimals	Not NULL
XCTH_ID	NUMBER	30		N
XCTH_NAME	VARCHAR2	30		Y
XCTH_ROOMNIGHTS	NUMBER	30		Y
XCTH_GROSSREV	NUMBER	30	4	Y
XCTH_GROSSROOMREV	NUMBER	30	4	Y
XCTH_NOOFATTENDEES	NUMBER	30		Y
XCTH_NOOFEVENTS	NUMBER	30		Y
XCTH_CCMGROSSREV	NUMBER	30	4	Y
XCTH_MASTER_XCTH_ID	NUMBER	30		Y
XCTH_WPHS_ID	NUMBER	30		Y
XCTH_EXPIRYDATE	DATE			Y
XCTH_SIGNUPDATE	DATE			Y
XCTH_STARTDATE	DATE			Y
XCTH_CONTRACTNAME	VARCHAR2	30		Y

### XCTL

link contracts to xmnr

Field Name	Type	Length	Decimals	Not NULL
XCTL_ID	NUMBER	30		N
XCTL_XCTH_ID	NUMBER	30		N
XCTL_XCMS_ID	NUMBER	30		Y
XCTL_XMNR_ID	NUMBER	30		Y

Obsolete column, not used anymore!!!

### XDEV

Document scanning devices

Field Name	Type	Length	Decimals	Not NULL	Description
XDEV_ID	NUMBER	30		N	Id of scanning device
XDEV_TYPE	NUMBER	1		Y	0 - Fujitsu; 1 - Belgian Eid reader; 2 - Samsotech
XDEV_ENABLEFASTSCANNING	NUMBER	1		Y	Scanning with no form interaction
XDEV_AUTOATTACHPICTURE	NUMBER	1		Y	Attach picture to profile if exists
XDEV_PICTURE_WDCG_ID	NUMBER	30		Y	Picture group
XDEV_PROMPTWHENMISSINGFIELDS	NUMBER	1		Y	Warning if missing fields

### XDEV

Document scanning devices

Field Name	Type	Length	Decimals	Not NULL	
XDEV_QUESTIONIFSECONDSIDE	NUMBER	1		Y	Question if second side needs to be scanned
XDEV_AUTOATTACHFULLPICTURE	NUMBER	1		Y	Attach full picture to profile if exists
XDEV_FULLPICTURE_WDCG_ID	NUMBER	30		Y	Full picture group
XDEV_USEWATERMARK	NUMBER	1		Y	Wattermark scanned pictures
XDEV_WATERMARK	VARCHAR2	200		Y	Picture used as wattermark
XDEV_USESCANNINGCENTER	NUMBER	1		Y	Use this device in scanning center
XDEV_UPLOADFOLDER	VARCHAR2	200		Y	Folder where scanned document will be uploaded for further processings/uploadings
XDEV_UPLOADUSER	VARCHAR2	60		Y	User that logs on network resource; otherwise blank
XDEV_UPLOADPASSWORD	VARCHAR2	60		Y	User password
XDEV_XPDG_ID	NUMBER	30		Y	Default document type if not recognized as passport or Id card
XDEV_SAVEPICTURESAUTOMATICALLY	NUMBER	1		Y	Auto adjust pictures to document group settings

### XDLT

Devices linked to terminals

Field Name	Type	Length	Decimals	Not NULL	
XDLT_ID	NUMBER	30		N	Id
XDLT_WPCA_ID	NUMBER	30		N	Terminal id
XDLT_XDEV_ID	NUMBER	30		N	Device id
XDLT_DISPLORDER	NUMBER	3		Y	Display order
XDLT_XPAD_ID	NUMBER	30		Y	Linked sign pad to terminal

### XECL

employee customer link

Field Name	Type	Length	Decimals	Not NULL	
XECL_ID	NUMBER	30		N	internal id
XECL_EMP_XCMS_ID	NUMBER	30		N	link to cms employee
XECL_CUST_XCMS_ID	NUMBER	30		N	link to cms employee
XECL_PRIMARY	NUMBER	1		Y	primary(1) or not(0)

### XECT

Employee Communication Types

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### XECT

Employee Communication Types

Field Name	Type	Length	Decimals	Not NULL	
XECT_ID	NUMBER	30		N	Unique internal ID
XECT_SHORTDESC	VARCHAR2	3		N	Short description for communication types
XECT_LONGDESC	VARCHAR2	30		N	Long description for communication types
XECT_DISPLORDER	NUMBER	3		N	Display order for communication types
XECT_TYPE	NUMBER	1		N	1=EMAIL 2=HOMEPAGE 3=TELEFAX 4=TELFON 9=MISCELLANEOUS
XECT_INACTIVE	NUMBER	1		N	0=active, 1=inactive
XECT_WRXP_ID	NUMBER	30		Y	

### XGCA

childage category groups

Field Name	Type	Length	Decimals	Not NULL	
XGCA_ID	NUMBER	30		N	
XGCA_SHORTDESC	VARCHAR2	5		N	
XGCA_LONGDESC	VARCHAR2	30		N	
XGCA_INACTIVE	NUMBER	1		Y	
XGCA_DISPLORDER	NUMBER	3		Y	

### XGCL

Field Name	Type	Length	Decimals	Not NULL	
XGCL_ID	NUMBER	30		N	
XGCL_XPAC_ID	NUMBER	30		N	
XGCL_WEGR_ID	NUMBER	30		N	

### XIIL

Individual to individual link

Field Name	Type	Length	Decimals	Not NULL	
XIIL_ID	NUMBER	30		N	Unique identifier
XIIL_FROM_XCMS_ID	NUMBER	30		Y	Link from individual
XIIL_TO_XCMS_ID	NUMBER	30		Y	Link to individual
XIIL_XCLR_ID	NUMBER	30		Y	Role ID

## XJET

JetWeb interface configuration table

Field Name	Type	Length	Decimals	Not NULL	
XJET_ID	NUMBER	30		N	
XJET_OESTAT	VARCHAR2	10		Y	
XJET_VERSION	VARCHAR2	5		Y	
XJET_BETRIEBNR	VARCHAR2	10		Y	
XJET_UVMNR	VARCHAR2	10		Y	
XJET_NUMBERSLEFT	NUMBER	30		Y	
XJET_URL	VARCHAR2	120		Y	
XJET_LOGIN	VARCHAR2	30		Y	
XJET_PASSWORD	VARCHAR2	30		Y	
XJET_GASTART_XPAC_ID	NUMBER	30		Y	
XJET_GASTTYP_XPAC_ID	NUMBER	30		Y	
XJET_MINIMUMARRIVAL	DATE			Y	
XJET_LAND_COUNTRY_CODE	NUMBER	1		Y	
XJET_STAAT_COUNTRY_CODE	NUMBER	1		Y	
XJET_NATION_COUNTRY_CODE	NUMBER	1		Y	
XJET_SWAP_NATION	NUMBER	1		Y	
XJET_ENCODING	NUMBER	1		Y	
XJET_DELIVERYMETHOD	NUMBER	1		Y	0 = JetWeb DLL, 1 = HTTP, 2 = File Export
XJET_EXPORTPATH	VARCHAR2	60		Y	
XJET_EXPORTONEFILE	NUMBER	1		Y	
XJET_DAYSRETRY	NUMBER	3		Y	
XJET_NOJETWEBGRPDEFAULT	NUMBER	1		Y	
XJET_ALLOWTENTATIVE	NUMBER	1		Y	
XJET_NADAYSINADVANCE	NUMBER	3		Y	
XJET_BETRIEBNRALPHA	VARCHAR2	10		Y	
XJET_CONFIG	VARCHAR2	4000		Y	

## XJLG

JetWeb export log

Field Name	Type	Length	Decimals	Not NULL	
XJLG_ID	NUMBER	30		N	
XJLG_DATE	DATE			Y	
XJLG_REGCARD	NUMBER	30		N	

### XJLG

JetWeb export log

Field Name	Type	Length	Decimals	Not NULL	
XJLG_SUCCESS	NUMBER	1		N	
XJLG_ERROR	VARCHAR2	200		Y	
XJLG_MESSAGETYPE	NUMBER	1		Y	1 = arrival 2 = departure
XJLG_YRES_ID	NUMBER	30		Y	
XJLG_YGRP_ID	NUMBER	30		Y	

### XJNB

JetWeb interface. Allocated registration card number slots

Field Name	Type	Length	Decimals	Not NULL	
XJNB_ID	NUMBER	30		N	XJNB primary key
XJNB_MELDEBLATT_FROM	NUMBER	30		N	Number start
XJNB_MELDEBLATT_TO	NUMBER	30		N	number end

### XMBC

For emails confirmation links group of attached reservations to incoming email, to an outgoing correspondence

Field Name	Type	Length	Decimals	Not NULL	
XMBC_ID	NUMBER	30		N	
XMBC_YRCO_ID	NUMBER	30		N	Outgoing correspondence
XMBC_XMLB_ID	NUMBER	30		N	Linked reservation to incoming email

### XMBL

Bonus Level rate link to dateranges

Field Name	Type	Length	Decimals	Not NULL	
XMBL_ID	NUMBER	30		N	
XMBL_XMBY_ID	NUMBER	30		N	
XMBL_YRCH_ID	NUMBER	30		N	

### XMBY

Bonus Level dateranges link for linked rates

Field Name	Type	Length	Decimals	Not NULL	
XMBY_ID	NUMBER	30		N	
XMBY_XMTL_ID	NUMBER	30		N	

### XMBY

Bonus Level dateranges link for linked rates

Field Name	Type	Length	Decimals	Not NULL
XMBY_FROMDATE	DATE			Y
XMBY_UNTILDATE	DATE			Y

### XMDY

Membership type rate dateranges link

Field Name	Type	Length	Decimals	Not NULL
XMDY_ID	NUMBER	30		N
XMDY_XMTY_ID	NUMBER	30		N
XMDY_FROMDATE	DATE			Y
XMDY_UNTILDATE	DATE			Y

### XMLA

Incoming E-Mail attachments

Field Name	Type	Length	Decimals	Not NULL	
XMLA_ID	NUMBER	30		N	
XMLA_XMLS_ID	NUMBER	30		N	Email attachment Link to email
XMLA_WTXT_ID	NUMBER	30		N	Body of attachment
XMLA_FILENAME	VARCHAR2	120		N	

### XMLB

Linked bookings

Field Name	Type	Length	Decimals	Not NULL	
XMLB_ID	NUMBER	30		N	
XMLB_XMLS_ID	NUMBER	30		N	Email ID
XMLB_YRES_ID	NUMBER	30		Y	Linked reservation id
XMLB_WPHS_ID	NUMBER	30		Y	Partner id

### XMLD

mail match directory settings

Field Name	Type	Length	Decimals	Not NULL
XMLD_ID	NUMBER	30		N
XMLD_XMSR_ID	NUMBER	30		N

### XMLD

mail match directory settings

Field Name	Type	Length	Decimals	Not NULL	
XMLD_NAME	VARCHAR2	1000		N	
XMLD_FULLPATH	VARCHAR2	1000		N	
XMLD_FOLDERID	VARCHAR2	1000		N	
XMLD_ENABLED	NUMBER	1		N	
XMLD_STOREID	VARCHAR2	1000		N	
XMLD_PARENT_XMLD_ID	NUMBER	30		Y	
XMLD_AUTOSUBFOLDERS	NUMBER	1		Y	1=subfolders are dynamically read from mail source. instead of adding them by user manually
XMLD_BACKUP_XMLD_ID	NUMBER	30		Y	Backup folder

### XMLI

ignored mails

Field Name	Type	Length	Decimals	Not NULL
XMLI_ID	NUMBER	30		N
XMLI_MAILID	VARCHAR2	500		N
XMLI_XCED_ID	NUMBER	30		N
XMLI_XMSR_ID	NUMBER	30		N

### XMLR

mail recipients if there are more than one. otherwise it is stored in xmls\_xcms\_id

Field Name	Type	Length	Decimals	Not NULL	
XMLR_ID	NUMBER	30		N	
XMLR_XMLS_ID	NUMBER	30		N	
XMLR_XCMS_ID	NUMBER	30		Y	null means user set recipient to ignore
XMLR_ADDRESS	VARCHAR2	200		N	
XMLR_SENDER	NUMBER	1		N	

### XMLS

mails

Field Name	Type	Length	Decimals	Not NULL	
XMLS_ID	NUMBER	30		N	
XMLS_MAILID	VARCHAR2	2000		N	any kind of id that identifies the mail uniquely in third party mailing systems
XMLS_STOREID	VARCHAR2	2000		N	

### XMLS

mails

Field Name	Type	Length	Decimals	Not NULL	
XMLS_INCOMING	NUMBER	1		N	0=outgoing mail 1=incoming mail
XMLS_SUBJECT	VARCHAR2	200		Y	
XMLS_SENTTIME	DATE			Y	
XMLS_RECEIVEDTIME	DATE			Y	
XMLS_PROCESSED	NUMBER	1		Y	
XMLS_XMSR_ID	NUMBER	30		Y	
XMLS_XMSR_TYPE	NUMBER	1		N	
XMLS_PROCESSEDBY_XCED_ID	NUMBER	30		Y	
XMLS_PROCESSEDTIME	DATE			Y	
XMLS_WTXT_ID	NUMBER	30		Y	
XMLS_IMPORTTIME	DATE			N	
XMLS_IMPORT_XCMS_ID	NUMBER	30		N	
XMLS_SENDER_XCMS_ID	NUMBER	30		Y	
XMLS_RECIPIENT_XCMS_ID	NUMBER	30		Y	
XMLS_SENDERADDRESS	VARCHAR2	1000		Y	
XMLS_RECIPIENTADDRESS	VARCHAR2	4000		Y	
XMLS_READY	NUMBER	1		Y	ready=1 means the mail is processed, does not need further user actions and matching
XMLS_YRCO_ID	NUMBER	30		Y	Link of incoming email to profile

### XMNR

Membership Numbers: different numbers assigned to the customer for different customizable purposes (like golf club membership number, iata number etc). The Profile object uses Membership objects to store frequent guest or other membership information for a profile.

Field Name	Type	Length	Decimals	Not NULL	
XMNR_ID	NUMBER	30		N	Unique internal ID
XMNR_XCMS_ID	NUMBER	30		N	Link from membership to customer
XMNR_XMTY_ID	NUMBER	30		N	XMNR_XMTY_ID is of XMNR
XMNR_VALUE	VARCHAR2	100		Y	Membership value
XMNR_LEVEL	VARCHAR2	30		Y	Used in points programs, etc., to represent the relative amount of credit awarded to this particular member, or his particular status within the program (VIP, Platinum, etc.).
XMNR_EXPIRYDATE	DATE			Y	Indicates when this membership expires.
XMNR_SIGNUPDATE	DATE			Y	Indicates when the member signed-up for the membership.
XMNR_STARTDATE	DATE			Y	Indicates when this membership starts.
XMNR_AACC_ID	NUMBER	30		Y	Link to the AR account (if XMTY_ROLE=1). In this case XMNR_VALUE remains empty.
XMNR_XMTY_ROLE	NUMBER	2		Y	XMNR_XMTY_ROLE is of XMNR

### XMNR

Membership Numbers: different numbers assigned to the customer for different customizable purposes (like golf club membership number, iata number etc). The Profile object uses Membership objects to store frequent guest or other membership information for a profile.

Field Name	Type	Length	Decimals	Not NULL	
XMNR_ZTRA_ID	NUMBER	30		Y	link to transponder card record. valid only for records linked to xmtty with xmtty_role=7(transponder)
XMNR_LEVELNUMBER	NUMBER	1		Y	
XMNR_INACTIVE	NUMBER	1		Y	1 = inactive
XMNR_ISSUEDBY_XCED_ID	NUMBER	30		Y	an employee who earns awards for generating a new guest membership
XMNR_INACTIVEREASON	VARCHAR2	60		Y	reason why card is inactive/active
XMNR_TAX_OFFICE	VARCHAR2	30		Y	Tax Office
XMNR_SIGNUPPROPERTY	VARCHAR2	100		Y	The property's (hotel's) name, where the membership enrollment happened

### XMRL

Membership type rate link to dateranges (xmdy)

Field Name	Type	Length	Decimals	Not NULL
XMRL_ID	NUMBER	30		N
XMRL_XMDY_ID	NUMBER	30		N
XMRL_YRCH_ID	NUMBER	30		N

### XMSL

Master- sub-link (companies)

Field Name	Type	Length	Decimals	Not NULL	
XMSL_ID	NUMBER	30		N	Unique internal ID
XMSL_MASTER_ID	NUMBER	30		N	Master Customer ID
XMSL_SUB_ID	NUMBER	30		N	Sub Customer ID

### XMSR

mail sources

Field Name	Type	Length	Decimals	Not NULL	
XMSR_ID	NUMBER	30		N	
XMSR_TYPE	NUMBER	1		N	0=outlook
XMSR_XCED_ID	NUMBER	30		N	
XMSR_WPCA_ID	NUMBER	30		N	
XMSR_URL	VARCHAR2	255		Y	Source URL
XMSR_USER	VARCHAR2	60		Y	Source login user
XMSR_PASSWORD	VARCHAR2	60		Y	Source login password

### XMTL

membership type levels

Field Name	Type	Length	Decimals	Not NULL
XMTL_ID	NUMBER	30		N
XMTL_XMTY_ID	NUMBER	30		N
XMTL_LEVEL	NUMBER	1		N
XMTL_SHORTDESC	VARCHAR2	5		N
XMTL_LONGDESC	VARCHAR2	30		N
XMTL_POINTLIMIT	NUMBER	30		Y

### XMTY

Membership types

Field Name	Type	Length	Decimals	Not NULL	
XMTY_ID	NUMBER	30		N	Unique internal ID
XMTY_SHORTDESC	VARCHAR2	3		N	Short description of membership types
XMTY_LONGDESC	VARCHAR2	30		N	Long description of membership types
XMTY_XCMSTYPE	NUMBER	1		Y	Defines customer type link - company(1); individual(2); employee(3)- any of them if not filled
XMTY_DISPLORDER	NUMBER	3		Y	Display order of membership types
XMTY_ROLE	NUMBER	2		Y	1 = A/R Number 2 = IATA Number 3 = VAT Number 4 = Frequent Flyer Cards and Loyalty Cards and Bonus point cards (differentiation will not be handled on this level) 5 = Corporate ID (also used for V8Online IFC) 6 = Unique 3rd party Profile ID for Property Interface 7 = Rebate cards 8 = Contract number 9 = Fiscal Code (Legge Bersani, needed in Italy) 10 = MVZV Membership 11 = Best Western 12 = Best Western Affiliate Programs ... to be continued for special numbers
XMTY_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XMTY_UNIQUE	NUMBER	1		Y	XMTY_UNIQUE is of XMTY
XMTY_ASKFORDUPL	NUMBER	1		Y	1= functionality that the system asks if it finds the same number in xmnr for the same xmt_y_id, just to advice
XMTY_EXPIRYCHECK	NUMBER	1		Y	1 = Expiry Check has been added to the membership configuration screen. If activated expiry dates can be entered
XMTY_SINGLEPER_XCMS	NUMBER	1		Y	1 = only one record per guest for this type
XMTY_RATEQUERY	NUMBER	1		Y	Allow for searching on rate query screen
XMTY_BONUSPOINT	NUMBER	1		Y	1=bonus point functionality is enabled for these cards. same as xmt_y_role=4 but this enables to combine bonus point feature with rebate card feature.
XMTY_WEBENABLED	NUMBER	1		Y	1=available over web interface when creating new bonus point card
XMTY_NUMBEROFLEVELS	NUMBER	1		Y	
XMTY_ZINN_ID	NUMBER	30		Y	membership numbers from zinn

### XMTY

Membership types

Field Name	Type	Length	Decimals	Not NULL
XMTY_WEBNAME	VARCHAR2	60		Y
XMTY_WEBSHORTDESC	VARCHAR2	300		Y
XMTY_WIMG_ID	NUMBER	30		Y
XMTY_CENTRAL	NUMBER	1		N
XMTY_LASTREQUESTVALUE	VARCHAR2	100		Y

### XMUA

Manager to user assignment

Field Name	Type	Length	Decimals	Not NULL	
XMUA_ID	NUMBER	30		N	Unique identifier
XMUA_FROM_XCMS_ID	NUMBER	30		Y	Manager ID
XMUA_TO_XCMS_ID	NUMBER	30		Y	User ID

### XMZF

MEMBERSHIP CARD LINK TO ZFAC (NEEDED TO HAVE HISTORY)

Field Name	Type	Length	Decimals	Not NULL	
XMZF_ID	NUMBER	30		N	XMZF_ID identifies XMZF
XMZF_XMNR_ID	NUMBER	30		N	XMZF_XMNR_ID is of XMZF
XMZF_ZFAC_ID	NUMBER	30		N	XMZF_ZFAC_ID is of XMZF

### XNDL

No Duplicate Storage

Field Name	Type	Length	Decimals	Not NULL	
XNDL_ID	NUMBER	30		N	Unique ID
XNDL_ONE_XCMS_ID	NUMBER	30		N	Link to one profile
XNDL_OTHER_XCMS_ID	NUMBER	30		N	Link to other profile

### XOPC

Opportunity Campaign

Field Name	Type	Length	Decimals	Not NULL
XOPC_ID	NUMBER	30		N
XOPC_SHORTDESC	VARCHAR2	3		Y

### XOPC

Opportunity Campaign

Field Name	Type	Length	Decimals	Not NULL
XOPC_LONGDESC	VARCHAR2	30		N
XOPC_SF_ID	VARCHAR2	30		Y
XOPC_DISPLORDER	NUMBER	3		Y

### XOPD

Opportunity Delivery Installation Status

Field Name	Type	Length	Decimals	Not NULL
XOPD_ID	NUMBER	30		N
XOPD_SHORTDESC	VARCHAR2	3		Y
XOPD_LONGDESC	VARCHAR2	30		N
XOPD_DISPLORDER	NUMBER	3		Y

### XOPL

Opportunity Lead Sources

Field Name	Type	Length	Decimals	Not NULL
XOPL_ID	NUMBER	30		N
XOPL_SHORTDESC	VARCHAR2	3		Y
XOPL_LONGDESC	VARCHAR2	30		N
XOPL_DISPLORDER	NUMBER	3		Y

### XOPP

Opportunities

Field Name	Type	Length	Decimals	Not NULL
XOPP_ID	NUMBER	30		N
XOPP_OWNER_XCED_ID	NUMBER	30		Y
XOPP_ACCOUNT_XCMS_ID	NUMBER	30		Y
XOPP_NAME	VARCHAR2	120		Y
XOPP_DESCRIPTION	VARCHAR2	1000		Y
XOPP_XOPS_ID	NUMBER	30		Y
XOPP_AMOUNT	NUMBER	30	4	Y
XOPP_PROBABILITY	NUMBER	3		Y
XOPP_EXPECTEDREVENUE	NUMBER	30	4	Y

### XOPP

Opportunities

Field Name	Type	Length	Decimals	Not NULL	
XOPP_TOTALOPPORTUNITYQUANTITY	NUMBER	30	4	Y	
XOPP_CLOSEDATE	DATE			Y	
XOPP_XOPT_ID	NUMBER	30		Y	
XOPP_XOPL_ID	NUMBER	30		Y	
XOPP_ISCLOSED	NUMBER	1		Y	
XOPP_ISWON	NUMBER	1		Y	
XOPP_XOPC_ID	NUMBER	30		Y	
XOPP_HASOPPORTUNITYLINEITEM	NUMBER	1		Y	
XOPP_FISCALQUARTER	NUMBER	1		Y	
XOPP_FISCALYEAR	NUMBER	4		Y	
XOPP_XOPD_ID	NUMBER	30		Y	
XOPP_TRACKINGNUMBER	VARCHAR2	30		Y	
XOPP_ORDERNUMBER	VARCHAR2	30		Y	
XOPP_CURRENTGENERATOR	VARCHAR2	100		Y	
XOPP_MAINCOMPETITOR	VARCHAR2	100		Y	
XOPP_THIRD_PARTY_ID	VARCHAR2	30		Y	
XOPP_SF_LASTMODIFIED_DATE	DATE			Y	
XOPP_INACTIVE_REASON	VARCHAR2	100		Y	
XOPP_NEXTSTEP	VARCHAR2	255		Y	
XOPP_PRIVATE	NUMBER	1		Y	Opportunities marked as Private can only be accessed by its exclusive owner
XOPP_INACTIVE	NUMBER	1		Y	

### XOPS

Opportunity stages

Field Name	Type	Length	Decimals	Not NULL	
XOPS_ID	NUMBER	30		N	
XOPS_SHORTDESC	VARCHAR2	3		Y	
XOPS_LONGDESC	VARCHAR2	30		N	
XOPS_DISPLORDER	NUMBER	3		Y	

### XOPT

Opportunity types

Field Name	Type	Length	Decimals	Not NULL
XOPT_ID	NUMBER	30		N
XOPT_SHORTDESC	VARCHAR2	3		Y
XOPT_LONGDESC	VARCHAR2	30		N
XOPT_CLOSEDAYS	NUMBER	3		Y
XOPT_DISPLORDER	NUMBER	3		Y

### XPAC

Customer Pre-defined Attribute Categories

Field Name	Type	Length	Decimals	Not NULL	
XPAC_ID	NUMBER	30		N	MUST BE DISCUSSED FROM TIME TO TIME 1 = Industry Code 2 = Competition Code 3 = Scope 4 = Product Interest 5 = Action Codes 6 = Influence 7 = Preferred Distribution method 8 = Scope City 9 = Potential 10 = Sales territory 11 = Vip Codes 12 = Simple Commission Codes 13 = Mailing Codes 14 = Primary Sales Office 15 = Source 16 = Priority 17 = Newspapers 18 = Specials 19 = Micros Discounts >1000 user defined roles
XPAC_SHORTDESC	VARCHAR2	3		N	Short description of attribute categories
XPAC_LONGDESC	VARCHAR2	40		N	Long description of attribute categories
XPAC_APPLIND	NUMBER	1		N	Defines if attribute category applies for individuals(1) or not(0)
XPAC_APPLCOMP	NUMBER	1		N	Defines if attribute category applies for companies(1) or not(0)
XPAC_APPLEMP	NUMBER	1		N	Defines if attribute category applies for employees(1) or not(0)
XPAC_APPLHOT	NUMBER	1		N	Defines if attribute category applies for hotels(1) or not(0)
XPAC_SINGLE	NUMBER	1		N	Defines if single selection(1) or multiple selection(0)
XPAC_DISPLORDER	NUMBER	3		Y	Display order of attribute categories
XPAC_RESORDET	NUMBER	1		Y	0 = does not apply at all to reservation 1 = applies to yres 2 = applies to ydet
XPAC_COPY_TO_RES	NUMBER	1		Y	Link will be copied if exist in xpal to the reservation attribute link (where it can be changed for the reservation only)
XPAC_MANDATORYRES	NUMBER	1		Y	1 = mandatory for reservation
XPAC_MANDATORYACCOUNTS	NUMBER	1		Y	1 = mandatory for financial accounts
XPAC_SHOWACCOUNTS	NUMBER	1		Y	valid attribute for financial accounts
XPAC_FIRSTPAGE	NUMBER	1		Y	If set to 1 this group is shown on first reservation edit page, applies only to ones which apply to yres.
XPAC_IFC	NUMBER	1		Y	1 = IFC Attributes, are not displayed with the other Attributes on reservation and profile edits 2= IFC Attributes visible before checkin
XPAC_IFC_CODE	NUMBER	1		Y	1 = Key Access Rights 2 = TV Rights 3 = Miscellaneous Rights, as Minibar, Internet etc. 4 = Access Level Codes used for MAFIS Interface
XPAC_ISREHA	NUMBER	1		Y	if global Setting Isreha is true then a tab on reservation edit is added where all xpac entries are shown which are marked as 'isreha'

## XPAC

Customer Pre-defined Attribute Categories

Field Name	Type	Length	Decimals	Not NULL	
XPAC_APPLBOOKING	NUMBER	1		Y	Defines if attribute category applies to bookings=1 or not=0
XPAC_APPLEVENT	NUMBER	1		Y	Defines if attribute category applies to events=1 or not=0
XPAC_CCMPAGE	NUMBER	1		Y	0-none applied; 1 applied to booking; 2 applied to event; 3 applied to booking and event
XPAC_SHOWLONGDESC	NUMBER	1		Y	0 - Show Shortdescription, 1 - Show Longdescription
XPAC_MANDATORYBOOKING	NUMBER	1		Y	1= mandatory for CCM Booking
XPAC_MANDATORYEVENT	NUMBER	1		Y	1= mandatory for CCM Event
XPAC_MANDATORYCOMP	NUMBER	1		Y	1= mandatory for company profiles
XPAC_MANDATORYIND	NUMBER	1		Y	1= mandatory for individual profiles
XPAC_TABLERESERVATION	NUMBER	1		Y	table attribut for table reservations
XPAC_APPLRESGUEST	NUMBER	1		N	
XPAC_COPYTORESGUEST	NUMBER	1		Y	copy guest attributes to reservaton guests
XPAC_THIRDPARTYID	NUMBER	30		Y	ID defined in third party system. Used for synchronization
XPAC_APPLTURNAWAY	NUMBER	1		Y	
XPAC_APPLRATE	NUMBER	10		N	
XPAC_WEBENABLED	NUMBER	1		Y	flag to include this category in suite8 Homepage
XPAC_APPLRESOURCE	NUMBER	1		Y	Applied to function spaces, catering items, standard menus
XPAC_ADDRIND	NUMBER	1		Y	Individual address
XPAC_ADDRCOMP	NUMBER	1		Y	Company address
XPAC_COPY_FROM_RES_TO_GUEST	NUMBER	1		N	
XPAC_COPY_FROMRES_TOMULTIGUEST	NUMBER	1		N	
XPAC_APPLCOMMENTS	NUMBER	1		Y	Defines if attribute category applies for comments (1) or not(0)
XPAC_APPLMAINTENANCE	NUMBER	1		Y	Applies to Maintenance Attributes
XPAC_APPLSERVICEPLAN	NUMBER	1		Y	Applies to Service Plan in Service Module
XPAC_APPLSERVICEBOOKING	NUMBER	1		Y	Applies to Service Booking in Service Module
XPAC_APPLSERVICESCHEDULED	NUMBER	1		Y	Applies to Scheduled Service in Service Module
XPAC_APPLSERVICEALLOCATION	NUMBER	1		Y	Applies to Service Allocation in Service Module
XPAC_MANDATORYSERVICEPLAN	NUMBER	1		Y	Mandatory for Service Plan in Service Module
XPAC_MANDATORYSERVICEBOOKING	NUMBER	1		Y	Mandatory for Service Booking in Service Module
XPAC_MANDATORYSERVICESCHEDULED	NUMBER	1		Y	Mandatory for Scheduled Service in Service Module
XPAC_MANDATORYSERVICEALLOCATION	NUMBER	1		Y	Mandatory for Service Allocation in Service Module

### XPAD

Sign pad

Field Name	Type	Length	Decimals	Not NULL	
XPAD_ID	NUMBER	30		N	Pad id
XPAD_TYPE	NUMBER	3		N	Type of sign pad; 0 - StepOver

### XPAL

Customer Predefined Attribute Link

Field Name	Type	Length	Decimals	Not NULL	
XPAL_ID	NUMBER	30		N	Unique interal ID
XPAL_XCMS_ID	NUMBER	30		N	Link to customer table
XPAL_XPDA_ID	NUMBER	30		N	Link to predefined attribute
XPAL_PRIMARY	NUMBER	1		Y	primary(1) or not(0)
XPAL_XPAC_ID	NUMBER	30		Y	makes retrieving of data possible for crystal, filled by trigger

### XPCL

Field Name	Type	Length	Decimals	Not NULL	
XPCL_ID	NUMBER	30		N	
XPCL_XPAC_ID	NUMBER	30		N	
XPCL_XCED_ID	NUMBER	30		N	

### XPDA

Customer Predefined Attributes

Field Name	Type	Length	Decimals	Not NULL	
XPDA_ID	NUMBER	30		N	Unique internal ID
XPDA_XPAC_ID	NUMBER	30		N	Link to predefined attribute categories
XPDA_SHORTDESC	VARCHAR2	3		N	Short description for predefined attributes
XPDA_LONGDESC	VARCHAR2	30		N	Long description for predefined attributes
XPDA_APPCODE	NUMBER	1		Y	Application code (for hardcoded application functions like automatic emailing etc)
XPDA_DISPLORDER	NUMBER	4		Y	Display order of predefined attributes
XPDA_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XPDA_IFC_CODE	NUMBER	2		Y	Only Used if the XPAC group is XPAC_IFC=1 Needs to be setup by IFC Installer to match ifc config
XPDA_IFC_VALUE	VARCHAR2	5		Y	XPDA_IFC_VALUE is of XPDA
XPDA_WCOL_ID	NUMBER	30		Y	Color for VIP Codes

## XPDA

Customer Predefined Attributes

Field Name	Type	Length	Decimals	Not NULL	
XPDA_ICFG_ID	NUMBER	30		Y	Linked Interface number from icfg
XPDA_RETURNABLE	NUMBER	1		Y	1 = Returnable Items
XPDA_THIRDPARTYID	NUMBER	30		Y	ID defined in third party system. Used for synchronization
XPDA_WEBENABLED	NUMBER	1		Y	flag to include this attribute in suite8 Homepage

## XPDC

Personal Documents Information about identity papers, including passports, military ID's, driver's license, etc. for a guest.

Field Name	Type	Length	Decimals	Not NULL	
XPDC_ID	NUMBER	30		N	XPDC_ID identifies XPDC
XPDC_XPDG_ID	NUMBER	30		N	XPDC_XPDG_ID is of XPDC
XPDC_XCMS_ID	NUMBER	30		N	XPDC_XCMS_ID is of XPDC
XPDC_NAME	VARCHAR2	70		Y	The person's name as it appears on the document.
XPDC_VALUE	VARCHAR2	30		Y	Document number (as applicable). As for instance Passport Number.
XPDC_XCOU_ID_COUNTRY	NUMBER	30		Y	The ISO standard country code of the country that issued the document. This links into XCOU
XPDC_XCOU_ID_NATION	NUMBER	30		Y	The ISO standard (country code) for the nationality of the guest, which may differ from the identity document(s). This links to XCOU
XPDC_VALIDFROM	DATE			Y	The effective date when the document becomes valid.
XPDC_EXPIRY	DATE			Y	The expiration date when the document becomes invalid.
XPDC_ISSUEDBY	VARCHAR2	30		Y	The institution where the document was issued.
XPDC_ISSUEPLACE	VARCHAR2	30		Y	The place/city institution where the document was issued. Required in Italy.
XPDC_FATHERS_NAME	VARCHAR2	30		Y	Father's name of guest - used for policy report in Turkey
XPDC_MOTHERS_NAME	VARCHAR2	30		Y	Mother's name of guest - used for policy report in Turkey
XPDC_REGISTER_CITY	VARCHAR2	30		Y	City of Registration
XPDC_REGISTER_MUNICIPAL	VARCHAR2	30		Y	Municipality of Registration
XPDC_REGISTER_STREET	VARCHAR2	30		Y	Street of Registration
XPDC_BORN_XCOU_ID	NUMBER	30		Y	Country of birth
XPDC_ISSUE_XCOU_ID	NUMBER	30		Y	
XPDC_BIRTHPLACE	VARCHAR2	50		Y	
XPDC_ISSUE_WTWN_ID	NUMBER	30		Y	
XPDC_BORN_WTWN_ID	NUMBER	30		Y	
XPDC_ISSUE_XSTA_ID	NUMBER	30		Y	State of issue
XPDC_BORN_XSTA_ID	NUMBER	30		Y	State of birth
XPDC_GLOBALID	NUMBER	30		Y	

## XPDC

Personal Documents Information about identity papers, including passports, military ID's, driver's license, etc. for a guest.

Field Name	Type	Length	Decimals	Not NULL	
XPDC_BIRTHDAY	DATE			Y	Date of Birth
XPDC_PRIMARY	NUMBER	1		Y	Primary Personal Document
XPDC_FIDCRSID	VARCHAR2	20		Y	
XPDC_PERSONALNUMBER	VARCHAR2	60		Y	Individual personal number

## XPDG

Element Setup for XPDC (personal documents).

Field Name	Type	Length	Decimals	Not NULL	
XPDG_ID	NUMBER	30		N	XPDG_ID identifies XPDG
XPDG_SHORTDESC	VARCHAR2	3		N	XPDG_SHORTDESC is of XPDG
XPDG_LONGDESC	VARCHAR2	30		N	XPDG_LONGDESC is of XPDG
XPDG_DISPLORDER	NUMBER	3		Y	XPDG_DISPLORDER is of XPDG
XPDG_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
XPDG_ROLE	NUMBER	2		Y	passports = 1, id card=2, drivers licence=3, visa=4 .. to be continued

## XPDT

Possible Duplicates

Field Name	Type	Length	Decimals	Not NULL	
XPDT_ID	NUMBER	30		N	Unique ID
XPDT_XCMS_ID	NUMBER	30		N	Possible candidate
XPDT_OTHER_XCMS_ID	NUMBER	30		Y	Other possible candidate
XPDT_POINT	NUMBER	5		Y	Number of matching points reached
XPDT_TIME	DATE			N	Date of duplicate check

## XPHN

TAPI phone call tracking

Field Name	Type	Length	Decimals	Not NULL	
XPHN_ID	NUMBER	30		N	
XPHN_XCMS_ID	NUMBER	30		N	
XPHN_XCMT_ID	NUMBER	30		Y	
XPHN_WPCA_ID	NUMBER	30		Y	
XPHN_PHONENUMBER	VARCHAR2	30		N	

## XPHN

TAPI phone call tracking

Field Name	Type	Length	Decimals	Not NULL
XPHN_CALLTIME	DATE			Y
XPHN_INCOMING	NUMBER	1		Y

## XPMI

Profile Match and Merge Initialization (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
XPMI_ID	NUMBER	30		N	Unique ID
XPMI_XCMS_ID	NUMBER	30		N	XPMI_XCMS_ID is of XPMI
XPMI_TIMESTAMP	DATE			N	XPMI_TIMESTAMP is of XPMI
XPMI_POINT	NUMBER	5		N	XPMI_POINT is of XPMI
XPMI_CANDIDATE_XCMS_ID	NUMBER	30		Y	XPMI_CANDIDATE_XCMS_ID is of XPMI
XPMI_UPLOADPOINT	NUMBER	5		Y	Initial profile upload points

## XPMR

Profile merge rules (Hotel Connector)

Field Name	Type	Length	Decimals	Not NULL	
XPMR_ID	NUMBER	30		N	Unique ID
XPMR_NAME	VARCHAR2	20		N	Name of merge rule
XPMR_CLIENTENTERED	NUMBER	1		N	0 = ignore 1 = copy to other side
XPMR_SERVERENTERED	NUMBER	1		N	0 = ignore 1 = copy to other side
XPMR_BOTHTENTERED	NUMBER	1		N	0 = ignore 1 = copy from client to server 2 = copy from server to client
XPMR_SYNC	NUMBER	1		N	0 = Ignore 1 = Upload 2 = Download 3 = Upload/Download
XPMR_DUPLICATE	NUMBER	1		N	0=ignore 1=copy
XPMR_SET	NUMBER	30		N	

## XPMS

Field Name	Type	Length	Decimals	Not NULL
XPMS_ID	NUMBER	30		N
XPMS_NAME	VARCHAR2	60		N
XPMS_XPMR_SET	NUMBER	30		N

### XPRG

BW points snapshot

Field Name	Type	Length	Decimals	Not NULL	
XPRG_ID	NUMBER	30		N	
XPRG_XCMS_ID	NUMBER	30		N	Linked profile
XPRG_NIGHTSTONEXTTIER	NUMBER	30		Y	Nights to next tier
XPRG_POINTSBALANCE	NUMBER	30		Y	Points balance
XPRG_PROGRAMCODE	VARCHAR2	10		Y	Program code
XPRG_TIERSINCE DATE	DATE			Y	Tier since date
XPRG_TIEREXPIRY DATE	DATE			Y	Tier expiry date
XPRG_NIGHTSTOMAINSTANSTATUS	NUMBER	30		Y	Nights to maintain status
XPRG_NIGHTSSTAYEDIN YEAR	NUMBER	30		Y	
XPRG_POINTSTOMAINSTANSTATUS	NUMBER	30		Y	Points to maintain status
XPRG_STAYSTOMAINSTANSTATUS	NUMBER	30		Y	Stays to maintain status
XPRG_NEXTLOYALLEVEL	VARCHAR2	10		Y	Next loyal level
XPRG_POINTSTONEXTTIER	NUMBER	30		Y	Points to next tier
XPRG_STAYSTONEXTTIER	NUMBER	30		Y	Stays to next tier
XPRG_ENROLLMENTSOURCE	VARCHAR2	30		Y	Enrollment source AAATW, CAATW, HARTW, NASTW
XPRG_ENROLLMENTDATE	DATE			Y	Date of enrollment

### XPRM

Customers preferred rooms. The selected rooms can be changed in display order and this means the room with the lowest number in XPRM\_DISPLORDER is the mostly preferred room. As for instance a guest always wants to stay in room 231, but if this is not possible i prefer 232 and if both rooms are not available i would like to have room 331. The rooms should be displayed in the edit screen as [231,232,331].

Field Name	Type	Length	Decimals	Not NULL	
XPRM_ID	NUMBER	30		N	XPRM_ID identifies XPRM
XPRM_XCMS_ID	NUMBER	30		N	XPRM_XCMS_ID is of XPRM
XPRM_YRMS_ID	NUMBER	30		Y	XPRM_YRMS_ID is of XPRM
XPRM_DISPLORDER	NUMBER	5		N	1-means most preferred room and 2 is 2nd choice and so on
XPRM_TYPE	NUMBER	1		N	1 = include 0 = Exclude
XPRM_YCAT_ID	NUMBER	30		Y	XPRM_YCAT_ID is of XPRM
XPRM_RTAB_ID	NUMBER	30		Y	
XPRM_RRST_ID	NUMBER	30		Y	
XPRM_REASON	VARCHAR2	2000		Y	Reason

### XPWH

user password history

Field Name	Type	Length	Decimals	Not NULL	
XPWH_ID	NUMBER	30		N	primary key
XPWH_XCED_ID	NUMBER	30		N	reference to the user
XPWH_PASSWORD	VARCHAR2	30		N	password
XPWH_CHNAGEDATE	DATE			N	timestamp of change

### XREG

Regions

Field Name	Type	Length	Decimals	Not NULL	
XREG_ID	NUMBER	30		N	Unique Identifier
XREG_SHORTDESC	VARCHAR2	3		Y	Short Description of Region
XREG_LONGDESC	VARCHAR2	50		N	Long Description of Region
XREG_INACTIVE	NUMBER	1		Y	1 = Inactive
XREG_DISPLORDER	NUMBER	3		Y	Display Order

### XRET

Returnable items

Field Name	Type	Length	Decimals	Not NULL	
XRET_ID	NUMBER	30		N	Unique ID
XRET_XPDA_ID	NUMBER	30		N	XRET_XPDA_ID is of XRET
XRET_ZDCO_ID	NUMBER	30		N	XRET_ZDCO_ID is of XRET
XRET_PRICE	NUMBER	30	4	Y	Usage price of the item, posted according to xret_postrhythym   NOT USED YET
XRET_POSTRHYTHYM	NUMBER	1		Y	Rhythym of price posting 0-None, 1-Daily, 2-Once   NOT USED YET
XRET_NOTRETURNPRICE	NUMBER	30	4	Y	Price to be paid when item is not returned on checkout
XRET_FROMDATE	DATE			N	XRET_FROMDATE is of XRET
XRET_TODATE	DATE			N	XRET_TODATE is of XRET
XRET_DEPOSIT	NUMBER	1		Y	XRET_DEPOSIT is of XRET

### XRPC

Field Name	Type	Length	Decimals	Not NULL	
XRPC_ID	NUMBER	30		N	
XRPC_XCMS_ID	NUMBER	30		N	

### XRPC

Field Name	Type	Length	Decimals	Not NULL
XRPC_TIME	DATE			N
XRPC_HASDIFFERENCE	NUMBER	1		N 0=no 1=yes
XRPC_LOG	VARCHAR2	2000		Y

### XSCA

Scheduled tasks attachments

Field Name	Type	Length	Decimals	Not NULL
XSCA_ID	NUMBER	30		N WMAA PK
XSCA_XSCD_ID	NUMBER	30		N Attachment link to the scheduled task
XSCA_FILENAME	VARCHAR2	128		N Attachment file name
XSCA_ATTACHMENT_WTXT_ID	NUMBER	30		N link to the binary storage

### XSCD

Scheduled report runs

Field Name	Type	Length	Decimals	Not NULL
XSCD_ID	NUMBER	30		N
XSCD_NAME	VARCHAR2	30		N Task name
XSCD_TYPE	NUMBER	1		N Task type. 0 = Report, 1 = HTML, 2 = Export
XSCD_DESTINATION	NUMBER	1		N Export destination, 0 = ftp 1 = email, 2 = file
XSCD_OBJ_ID	NUMBER	30		Y Linked object which has to be ran (wrpt_id or wnae_id)
XSCD_HTML_NAME	VARCHAR2	128		Y html file name
XSCD_RECIPIENT_LIST	VARCHAR2	300		Y List of the email addresses of recipients. In case of XSCD_RecipientIsQuery=1 - it is an SQL query of the recipients. When destination is not EMail, the field is used to hold an Execution list. For Execution List XSCD_RecipientIsQuery is automatically set to 1
XSCD_EXPORT_FORMAT	NUMBER	1		Y 0 = TXT 1 = RTF 2 = PDF 3 = RTF
XSCD_WRPT_SUBJ_ID	NUMBER	30		Y Report which has to be taken as a subject line
XSCD_WRPT_BODY_ID	NUMBER	30		Y Report which has to be sent as a body
XSCD_FTP	VARCHAR2	2000		Y FTP URL
XSCD_FTP_PORT	NUMBER	4		Y FTP port
XSCD_FTP_USERNAME	VARCHAR2	100		Y FTP username
XSCD_FTP_PASSWORD	VARCHAR2	100		Y FTP password
XSCD_EXPORT_PATH	VARCHAR2	100		Y Export path
XSCD_RHYTHM	NUMBER	1		Y 0 = Daily 1 = Weekly 2 = Monthly

## XSCD

Scheduled report runs

Field Name	Type	Length	Decimals	Not NULL	
XSCD_TIME	DATE			Y	Run time
XSCD_DAYSOFWEEK	VARCHAR2	7		Y	7 chars string indication if it should run on speicied day of week
XSCD_DAYOFMONTH	NUMBER	2		Y	Day of month in case of monthly rhythm
XSCD_LASTRUN	DATE			Y	Time of last run
XSCD_NEXTRUN	DATE			Y	Time of next run
XSCD_INACTIVE	NUMBER	1		Y	
XSCD_CONDITION	VARCHAR2	1000		Y	
XSCD_SENDER	VARCHAR2	100		Y	Sender email if different from global setting
XSCD_HTMLBODY	NUMBER	1		Y	1 = report will be sent as a email body (mhtml)
XSCD_RECIPIENTISQUERY	NUMBER	1		Y	When 1, Recipient List treated as SQL query
XSCD_EXPORTBATCH	NUMBER	1		Y	
XSCD_FILENAMEEMASK	VARCHAR2	200		Y	
XSCD_ADDDEFAULTATTACHMENTSNUMBER	NUMBER	1		Y	
XSCD_WFTP_ID	NUMBER	30		Y	Linked FTP Account
XSCD_FTP_REMOTEDIR	VARCHAR2	100		Y	Remote directory on FTP Server
XSCD_TRIGGERCONDITION	VARCHAR2	1000		Y	

## XSST

Sub States / Provinces

Field Name	Type	Length	Decimals	Not NULL	
XSST_ID	NUMBER	30		N	
XSST_SHORTDESC	VARCHAR2	3		N	
XSST_LONGDESC	VARCHAR2	30		N	
XSST_DISPLORDER	NUMBER	3		Y	
XSST_GVMNT_ID	NUMBER	30		Y	

## XSTA

States, incl. the ISO/postal service standard for state codes.

Field Name	Type	Length	Decimals	Not NULL	
XSTA_ID	NUMBER	30		N	Unique internal id
XSTA_SHORTDESC	VARCHAR2	3		N	The ISO/postal service standard for state codes.
XSTA_LONGDESC	VARCHAR2	30		N	Long description of states

## XSTA

States, incl. the ISO/postal service standard for state codes.

Field Name	Type	Length	Decimals	Not NULL	
XSTA_XCOU_ID	NUMBER	30		N	Link to country table
XSTA_DISPLORDER	NUMBER	3		Y	Display order of states
XSTA_GVMNT_ID	NUMBER	30		Y	For those countries which need a government id for state statistics

## XSTZ

Contains the ZIP Codes which belong to the states (XSTA)

Field Name	Type	Length	Decimals	Not NULL	
XSTZ_ID	NUMBER	30		N	XSTZ_ID identifies XSTZ
XSTZ_XSTA_ID	NUMBER	30		N	Link to the states table (XSTA)
XSTZ_FROMZIP	VARCHAR2	10		N	XSTZ_FROMZIP is of XSTZ
XSTZ_TOZIP	VARCHAR2	10		N	XSTZ_TOZIP is of XSTZ

## XUDS

User Dashboard files

Field Name	Type	Length	Decimals	Not NULL	
XUDS_ID	NUMBER	30		N	
XUDS_NAME	VARCHAR2	200		N	
XUDS_WEGR_ID	NUMBER	30		Y	User Group
XUDS_XCED_ID	NUMBER	30		Y	User id
XUDS_DISPLAYTYPE	NUMBER	1		N	1=Single 2=Double 3=Quadruple
XUDS_WDBF_ID_1	NUMBER	30		Y	wdbf_id of the file, shown in container 1
XUDS_WDBF_ID_2	NUMBER	30		Y	wdbf_id of the file, shown in container 2
XUDS_WDBF_ID_3	NUMBER	30		Y	wdbf_id of the file, shown in container 3
XUDS_WDBF_ID_4	NUMBER	30		Y	wdbf_id of the file, shown in container 4
XUDS_DEFAULT	NUMBER	1		Y	Default display setup
XUDS_DISPLORDER	NUMBER	3		Y	

## YACC

AMENITY CHANGE CYCLES

Field Name	Type	Length	Decimals	Not NULL	
YACC_ID	NUMBER	30		N	YACC_ID identifies YACC
YACC_SHORTDESC	VARCHAR2	3		N	YACC_SHORTDESC is of YACC

### YACC

AMENITY CHANGE CYCLES

Field Name	Type	Length	Decimals	Not NULL	
YACC_LONGDESC	VARCHAR2	30		N	YACC_LONGDESC is of YACC
YACC_PRIORITY	NUMBER	3		N	YACC_PRIORITY is of YACC
YACC_INACTIVE	NUMBER	1		Y	YACC_INACTIVE is of YACC

### YACL

AMENITY LINK TO CHANGE CYCLE

Field Name	Type	Length	Decimals	Not NULL	
YACL_ID	NUMBER	30		N	YACL_ID identifies YACL
YACL_YACC_ID	NUMBER	30		N	YACL_YACC_ID is of YACL
YACL_YAMN_ID	NUMBER	30		N	YACL_YAMN_ID is of YACL
YACL_YPFR_ID	NUMBER	30		N	YACL_YPFR_ID is of YACL

### YADB

City Ledger Authorization log

Field Name	Type	Length	Decimals	Not NULL	
YADB_ID	NUMBER	30		N	
YADB_YRES_ID	NUMBER	30		Y	
YADB_ZFAC_ID	NUMBER	30		Y	
YADB_XCED_ID	NUMBER	30		N	
YADB_COMMENT	VARCHAR2	100		Y	
YADB_ROLE	NUMBER	1		N	0=Direct Bill/City Ledger Auth

### YAFC

FIXED CHARGES FOR FINANCIAL ACCOUNTS

Field Name	Type	Length	Decimals	Not NULL	
YAFC_ID	NUMBER	30		N	YAFC_ID identifies YAFC
YAFC_ZFAC_ID	NUMBER	30		N	YAFC_ZFAC_ID is of YAFC
YAFC_QUANTITY	NUMBER	5		N	YAFC_QUANTITY is of YAFC
YAFC_AMOUNT	NUMBER	30	4	N	YAFC_AMOUNT is of YAFC
YAFC_FOREIGNAMOUNT	NUMBER	30	4	N	YAFC_FOREIGNAMOUNT is of YAFC
YAFC_ZCUR_ID	NUMBER	30		N	YAFC_ZCUR_ID is of YAFC
YAFC_EXCHANGE_RATE	NUMBER	38	18	Y	YAFC_EXCHANGE_RATE is of YAFC

### YAFC

FIXED CHARGES FOR FINANCIAL ACCOUNTS

Field Name	Type	Length	Decimals	Not NULL	
YAFC_ZDCO_ID	NUMBER	30		N	YAFC_ZDCO_ID is of YAFC
YAFC_LASTPOSTDATE	DATE			Y	YAFC_LASTPOSTDATE partly identifies YAFC
YAFC_REVERSEEXCHANGERATE	NUMBER	1		Y	

### YAGL

AMENITY GENERIC LINK

Field Name	Type	Length	Decimals	Not NULL	
YAGL_ID	NUMBER	30		N	Uniqye Identifier
YAGL_YACC_ID	NUMBER	30		N	YAGL_YACC_ID is of YAGL
YAGL_TABLENAME	VARCHAR2	4		N	YAGL_TABLENAME is of YAGL
YAGL_TABLEID	NUMBER	30		N	YAGL_TABLEID is of YAGL

### YALB

Booking or event link table to attribute categories

Field Name	Type	Length	Decimals	Not NULL	
YALB_ID	NUMBER	30		N	Table id
YALB_TABLENAME	VARCHAR2	4		Y	Booking or event table
YALB_TABLE_ID	NUMBER	30		N	Booking or event id linked
YALB_XPAC_ID	NUMBER	30		N	Attribute id
YALB_XPDA_ID	NUMBER	30		N	Attribute value linked id

### YALG

Availability limit group

Field Name	Type	Length	Decimals	Not NULL	
YALG_ID	NUMBER	30		N	
YALG_NAME	VARCHAR2	30		N	

### YALT

Field Name	Type	Length	Decimals	Not NULL	
YALT_ID	NUMBER	30		N	ID
YALT_TABLELINKEDTO	VARCHAR2	4		Y	YEBS, YEBR, YEMN, YEMI, YEVM, YPKD, YETB

### YALT

Field Name	Type	Length	Decimals	Not NULL	
YALT_TABLE_ID	NUMBER	30		Y	ID to which alternatives are defined
YALT_ALTERNATIVE_ID	NUMBER	30		Y	ID of alternative

### YAMN

Amenities

Field Name	Type	Length	Decimals	Not NULL	
YAMN_ID	NUMBER	30		N	YAMN_ID identifies YAMN
YAMN_SHORTDESC	VARCHAR2	3		N	YAMN_SHORTDESC is of YAMN
YAMN_LONGDESC	VARCHAR2	30		N	YAMN_LONGDESC is of YAMN
YAMN_DISPLORDER	NUMBER	5		N	YAMN_DISPLORDER is of YAMN
YAMN_INACTIVE	NUMBER	1		Y	YAMN_INACTIVE is of YAMN
YAMN_WHDE_ID	NUMBER	30		Y	RESPONSIBLE DEPARTMENT
YAMN_ROLE	NUMBER	1		Y	1 - Linen Change, 2 - Towel Change
YAMN_HSK_CREDITS	NUMBER	3		Y	housekeeping credits

### YBAL

block header attribute link

Field Name	Type	Length	Decimals	Not NULL	
YBAL_ID	NUMBER	30		N	YBAL_ID identifies YBAL
YBAL_YBLH_ID	NUMBER	30		N	YBAL_YBLH_ID is of YBAL
YBAL_YRAS_ID	NUMBER	30		N	YBAL_YRAS_ID is of YBAL

### YBAR

BAR Rate interface table

Field Name	Type	Length	Decimals	Not NULL	
YBAR_ID	NUMBER	30		N	
YBAR_BARCODE	VARCHAR2	10		Y	
YBAR_ARRIVALDATE	DATE			Y	
YBAR_LOS	NUMBER	3		Y	

## YBAS

Homepage booking Basket links to the reservation, table reservation, vouchers etc

Field Name	Type	Length	Decimals	Not NULL
YBAS_ID	NUMBER	30		N
YBAS_TABLE_ID	NUMBER	30		N
YBAS_TABLENAME	VARCHAR2	4		N
YBAS_BASKETID	VARCHAR2	20		N

## YBCF

User defined fields for CCM Bookings

Field Name	Type	Length	Decimals	Not NULL
YBCF_ID	NUMBER	30		N Unique ID
YBCF_YBOM_ID	NUMBER	30		N Link to CCM Bookings

## YBCL

block customer link (primary is the one who requested this block)

Field Name	Type	Length	Decimals	Not NULL
YBCL_ID	NUMBER	30		N YBCL_ID identifies YBCL
YBCL_YBLH_ID	NUMBER	30		N YBCL_YBLH_ID is of YBCL
YBCL_XCMS_ID	NUMBER	30		N YBCL_XCMS_ID is of YBCL
YBCL_PRIMARY	NUMBER	1		N 1 = true 0 = False
YBCL_INTERNALCATEGORY	CHAR			Y tracks the customer type 1=Company 2=Travel Agent 3=Source 4=Individual and Booker 5=Vendors 6=Meeting Planner

## YBCN

Contract number history

Field Name	Type	Length	Decimals	Not NULL
YBCN_ID	NUMBER	30		N Contract number history id
YBCN_CONTRACTNUMBER	NUMBER	3		N Contract number
YBCN_TIMESTAMP	DATE			N When contract number has been created
YBCN_YBOM_ID	NUMBER	30		Y Booking id link

## YBEF

Booked Event Forecast

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YBEF

Booked Event Forecast

Field Name	Type	Length	Decimals	Not NULL	
YBEF_ID	NUMBER	30		N	Unique ID
YBEF_YEVM_ID	NUMBER	30		N	Contains link to event
YBEF_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YBEF_PER_PERSON	NUMBER	30	4	Y	NOT USED ANYMORE
YBEF_FLAT_AMOUNT	NUMBER	30	4	Y	NOT USED ANYMORE
YBEF_ZCUR_ID	NUMBER	30		Y	Contains link to currency table
YBEF_REV_AMOUNT	NUMBER	30	4	Y	Forecast Amount
YBEF_YPKD_ID	NUMBER	30		Y	Linked to booked package
YBEF_YETY_ID	NUMBER	30		Y	Link to Event Type
YBEF_ZDCO_ID	NUMBER	30		N	Link to department code
YBEF_POSTTYPE	NUMBER	1		Y	YBEF_POSTTYPE is of YBEF
YBEF_REBATE_PERC	NUMBER	3		Y	Rebate Percentage
YBEF_ORG_REV_AMOUNT	NUMBER	30	4	Y	Original Amount
YBEF_REBATE_FLAT	NUMBER	30	4	Y	Rebate flat amount
YBEF_REBATE_UNITPRICE	NUMBER	30	4	Y	Rebate unit price
YBEF_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YBEF_PRICE_NET	NUMBER	30	4	Y	Revenue net value
YBEF_PRICE_VAT	NUMBER	30	4	Y	Revenue tax value

### YBFM

Table of YBFM

Field Name	Type	Length	Decimals	Not NULL	
YBFM_ID	NUMBER	30		N	unique identifier
YBFM_YEBS_ID	NUMBER	30		N	booked linked function space id
YBFM_QUANTITY	NUMBER	30	2	N	booked quantity of misc. item
YBFM_YEBR_ID	NUMBER	30		N	booked linked catering item id

### YBFO

Meal Plan

Field Name	Type	Length	Decimals	Not NULL	
YBFO_ID	NUMBER	30		N	YBFO_ID identifies YBFO
YBFO_YRES_ID	NUMBER	30		N	Link to Reservation

## YBFO

Meal Plan

Field Name	Type	Length	Decimals	Not NULL	
YBFO_DATE	DATE			N	YBFO_DATE is of YBFO
YBFO_B	NUMBER	5		N	Number of Breakfast
YBFO_L	NUMBER	5		N	Number of Lunch
YBFO_D	NUMBER	5		N	Number of Dinner
YBFO_BMANUAL	NUMBER	1		N	1 = if manual set
YBFO_LMANUAL	NUMBER	1		N	1 = if manual set
YBFO_DMANUAL	NUMBER	1		N	1 = if manual set

## YBID

billing instruction details

Field Name	Type	Length	Decimals	Not NULL	
YBID_ID	NUMBER	30		N	YBID_ID identifies YBID
YBID_YBIS_ID	NUMBER	30		N	YBID_YBIS_ID is of YBID
YBID_ZDCO_ID	NUMBER	30		Y	YBID_ZDCO_ID is of YBID
YBID_ZBIC_ID	NUMBER	30		Y	YBID_ZBIC_ID is of YBID
YBID_TYPE	NUMBER	1		N	1 = include, 2 = exclude, 3 = all postings included (for Master Share)
YBID_LIMIT	NUMBER	10	4	Y	Maximum posting value on a given department or billing instruction code

## YBIS

Billing Instructions

Field Name	Type	Length	Decimals	Not NULL	
YBIS_ID	NUMBER	30		N	YBIS_ID identifies YBIS
YBIS_FROMDATE	DATE			N	billing is valid from this time
YBIS_TODATE	DATE			Y	billing is valid until this time
YBIS_FROM_YRES_ID	NUMBER	30		Y	billing from reservation
YBIS_TO_YRES_ID	NUMBER	30		Y	billing to reservation
YBIS_FROM_ZFAC_ID	NUMBER	30		Y	Billing from financial account
YBIS_TO_ZFAC_ID	NUMBER	30		Y	billing to financial account (former PM)
YBIS_WINDOW	NUMBER	3		Y	billing to window in case of routing to same reservation
YBIS_XCMS_ID	NUMBER	30		Y	If a different profile is selected for this billing instruction
YBIS_ZWIN_ID	NUMBER	30		N	YBIS_ZWIN_ID is of YBIS
YBIS_YBOM_ID	NUMBER	30		Y	Link to CCM Booking

### YBIS

Billing Instructions

Field Name	Type	Length	Decimals	Not NULL	
YBIS_NOTES	LONG			Y	Billing Notes
YBIS_AUTO	NUMBER	1		Y	auto if created automatically by reservation not by user
YBIS_CASHFLAG	NUMBER	1		Y	For CCM only - when the flag is activated only department code and payment has to be entered
YBIS_GRP_LINK_ID	NUMBER	30		Y	Group Identifier for common entered Billing Instructions, for updates on Group Billing Instructions
YBIS_YBLH_ID	NUMBER	30		Y	Billing instruction link to block

### YBLA

Participant List for CCM Bookings

Field Name	Type	Length	Decimals	Not NULL	
YBLA_ID	NUMBER	30		N	Unique Code
YBLA_XCMS_ID	NUMBER	30		N	Link to Profile
YBLA_YBOM_ID	NUMBER	30		N	Link to CCM Booking
YBLA_ZFAC_ID	NUMBER	30		Y	Link to Financial Account
YBLA_NOOFPAX	NUMBER	4		Y	NOT USED ANYMORE

### YBLD

block detail

Field Name	Type	Length	Decimals	Not NULL	
YBLD_ID	NUMBER	30		N	YBLD_ID identifies YBLD
YBLD_DATE	DATE			N	YBLD_DATE is of YBLD
YBLD_YBLH_ID	NUMBER	30		N	YBLD_YBLH_ID is of YBLD
YBLD_YCAT_ID	NUMBER	30		N	YBLD_YCAT_ID is of YBLD
YBLD_CUTOFFDATE	DATE			Y	YBLD_CUTOFFDATE is of YBLD
YBLD_YRCH_ID	NUMBER	30		Y	YBLD_YRCH_ID is of YBLD
YBLD_INITIALNOOFROOMS	NUMBER	3		Y	YBLD_INITIALNOOFROOMS is of YBLD
YBLD_INITIALNOOFBEDS	NUMBER	3		Y	YBLD_INITIALNOOFBEDS is of YBLD
YBLD_ACTUALNOOFROOMS	NUMBER	3		Y	YBLD_ACTUALNOOFROOMS is of YBLD
YBLD_ACTUALNOOFBEDS	NUMBER	3		Y	YBLD_ACTUALNOOFBEDS is of YBLD
YBLD_EXPECTEDNOOFROOMS	NUMBER	3		Y	YBLD_EXPECTEDNOOFROOMS is of YBLD
YBLD_EXPECTEDNOOFBEDS	NUMBER	3		Y	YBLD_EXPECTEDNOOFBEDS is of YBLD
YBLD_SALESTATUS	NUMBER	1		Y	(1) sales free (cutoff date is not performed) (2) sales stop (user gets a user message if a reservation is attached (0 or null) none

### YBLD

block detail

Field Name	Type	Length	Decimals	Not NULL	
YBLD_NOOFADULTS	NUMBER	3		Y	YBLD_NOOFADULTS is filled on block creation with value from ycat_defaultnoofpersons, this value is per room
YBLD_TENTATIVE	NUMBER	3		Y	Used mainly in runtime when user planing to pickup rooms but process not finished

### YBLH

block header

Field Name	Type	Length	Decimals	Not NULL	
YBLH_ID	NUMBER	30		N	YBLH_ID identifies YBLH
YBLH_SHORTDESC	VARCHAR2	10		N	Block Code
YBLH_LONGDESC	VARCHAR2	60		N	Block Name (description)
YBLH_STARTDATE	DATE			N	Block start date
YBLH_ENDDATE	DATE			N	Block end date
YBLH_CUTOFFDATE	DATE			Y	Block cutoff date
YBLH_CUTOFFDAYS	NUMBER	3		Y	Cutoff days for block
YBLH_ELASTIC	NUMBER	1		Y	Elastic block?
YBLH_YBST_ID	NUMBER	30		Y	Link to block status
YBLH_YRCH_ID	NUMBER	30		Y	Link to rate code header
YBLH_XCMA_ID	NUMBER	30		Y	Default Market Code for this Block
YBLH_BACKTOHOUSE	NUMBER	1		Y	1 = Rooms after cutoff date are going back to house 0 = Rooms after cutoff date are going back to block Before cutoff is reached we count blocked rooms from ybld_actualnoofrooms, after cut off date from calculated figures from ydet + ybld_cutofftimenoofrooms /-beds
YBLH_YBOM_ID	NUMBER	30		Y	link to ccm booking
YBLH_ROOMINGLISTDATE	DATE			Y	roominglist date
YBLH_XMNR_ID	NUMBER	30		Y	Link to the contract record
YBLH_ZFAC_ID	NUMBER	30		Y	Link to financial account.
YBLH_ONLINEINTERFACEENABLE	NUMBER	1		Y	
YBLH_ONLINEINTERFACEENABLED	NUMBER	1		Y	Used by Online Interfaces to decide whether third party system should be notified about changes of this block
YBLH_SEARCHNAME	VARCHAR2	30		Y	Alternate block search name
YBLH_AUTOGROUP	NUMBER	1		Y	
YBLH_WEBPROMOTION	VARCHAR2	30		Y	Web promotion codes
YBLH_ADDTOMEALPLAN	NUMBER	1		N	
YBLH_INACTIVE	NUMBER	1		Y	

### YBLP

Link table from booking to postings

Field Name	Type	Length	Decimals	Not NULL	
YBLP_ID	NUMBER	30		N	YBLP table unique id
YBLP_ZPOS_ID	NUMBER	30		N	Link to the posting record made by current resource
YBLP_ZDCO_ID	NUMBER	30		N	Linked department code
YBLP_DATE	DATE			N	Date when posting has been made
YBLP_RESOURCE_ID	NUMBER	30		N	id of posted resource - package events=ybef   function spaces=yeps   misc. items=yebr   standard menu split=yprd   menu items=yemi
YBLP_RESOURCE_TYPE	NUMBER	2		N	resource type of booking which has posted amount - 1=package events   2=function spaces   3=misc. items   5=menu items   8= Standard Menu Split   9 = package header  10- standard menu
YBLP_AMOUNT	NUMBER	30	4	N	Amount posted by the resource
YBLP_AMOUNT_TYPE	NUMBER	1		N	Amount posted type;1-original amount posted;2-amount represent the difference posted
YBLP_POSTING_TYPE	NUMBER	1		N	The type of posting;1-automatic;2-manual;3...

### YBLR

Manual Block Rates

Field Name	Type	Length	Decimals	Not NULL	
YBLR_ID	NUMBER	30		N	Unique Id of YBLR
YBLR_YBLD_ID	NUMBER	30		N	Links to Room Block Detail Table
YBLR_ADULTNO	NUMBER	30		N	Number of Adults
YBLR_RATEAMOUNT	NUMBER	30	4	N	Rate

### YBLS

Manual occupancy split per block detail

Field Name	Type	Length	Decimals	Not NULL	
YBLS_ID	NUMBER	30		N	
YBLS_YBLD_ID	NUMBER	30		N	
YBLS_OCCUPANCYSPLIT	NUMBER	5		N	
YBLS_ADULTNO	NUMBER	5		Y	

### YBLW

Agents allowed to pick up from the block

Field Name	Type	Length	Decimals	Not NULL	
YBLW_ID	NUMBER	30		N	
YBLW_YBLH_ID	NUMBER	30		N	

### YBLW

Agents allowed to pick up from the block

Field Name	Type	Length	Decimals	Not NULL
YBLW_XCMS_ID	NUMBER	30		N
YBLW_STARTDATE	DATE			Y
YBLW_ENDDATE	DATE			Y

### YBMI

Responsible departments for booked items

Field Name	Type	Length	Decimals	Not NULL	
YBMI_ID	NUMBER	30		N	YBMI_ID identifies YBMI
YBMI_WHDE_ID	NUMBER	30		N	YBMI_WHDE_ID is of YBMI
YBMI_YEBR_ID	NUMBER	30		N	YBMI_YEBR_ID is of YBMI

### YBML

booking master link to managers

Field Name	Type	Length	Decimals	Not NULL	
YBML_ID	NUMBER	30		N	YBML_ID identifies YBML
YBML_YBOM_ID	NUMBER	30		N	YBML_YBOM_ID is of YBML
YBML_XCMS_ID	NUMBER	30		N	YBML_XCMS_ID is of YBML
YBML_TYPE	NUMBER	1		Y	null= not defined. in this case we display the wegr types. 1=Account/company manager, 2=conference manager and 3=rooms manager, 4=linked companies, 5=linked contacts

### YBOM

Booking Master

Field Name	Type	Length	Decimals	Not NULL	
YBOM_ID	NUMBER	30		N	Unique internal ID
YBOM_XCMS_ID	NUMBER	30		Y	Link to customer table
YBOM_ARRIVAL	DATE			N	Booking Master arrival date
YBOM_DEPARTURE	DATE			N	Booking Master departure date
YBOM_NAME	VARCHAR2	60		Y	Booking Master name
YBOM_CATERINGONLY	NUMBER	1		Y	Catering only flag - catering(1) or for rooms too (0 or null) (2=rooms only)
YBOM_NOOFATTENDEES	NUMBER	5		Y	Number of attendees
YBOM_INFOBOARD	VARCHAR2	60		Y	Information Board
YBOM_CATDECISIONDATE	DATE			Y	Catering decision date

### YBOM

Booking Master

Field Name	Type	Length	Decimals	Not NULL	
YBOM_CATCUTOFFDATE	DATE			Y	Catering cutoff date
YBOM_CATFOLLOWUPDATE	DATE			Y	Catering follow up date
YBOM_DETAILSOK	NUMBER	1		Y	Details OK flag
YBOM_DISTRIBUTED	NUMBER	1		Y	Distributed flag
YBOM_CONTRACTNUMBER	VARCHAR2	30		Y	Contract number
YBOM_RMSFOLLOWUPDATE	DATE			Y	Rooms follow up date
YBOM_YRSM_ID	NUMBER	30		Y	Link to reservation method
YBOM_XCMA_ID	NUMBER	30		Y	YBOM_XCMA_ID is of YBOM
YBOM_CREDITSTATUS	CHAR			Y	Credit Status
YBOM_CON_YEST_ID	NUMBER	30		Y	Catering status
YBOM_YRAS_ID	NUMBER	30		Y	Link between Source code and booking master
YBOM_BUDGETPERPERSON	NUMBER	1		Y	Defines if the budget is based on a per person basis or on total
YBOM_AVAILBUDGET	NUMBER	30	4	Y	Enter the available budget amount per booking
YBOM_IND_XCMS_ID	NUMBER	30		Y	Contains link to individual that is linked to the booking master
YBOM_RMS_YEST_ID	NUMBER	30		Y	YBOM_RMS_YEST_ID is of YBOM
YBOM_BASE_ZCUR_ID	NUMBER	30		Y	YBOM_BASE_ZCUR_ID is of YBOM
YBOM_PREF_ZCUR_ID	NUMBER	30		Y	YBOM_PREF_ZCUR_ID is of YBOM
YBOM_CONTACTONSITE	VARCHAR2	60		Y	YBOM_CONTACTONSITE is of YBOM
YBOM_YFTY_ID	NUMBER	30		Y	Link to function space type
YBOM_ZFAC_ID	NUMBER	30		Y	Financial Account Link
YBOM_RMSDECISIONDATE	DATE			Y	rooms decision date
YBOM_CONTRACTEXCHRATE	NUMBER	38	18	Y	Current defined rate for posting
YBOM_REVERSEEXCHRATE	NUMBER	1		Y	Direction of rate defined by the user in setup
YBOM_SERIES_ID	NUMBER	30		Y	Series ID
YBOM_YGRT_ID	NUMBER	30		Y	Link to Group Templates
YBOM_CHANNEL_YRAS_ID	NUMBER	30		Y	Channel code link
YBOM_XOPP_ID	NUMBER	30		Y	Opportunity Link
YBOM_YCAD_ID	NUMBER	30		Y	Linked segment id

### YBOS

Table of YBOS

Field Name	Type	Length	Decimals	Not NULL	
YBOS_ID	NUMBER	30		N	YBOS_ID identifies YBOS

### YBOS

Table of YBOS

Field Name	Type	Length	Decimals	Not NULL	
YBOS_YBLH_ID	NUMBER	30		N	YBOS_YBLH_ID is of YBOS
YBOS_YCAT_ID	NUMBER	30		N	YBOS_YCAT_ID is of YBOS
YBOS_DATE	DATE			N	YBOS_DATE is of YBOS
YBOS_ZDCO_ID	NUMBER	30		N	YBOS_ZDCO_ID is of YBOS
YBOS_UNITPRICE	NUMBER	30	4	N	YBOS_UNITPRICE is of YBOS
YBOS_QUANTITY	NUMBER	10		N	YBOS_QUANTITY is of YBOS
YBOS_TAXLINK_ID	NUMBER	30		N	YBOS_TAXLINK_ID is of YBOS
YBOS_INTERNALSPLIT_ID	NUMBER	30		N	YBOS_INTERNALSPLIT_ID is of YBOS
YBOS_DT	NUMBER	1		Y	1 = DEBIT 2 = TAX
YBOS_TYPE	NUMBER	1		N	0=NORMAL POSTINGS 2=PACKAGE RELATED POSTINGS
YBOS_YBLD_ID	NUMBER	30		N	
YBOS_GROSSUNITPRICE	NUMBER	30	4	Y	

### YBPC

Packages attached to the block

Field Name	Type	Length	Decimals	Not NULL	
YBPC_ID	NUMBER	30		N	
YBPC_YBLH_ID	NUMBER	30		N	
YBPC_YPAC_ID	NUMBER	30		N	

### YBSI

Event booked items (linked responsible departments)

Field Name	Type	Length	Decimals	Not NULL	
YBSI_ID	NUMBER	30		N	Unique identifier
YBSI_WHDE_ID	NUMBER	30		Y	Link to responsible department
YBSI_YEMI_ID	NUMBER	30		Y	Link to menu item

### YBSO

block status following order

Field Name	Type	Length	Decimals	Not NULL	
YBSO_ID	NUMBER	30		N	YBSO_ID identifies YBSO
YBSO_YBST_ID_PREVIOUS	NUMBER	30		N	YBSO_YBST_ID_PREVIOUS is of YBSO

## YBSO

block status following order

Field Name	Type	Length	Decimals	Not NULL	
YBSO_YBST_ID_NEXT	NUMBER	30		N	YBSO_YBST_ID_NEXT is of YBSO

## YBSS

Block split forecast

Field Name	Type	Length	Decimals	Not NULL	
YBSS_ID	NUMBER	30		N	
YBSS_YBLH_ID	NUMBER	30		Y	
YBSS_YBLD_ID	NUMBER	30		Y	
YBSS_YBLS_ID	NUMBER	30		Y	
YBSS_YCAT_ID	NUMBER	30		Y	
YBSS_DATE	DATE			Y	
YBSS_ZDCO_ID	NUMBER	30		Y	
YBSS_UNITPRICE	NUMBER	30	4	Y	
YBSS_QUANTITY	NUMBER	10		Y	
YBSS_TAXLINK_ID	NUMBER	30		Y	
YBSS_INTERNALSPLIT_ID	NUMBER	30		Y	
YBSS_DT	NUMBER	1		Y	
YBSS_TYPE	NUMBER	1		Y	
YBSS_ADULTNO	NUMBER	3		Y	
YBSS_OCCUPANCYSPLIT	NUMBER	3		Y	
YBSS_GROSSUNITPRICE	NUMBER	30	4	Y	

## YBST

Block status

Field Name	Type	Length	Decimals	Not NULL	
YBST_ID	NUMBER	30		N	YBST_ID identifies YBST
YBST_SHORTDESC	VARCHAR2	3		N	YBST_SHORTDESC is of YBST
YBST_LONGDESC	VARCHAR2	30		N	YBST_LONGDESC is of YBST
YBST_DISPLORDER	NUMBER	3		Y	YBST_DISPLORDER is of YBST
YBST_CANSTART	NUMBER	1		N	YBST_CANSTART is of YBST
YBST_RESSTATUS	NUMBER	1		Y	0=tentative 1=definitive 3=not effecting availability, as an example reservation offers and waitlist entries will have a YRES_RESSTATUS=3. this field can be found in yres and ybst

## YBST

Block status

Field Name	Type	Length	Decimals	Not NULL	
YBST_OPENFORPICKUP	NUMBER	1		Y	YBST_OPENFORPICKUP is of YBST
YBST_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YBST_CANCELSTATUS	NUMBER	1		Y	Cancellation status

## YCAD

Hotel Segmentation, used for PMS and CCM

Field Name	Type	Length	Decimals	Not NULL	
YCAD_ID	NUMBER	30		N	YCAD_ID identifies YCAD
YCAD_SHORTDESC	VARCHAR2	3		N	YCAD_SHORTDESC is of YCAD
YCAD_LONGDESC	VARCHAR2	30		N	YCAD_LONGDESC is of YCAD
YCAD_DISPLORDER	NUMBER	3		N	YCAD_DISPLORDER is of YCAD
YCAD_TYPE	NUMBER	1		N	1 = Hotel Segment for CCM, 2 = Hotel Segment for PMS, 3 = Hotel Segment for PMS and CCM
YCAD_INACTIVE	NUMBER	1		Y	0 = active 1 = inactive
YCAD_DEFAULT	NUMBER	1		Y	Default category
YCAD_WEEKDAY_WCOL_ID	NUMBER	30		Y	Custom Color shown on the Availability Screen for Weekends
YCAD_WEEKEND_WCOL_ID	NUMBER	30		Y	
YCAD_EMAIL	VARCHAR2	30		Y	sender email per hotel segment
YCAD_THIRDPARTYID	VARCHAR2	30		Y	

## YCAL

Guest Comment Attribute Links

Field Name	Type	Length	Decimals	Not NULL	
YCAL_ID	NUMBER	30		N	
YCAL_YCMG_ID	NUMBER	30		Y	Linked Guest Comment Type Id
YCAL_XPDA_ID	NUMBER	30		Y	Linked Guest Comment Attribute Item Id
YCAL_XPAC_ID	NUMBER	30		Y	Linked Guest Comment Attribute Categories Id

## YCAN

Cancellations

Field Name	Type	Length	Decimals	Not NULL	
YCAN_ID	NUMBER	30		N	Unique Cancellation ID
YCAN_YBOM_ID	NUMBER	30		Y	Contains link to Booking Master

## YCAN

Cancellations

Field Name	Type	Length	Decimals	Not NULL	
YCAN_WMLG_ID	NUMBER	30		Y	Contains link to WMLG (track creation date and user, modification date and user)
YCAN_DATE_CONF	DATE			Y	Cancellation date (cancell by)
YCAN_PERCENTAGE_CONF	NUMBER	3		Y	Cancellation percentage
YCAN_AMOUNT_DUE_CONF	NUMBER	30	4	Y	Cancellation amount that is due
YCAN_DATE_RMS	DATE			Y	Cancellation due date for rooms
YCAN_PERCENTAGE_RMS	NUMBER	3		Y	Cancellation percentage rooms
YCAN_AMOUNT_DUE_RMS	NUMBER	30	4	Y	Cancellation amount due rooms

## YCAS

Field Name	Type	Length	Decimals	Not NULL	
YCAS_ID	NUMBER	30		N	
YCAS_SUITE_YCAT_ID	NUMBER	30		N	
YCAS_ROOM_YCAT_ID	NUMBER	30		N	
YCAS_NUMBER	NUMBER	3		N	

## YCAT

YCAT is the setup table of the room types in the hotel.

Field Name	Type	Length	Decimals	Not NULL	
YCAT_ID	NUMBER	30		N	YCAT_ID identifies YCAT
YCAT_SHORTDESC	VARCHAR2	5		N	YCAT_SHORTDESC is the short description of the room type
YCAT_LONGDESC	VARCHAR2	30		N	YCAT_LONGDESC is of YCAT
YCAT_DISPLORDER	NUMBER	3		Y	YCAT_DISPLORDER is of YCAT
YCAT_DISABLED	NUMBER	1		Y	YCAT_DISABLED is of YCAT
YCAT_DEFAULT_YRCH_ID	NUMBER	30		Y	YCAT_DEFAULT_YRCH_ID is of YCAT
YCAT_DEFAULTNOOPPERSONS	NUMBER	3		Y	YCAT_DEFAULTNOOPPERSONS is of YCAT
YCAT_SC_YCAD_ID	NUMBER	30		Y	YCAT_SC_YCAD_ID is of YCAT
YCAT_SUM_ROOMTYPE_YCAD_ID	NUMBER	30		Y	YCAT_SUM_ROOMTYPE_YCAD_ID is of YCAT
YCAT_YIELDABLE	NUMBER	1		Y	0 = Non Yieldable, 1 = Yieldable
YCAT_NORMALBEDS	NUMBER	2		Y	Number of regular beds per category
YCAT_SPACEFOREXTRABEDS	NUMBER	2		Y	Number of possible extra beds per category
YCAT_THRESHOLD	NUMBER	3		Y	Number of rooms closed for web booking.

### YCAT

YCAT is the setup table of the room types in the hotel.

Field Name	Type	Length	Decimals	Not NULL	
YCAT_SHORTWEBINFO	VARCHAR2	2000		Y	Web Short Information
YCAT_SUITE_PRIMARY_YCAT_ID	NUMBER	30		Y	
YCAT_NOTINAVL	NUMBER	1		N	
YCAT_DONTSELLALONE	NUMBER	1		N	
YCAT_DISABLEMAKEKEY	NUMBER	1		N	1=no make key screen comes up when check-in
YCAT_SUITE	NUMBER	1		N	
YCAT_MAXNOOFPERSONS	NUMBER	3		Y	Max No of persons (Including children) which can be booked for this room type
YCAT_MAX	NUMBER	4		Y	Maximum number to sell
YCAT_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information
YCAT_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information for Mobile Device
YCAT_MD_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information for Mobile Device
YCAT_EXTENDEDWEBINFO	VARCHAR2	2000		Y	Extended Web Information
YCAT_MD_EXTENDEDWEBINFO	VARCHAR2	2000		Y	Extended Web Information for Mobile Device
YCAT_KEYIFC_ICFG_ID	NUMBER	30		Y	linked Key Interface
YCAT_MINNOOFPERSONS	NUMBER	3		Y	Miniumum number of persons (Including children) that can be booked for this room type

### YCDD

Policy description

Field Name	Type	Length	Decimals	Not NULL	
YCDD_ID	NUMBER	30		N	
YCDD_WLAN_ID	NUMBER	30		N	
YCDD_YCDP_ID	NUMBER	30		N	
YCDD_LONGDESC	VARCHAR2	2000		N	

### YCDP

Policy

Field Name	Type	Length	Decimals	Not NULL	
YCDP_ID	NUMBER	30		N	YCDP_ID identifies YCDP
YCDP_SHORTDESC	VARCHAR2	3		N	YCDP_SHORTDESC is of YCDP
YCDP_LONGDESC	VARCHAR2	30		N	YCDP_LONGDESC is of YCDP
YCDP_COMMENT	VARCHAR2	2000		Y	YCDP_COMMENT is of YCDP
YCDP_MANDATORYCC	NUMBER	1		Y	1=Reservations request cc in this timerange

### YCDP

Policy

Field Name	Type	Length	Decimals	Not NULL	
YCDP_ONLINEPAYMENT	NUMBER	1		Y	1=collect online payment directly on homepage

### YCDR

Policy Details

Field Name	Type	Length	Decimals	Not NULL	
YCDR_ID	NUMBER	30		N	YCDR_ID partly identifies YCDR
YCDR_TYPE	NUMBER	1		N	0=DEPOSIT 1=CANCELLATION 2=NOSHOW 3=EARLY DEPARTURE 4=EARLY ARRIVAL 5=LATE DEPARTURE
YCDR_NOOFDAYS	NUMBER	3		Y	NUMBER OF DAYS BEFORE ARRIVAL (CAN BE NULL FOR EARLY DEPARTURE)
YCDR_AMOUNT	NUMBER	30	4	Y	FIXED AMOUNT TO PAY NOT PERCENTAGE
YCDR_PERCENTAGE	NUMBER	30	4	Y	PERCENTAGE NOT FIXED AMOUNT
YCDR_MAXPERCENTAGEDAYS	NUMBER	3		Y	MAX NO OF DAYS TO TAKE WHEN COUNTING PERCENTAGE
YCDR_TOLERANCEDAYS	NUMBER	3		Y	IN CASE OF DEPOSIT
YCDR_YCDP_ID	NUMBER	30		N	RULE SET BEING LINKED TO
YCDR_FROMCREATION	NUMBER	1		Y	Deposit to be due by a date calculated based on reservation creation date (like 14 days after reservation creation)
YCDR_HOURLYFEE	NUMBER	1		Y	Early Arrival/Late Departure Type : 1 - Hourly Fee calculation is selected
YCDR_HOURS	NUMBER	2		Y	Early Arrival/Late Departure Type: For hourly type this tells the amount of hours that have passed
YCDR_DEFHOURLYFEE	NUMBER	1		Y	Early Arrival/Late Departure Type : 1 - Default Hourly Fee for cases where otherwise no hourly config exists

### YCEF

Reservation Calendar Event Fixed Charge Link

Field Name	Type	Length	Decimals	Not NULL	
YCEF_ID	NUMBER	30		N	
YCEF_YCEP_ID	NUMBER	30		N	
YCEF_YFXC_SCRID	NUMBER	30		N	

### YCEP

Link table: Profiles linked to Calendar events

Field Name	Type	Length	Decimals	Not NULL	
YCEP_ID	NUMBER	30		N	
YCEP_YCEV_ID	NUMBER	30		Y	
YCEP_XCMS_ID	NUMBER	30		Y	
YCEP_NOOFADULTS	NUMBER	2		Y	Number of Adults

### YCEP

Link table: Profiles linked to Calendar events

Field Name	Type	Length	Decimals	Not NULL	
YCEP_TICKETPRICE	NUMBER	30	4	Y	Ticket Price
YCEP_AMOUNT	NUMBER	30	4	Y	Ticket Amount
YCEP_ZFAC_ID	NUMBER	30		Y	Zfac id of ticket
YCEP_VOID_ZFAC_ID	NUMBER	30		Y	Link to FA of the cancelled tickets
YCEP_FULLYPAID	NUMBER	1		Y	1.Fullpaid
YCEP_PRINTED	NUMBER	1		Y	1.Tickets Printed
YCEP_NOTES	VARCHAR2	1000		Y	Participant Notes
YCEP_CANCELLED	NUMBER	1		N	
YCEP_ENTEREDDATE	DATE			Y	Entered Date
YCEP_YRES_ID	NUMBER	30		Y	
YCEP_YPAC_ID	NUMBER	30		Y	Linked Package id
YCEP_REVENUE_POSTDATE	DATE			Y	revenue post date
YCEP_RESCREATED	NUMBER	1		Y	indicates this participant is created to link to a reservation

### YCER

Recurring calendar Events

Field Name	Type	Length	Decimals	Not NULL	
YCER_ID	NUMBER	30		N	
YCER_SHORTDESC	VARCHAR2	3		N	
YCER_LONGDESC	VARCHAR2	60		N	
YCER_DISPLORDER	NUMBER	3		Y	
YCER_WCOL_ID	NUMBER	30		Y	Default colour
YCER_AVLINFLUENCELEVEL	NUMBER	1		Y	Availabilty influence Level 0(low) - 9(high)
YCER_YCET_ID	NUMBER	30		Y	Default Event type

### YCET

Calendar event types

Field Name	Type	Length	Decimals	Not NULL	
YCET_ID	NUMBER	30		N	YCET_ID identifies YCET
YCET_LONGDESC	VARCHAR2	30		N	YCET_LONGDESC is of YCET
YCET_SHORTDESC	VARCHAR2	3		N	YCET_SHORTDESC is of YCET
YCET_TYPE	NUMBER	2		N	0 = miscellaneous event 1 = availability event 2 = public holiday event 3= conference booking 4 = Day Rebates

### YCET

Calendar event types

Field Name	Type	Length	Decimals	Not NULL	
YCET_DEFAULT	NUMBER	1		Y	1 = Default
YCET_DISPLORDER	NUMBER	3		Y	YCET_DISPLORDER is of YCET
YCET_SHOW	NUMBER	1		Y	0-show all; 1-show diary; 2-show F4; 3-show CTRL-D; 4-show diary+F4; 5-show diary+CTRL-D; 6-show F4+CTRL-D
YCET_INACTIVE	NUMBER	1		Y	1=inactive
YCET_WEBENABLED	NUMBER	1		Y	
YCET_TICKET_ZDCO_ID	NUMBER	30		Y	Default Department code for Ticket Revenue
YCET_ADDATTENDEES	NUMBER	1		Y	Allow to add Attendees List
YCET_TICKETBILLING	NUMBER	1		Y	Ticket Billing
YCET_SHORTWEBDESC	VARCHAR2	1000		Y	Short Web Description
YCET_WEB_DELETE_PARTICIPANT	NUMBER	1		Y	1. Allow Participant deletion in Webconnect

### YCEV

Calendar Events

Field Name	Type	Length	Decimals	Not NULL	
YCEV_ID	NUMBER	30		N	YCEV_ID identifies YCEV
YCEV_LONGDESC	VARCHAR2	60		N	YCEV_LONGDESC is of YCEV
YCEV_NOTES	LONG			Y	YCEV_NOTES is of YCEV
YCEV_FROMDATE	DATE			N	YCEV_FROMDATE is of YCEV
YCEV_TODATE	DATE			N	YCEV_TODATE is of YCEV
YCEV_WCOL_ID	NUMBER	30		Y	For Display in Availbaility Screen Colors can be defined for critical events. These colors will be displayed in the relevant availability screen
YCEV_YCET_ID	NUMBER	30		N	YCEV_YCET_ID is of YCEV
YCEV_YBOM_ID	NUMBER	30		Y	link to ccm booking
YCEV_WEBENABLED	NUMBER	1		Y	
YCEV_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information
YCEV_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information
YCEV_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information for Mobile Device
YCEV_MD_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information for Mobile Device
YCEV_EST_ATTENDANCE	NUMBER	5		Y	Projeced number of attendees
YCEV_LOCATIONID	NUMBER	30		Y	linked location ID
YCEV_LOCATIONTYPE	NUMBER	1		Y	Location type 1. Public place(ypub) 2. Restaurant(RRST), 3.Function space(ysfc)
YCEV_TICKET_ZDCO_ID	NUMBER	30		Y	Department code for Ticket Revenue
YCEV_DEFAULT_TICKETPRICE	NUMBER	30	4	Y	Default Ticket Price

### YCEV

Calendar Events

Field Name	Type	Length	Decimals	Not NULL	
YCEV_MAX_WEB_SELL	NUMBER	5		Y	Maximum number of tickes can be sold through web
YCEV_TICKETBILLING	NUMBER	1		Y	Ticket Billing
YCEV_YCER_ID	NUMBER	30		Y	Linked recurring calendar Event
YCEV_AVLINFLUENCELEVEL	NUMBER	1		Y	Availabilty influence Level 0(low) - 9(high)
YCEV_REQUESTCC	NUMBER	1		Y	1=Reservations request cc in this timerange
YCEV_NOPARTICIPANTLIMIT	NUMBER	1		Y	This event does not have any limit for registered attendees
YCEV_SET_WEB_SELLLIMIT	NUMBER	1		Y	1. Indicates this event have a limit for Online registration
YCEV_SET_GUEST_WEB_SELLLIMIT	NUMBER	1		Y	1. Indicates this event have a limit per Guest for Online registration
YCEV_INACTIVE	NUMBER	1		Y	
YCEV_GUEST_MAX_WEB_SELL	NUMBER	5		Y	Maximum Number of participants per Guest
YCEV_YPAC_ID	NUMBER	30		Y	
YCEV_USEPACKAGE	NUMBER	1		Y	Link Package to Calendar Event

### YCGV

Government room typevalue evaluation for tax exempt part of room charge

Field Name	Type	Length	Decimals	Not NULL	
YCGV_ID	NUMBER	30		N	
YCGV_YCAT_ID	NUMBER	30		N	
YCGV_FROM	DATE			N	
YCGV_TO	DATE			N	
YCGV_VALUE	NUMBER	30	4	N	

### YCIA

Catering Item Attributes

Field Name	Type	Length	Decimals	Not NULL	
YCIA_ID	NUMBER	30		N	YCIA_ID identifies YCIA
YCIA_LONGDESC	VARCHAR2	30		Y	Long description for catering item attributes
YCIA_DISPORDER	NUMBER	3		Y	Display order for catering item attributes
YCIA_YCIT_ID	NUMBER	30		Y	Link to catering item
YCIA_INACTIVE	NUMBER	1		Y	0= active 1=inactive

### YCIC

Catering Item Categories

Field Name	Type	Length	Decimals	Not NULL	
YCIC_ID	NUMBER	30		N	Catering Item Category ID
YCIC_LONGDESC	VARCHAR2	30		N	Long description for catering item categories
YCIC_DISPLORDER	NUMBER	3		Y	Display order of catering item categories
YCIC_PMS	NUMBER	1		Y	Separate the categories of misc items 1-PMS, 0-ALL

### YCIL

Crs Item sync Log

Field Name	Type	Length	Decimals	Not NULL	
YCIL_ID	NUMBER	30		N	
YCIL_START	DATE			N	
YCIL_KEEPLIVE	DATE			N	
YCIL_FINISH	DATE			Y	
YCIL_APP	VARCHAR2	20		N	
YCIL_WPCA_ID	NUMBER	30		Y	
YCIL_TABLENAME	VARCHAR2	40		N	
YCIL_LOG	VARCHAR2	2000		Y	
YCIL_ITEMCOUNT	NUMBER	6		Y	
YCIL_ERRORCOUNT	NUMBER	6		Y	

### YCIM

Room type images

Field Name	Type	Length	Decimals	Not NULL	
YCIM_ID	NUMBER	30		N	
YCIM_YCAT_ID	NUMBER	30		Y	
YCIM_WIMG_ID	NUMBER	30		Y	
YCIM_DESCRIPTION	VARCHAR2	60		Y	
YCIM_IMAGETYPE	NUMBER	3		Y	0 = Full Size Room Picture; 1 = Thumbnail; 2 = Room Plan
YCIM_WEBENABLED	NUMBER	3		Y	

### YCIR

Catering Item Rates

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

## YCIR

### Catering Item Rates

Field Name	Type	Length	Decimals	Not NULL	
YCIR_ID	NUMBER	30		N	Catering Item Rate ID
YCIR_DESCRIPTION	VARCHAR2	60		Y	Description of catering item rates
YCIR_PERHOUR	NUMBER	1		N	Hourly charge for catering items
YCIR_VALUE	NUMBER	30	4	Y	Rate value
YCIR_YCIT	NUMBER	30		N	Link to catering item
YCIR_YCRD_ID	NUMBER	30		Y	Contains link of selected catering item rate code
YCIR_SHORTDESC	VARCHAR2	3		Y	Short description
YCIR_DEFAULT	NUMBER	1		Y	default rate for misc items
YCIR_VALIDFROM	DATE			Y	Rate Valid Date From
YCIR_VALIDTO	DATE			Y	Rate Valid Date To
YCIR_INACTIVE	NUMBER	1		Y	0= active 1=inactive
YCIR_COSTPRICE	NUMBER	30	4	Y	Cost price
YCIR_YCWI_ID	NUMBER	30		Y	Extends Catering item rate with a config for web

## YCIT

### Catering Items

Field Name	Type	Length	Decimals	Not NULL	
YCIT_ID	NUMBER	30		N	Catering Item ID
YCIT_SHORTDESC	VARCHAR2	3		Y	YCIT_SHORTDESC is of YCIT
YCIT_LONGDESC	VARCHAR2	60		N	Long description for catering items
YCIT_DISPLORDER	NUMBER	4		Y	Display order of catering items
YCIT_YCIC_ID	NUMBER	30		N	Link to catering item category
YCIT_DESCRIPTION	VARCHAR2	500		Y	Description of catering items
YCIT_EXTERNAL	NUMBER	1		Y	the hotel gets this item from a 3rd party
YCIT_QUANTITY	NUMBER	5		Y	number of items in house
YCIT_ARTICLENUMBER	VARCHAR2	10		Y	Article number of the catering item
YCIT_LEADDAYS	VARCHAR2	30		Y	time needed to get the item if the inventory shows 0 in days
YCIT_SOURCE_XCMS_ID	NUMBER	30		Y	Link to vendor
YCIT_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YCIT_SHOWFO	NUMBER	1		Y	show in fo reservations
YCIT_SHOWSC	NUMBER	1		Y	show in sales and catering reservations
YCIT_TRACKINVENTORY	NUMBER	1		Y	ie for flowers we don't have to check inventory.
YCIT_DEFAULTFO	NUMBER	1		Y	should be displayed on fo reservation screen by default

### YCIT

Catering Items

Field Name	Type	Length	Decimals	Not NULL	
YCIT_SETDOWNTIME	NUMBER	4		Y	setdowntime for misc items
YCIT_SETUPTIME	NUMBER	4		Y	setup time for misc items
YCIT_ZDCO_ID	NUMBER	30		Y	Misc Item - Department Code link
YCIT_POSTTYPE	NUMBER	1		Y	YCIT_POSTTYPE is of YCIT
YCIT_INACTIVE	NUMBER	1		Y	0 = active   1 = inactive
YCIT_ROLE	NUMBER	1		Y	1 = Extra Bed (to be continued)
YCIT_WEBSTATUS	NUMBER	1		Y	0=No 1=Yes
YCIT_ROOMMOVEWARNING	NUMBER	1		Y	
YCIT_NOFPAX	NUMBER	1		Y	1=yes
YCIT_COSTPRICE	NUMBER	30	4	Y	Cost price
YCIT_YCWI_ID	NUMBER	30		Y	Extends Catering item definition with a config for web

### YCLN

reservation customer link (one record for each built in customer type like travel agent, vendor, etc) (maybe we should store this in ydet in separate fields for all built in customer types.)

Field Name	Type	Length	Decimals	Not NULL	
YCLN_ID	NUMBER	30		N	YCLN_ID identifies YCLN
YCLN_YDET_ID	NUMBER	30		N	YCLN_YDET_ID is of YCLN
YCLN_XCMS_ID	NUMBER	30		N	YCLN_XCMS_ID is of YCLN
YCLN_XCCA_INTERNALCATEGORY	NUMBER	2		N	YCLN_XCCA_INTERNALCATEGORY is of YCLN

### YCLR

Predefined Cancellation and Reinstatement Reasons

Field Name	Type	Length	Decimals	Not NULL	
YCLR_ID	NUMBER	30		N	Unique internal ID
YCLR_SHORTDESC	VARCHAR2	3		N	Short description/code
YCLR_LONGDESC	VARCHAR2	30		N	YCLR_LONGDESC is of YCLR
YCLR_DISPLORDER	NUMBER	3		Y	YCLR_DISPLORDER is of YCLR
YCLR_CCMDISPLORDER	NUMBER	3		Y	YCLR_CCMDISPLORDER is of YCLR
YCLR_CANCELORREINSTATE	NUMBER	1		N	cancellation (1) or reinstate(0)
YCLR_YRES	NUMBER	1		Y	0=No, 1=Yes
YCLR_YBOMCONF	NUMBER	1		Y	YCLR_YBOMCONF is of YCLR
YCLR_YBOMROOMS	NUMBER	1		Y	0=No, 1=Yes

### YCLR

Predefined Cancellation and Reinstatement Reasons

Field Name	Type	Length	Decimals	Not NULL	
YCLR_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YCLR_WALKED	NUMBER	1		Y	was cancelled because no room left in hotel and had to take other hotel (for TLP)

### YCMC

pre-defined course order on category

Field Name	Type	Length	Decimals	Not NULL	
YCMC_ID	NUMBER	30		N	Menu Item Category ID
YCMC_LONGDESC	VARCHAR2	30		N	Long description of menu item category
YCMC_DISPLORDER	NUMBER	3		Y	Display order of menu item categories
YCMC_FOODORBEVERAGE	NUMBER	1		N	food(1) or beverage(0)
YCMC_COURSE	NUMBER	3		Y	YCMC_COURSE is of YCMC
YCMC_MC_ID	NUMBER	30		Y	Link to MC category
YCMC_FMGR_ID	NUMBER	30		Y	
YCMC_ROLE	NUMBER	2		Y	

### YCMG

Grouping for Complaints (in YCMP)

Field Name	Type	Length	Decimals	Not NULL	
YCMG_ID	NUMBER	30		N	YCMG_ID identifies YCMG
YCMG_SHORTDESC	VARCHAR2	3		N	YCMG_SHORTDESC is of YCMG
YCMG_LONGDESC	VARCHAR2	30		N	YCMG_LONGDESC is of YCMG
YCMG_DISPLORDER	NUMBER	3		Y	YCMG_DISPLORDER is of YCMG
YCMG_TYPESTATUS	NUMBER	1		Y	0=Neutral, 1=Positive, 2=Negative
YCMG_YCMO_ID	NUMBER	30		Y	Linked Guest Comment Origin ID
YCMG_INACTIVE	NUMBER	1		Y	1 = Inactive
YCMG_YCTG_ID	NUMBER	30		Y	

### YCMI

Catering Menu Items (Configuration)

Field Name	Type	Length	Decimals	Not NULL	
YCMI_ID	NUMBER	30		N	Menu Item ID
YCMI_LONGDESC	VARCHAR2	55		N	Menu Item Long description

## YCFMI

Catering Menu Items (Configuration)

Field Name	Type	Length	Decimals	Not NULL	
YCFMI_DISPLORDER	NUMBER	4		Y	Menu Item Display order
YCFMI_YCFMC_ID	NUMBER	30		N	Link to menu item category
YCFMI_MINIMUMAMOUNT	NUMBER	4		Y	Minimum amount (to sell)
YCFMI_MAXIMUMAMOUNT	NUMBER	4		Y	Maximum amount (to sell)
YCFMI_ORIGIN	VARCHAR2	55		Y	Origin (for beverages only)
YCFMI_ARTICLENUMBER	VARCHAR2	15		Y	Article number
YCFMI_COSTPRICE	NUMBER	30	4	Y	Cost Price
YCFMI_PORTION	VARCHAR2	30		Y	Portion sold
YCFMI_LEADDAYS	VARCHAR2	30		Y	Number of days article takes for ordering
YCFMI_AVAILABLEFROM	NUMBER	2		Y	article available from (for seasonal items)
YCFMI_AVAILABLEUNTIL	NUMBER	2		Y	Available until (for seasonal items)
YCFMI_INCLMENU	NUMBER	1		Y	Defines if price of menu item is included in Menu or not 1=included 0=not included
YCFMI_ZDCO_ID	NUMBER	30		N	Link to Department Codes.
YCFMI_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YCFMI_LONGDESC2	VARCHAR2	55		Y	YCFMI_LONGDESC2 is of YCFMI
YCFMI_LONGDESC3	VARCHAR2	55		Y	YCFMI_LONGDESC3 is of YCFMI
YCFMI_LONGDESC4	VARCHAR2	55		Y	YCFMI_LONGDESC4 is of YCFMI
YCFMI_ORIGIN2	VARCHAR2	55		Y	YCFMI_ORIGIN2 is of YCFMI
YCFMI_ORIGIN3	VARCHAR2	55		Y	YCFMI_ORIGIN3 is of YCFMI
YCFMI_VINTAGE	VARCHAR2	4		Y	Vintage (year of the wine)
YCFMI_DESCRIPTION	LONG			Y	Menu Item Description
YCFMI_INACTIVE	NUMBER	1		Y	0 = active   1 = inactive
YCFMI_MC_LONGDESC	VARCHAR2	60		Y	MC Product name
YCFMI_MC_POS_IFC	NUMBER	30		Y	Link to MC interface
YCFMI_TYPE	NUMBER	1		Y	0=CCM; 1 Materials Control
YCFMI_YCFWI_ID	NUMBER	30		Y	Extends Menu item with a config for web

## YCFMO

Comment Type Origin

Field Name	Type	Length	Decimals	Not NULL	
YCFMO_ID	NUMBER	30		N	YCFMO unique Id
YCFMO_SHORTDESC	VARCHAR2	3		N	Comment Type Origin Code
YCFMO_LONGDESC	VARCHAR2	30		N	Comment Type Origin Description

### YCMO

Comment Type Origin

Field Name	Type	Length	Decimals	Not NULL	
YCMO_DISPLORDER	NUMBER	3		Y	Display Order
YCMO_INACTIVE	NUMBER	1		Y	1 = Inactive

### YCMP

Complaints / Guest Comments

Field Name	Type	Length	Decimals	Not NULL	
YCMP_ID	NUMBER	30		N	YCMP_ID identifies YCMP
YCMP_YCMG_ID	NUMBER	30		N	YCMP_YCMG_ID is of YCMP
YCMP_YRES_ID	NUMBER	30		Y	YCMP_YRES_ID is of YCMP
YCMP_DATE	DATE			N	The system date when the guest complained
YCMP_TEXT	LONG			N	Free editable text with a description about the complaint.
YCMP_XCMS_ID	NUMBER	30		Y	for profile linked guest comments
YCMP_GLOBALID	NUMBER	30		Y	
YCMP_YBOM_ID	NUMBER	30		Y	Linked to Booking ID
YCMP_FIDCRSID	VARCHAR2	20		Y	
YCMP_REPLYNOTE	CLOB			Y	Hotel response to guest
YCMP_YCMT_BEGINING_ID	NUMBER	30		Y	Initial Linked Guest Temper Id
YCMP_YCMT_ENDING_ID	NUMBER	30		Y	Final Linked Guest Temper Id
YCMP_CREDITS	NUMBER	4		Y	Complaint cost amount
YCMP_TYPESTATUS	NUMBER	1		Y	
YCMP_RECEIVED_XCED_ID	NUMBER	30		Y	received by xced_id

### YCMR

Menu Item Rates

Field Name	Type	Length	Decimals	Not NULL	
YCMR_ID	NUMBER	30		N	YCMR_ID identifies YCMR
YCMR_YCMI_ID	NUMBER	30		N	YCMR_YCMI_ID is of YCMR
YCMR_PRICE	NUMBER	30	4	Y	YCMR_PRICE is of YCMR
YCMR_VALIDFROM	DATE			Y	YCMR_VALIDFROM is of YCMR
YCMR_VALIDTO	DATE			Y	YCMR_VALIDTO is of YCMR
YCMR_DEFAULT	NUMBER	1		Y	Default Rate
YCMR_YOUT_ID	NUMBER	30		Y	Link to Outlet

## YCMR

Menu Item Rates

Field Name	Type	Length	Decimals	Not NULL	
YCMR_ZDCO_ID	NUMBER	30		Y	Link to Department Code
YCMR_COSTPRICE	NUMBER	30	4	Y	Cost price
YCMR_MC_PRO_ID	NUMBER	30		Y	Link to interface
YCMR_YCWI_ID	NUMBER	30		Y	Extends Menu item rates with a config for web

## YCMT

Track Guest Temper for Complaints in YCMT

Field Name	Type	Length	Decimals	Not NULL	
YCMT_ID	NUMBER	30		N	YCMT Unique Id
YCMT_SHORTDESC	VARCHAR2	3		N	Guest Temper Code
YCMT_LONGDESC	VARCHAR2	30		N	Guest Temper Description
YCMT_DISPLORDER	NUMBER	3		Y	Display Order
YCMT_NUMERICVALUE	NUMBER	2		Y	
YCMT_INACTIVE	NUMBER	1		Y	1 = Inactive

## YCPC

Calendar Event Participant - Age Category wise split details

Field Name	Type	Length	Decimals	Not NULL	
YCPC_ID	NUMBER	30		N	
YCPC_YCEP_ID	NUMBER	30		N	Linked to ycep
YCPC_XCAC_ID	NUMBER	30		Y	Linked to xcac Child Categories value 0 is for Adults
YCPC_TYPE	NUMBER	1		Y	0.Children 1.Adult
YCPC_COUNT	NUMBER	30		Y	Number of persons
YCPC_PRICE	NUMBER	30	4	Y	Ticket Price
YCPC_AMOUNT	NUMBER	30	4	Y	Ticket Amount

## YCRD

Rate codes for catering items

Field Name	Type	Length	Decimals	Not NULL	
YCRD_ID	NUMBER	30		N	YCRD_ID identifies YCRD
YCRD_SHORTDESC	VARCHAR2	3		N	YCRD_SHORTDESC is of YCRD
YCRD_LONGDESC	VARCHAR2	30		N	YCRD_LONGDESC is of YCRD

### YCRD

Rate codes for catering items

Field Name	Type	Length	Decimals	Not NULL	
YCRD_DESCRIPTION	VARCHAR2	60		Y	YCRD_DESCRIPTION is of YCRD
YCRD_DISPLORDER	NUMBER	3		Y	YCRD_DISPLORDER is of YCRD

### YCRF

Cross reference details recieved from the EFT systems

Field Name	Type	Length	Decimals	Not NULL	
YCRF_ID	NUMBER	30		N	
YCRF_XCAP_ID	NUMBER	30		N	
YCRF_CROSSREF_1	VARCHAR2	3000		Y	
YCRF_CROSSREF_2	VARCHAR2	50		Y	
YCRF_CROSSREF_3	VARCHAR2	50		Y	
YCRF_CROSSREF_4	VARCHAR2	50		Y	
YCRF_CROSSREF_5	VARCHAR2	50		Y	
YCRF_CROSSREF_6	VARCHAR2	50		Y	
YCRF_CROSSREF_7	VARCHAR2	50		Y	
YCRF_CROSSREF_8	VARCHAR2	50		Y	
YCRF_CROSSREF_9	VARCHAR2	400		Y	

### YCRG

CRS needs to transfer xcms globalids listed here

Field Name	Type	Length	Decimals	Not NULL	
YCRG_ID	NUMBER	30		N	
YCRG_CRSID	VARCHAR2	60		N	
YCRG_GLOBALID	NUMBER	30		N	
YCRG_TIMESTAMP	DATE			N	
YCRG_LASTTRY	DATE			Y	

### YCRL

Central Reservation Lock for rooms in mirror and parnter

Field Name	Type	Length	Decimals	Not NULL	
YCRL_ID	NUMBER	30		N	
YCRL_YRMS_ID	NUMBER	30		N	

### YCRL

Central Reservation Lock for rooms in mirror and parnter

Field Name	Type	Length	Decimals	Not NULL	
YCRL_DAY	DATE			N	
YCRL_TIMESTAMP	DATE			N	
YCRL_ORIGIN	NUMBER	1		N	0=locally made 1=remotely requested
YCRL_RESGLOBALID	VARCHAR2	60		N	

### YCRN

Third party CRS id for reservation

Field Name	Type	Length	Decimals	Not NULL	
YCRN_ID	NUMBER	30		N	
YCRN_YRES_ID	NUMBER	30		N	
YCRN_CRSSYSTEM	VARCHAR2	30		N	
YCRN_CRSRESNR	VARCHAR2	50		Y	

### YCRS

Field Name	Type	Length	Decimals	Not NULL	
YCRS_TABLEID	NUMBER	30		N	
YCRS_TABLENAME	VARCHAR2	4		N	
YCRS_GLOBALID	VARCHAR2	60		Y	unique id for reservation in partner and mirror
YCRS_OWNED	NUMBER	1		N	1=reservation is owned and allowed to modify
YCRS_LOCALTIMESTAMP	DATE			Y	timestamp of last data transfer regardless of direction (depends on ownership)
YCRS_LOCALHASH	VARCHAR2	32		Y	
YCRS_HASHMISMATCH	DATE			Y	remote hash mismatch detection timestamp.
YCRS_TRANSFERERROR	DATE			Y	data transfer error timestamp
YCRS_ERRORTEXT	VARCHAR2	1000		Y	data transfer error text
YCRS_MODIFIEDWITHOUTOWNED	NUMBER	1		N	
YCRS_FIRSTTRANSFER	DATE			Y	timestamp of first successful transfer. indicates wether item can be found on other side or not
YCRS_LOCALUPDATETIMESTAMP	DATE			Y	code can request crs upload for items by updating this field with oracle sysdate
YCRS_DELETED	DATE			Y	
YCRS_PROBLEMEVERSION	VARCHAR2	10		Y	Exe version when error or hash mismatch happened. Automatic retry is based on this information after exe update.

## YCRT

Vacation sharing template (reservation contract template)

Field Name	Type	Length	Decimals	Not NULL	
YCRT_ID	NUMBER	30		N	
YCRT_SHORTDESC	VARCHAR2	5		N	
YCRT_LONGDESC	VARCHAR2	200		N	
YCRT_XCMA_ID	NUMBER	30		Y	
YCRT_YCAT_ID	NUMBER	30		Y	
YCRT_YRCH_ID	NUMBER	30		Y	ratecode for reservations
YCRT_CONTRACT_YRCH_ID	NUMBER	30		Y	ratecode for contract yearly charges
YCRT_WEEKSTARTTYPE	NUMBER	1		Y	0=n. day of the year according to calendar 1=first instance of n. day of the week (n=yCRT_weekstartvalue)
YCRT_WEEKSTARTVALUE	NUMBER	2		Y	
YCRT_INACTIVE	NUMBER	1		Y	
YCRT_DISPLORDER	NUMBER	3		N	
YCRT_WCOL_ID	NUMBER	30		Y	
YCRT_MANDATORYCONTRACTNUMBER	NUMBER	1		Y	1=yrcs_contractnumber is mandatory
YCRT_SOURCE_YRAS_ID	NUMBER	30		Y	
YCRT_COMPANY_XCMS_ID	NUMBER	30		Y	
YCRT_SOURCE_XCMS_ID	NUMBER	30		Y	
YCRT_TRAVELAGENT_XCMS_ID	NUMBER	30		Y	

## YCTG

Guest Comment Type Groups

Field Name	Type	Length	Decimals	Not NULL	
YCTG_ID	NUMBER	30		N	YCTG_ID identifies YCTG
YCTG_SHORTDESC	VARCHAR2	3		N	YCTG_SHORTDESC is of YCTG
YCTG_LONGDESC	VARCHAR2	30		N	YCTG_LONGDESC is of YCTG
YCTG_DISPLORDER	NUMBER	3		Y	YCTG_DISPLORDER is of YCTG
YCTG_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YCTG_WHDE_ID	NUMBER	30		Y	Link to responsible departments

## YCUS

Custom order for conference diary

Field Name	Type	Length	Decimals	Not NULL	
YCUS_ID	NUMBER	30		N	YCUS_ID identifies YCUS

## YCUS

Custom order for conference diary

Field Name	Type	Length	Decimals	Not NULL	
YCUS_YFCO_ID	NUMBER	30		N	YCUS_YFCO_ID is of YCUS
YCUS_YFSC_ID	NUMBER	30		N	YCUS_YFSC_ID is of YCUS
YCUS_DISPLORDER	NUMBER	3		Y	YCUS_DISPLORDER is of YCUS

## YCWI

Web info

Field Name	Type	Length	Decimals	Not NULL	
YCWI_ID	NUMBER	30		N	
YCWI_WEBENABLED	NUMBER	1		Y	0 - not enabled for web; 1 - enabled for web
YCWI_SHORTWEBINFO	VARCHAR2	2000		Y	Short web info
YCWI_LONGWEBINFO	VARCHAR2	2000		Y	Long web info

## YCXL

cancellation and reinstate log for the reservation (if a res is cancelled, yres\_resstatus must be 3 (not affecting availability))

Field Name	Type	Length	Decimals	Not NULL	
YCXL_ID	NUMBER	30		N	YCXL_ID identifies YCXL
YCXL_YCLR_ID	NUMBER	30		N	Selected cancellation reason from YCLR. The YCXL_REASON is defaulting to YCLR_LONGDESC of the selected cancellation reason. But can be overridden.
YCXL_CANCELORREINSTATE	NUMBER	1		N	cancellation (1) or reinstate(0)
YCXL_REASON	VARCHAR2	200		Y	The text for YCXL_REASON is defaulting from YCLR_LONGDESC but can be overwritten by the user.
YCXL_YRES_ID	NUMBER	30		Y	YCXL_YRES_ID is of YCXL
YCXL_YBOM_ID	NUMBER	30		Y	YCXL_YBOM_ID is of YCXL
YCXL_ORG_RESSTATUS	NUMBER	1		Y	When a cancellation is performed we store here the original YRES_RESSTATUS. When reinstating the reservation we come up with this reservation status (ten. or definite) again.
YCXL_DATE	DATE			N	Fidelio Date when cancelation or reinstate was performed
YCXL_PCDATE	DATE			N	PC Date when cancelation or reinstate was performed
YCXL_NUMBER	VARCHAR2	30		Y	Cancellation number (random)
YCXL_YLTO_ID	NUMBER	30		Y	YCXL_YLTO_ID is of YCXL
YCXL_XCMS_ID	NUMBER	30		Y	Profile ID of user performed this action
YCXL_TYPE	NUMBER	1		Y	1=Conference, 2=Rooms (only valid if YBOM ID is filled)
YCXL_ORGNOAVAILREASON	NUMBER	1		Y	backup noavailreason

## YDDK

doors the guest will have keys for. this will be filled if the hotel wants to track keys and not just to make them

Field Name	Type	Length	Decimals	Not NULL	
YDDK_ID	NUMBER	30		N	YDDK_ID identifies YDDK
YDDK_YDET_ID	NUMBER	30		N	YDDK_YDET_ID is of YDDK
YDDK_YDOR_ID	NUMBER	30		N	YDDK_YDOR_ID is of YDDK

## YDEP

Deposit table (used for reservations and conference (sales) bookings)

Field Name	Type	Length	Decimals	Not NULL	
YDEP_ID	NUMBER	30		N	YDEP_ID identifies YDEP
YDEP_YRES_ID	NUMBER	30		Y	YDEP_YRES_ID is of YDEP
YDEP_YBOM_ID	NUMBER	30		Y	Link to Booking Master
YDEP_TOTAL_RMS	NUMBER	30	4	Y	Total requested deposit for Rooms
YDEP_AMOUNT_RMS	NUMBER	30	4	Y	Requested Deposit installment Rooms
YDEP_PERCENTAGE_RMS	NUMBER	3		Y	Requested percentage rooms
YDEP_DUEDATE_RMS	DATE			Y	YDEP_DUEDATE_RMS is of YDEP
YDEP_PAID_RMS	NUMBER	1		Y	Deposit (rooms) paid? 1=Yes, 0=No
YDEP_TOTAL_CONF	NUMBER	30	4	Y	Total requested deposit for conferences
YDEP_AMOUNT_CONF	NUMBER	30	4	Y	Deposit installment for conferences
YDEP_PERCENTAGE_CONF	NUMBER	3		Y	Deposit percentage for conferences
YDEP_DUEDATE_CONF	DATE			Y	Due Date for conferences
YDEP_PAID_CONF	NUMBER	1		Y	Deposit (conference) paid? 1=Yes, 0=No
YDEP_TYPE	NUMBER	1		Y	1 = Conference Deposit   2 = Rooms Deposit
YDEP_WMLG_ID	NUMBER	30		Y	YDEP_WMLG_ID is of YDEP
YDEP_AUTO	NUMBER	1		Y	INDICATING IF IT WAS AUTOMATICALLY CREATED BY A POLICY

## YDER

real rooms in case of a suite

Field Name	Type	Length	Decimals	Not NULL	
YDER_ID	NUMBER	30		N	YDER_ID identifies YDER
YDER_YDET_ID	NUMBER	30		N	YDER_YDET_ID is of YDER
YDER_YRMS_ID	NUMBER	30		N	YDER_YRMS_ID is of YDER

## YDET

YDET contains all reservation details on a daily basis.

Field Name	Type	Length	Decimals	Not NULL	
YDET_ID	NUMBER	30		N	YDET_ID is the unique identifier of YDET.
YDET_YRES_ID	NUMBER	30		N	YDET_YRES_ID is the link to the reservation header in YRES.
YDET_DATE	DATE			N	YDET_DATE is the date field.
YDET_YRCH_ID	NUMBER	30		Y	Link to rate code table.
YDET_XCMA_ID	NUMBER	30		Y	Link to market code.
YDET_ADULTNO	NUMBER	3		Y	Number of adults
YDET_NOOFROOMS	NUMBER	3		Y	Number of rooms for this night.
YDET_SHARENUM	NUMBER	30		Y	Share number (sharing reservation details have the same number)
YDET_YRMS_ID	NUMBER	30		Y	YDET_YRMS_ID is the link to rooms setup database.
YDET_YCAT_ID	NUMBER	30		N	YDET_YCAT_ID is the link to room type setup database.
YDET_YCAT_ID_RATE	NUMBER	30		N	room type the room charge calculation is based on
YDET_YBLD_ID	NUMBER	30		Y	YDET_YBLD_ID is of YDET
YDET_YGRP_ID	NUMBER	30		Y	YDET_YGRP_ID is of YDET
YDET_EXPROOMMOVETIME	DATE			Y	YDET_EXPROOMMOVETIME is of YDET
YDET_ACTROOMMOVETIME	DATE			Y	YDET_ACTROOMMOVETIME is of YDET
YDET_RATEAMOUNT	NUMBER	30	4	Y	some kind of rate amount (needs to be discussed)
YDET_RATEDIFF	NUMBER	30	4	Y	Used for manual rate differences.The entered amount is added to YDET_RATEAMOUNT
YDET_RATEMANUAL	NUMBER	30	4	Y	This is i.e. the contracted rate, this amount overwrites YDET_RATEAMOUNT if not null. In this case RATEDIFF and RATEDISCOUNTPERC are emptied.
YDET_FOREIGNRATEAMOUNT	NUMBER	30	4	Y	YDET_FOREIGNRATEAMOUNT is of YDET
YDET_FOREIGNRATEDIFF	NUMBER	30	4	Y	YDET_FOREIGNRATEDIFF is of YDET
YDET_FOREIGNRATEMANUAL	NUMBER	30	4	Y	YDET_FOREIGNRATEMANUAL is of YDET
YDET_NETAMOUNT	NUMBER	30	4	Y	YDET_NETAMOUNT is of YDET
YDET_NETFOREIGNAMOUNT	NUMBER	30	4	Y	YDET_NETFOREIGNAMOUNT is of YDET
YDET_BREAKFAST	NUMBER	1		Y	YDET_BREAKFAST is of YDET
YDET_LUNCH	NUMBER	1		Y	YDET_LUNCH is of YDET
YDET_DINNER	NUMBER	1		Y	YDET_DINNER is of YDET
YDET_RATEMODIFIER	NUMBER	30	4	Y	YDET_RATEMODIFIER is of YDET
YDET_FOREIGNRATEMODIFIER	NUMBER	30	4	Y	YDET_FOREIGNRATEMODIFIER is of YDET
YDET_YFRN_ID	NUMBER	30		Y	Link to Free Nights table
YDET_SUITE_YCAT_ID	NUMBER	30		Y	
YDET_SUITE_YRMS_ID	NUMBER	30		Y	
YDET_NODISCOUNTPACKAGE	NUMBER	30	4	N	

### YDET

YDET contains all reservation details on a daily basis.

Field Name	Type	Length	Decimals	Not NULL	
YDET_FOREIGNNODISCOUNTPACK AGE	NUMBER	30	4	N	
YDET_BLOCKPRICE	NUMBER	1		Y	1= manual price comes from block price config
YDET_FINALAMOUNT	NUMBER	30	4	N	Total amount with discounts applied
YDET_FINALFOREIGNAMOUNT	NUMBER	30	4	Y	Total foreign amount with discounts applied
YDET_RATEDISCOUNTPERC	NUMBER	5	2	Y	

### YDOR

Doors

Field Name	Type	Length	Decimals	Not NULL	
YDOR_ID	NUMBER	30		N	YDOR_ID identifies YDOR
YDOR_LONGDESC	NUMBER	30		N	YDOR_LONGDESC is of YDOR
YDOR_ROOMA_YRMS_ID	NUMBER	30		N	a room that the door is linked to. equivalent to roomb but not null because at least one room should be assigned.
YDOR_ROOMB_YRMS_ID	NUMBER	30		Y	a room that the door is linked to. equivalent to rooma but this can be null because one room is enough to link to the door
YDOR_MAKEKEYBYDEFAULT	NUMBER	1		N	the guest will get keys for all flagged doors linked to the room. can be changed by user of course

### YDRC

Loooong descriptions for rooms and room types

Field Name	Type	Length	Decimals	Not NULL	
YDRC_ID	NUMBER	30		N	
YDRC_WLAN_ID	NUMBER	30		Y	
YDRC_YRMS_ID	NUMBER	30		Y	
YDRC_YCAT_ID	NUMBER	30		Y	
YDRC_DESC	VARCHAR2	2000		Y	

### YEBD

Stores combination rooms and part of combinations (dummy)

Field Name	Type	Length	Decimals	Not NULL	
YEBD_ID	NUMBER	30		N	Unique internal ID
YEBD_YEBS_ID	NUMBER	30		N	link to resource record
YEBD_YFSC_ID	NUMBER	30		N	contains ID of linked function space

## YEBR

booked resources for the event

Field Name	Type	Length	Decimals	Not NULL	
YEBR_ID	NUMBER	30		N	YEBR_ID identifies YEBR
YEBR_YEVM_ID	NUMBER	30		Y	link to event (yebr_ydet_id must be empty)
YEBR_YDET_ID	NUMBER	30		Y	link to reservation detail (yebr_yevm_id must be empty)
YEBR_YCIT_ID	NUMBER	30		N	YEBR_YCIT_ID is of YEBR
YEBR_YCIR_ID	NUMBER	30		Y	YEBR_YCIR_ID is of YEBR
YEBR_YCIA_ID	NUMBER	30		Y	YEBR_YCIA_ID is of YEBR
YEBR_QUANTITY	NUMBER	5		N	YEBR_QUANTITY is of YEBR
YEBR_EXTERNALORDER	NUMBER	1		Y	YEBR_EXTERNALORDER is of YEBR
YEBR_STARTTIME	DATE			Y	YEBR_STARTTIME is of YEBR
YEBR_ENDTIME	DATE			Y	YEBR_ENDTIME is of YEBR
YEBR_SETUPTIME	NUMBER	4		Y	IN MINUTES
YEBR_SETDOWNTIME	NUMBER	4		Y	IN MINUTES
YEBR_MANUALPRICE	NUMBER	30	4	Y	YEBR_MANUALPRICE is of YEBR
YEBR_SOURCE_XCMS_ID	NUMBER	30		Y	YEBR_SOURCE_XCMS_ID is of YEBR
YEBR_NAME	VARCHAR2	60		Y	Name
YEBR_PKGINCL	NUMBER	1		Y	Included in Package? 0=No, 1=Yes
YEBR_ZDCO_ID	NUMBER	30		Y	Booked Misc Resources - Department code link
YEBR_POSTTYPE	NUMBER	1		Y	YEBR_POSTTYPE is of YEBR
YEBR_DISPLORDER	NUMBER	3		Y	Misc. Items Display Order
YEBR_PERHOUR	NUMBER	1		Y	1= hourly charge of rate
YEBR_REBATE_PERC	NUMBER	3		Y	Percentage of rebate
YEBR_ORG_MANUALPRICE	NUMBER	30	4	Y	Original price
YEBR_REBATE_FLAT	NUMBER	30	4	Y	Rebate flat amount
YEBR_REBATE_UNITPRICE	NUMBER	30	4	Y	Rebate per unit price
YEBR_DESCRIPTION	VARCHAR2	500		Y	Misc. Item description
YEBR_COSTPRICE	NUMBER	30	4	Y	Cost Price
YEBR_NOOFPAX	NUMBER	1		Y	Per Person 1=Yes
YEBR_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YEBR_MERGEDTO_YEBR_ID	NUMBER	30		Y	Merged to catering item ID
YEBR_PRICE_NET	NUMBER	30	4	Y	Catering Item net value
YEBR_PRICE_VAT	NUMBER	30	4	Y	Catering Item tax value

### YEBS

Booked function spaces

Field Name	Type	Length	Decimals	Not NULL	
YEBS_ID	NUMBER	30		N	Unique ID for booked function spaces
YEBS_YEVM_ID	NUMBER	30		N	Link to event
YEBS_YFSC_ID	NUMBER	30		N	Link to booked function space
YEBS_YFSR_ID	NUMBER	30		Y	Link to booked function space rate
YEBS_YSSL_ID	NUMBER	30		Y	Link to booked seating arrangement
YEBS_SETUPTIME	NUMBER	3		Y	Setup time of booked function space (in minutes)
YEBS_SETDOWNTIME	NUMBER	3		Y	Setdown time of booked function space (in minutes)
YEBS_STARTTIME	DATE			N	Start time of booked function space
YEBS_ENDTIME	DATE			N	End time of booked function space
YEBS_SPECIALRATE	NUMBER	30	4	Y	Special Rate for booked Function Space
YEBS_DONTMOVE	NUMBER	1		Y	Do not move (0=No, 1=Yes)
YEBS_PKGINCL	NUMBER	1		Y	included in package? 0=No, 1=Yes
YEBS_SHAREABLE	NUMBER	1		Y	YEBS_SHAREABLE is of YEBS
YEBS_ZDCO_ID	NUMBER	30		N	Booked Function Spaces - Department code link
YEBS_POSTTYPE	NUMBER	1		Y	YEBS_POSTTYPE is of YEBS
YEBS_PRIORITY	NUMBER	3		Y	Event Waitlist priority
YEBS_RPDW_ID	NUMBER	30		Y	Link to Roomplanner drawing
YEBS_PERHOUR	NUMBER	1		Y	1= hourly charge of rate
YEBS_REBATE_PERC	NUMBER	3		Y	Percentage of rebate
YEBS_ORG_SPECIALRATE	NUMBER	30	4	Y	Original rate
YEBS_REBATE_FLAT	NUMBER	30	4	Y	Rebate flat amount
YEBS_COSTPRICE	NUMBER	30	4	Y	Cost price
YEBS_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YEBS_MERGEDTO_YEBS_ID	NUMBER	30		Y	Merged to function space ID
YEBS_MERGEDFLAG	NUMBER	3		Y	0-booked by package; 1-created by merge functionality
YEBS_DISPLORDER	NUMBER	3		Y	Display order
YEBS_STARTDATE	DATE			Y	Start date
YEBS_ENDDATE	DATE			Y	End date
YEBS_PRICE_NET	NUMBER	30	4	Y	Function Space net value
YEBS_PRICE_VAT	NUMBER	30	4	Y	Function Space tax value

## YECF

User defined fields for CCM Events

Field Name	Type	Length	Decimals	Not NULL	
YECF_ID	NUMBER	30		N	Unique ID
YECF_YEVM_ID	NUMBER	30		N	Link to CCM Events

## YEFC

Event Defaults

Field Name	Type	Length	Decimals	Not NULL	
YEFC_ID	NUMBER	30		N	Unique ID
YEFC_VALIDFROM	DATE			N	Event Forecast valid from (date)
YEFC_VALIDTO	DATE			N	Event Forecast valid to
YEFC_EVENTSTARTTIME	DATE			Y	Enter default event start time
YEFC_EVENTENDTIME	DATE			Y	Enter default event end time
YEFC_YETY_ID	NUMBER	30		N	Contains link to event type

## YELA

List of Attendees for CCM Events

Field Name	Type	Length	Decimals	Not NULL	
YELA_ID	NUMBER	30		N	Unique Code
YELA_YBLA_ID	NUMBER	30		N	Link to List of Attendees for Bookings
YELA_YEVM_ID	NUMBER	30		N	Link to Event

## YEMD

Event Default Details

Field Name	Type	Length	Decimals	Not NULL	
YEMD_ID	NUMBER	30		N	YEMD_ID identifies YEMD
YEMD_YEFC_ID	NUMBER	30		N	Link to Event Defaults
YEMD_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YEMD_AMOUNTPERPERSON	NUMBER	30	4	Y	Expected per person
YEMD_FLATRATE	NUMBER	30	4	Y	Expected flat rate
YEMD_ZDCO_ID	NUMBER	30		Y	Link to department code

### YEMI

Booked Menu Items

Field Name	Type	Length	Decimals	Not NULL	
YEMI_ID	NUMBER	30		N	Unique ID of booked menu item
YEMI_YEVM_ID	NUMBER	30		N	Link to event
YEMI_YEMN_ID	NUMBER	30		Y	if null, the item is not linked to a menu
YEMI_YCMI_ID	NUMBER	30		Y	Link to menu item category
YEMI_PRICE	NUMBER	30	4	Y	Price of booked menu item
YEMI_INCLUDEDINTHEMENU	NUMBER	1		Y	menu item is included in the price of the menu or not (meaningful only if yemn_id is not null
YEMI_NAME	VARCHAR2	55		Y	Name
YEMI_QUANTITY	NUMBER	30	4	Y	Quantity
YEMI_COURSE	NUMBER	3		Y	Course for booked menu items
YEMI_COURSEORDER	NUMBER	3		Y	course order for booked menu items
YEMI_ORIGIN	VARCHAR2	100		Y	Origin
YEMI_MINIMUMAMOUNT	NUMBER	4		Y	Sell minimum amount
YEMI_MAXIMUMAMOUNT	NUMBER	4		Y	Sell maximum amount
YEMI_PORTION	VARCHAR2	30		Y	Portion
YEMI_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YEMI_LONGDESC2	VARCHAR2	55		Y	YEMI_LONGDESC2 is of YEMI
YEMI_LONGDESC3	VARCHAR2	55		Y	YEMI_LONGDESC3 is of YEMI
YEMI_LONGDESC4	VARCHAR2	55		Y	YEMI_LONGDESC4 is of YEMI
YEMI_ORIGIN2	VARCHAR2	55		Y	YEMI_ORIGIN2 is of YEMI
YEMI_ORIGIN3	VARCHAR2	55		Y	YEMI_ORIGIN3 is of YEMI
YEMI_VINTAGE	VARCHAR2	4		Y	Vintage (for beverage items only).
YEMI_FOODORBEVERAGE	NUMBER	1		Y	YEMI_FOODORBEVERAGE is of YEMI
YEMI_ZDCO_ID	NUMBER	30		N	Menu Items - Department code link
YEMI_DESCRIPTION	LONG			Y	YEMI_DESCRIPTION is of YEMI
YEMI_YOUT_ID	NUMBER	30		Y	Link with outlet
YEMI_COSTPRICE	NUMBER	30	4	Y	Cost price
YEMI_REBATE_PERC	NUMBER	3		Y	Percentage of rebate
YEMI_ORG_PRICE	NUMBER	30	4	Y	Original price
YEMI_REBATE_FLAT	NUMBER	30	4	Y	Rebate flat amount
YEMI_REBATE_UNITPRICE	NUMBER	30	4	Y	Rebate unit price
YEMI_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YEMI_MERGEDTO_YEMI_ID	NUMBER	30		Y	Merged to menu item ID
YEMI_PRICE_NET	NUMBER	30	4	Y	Menu item net value

### YEMI

Booked Menu Items

Field Name	Type	Length	Decimals	Not NULL	
YEMI_PRICE_VAT	NUMBER	30	4	Y	Menu item tax value

### YEMN

Booked menus for events

Field Name	Type	Length	Decimals	Not NULL	
YEMN_ID	NUMBER	30		N	Unique ID for booked menu
YEMN_YEVM_ID	NUMBER	30		Y	Link to event
YEMN_MENUNAME	VARCHAR2	50		Y	Menu name
YEMN_CHARGEDONCONSUMPTION	NUMBER	1		Y	Charged on consumption
YEMN_MENUPRICE	NUMBER	30	4	Y	Menu Price
YEMN_QUANTITY	NUMBER	5		Y	Quantity of booked menus
YEMN_COMPLIMENTARY	NUMBER	5		Y	number of complimentary menus
YEMN_EXPECTEDNOOFPEOPLE	NUMBER	5		Y	Expected number of people (menu)
YEMN_GUARANTEEDNOOFPEOPLE	NUMBER	5		Y	Guaranteed number of people (menu)
YEMN_NOOFSETS	NUMBER	5		Y	Set number of people (menu)
YEMN_YSME_ID	NUMBER	30		Y	Link to menu (from configuration)
YEMN_SERVESTART	DATE			Y	Serve start of booked menu
YEMN_SERVEEND	DATE			Y	Serve end of booked menu
YEMN_GRATUITYINCLUDED	NUMBER	1		Y	YEMN_GRATUITYINCLUDED is of YEMN
YEMN_PKGINCL	NUMBER	1		Y	Included in package? 0=No, 1=Yes
YEMN_ZDCO_ID	NUMBER	30		Y	Booked Standard Menus - Department code link
YEMN_POSTTYPE	NUMBER	1		Y	YEMN_POSTTYPE is of YEMN
YEMN_DISPLORDER	NUMBER	3		Y	Standard Menu Display Order
YEMN_YOUT_ID	NUMBER	30		Y	Link to outlets
YEMN_DESCRIPTION	VARCHAR2	500		Y	Std. Menu description
YEMN_COSTPRICE	NUMBER	30	4	Y	Cost Price
YEMN_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YEMN_MERGEDTO_YEMN_ID	NUMBER	30		Y	Merged to standard menu ID
YEMN_POSTGUARANTEED	NUMBER	1		Y	1 - Post guaranteed number of attendees

## YESN

Event status next possible status link

Field Name	Type	Length	Decimals	Not NULL	
YESN_ID	NUMBER	30		N	Unique ID
YESN_CURRENT_YEST_ID	NUMBER	30		N	Contains ID of current status
YESN_NEXT_YEST_ID	NUMBER	30		N	Contains ID of next possible status

## YEST

Booking status Defines whether or not this status is a cancellation status (such as CAN or LOS). 0=No, 1=Yes

Field Name	Type	Length	Decimals	Not NULL	
YEST_ID	NUMBER	30		N	Unique status ID
YEST_SHORTDESC	VARCHAR2	3		N	Status short description
YEST_LONGDESC	VARCHAR2	30		N	Status long description
YEST_DISPLORDER	NUMBER	3		Y	Status display order
YEST_ALLOWWAITLIST	NUMBER	1		N	Waitlist status
YEST_ALLOWCREATION	NUMBER	1		N	Allow creation
YEST_WCOL_ID	NUMBER	30		Y	Contains link to colour table.
YEST_DEDUCTINVENTORY	NUMBER	1		N	Deduct from inventory
YEST_CANLINKTOYBOM	NUMBER	1		N	Booking Master status
YEST_CANLINKTOYEVN	NUMBER	1		N	Event status
YEST_DISPLAYINDIARY	NUMBER	1		Y	Display status in diary
YEST_POSTREVENUE	NUMBER	1		Y	Post Forecast   1= Yes filled by default
YEST_POSTFORECAST	NUMBER	1		Y	Post Expected   1= Yes
YEST_CANCELSTATUS	NUMBER	1		N	YEST_CANCELSTATUS is of YEST
YEST_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YEST_AVAAILDISP	NUMBER	1		Y	1=DEF, 2=TEN, 0=Others
YEST_YRES_STATUS	NUMBER	1		Y	CCM booking status <-> YRES reservation status
YEST_WEBSTATUS	NUMBER	1		Y	0=No 1=Yes
YEST_WEBNAME	VARCHAR2	30		Y	Status Name to display for web bookings

## YETB

Booked Event Groups

Field Name	Type	Length	Decimals	Not NULL	
YETB_ID	NUMBER	30		N	Booked Event group ID
YETB_YBOM_ID	NUMBER	30		N	Linked Booking ID

### YETB

Booked Event Groups

Field Name	Type	Length	Decimals	Not NULL	
YETB_YETG_ID	NUMBER	30		N	Event group ID
YETB_NAME	VARCHAR2	60		Y	Booked Event group Name
YETB_NOOFATTENDEES	NUMBER	5		Y	Booked Event group Number of Attendees
YETB_STARTTIME	DATE			Y	Booked Event group Start Date
YETB_ENDTIME	DATE			Y	Booked Event group End Date
YETB_COPIEDFROM_YETB_ID	NUMBER	30		Y	Booked Event group copied ID
YETB_DISPLORDER	NUMBER	30		Y	Event group display order
YETB_ALTERNATIVE	NUMBER	1		Y	Alternative=1

### YETE

Event Group Events

Field Name	Type	Length	Decimals	Not NULL	
YETE_ID	NUMBER	30		N	Event group Event ID
YETE_YETG_ID	NUMBER	30		N	Event group ID
YETE_YETY_ID	NUMBER	30		Y	Event Status ID
YETE_STARTTIME	DATE			Y	Start time
YETE_ENDTIME	DATE			Y	End time
YETE_FROMDAY	NUMBER	3		Y	Start day
YETE_TODAY	NUMBER	3		Y	End day
YETE_ZDCO_ID	NUMBER	30		Y	Department code ID
YETE_MASTER_YETE_ID	NUMBER	30		Y	Master Event ID

### YETF

Event Group Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YETF_ID	NUMBER	30		N	Function Space ID
YETF_YETE_ID	NUMBER	30		N	Event group ID
YETF_YFSC_ID	NUMBER	30		N	Linked Function Space ID
YETF_YFSR_ID	NUMBER	30		Y	Linked Function Space Rate ID
YETF_YSSL_ID	NUMBER	30		Y	Linked Function Space Seating ID
YETF_RATE	NUMBER	30	4	Y	function space rate
YETF_PERHOUR	NUMBER	1		Y	function space rate

### YETF

Event Group Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YETF_ZDCO_ID	NUMBER	30		Y	Linked Department Code

### YETG

Event Groups

Field Name	Type	Length	Decimals	Not NULL	
YETG_ID	NUMBER	30		N	Event Group ID
YETG_SHORTDESC	VARCHAR2	3		Y	Event group short description
YETG_NAME	VARCHAR2	60		Y	Event group name
YETG_VALIDFROM	DATE			Y	Event group valid start date
YETG_VALIDTO	DATE			Y	Event group valid end date
YETG_DISPLORDER	NUMBER	3		Y	Event group display order
YETG_INACTIVE	NUMBER	1		Y	Event group inactive flag

### YETM

Event Group Std. Menus

Field Name	Type	Length	Decimals	Not NULL	
YETM_ID	NUMBER	30		N	Standard Menu ID
YETM_YETE_ID	NUMBER	30		N	Linked Event group ID
YETM_YSME_ID	NUMBER	30		N	Linked Standard Menu ID
YETM_YSMR_ID	NUMBER	30		Y	Linked Rate ID
YETM_QUANTITY	NUMBER	5		Y	Quantity
YETM_RATE	NUMBER	30	4	Y	standard menu rate
YETM_FOOD_ZDCO_ID	NUMBER	30		Y	Linked Department Code
YETM_BEVERAGE_ZDCO_ID	NUMBER	30		Y	Linked Department Code
YETM_FOOD_RATE	NUMBER	30	4	Y	Linked Department Code
YETM_BEVERAGE_RATE	NUMBER	30	4	Y	Linked Department Code
YETM_CHARGEDONCONSUMPTION	NUMBER	1		Y	Charged on consumption

### YETR

Event Group Misc. Items

Field Name	Type	Length	Decimals	Not NULL	
YETR_ID	NUMBER	30		N	Misc. Item ID

### YETR

Event Group Misc. Items

Field Name	Type	Length	Decimals	Not NULL	
YETR_YETE_ID	NUMBER	30		N	Linked Event group ID
YETR_YCIT_ID	NUMBER	30		N	Linked Catering Item ID
YETR_YCIA_ID	NUMBER	30		Y	Linked Attributes ID
YETR_YCIR_ID	NUMBER	30		Y	Linked Rate ID
YETR_QUANTITY	NUMBER	5		Y	Quantity
YETR_RATE	NUMBER	30	4	Y	catering item rate
YETR_PERHOUR	NUMBER	1		Y	catering item rate
YETR_ZDCO_ID	NUMBER	30		Y	Linked Department Code
YETR_NOOFPAX	NUMBER	1		Y	1=yes

### YETS

Link Functions Spaces / Event Types

Field Name	Type	Length	Decimals	Not NULL	
YETS_ID	NUMBER	30		N	Unique ID
YETS_YETY_ID	NUMBER	30		N	Link to Event Types
YETS_YFSC_ID	NUMBER	30		N	Link to Function Spaces

### YETY

Event Types

Field Name	Type	Length	Decimals	Not NULL	
YETY_ID	NUMBER	30		N	Unique Event Type ID
YETY_SHORTDESC	VARCHAR2	3		N	Event Type short description
YETY_LONGDESC	VARCHAR2	30		N	Event Type Long description
YETY_DISPLORDER	NUMBER	3		Y	Event Type Display Order
YETY_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YETY_WEBSTATUS	NUMBER	1		Y	0=No 1=Yes
YETY_ROLE	NUMBER	1		Y	0 = none; 1 = Breakfast; 2 = Lunch; 3 = Dinner; 4 = Coffee Break
YETY_YCWI_ID	NUMBER	30		Y	Linked to web config

### YEVN

Event Main Table

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YEVM

Event Main Table

Field Name	Type	Length	Decimals	Not NULL	
YEVM_ID	NUMBER	30		N	Unique Event ID
YEVM_YBOM_ID	NUMBER	30		N	Contains link to Booking Master
YEVM_YETY_ID	NUMBER	30		N	Contains link to event type
YEVM_YEST_ID	NUMBER	30		N	Contains link to status
YEVM_NAME	VARCHAR2	60		N	Event Name
YEVM_NOOFATTENDEES	NUMBER	5		Y	No of attendees
YEVM_MINIMUMGUARANTEE	NUMBER	5		Y	Minimum number of guaranteed attendees
YEVM_STARTTIME	DATE			N	Event date and start time
YEVM_ENDTIME	DATE			N	Event end date and time
YEVM_DOORCARD	VARCHAR2	60		Y	name of event that is written on onformation signs in the hotel
YEVM_MASTER_YEVM_ID	NUMBER	30		Y	ID of master event
YEVM_NOISY	NUMBER	1		Y	the event will be loud (like a birthday party)
YEVM_NOOFACTUALATTENDEES	CHAR			Y	Number of actual attendees
YEVM_PKGINCL	NUMBER	1		Y	Included in Package? 0=No, 1=Yes
YEVM_YPKD_ID	NUMBER	30		Y	YEVM_YPKD_ID is of YEVM
YEVM_DOORCARD_PROF	VARCHAR2	100		Y	Doorcard for Profile, will be used if Profile Name is different from entered profile in Booking
YEVM_DISPLORDER	NUMBER	3		Y	Event display order
YEVM_YETB_ID	NUMBER	30		Y	Event group link ID
YEVM_ALTERNATIVE	NUMBER	1		Y	Alternative=1
YEVM_MERGEDTO_YEVM_ID	NUMBER	30		Y	Package event id to which current package event gets merged
YEVM_STARTDATE	DATE			Y	Speed purpose
YEVM_MANUALDISPLORDER	NUMBER	1		Y	Display order manually changed by user

### YFAL

reservation - financial account link

Field Name	Type	Length	Decimals	Not NULL	
YFAL_ID	NUMBER	30		N	
YFAL_YRES_ID	NUMBER	30		N	
YFAL_ZFAC_ID	NUMBER	30		N	
YFAL_ROLE	NUMBER	1		N	0=prearrival 1=postdeparture

### YFBK

Facebook accounts table

Field Name	Type	Length	Decimals	Not NULL
YFBK_OBJECT_ID	VARCHAR2	30		N
YFBK_NAME	VARCHAR2	100		Y
YFBK_ACCESSTOKEN	VARCHAR2	400		Y
YFBK_TYPE	NUMBER	1		Y
YFBK_LASTUSED	NUMBER	1		Y
YFBK_LASTLOGIN	DATE			Y
YFBK_DISPLORDER	NUMBER	2		Y

### YFCA

NOT USED ANYMORE

Field Name	Type	Length	Decimals	Not NULL	
YFCA_ID	NUMBER	30		N	Unique ID
YFCA_SHORTDESC	VARCHAR2	3		N	YFCA_SHORTDESC is of YFCA
YFCA_LONGDESC	VARCHAR2	30		N	YFCA_LONGDESC is of YFCA
YFCA_DISPLORDER	NUMBER	3		Y	YFCA_DISPLORDER is of YFCA
YFCA_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YFCA_ZDCO_ID	NUMBER	30		Y	Link to department codes

### YFCB

Link Standard Menu Rates to Department Codes

Field Name	Type	Length	Decimals	Not NULL	
YFCB_ID	NUMBER	30		N	YFCB_ID identifies YFCB
YFCB_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YFCB_AMOUNT	NUMBER	30	4	N	YFCB_AMOUNT is of YFCB
YFCB_TYPE	NUMBER	1		N	1 = Forecast Split
YFCB_YSMR_ID	NUMBER	30		Y	YFCB_YSMR_ID is of YFCB
YFCB_ZDCO_ID	NUMBER	30		N	Link to department code

### YFCC

Function Space Capacity Category

Field Name	Type	Length	Decimals	Not NULL	
YFCC_ID	NUMBER	30		N	Unique Function Space capacity category ID

### YFCC

Function Space Capacity Category

Field Name	Type	Length	Decimals	Not NULL	
YFCC_SHORTDESC	VARCHAR2	3		N	Short description
YFCC_LONGDESC	VARCHAR2	30		N	Long description
YFCC_DISPLORDER	NUMBER	3		Y	Display order
YFCC_VALUE	NUMBER	4		N	higher value of the range

### YFCO

Table of YFCO

Field Name	Type	Length	Decimals	Not NULL	
YFCO_ID	NUMBER	30		N	Unique identifier
YFCO_NAME	VARCHAR2	30		Y	Custom order name

### YFLC

room feature link to customer

Field Name	Type	Length	Decimals	Not NULL	
YFLC_ID	NUMBER	30		N	YFLC_ID identifies YFLC
YFLC_YRFT_ID	NUMBER	30		N	YFLC_YRFT_ID is of YFLC
YFLC_XCMS_ID	NUMBER	30		N	YFLC_XCMS_ID is of YFLC

### YFLR

room feature link to room

Field Name	Type	Length	Decimals	Not NULL	
YFLR_ID	NUMBER	30		N	YFLR_ID identifies YFLR
YFLR_YRFT_ID	NUMBER	30		N	YFLR_YRFT_ID is of YFLR
YFLR_YRMS_ID	NUMBER	30		N	YFLR_YRMS_ID is of YFLR

### YFLS

room feature link to reservation

Field Name	Type	Length	Decimals	Not NULL	
YFLS_ID	NUMBER	30		N	YFLS_ID identifies YFLS
YFLS_YRFT_ID	NUMBER	30		N	YFLS_YRFT_ID is of YFLS
YFLS_YRES_ID	NUMBER	30		N	YFLS_YRES_ID is of YFLS

### YFMI

Table of YFMI

Field Name	Type	Length	Decimals	Not NULL	
YFMI_ID	NUMBER	30		N	Unique Identifier
YFMI_YFSC_ID	NUMBER	30		N	linked function space id
YFMI_YCIT_ID	NUMBER	30		N	linked Misc item id
YFMI_YCIA_ID	NUMBER	30		Y	Item attribute link
YFMI_ZDCO_ID	NUMBER	30		Y	department code link
YFMI_QUANTITY	NUMBER	30	2	Y	quantity of misc. item
YFMI_NOOFPAX	NUMBER	1		Y	Per Person 1=Yes

### YFMR

default misc. item rates

Field Name	Type	Length	Decimals	Not NULL	
YFMR_ID	NUMBER	30		N	unique id
YFMR_YFMI_ID	NUMBER	30		N	link to default misc. items
YFMR_YCIR_ID	NUMBER	30		Y	link to misc. item rates
YFMR_PRICE	NUMBER	30	4	Y	default misc. item rate

### YFOR

Formulas

Field Name	Type	Length	Decimals	Not NULL	
YFOR_ID	NUMBER	30		N	
YFOR_SHORTDESC	VARCHAR2	10		N	
YFOR_LONGDESC	VARCHAR2	30		N	
YFOR_FORMULA	VARCHAR2	2000		N	
YFOR_INACTIVE	NUMBER	1		Y	
YFOR_DISPLORDER	VARCHAR2	3		Y	
YFOR_CATEGORY	NUMBER	1		Y	

### YFRD

Function Space Rate definition

Field Name	Type	Length	Decimals	Not NULL	
YFRD_ID	NUMBER	30		N	YFRD_ID identifies YFRD
YFRD_SHORTDESC	VARCHAR2	3		N	Function space rate code (e.g. FUL)

## YFRD

Function Space Rate definition

Field Name	Type	Length	Decimals	Not NULL	
YFRD_LONGDESC	VARCHAR2	30		N	Function space rate name (e.g. Full day)
YFRD_DESCRIPTION	VARCHAR2	60		Y	Rate description (e.g. valid 09.00 - 18.00)
YFRD_DISPLORDER	NUMBER	3		Y	YFRD_DISPLORDER is of YFRD
YFRD_INACTIVE	NUMBER	1		Y	1 = inactive

## YFRE

Future Reservation Extracts for Master Hotel

Field Name	Type	Length	Decimals	Not NULL	
YFRE_ID	NUMBER	30		N	Unique ID
YFRE_WPHS_ID	NUMBER	30		N	Link to Partner Hotels
YFRE_UPLOADTIME	DATE			N	YFRE_UPLOADTIME is of YFRE
YFRE_ARRIVAL	DATE			N	YFRE_ARRIVAL is of YFRE
YFRE_DEPARTURE	DATE			N	YFRE_DEPARTURE is of YFRE
YFRE_XCMS_GLOBALID	NUMBER	30		N	Global ID
YFRE_ROOMTYPE	VARCHAR2	10		Y	YFRE_ROOMTYPE is of YFRE
YFRE_ROOM	VARCHAR2	10		Y	YFRE_ROOM is of YFRE
YFRE_DAYPRICE	NUMBER	30	4	N	YFRE_DAYPRICE is of YFRE
YFRE_TOTALSTAYPRICE	NUMBER	30	4	N	YFRE_TOTALSTAYPRICE is of YFRE
YFRE_NOOFROOMS	NUMBER	3		N	YFRE_NOOFROOMS is of YFRE
YFRE_NOOFADULTS	NUMBER	3		N	YFRE_NOOFADULTS is of YFRE
YFRE_NOOFCHILDREN	NUMBER	3		N	YFRE_NOOFCHILDREN is of YFRE
YFRE_CREATIONTIME	DATE			N	YFRE_CREATIONTIME is of YFRE
YFRE_LASTMODTIME	DATE			N	YFRE_LASTMODTIME is of YFRE
YFRE_YRES_ID	NUMBER	30		N	Future reservations
YFRE_CRRESNR	VARCHAR2	30		Y	
YFRE_CRSSYSTEM	VARCHAR2	30		Y	
YFRE_CALCSTATUS	NUMBER	1		Y	
YFRE_NOAVAILREASON	NUMBER	1		Y	
YFRE_ACTARRTIME	DATE			Y	
YFRE_ACTDEPTIME	DATE			Y	

## YFRN

Free Nights

Field Name	Type	Length	Decimals	Not NULL	
YFRN_ID	NUMBER	30		N	YFRN_ID identifies YFRN
YFRN_ZFAC_ID	NUMBER	30		Y	WHICH REBATE CARD ZFAC CREATED. NULL IF CREATED MANUALLY
YFRN_XCMS_ID	NUMBER	30		Y	CAN BE NULL IF ZFACID IS FILLED ONLY
YFRN_NUMBER	NUMBER	30		N	YFRN_NUMBER is of YFRN
YFRN_VALIDUNTIL	DATE			Y	YFRN_VALIDUNTIL is of YFRN
YFRN_MAXADULTS	NUMBER	3		Y	YFRN_MAXADULTS is of YFRN
YFRN_TRANSFERABLE	NUMBER	1		N	0=ONLY XCMSID GIVEN HERE CAN USE IT 1=OTHERS CAN USE IT UP
YFRN_COMMENT	VARCHAR2	2000		Y	YFRN_COMMENT is of YFRN

## YFRQ

frequency definition

Field Name	Type	Length	Decimals	Not NULL	
YFRQ_ID	NUMBER	30		N	YFRQ_ID identifies YFRQ
YFRQ_DAY1	NUMBER	1		Y	YFRQ_DAY1 is of YFRQ
YFRQ_DAY2	NUMBER	1		Y	YFRQ_DAY2 is of YFRQ
YFRQ_DAY3	NUMBER	1		Y	YFRQ_DAY3 is of YFRQ
YFRQ_DAY4	NUMBER	1		Y	YFRQ_DAY4 is of YFRQ
YFRQ_DAY5	NUMBER	1		Y	YFRQ_DAY5 is of YFRQ
YFRQ_DAY6	NUMBER	1		Y	YFRQ_DAY6 is of YFRQ
YFRQ_DAY7	NUMBER	1		Y	YFRQ_DAY7 is of YFRQ
YFRQ_DAY8	NUMBER	1		Y	YFRQ_DAY8 is of YFRQ
YFRQ_DAY9	NUMBER	1		Y	YFRQ_DAY9 is of YFRQ
YFRQ_DAY10	NUMBER	1		Y	YFRQ_DAY10 is of YFRQ
YFRQ_DAY11	NUMBER	1		Y	YFRQ_DAY11 is of YFRQ
YFRQ_DAY12	NUMBER	1		Y	YFRQ_DAY12 is of YFRQ
YFRQ_DAY13	NUMBER	1		Y	YFRQ_DAY13 is of YFRQ
YFRQ_DAY14	NUMBER	1		Y	YFRQ_DAY14 is of YFRQ
YFRQ_REPEATDAYS	NUMBER	1		N	repeat dayxx fields if stay is longer than 14 days 1=yes 0=no
YFRQ_MONDAY	NUMBER	1		Y	YFRQ_MONDAY is of YFRQ
YFRQ_TUESDAY	NUMBER	1		Y	YFRQ_TUESDAY is of YFRQ
YFRQ_WEDNESDAY	NUMBER	1		Y	YFRQ_WEDNESDAY is of YFRQ
YFRQ_THURSDAY	NUMBER	1		Y	YFRQ_THURSDAY is of YFRQ
YFRQ_FRIDAY	NUMBER	1		Y	YFRQ_FRIDAY is of YFRQ

### YFRQ

frequency definition

Field Name	Type	Length	Decimals	Not NULL	
YFRQ_SATURDAY	NUMBER	1		Y	YFRQ_SATURDAY is of YFRQ
YFRQ_SUNDAY	NUMBER	1		Y	YFRQ_SUNDAY is of YFRQ
YFRQ_FIRSTDAY	NUMBER	1		Y	YFRQ_FIRSTDAY is of YFRQ
YFRQ_LASTDAY	NUMBER	1		Y	YFRQ_LASTDAY is of YFRQ
YFRQ_STARTINGDAY	NUMBER	3		Y	the first day
YFRQ_REPEATAFTERDAYS	NUMBER	3		Y	repeat n days afetr startingday
YFRQ_STARTFROMSTAYNOTVALIDINNUMBER TY	NUMBER	1		Y	1 = frequency settings apply from beginning of stay, else from beginning of validity (i.e. first day when package frequency is valid)

### YFSC

Function Space Configuration (instead of description field use generic notes table)

Field Name	Type	Length	Decimals	Not NULL	
YFSC_ID	NUMBER	30		N	Unique Function Space ID
YFSC_LONGDESC	VARCHAR2	60		N	Function Space long description
YFSC_COMBINED	NUMBER	1		N	built up by some other function spaces(1) or real function space (0/null)
YFSC_MINIMUMCAPACITY	NUMBER	4		N	Minimum capacity of function space
YFSC_MAXIMUMCAPACITY	NUMBER	4		N	Maximum capacity for function space
YFSC_SHAREABLE	NUMBER	1		N	multiple events can be int the same room (1) or not (0/null) (shareable)
YFSC_VISIBLEINDIARY	NUMBER	1		N	Function space is visible in conference diary
YFSC_YSTY_ID	NUMBER	30		Y	YFSC_YSTY_ID is of YFSC
YFSC_AREA	NUMBER	7	2	Y	important for non rectangular spaces (area)
YFSC_MINHEIGHT	NUMBER	5	2	Y	Minimum Height
YFSC_MAXHEIGHT	NUMBER	5	2	Y	Maximum Height
YFSC_WIDTH	NUMBER	5	2	Y	Width
YFSC_LENGTH	NUMBER	5	2	Y	Lenght
YFSC_MAXFLOORLOAD	NUMBER	7	2	Y	Maximal floor loading
YFSC_MINDOORWIDTH	NUMBER	5	2	Y	Minimum door width
YFSC_MINDOORHEIGHT	NUMBER	5	2	Y	Minimum door height
YFSC_MAXDOORWIDTH	NUMBER	5	2	Y	Maximum door width
YFSC_MAXDOORHEIGHT	NUMBER	5	2	Y	Maximum door height
YFSC_DESCRIPTION	VARCHAR2	60		Y	Function Space description
YFSC_YFCC_ID	NUMBER	30		Y	Contains Iink to function space capacity category
YFSC_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE

### YFSC

Function Space Configuration (instead of description field use generic notes table)

Field Name	Type	Length	Decimals	Not NULL	Description
YFSC_GENERIC_NAME	VARCHAR2	60		Y	Generic function space name that can be used on correspondence w/o giving the real name
YFSC_SHORTNAME	VARCHAR2	20		Y	Short Name for Display in Diary
YFSC_AREA_FT	NUMBER	7	2	Y	Function Space Square footage
YFSC_MINHEIGHT_FT	NUMBER	5	2	Y	Minimum height in feet
YFSC_MAXHEIGHT_FT	NUMBER	5	2	Y	Maximum height in feet
YFSC_WIDTH_FT	NUMBER	5	2	Y	Width in feet
YFSC_LENGTH_FT	NUMBER	5	2	Y	Length in feet
YFSC_MINDOORWIDTH_FT	NUMBER	5	2	Y	Minimum door with in feet
YFSC_MAXFLOORLOAD_FT	NUMBER	7	2	Y	Max floorloading in feet
YFSC_MAXDOORWIDTH_FT	NUMBER	5	2	Y	Max door width in feet
YFSC_MINDOORHEIGHT_FT	NUMBER	5	2	Y	Min door height in feet
YFSC_MAXDOORHEIGHT_FT	NUMBER	5	2	Y	Max door height in feet
YFSC_ZDCO_ID	NUMBER	30		N	Function Space - Department code link
YFSC_POSTTYPE	NUMBER	1		Y	YFSC_POSTTYPE is of YFSC
YFSC_RPDW_ID	NUMBER	30		Y	Link to Roomplanner drawing
YFSC_YOUT_ID	NUMBER	30		Y	Link to Outlet
YFSC_OCCUPANCY	NUMBER	4	2	Y	Function Space Occupancy
YFSC_FREETEXT	VARCHAR2	1000		Y	Free text
YFSC_PICTURE	LONG RAW			Y	Picture
YFSC_COSTPRICE	NUMBER	30	4	Y	Cost price
YFSC_FLOOR	NUMBER	3		Y	FUNCTION SPACE FLOOR
YFSC_INACTIVE	NUMBER	1		Y	Inactive = 1
YFSC_DEFAULTCREDITS	NUMBER	3		Y	Housekeeping credits (credits are indicating how many units as for instance minutes the maid needs to clean the function space)
YFSC_DEPARTURECREDITS	NUMBER	3		Y	Housekeeping credits on departure
YFSC_CLEANCREDITS	NUMBER	3		Y	Housekeeping credits for clean function space
YFSC_YCAD_ID	NUMBER	30		Y	Link segment to function spaces
YFSC_YCWI_ID	NUMBER	30		Y	Extends function space definition with a config for web

### YFSP

FUNCTION SPACES FLOOR PLAN

Field Name	Type	Length	Decimals	Not NULL	Description
YFSP_ID	NUMBER	30		N	YFSP_ID

## YFSP

### FUNCTION SPACES FLOOR PLAN

Field Name	Type	Length	Decimals	Not NULL	
YFSP_DISPLAY	NUMBER	3		Y	DISPLAY ORDER
YFSP_FLOOR	VARCHAR2	3		N	FLOOR CODE
YFSP_FLOORNAME	VARCHAR2	30		Y	FLOOR NAME
YFSP_PICTURE	LONG RAW			Y	FLOOR PLAN
YFSP_PICTURE_C	VARCHAR2	2000		Y	FLOOR PLAN FUNCTION SPACES
YFSP_SHORTDESC	VARCHAR2	3		Y	SHORTDESC

## YFSR

### Function Space Rates

Field Name	Type	Length	Decimals	Not NULL	
YFSR_ID	NUMBER	30		N	Unique ID
YFSR_DESCRIPTION	VARCHAR2	60		Y	Description
YFSR_PERHOUR	NUMBER	1		N	Hourly?
YFSR_VALUE	NUMBER	30	4	Y	Rate value
YFSR_YFSC_ID	NUMBER	30		Y	Contains link to function space
YFSR_YFRD_ID	NUMBER	30		N	YFSR_YFRD_ID is of YFSR
YFSR_DEFAULT	NUMBER	1		Y	Default rate for reserving multiple function spaces (0=no, 1=yes)
YFSR_INACTIVE	NUMBER	1		Y	1 = Inactive
YFSR_VALIDFROM	DATE			Y	Rate Valid Date From
YFSR_VALIDTO	DATE			Y	Rate Valid Date To
YFSR_COSTPRICE	NUMBER	30	4	Y	Cost price
YFSR_YCWI_ID	NUMBER	30		Y	Extends function space rate with a config for web

## YFTY

### Function Space types

Field Name	Type	Length	Decimals	Not NULL	
YFTY_ID	NUMBER	30		N	YFTY_ID identifies YFTY
YFTY_SHORTDESC	VARCHAR2	3		N	Function Space type code
YFTY_LONGDESC	VARCHAR2	30		N	Function space type description
YFTY_DISPLORDER	NUMBER	3		Y	Display order of function space type
YFTY_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
YFTY_YCWI_ID	NUMBER	30		Y	Linked to web info

### YFVT

Interface Room Status

Field Name	Type	Length	Decimals	Not NULL	
YFVT_ID	NUMBER	30		N	Unique Identifier
YFVT_IFC_CODE	NUMBER	30		Y	numeric code, as it is received from the interface
YFVT_YHKS_ID	NUMBER	30		Y	Link to Front Office Room Status
YFVT_OCC_STATUS	NUMBER	1		Y	0=Vacant, 1=Occupied
YFVT_WATY_ID	NUMBER	30		Y	
YFVT_WATY_ACTION	NUMBER	1		Y	0.New Task 1. Task resolved
YFVT_GUESTSERVICE_STATUS	NUMBER	1		Y	1. Make up Room, 2. Do not Disturb, 3. Reset

### YFXC

fixed charges posted automatically

Field Name	Type	Length	Decimals	Not NULL	
YFXC_ID	NUMBER	30		N	YFXC_ID identifies YFXC
YFXC_YDET_ID	NUMBER	30		N	YFXC_YDET_ID is of YFXC
YFXC_AMOUNT	NUMBER	30	4	N	YFXC_DEFAULTAMOUNT is the default amount. If the amount does not change all entries in YFCL_AMOUNT are the same. A 3 days stay will result in one record in YFXC and 3 records in YFCL
YFXC_ZDCO_ID	NUMBER	30		N	YFXC_ZDCO_ID is of YFXC
YFXC_QUANTITY	NUMBER	10		N	YFXC_QUANTITY is of YFXC
YFXC_FOREIGNAMOUNT	NUMBER	30	4	Y	foreign amount
YFXC_POSTDATE	DATE			Y	Last date the fix charge was posted
YFXC_ZCUR_ID	NUMBER	30		Y	fixed charges in third currency other than home or contracted (under construction)
YFXC_SCRID	NUMBER	30		Y	screen id to display fixed charges for the same zdcoc for different days as one group even if the same zdcoc is added more than once. this practically aligns records in one row on the screen.

### YGCL

Group Customer Link Table, as for instance for linking to Agents, companies and other profile types. This table follows the same logic as YBCL and YCLN.

Field Name	Type	Length	Decimals	Not NULL	
YGCL_ID	NUMBER	30		N	YGCL_ID identifies YGCL
YGCL_YGRP_ID	NUMBER	30		N	YGCL_YGRP_ID is the link into the group table
YGCL_XCMS_ID	NUMBER	30		N	YGCL_XCMS_ID is the link into the customer table. We do not define the type of profile linked here. This needs to get looked up from the Profile itself.
YGCL_XCCA_INTERNALCATEGORY	NUMBER	1		N	Defines internal role of selected profile. This is needed to store for select statements

### YGCO

Guarantee Codes

Field Name	Type	Length	Decimals	Not NULL	
YGCO_ID	NUMBER	30		N	YGCO_ID identifies YGCO
YGCO_SHORTDESC	VARCHAR2	3		N	YGCO_SHORTDESC is of YGCO
YGCO_LONGDESC	VARCHAR2	30		N	YGCO_LONGDESC is of YGCO
YGCO_RELEASETIME	DATE			Y	res is released after this time, as for instance 6 pm
YGCO_DISPLORDER	NUMBER	3		Y	YGCO_DISPLORDER is of YGCO
YGCO_DEFAULTRESSTATUS	NUMBER	1		Y	If the resstatus is set for the guarantee type this is the default for the YRES_RESSTATUS. 0=tentative 1=definitive 3=not affecting availability
YGCO_INACTIVE	NUMBER	1		Y	1 = inactive
YGCO_GUARANTEED	NUMBER	1		Y	1 = Guaranteed (implemented for TLP Interface) can get used for general purpose
YGCO_WCOL_ID	NUMBER	30		Y	
YGCO_LIMITEDRESEEDIT	NUMBER	1		N	Some edit features are disabled for reservations with this guarantee code
YGCO_CRSONLY	NUMBER	1		N	Only crs can select

### YGFA

If financial accounts are created for groupst ehv get linked in this link table.

Field Name	Type	Length	Decimals	Not NULL	
YGFA_ID	NUMBER	30		N	YGFA_ID identifies YGFA
YGFA_YGRP_ID	NUMBER	30		N	YGFA_YGRP_ID is of YGFA
YGFA_ZFAC_ID	NUMBER	30		N	YGFA_ZFAC_ID partly identifies YGFA

### YGRL

Rate Plan Group and Rate Code Link table

Field Name	Type	Length	Decimals	Not NULL	
YGRL_ID	NUMBER	30		N	
YGRL_YRPG_ID	NUMBER	30		N	Rate Plan Group ID
YGRL_YRCH_ID	NUMBER	30		N	Rate Code

### YGRP

Table YGRP contains the group names, which can link several reservations to a group.

Field Name	Type	Length	Decimals	Not NULL	
YGRP_ID	NUMBER	30		N	YGRP_ID identifies YGRP
YGRP_YGRT_ID	NUMBER	30		N	YGRP_YGRT_ID is of YGRP
YGRP_NAME	VARCHAR2	60		N	Group Name

## YGRP

Table YGRP contains the group names, which can link several reservations to a group.

Field Name	Type	Length	Decimals	Not NULL	
YGRP_CONTACT_XCMS_ID	NUMBER	30		Y	Contact person for this Group, links to XCMS
YGRP_WLAN_ID	NUMBER	30		Y	Default Language for members of this Group.
YGRP_COMMENT	VARCHAR2	1000		Y	Comment for this Group (should be long in a separate table)
YGRP_FROMDATE	DATE			N	YGRP_FROMDATE is of YGRP
YGRP_TODATE	DATE			N	YGRP_TODATE is of YGRP
YGRP_YBOM_ID	NUMBER	30		Y	YGRP_YBOM_ID is of YGRP
YGRP_INACTIVE	NUMBER	1		Y	If no expected is reservation is linked to a group , groups can get inactive
YGRP_XCOU_ID	NUMBER	30		Y	Country Default for Group
YGRP_ROOMINGLISTDATE	DATE			Y	roominglist date
YGRP_XSTA_ID	NUMBER	30		Y	Link to state information table
YGRP_YBLH_ID	NUMBER	30		Y	
YGRP_NOJETWEBGROUP	NUMBER	1		Y	
YGRP_XCOU_NAT_ID	NUMBER	30		Y	Nationality
YGRP_YCAD_ID	NUMBER	30		Y	Hotel segmentation link
YGRP_BLOCK_DEFAULT	NUMBER	1		Y	1 - default group of linked block in case yblh_autogroup = 1
YGRP_EXCHRATE	NUMBER	10	4	Y	Stored exchange rate to be assigned to all group members at checkin
YGRP_BACKRATE	NUMBER	10	4	Y	Stored exchange rate to be assigned to all group members at checkin
YGRP_ZCUR_ID	NUMBER	30		Y	ID of the currency used
YGRP_FIXEXCHRATE	NUMBER	1		Y	if checked, reservation will update exchange rate information in some cases

## YGRT

Group Info Template (something like former group profile)

Field Name	Type	Length	Decimals	Not NULL	
YGRT_ID	NUMBER	30		N	YGRT_ID identifies YGRT
YGRT_NAME	VARCHAR2	60		N	YGRT_NAME is of YGRT
YGRT_WLAN_ID	NUMBER	30		Y	Default Language for this Group Template
YGRT_COMMENT	LONG			Y	Default Comment for this Group Template
YGRT_CONTACT_XCMS_ID	NUMBER	30		Y	Default Contact for this Group Template
YGRT_XCOU_ID	NUMBER	30		Y	Country Default for this group
YGRT_INACTIVE	NUMBER	1		Y	1 = inactive
YGRT_XSTA_ID	NUMBER	30		Y	Link to state information table
YGRT_ROLE	NUMBER	1		Y	1=PMS Groups 2=CCM Groups 3=Block Template(for future purpose, not implemented yet)
YGRT_YRCH_ID	NUMBER	30		Y	ratecode

## YGRT

Group Info Template (something like former group profile)

Field Name	Type	Length	Decimals	Not NULL	
YGRT_XCMA_ID	NUMBER	30		Y	marketcode
YGRT_SOU_ID	NUMBER	30		Y	Source code
YGRT_CHA_ID	NUMBER	30		Y	Channel code
YGRT_XCOU_NAT_ID	NUMBER	30		Y	Nationality
YGRT_YCAD_ID	NUMBER	30		Y	Hotel segmentation link

## YGTL

Group Customer Link Table, as for instance for linking to Agents, companies and other profile types. This table follows the same logic as YBCL and YCLN.

Field Name	Type	Length	Decimals	Not NULL	
YGTL_ID	NUMBER	30		N	YGTL_ID identifies YGTL
YGTL_YGRT_ID	NUMBER	30		N	YGCL_YGRP_ID is the link into the group template table
YGTL_XCMS_ID	NUMBER	30		N	YGTL_XCMS_ID is the link into the customer table. We do not define the type of profile linked here. This needs to get looked up from the Profile itself.
YGTL_XCCA_INTERNALCATEGORY	NUMBER	1		N	Defines internal role of selected profile. This is needed to store for select statements

## YHAC

Attendant comments

Field Name	Type	Length	Decimals	Not NULL	
YHAC_ID	NUMBER	30		N	
YHAC_COMMENT	VARCHAR2	4000		Y	

## YHAE

House Keeping Assignment Elements

Field Name	Type	Length	Decimals	Not NULL	
YHAE_ID	NUMBER	30		N	YHAE_ID identifies YHAE
YHAE_YHAG_ID	NUMBER	30		N	Link to assignment group
YHAE_SHORTDESC	VARCHAR2	3		N	Short description for assignment element
YHAE_LONGDESC	VARCHAR2	30		N	Long description for assignment element
YHAE_INACTIVE	NUMBER	1		Y	0 = active 1 = inactive
YHAE_DISPLORDER	NUMBER	5		Y	Displayorder

## YHAG

House Keeping Assignment Group, as general or housekeeping

Field Name	Type	Length	Decimals	Not NULL	
YHAG_ID	NUMBER	30		N	YHAG_ID identifies YHAG
YHAG_SHORTDESC	VARCHAR2	3		N	Short description for assignment group
YHAG_LONGDESC	VARCHAR2	30		N	Long description for assignment group
YHAG_INACTIVE	NUMBER	1		Y	0 = active 1 = inactive
YHAG_DISPLORDER	NUMBER	5		Y	Displayorder

## YHAL

House Keeping Assignment Link

Field Name	Type	Length	Decimals	Not NULL	
YHAL_ID	NUMBER	30		N	YHAL_ID identifies YHAL
YHAL_YRMS_ID	NUMBER	30		N	Assignment Link to Rooms table
YHAL_YHAE_ID	NUMBER	30		N	Assignment Link to Assignment Element

## YHAT

Housekeeping Attendants

Field Name	Type	Length	Decimals	Not NULL	
YHAT_ID	NUMBER	30		N	YHAT_ID identifies YHAT
YHAT_NAME	VARCHAR2	30		N	YHAT_NAME is of YHAT
YHAT_MAXCREDITS	NUMBER	4		Y	The credit this maid is able to solve on one day.
YHAT_ACTIVE	NUMBER	1		Y	YHAT_ACTIVE is of YHAT
YHAT_YHHC_ID	NUMBER	30		N	
YHAT_XCED_ID	NUMBER	30		Y	Attendant link to user

## YHFS

Attendant calculation settings for saved attendant plans

Field Name	Type	Length	Decimals	Not NULL	
YHFS_ID	NUMBER	30		N	
YHFS_NUMBEROFATTENDANTS	NUMBER	3		Y	
YHFS_DEFAULTCREDITS	NUMBER	3		Y	
YHFS_ALLOWAUTOEXTEND	NUMBER	1		Y	
YHFS_AUTOREDUCE	NUMBER	1		Y	
YHFS_AUTOMAIDNAME	VARCHAR2	50		Y	

## YHFS

Attendant calculation settings for saved attendant plans

Field Name	Type	Length	Decimals	Not NULL	
YHFS_USEDEFINED	NUMBER	1		Y	
YHFS_USEATTENDANTCONFIG	NUMBER	1		Y	
YHFS_ATTENDANTTYPE	NUMBER	30		Y	
YHFS_METHOD	NUMBER	1		N	0=Fill to maxcredits 1=Balance equally 2=Attendant per section
YHFS_INCLUDEPUBLICPLACES	NUMBER	1		Y	
YHFS_INCLUDEFUNCTIONSPACES	NUMBER	1		Y	
YHFS_INCLUDECLEANROOMS	NUMBER	1		Y	
YHFS_INCLUDEONLYFORARRIVALS	NUMBER	1		Y	
YHFS_INCLUDEOOOROOMS	NUMBER	1		Y	
YHFS_LISTCLEANASNOTASSIGNED	NUMBER	1		Y	

## YHHC

Attendant Types

Field Name	Type	Length	Decimals	Not NULL	
YHHC_ID	NUMBER	30		N	
YHHC_ROLE	NUMBER	1		N	0 = Maid, 1 = Housekeeper
YHHC_SHORTDESC	VARCHAR2	3		N	
YHHC_LONGDESC	VARCHAR2	30		N	
YHHC_WRPT_ID	NUMBER	30		Y	
YHHC_DEFAULT	NUMBER	1		N	1 - default housekeeping group, only 1 default is allowed. 0 - if not default

## YHKI

House Keeping Occupied status from interface

Field Name	Type	Length	Decimals	Not NULL	
YHKI_ID	NUMBER	30		N	YHKI_ID identifies YHKI
YHKI_YRMS_ID	NUMBER	30		N	YHKI_YRMS_ID is of YHKI
YHKI_OCC_STATUS	NUMBER	1		Y	0 = vacant 1 = occupied
YHKI_MAID_ID	VARCHAR2	10		Y	Friedemann promise to fill with maid id one day
YHKI_TIMESTAMP	DATE			N	YHKI_TIMESTAMP is of YHKI

### YHKS

house keeping status definitions

Field Name	Type	Length	Decimals	Not NULL	
YHKS_ID	NUMBER	30		N	YHKS_ID identifies YHKS
YHKS_SHORTDESC	VARCHAR2	3		N	YHKS_SHORTDESC is of YHKS
YHKS_LONGDESC	VARCHAR2	30		N	YHKS_LONGDESC is of YHKS
YHKS_DISPLORDER	NUMBER	3		Y	YHKS_DISPLORDER is of YHKS
YHKS_CLEAN	NUMBER	1		Y	1 = Clean 0 = Dirty
YHKS_WCOL_ID	NUMBER	30		Y	YHKS_WCOL_ID is of YHKS
YHKS_IFC_STATUS	NUMBER	1		Y	Obsolete column, YFVT is used instead
YHKS_GREENSTATUS	NUMBER	1		Y	One record in YHKS to be identified for Green Status (not used too long and review needed)
YHKS_GREENSTATUSDAYS	NUMBER	3		Y	Number of days for Green Status (not used too long and review needed)

### YHRA

Attendant plan link to Amenities

Field Name	Type	Length	Decimals	Not NULL	
YHRA_ID	NUMBER	30		N	
YHRA_YHRL_ID	NUMBER	30		N	
YHRA_YAMN_ID	NUMBER	30		N	
YHRA_CREDITS	NUMBER	3		Y	

### YHRD

Rate Hurdle Control File

Field Name	Type	Length	Decimals	Not NULL	
YHRD_ID	NUMBER	30		N	Unique Identifier
YHRD_YCAT_ID	NUMBER	30		N	Link to Room Types
YHRD_ARRDATE	DATE			N	Arrival Date
YHRD_LOS	NUMBER	2		N	Length of stay
YHRD_HURDLEAMOUNT	NUMBER	30	4	N	Amount of Hurdle, Rate should >= than this amount for this arrival day and length of stay to pass the hurdle
YHRD_CLOSED	NUMBER	1		Y	1 - closed for this arrival day and this length of stay
YHRD_3RDPARTYIMPORTDATE	DATE			Y	Date of 3rd party Yield software Import
YHRD_DELTA	NUMBER	30	4	Y	variation of the hurdle rate each time a reservation is made
YHRD_MAXHURDLEAMOUNT	NUMBER	30	4	Y	maximal value of the hurdle rate
YHRD_ORIGIN	NUMBER	1		Y	System originated this record. 0- TLP 1-Hurdle rates XML Interface

### YHRI

Field Name	Type	Length	Decimals	Not NULL	
YHRI_ID	NUMBER	30		N	
YHRI_DATE	DATE			N	Date of property selling
YHRI_MAXSOLD	NUMBER	10		N	maximum sold of rooms until next ideas update
YHRI_ROOMSOLD	NUMBER	10		Y	currently sold properties since last ideas update
YHRI_CEILING	NUMBER	10		N	maximum sold value to calculate the hurdle if roomsold already higher than ceiling
YHRI_SOLD	NUMBER	10		Y	
YHRI_OCCUPANCY	NUMBER	10		Y	Occupancy figure at the time of decision import for yhri_arrdate

### YHRL

Link from attendant table to rooms table

Field Name	Type	Length	Decimals	Not NULL	
YHRL_ID	NUMBER	30		N	YHRL_ID identifies YHRL
YHRL_YRMS_ID	NUMBER	30		N	YHRL_YRMS_ID is of YHRL
YHRL_YHAT_ID	NUMBER	30		Y	YHRL_YHAT_ID is of YHRL
YHRL_AUTOMAID_NR	NUMBER	3		Y	YHRL_AUTOMAID_NR is of YHRL
YHRL_DATE	DATE			N	YHRL_DATE is of YHRL
YHRL_CREDIT	NUMBER	3		N	YHRL_CREDIT is of YHRL
YHRL_AUTOMAID_MAXCREDITS	NUMBER	3		Y	Filled when automatic attendants are used
YHRL_YHAC_ID	NUMBER	30		Y	
YHRL_YHHC_ID	NUMBER	30		Y	
YHRL_YPUB_ID	NUMBER	30		Y	Link to Public places (can only be filled if yrms_id and yfsc_id are null)
YHRL_YFSC_ID	NUMBER	30		Y	Link to Function spaces (can only be filled if yrms_id and ypub_id are null)
YHRL_YHFS_ID	NUMBER	30		Y	Link to the filter settings

### YHSL

Field Name	Type	Length	Decimals	Not NULL	
YHSL_ID	NUMBER	30		N	
YHSL_YHAT_ID	NUMBER	30		N	
YHSL_YSRM_ID	NUMBER	30		Y	
YHSL_YRMS_ID	NUMBER	30		Y	

### YHSP

Storage of manipulated HSK Screen to be printed from

Field Name	Type	Length	Decimals	Not NULL
YHSP_ID	NUMBER	30		N
YHSP_DATE	DATE			Y
YHSP_ROOM	VARCHAR2	10		Y
YHSP_ROOMTYPE	VARCHAR2	5		Y
YHSP_STATUS	VARCHAR2	30		Y
YHSP_SECTION	VARCHAR2	100		Y
YHSP_CONDITION	VARCHAR2	100		Y
YHSP_LASTHSKCHANGE	DATE			Y
YHSP_YRMS_ID	NUMBER	30		N

### YIRL

catering items link to responsible departments

Field Name	Type	Length	Decimals	Not NULL	
YIRL_ID	NUMBER	30		N	YIRL_ID identifies YIRL
YIRL_YCIT_ID	NUMBER	30		N	YIRL_YCIT_ID is of YIRL
YIRL_WHDE_ID	NUMBER	30		N	YIRL_WHDE_ID is of YIRL
YIRL_YCMI_ID	NUMBER	30		N	YIRL_YCMI_ID is of YIRL

### YLCK

Temporary Locking Table for Room Blocking

Field Name	Type	Length	Decimals	Not NULL	
YLCK_ID	NUMBER	30		N	Unique Identifier
YLCK_DAY	DATE			N	Day
YLCK_YRMS_ID	NUMBER	30		N	Link to Rooms Table
YLCK_WPCA_ID	NUMBER	30		N	YLCK_WPCA_ID is of YLCK

### YLPR

Rate Promotion Storage on Reservation level

Field Name	Type	Length	Decimals	Not NULL	
YLPR_ID	NUMBER	30		N	Unique ID
YLPR_YDET_ID	NUMBER	30		N	Link to reservation detail
YLPR_YPRM_ID	NUMBER	30		N	Link to promotion

## YLPR

Rate Promotion Storage on Reservation level

Field Name	Type	Length	Decimals	Not NULL	
YLPR_YPRR_ID	NUMBER	30		N	Link to promotion rule link table
YLPR_AMOUNT	NUMBER	30	4	Y	Promotion amount storage on reservation level per promotion rule
YLPR_FOREIGNAMOUNT	NUMBER	30	4	Y	Promotion amount storage on reservation level per promotion rule

## YLSP

Lease period

Field Name	Type	Length	Decimals	Not NULL	
YLSP_ID	NUMBER	30		N	
YLSP_YRES_ID	NUMBER	30		N	
YLSP_START	DATE			N	
YLSP_END	DATE			N	
YLSP_MANUAL	NUMBER	1		N	
YLSP_AMOUNT	NUMBER	30	4	N	
YLSP_FAMOUNT	NUMBER	30	4	Y	
YLSP_PARTIAL	NUMBER	1		N	
YLSP_ZINV_ID	NUMBER	30		Y	
YLSP_POSTDATE	DATE			Y	
YLSP_ZWIN_ID	NUMBER	30		Y	

## YLTO

Lost To (for cancellation with known competitor, such as hotel near by)

Field Name	Type	Length	Decimals	Not NULL	
YLTO_ID	NUMBER	30		N	YLTO_ID identifies YLTO
YLTO_SHORTDESC	VARCHAR2	3		N	YLTO_SHORTDESC is of YLTO
YLTO_LONGDESC	VARCHAR2	30		N	YLTO_LONGDESC is of YLTO
YLTO_DISPLORDER	NUMBER	3		Y	YLTO_DISPLORDER is of YLTO
YLTO_INACTIVE	NUMBER	1		Y	0=active, 1=inactive

## YMCF

Field Name	Type	Length	Decimals	Not NULL	
YMCF_ID	NUMBER	30		N	

## YMCF

Field Name	Type	Length	Decimals	Not NULL
YMCF_YRPL_ID	NUMBER	30		N

## YMES

Messages

Field Name	Type	Length	Decimals	Not NULL	
YMES_ID	NUMBER	30		N	YMES_ID identifies YMES
YMES_YRES_ID	NUMBER	30		N	YRES_ID is link to reservation table YRES.
YMES_DELIVEREDTIME	DATE			Y	The date and time that the message was delivered (stored in YMES)
YMES_DELIVEREDTO_XCMS_ID	NUMBER	30		Y	The internal ID of the employee to whom the message was delivered at the property. Examp1 if a message is entered manually the user id of the logged in user will be stored.
YMES_FROMWHOM	VARCHAR2	30		Y	The name of the person who left the message.
YMES_CONTACTINFO	VARCHAR2	30		Y	Information about how to contact the originator of the message (e.g., phone number).Used for interfacing. /not used right now.
YMES_TOWHOM	VARCHAR2	100		Y	The name of the guest to whom the message should be delivered. This defaults to guests name linked to YRES record. Needed for interfacing with 3 rd party. (filled only if message comes from 3rd party, not from us)
YMES_TOWHOM_XCMS_ID	NUMBER	30		Y	filled if the message was created by us not by a 3rd party
YMES_RECEIVEDTYPE	NUMBER	2		Y	Status of message: 0=Not received 1=Manually received 2=Printed 3=Sent to video system 4=Received on video system 5=not delivered to interface
YMES_RECEIVEDDATE	DATE			Y	Date and time stamp whne the guest received the message
YMES_RECEIVEDBY_XCMS_ID	NUMBER	30		Y	Employee ID who printed or gave the message to guest.
YMES_TYPE	NUMBER	1		Y	0 or null is normal text message 1 = VoiceMail
YMES_WACT_ID	NUMBER	30		Y	Response message on the maintenance task

## YMGA

Field Name	Type	Length	Decimals	Not NULL
YMGA_ID	NUMBER	30		N
YMGA_YRES_ID	NUMBER	30		N
YMGA_XCMS_ID	NUMBER	30		N
YMGA_XPDA_ID	NUMBER	30		N

### YMIL

Menu Item link to the Menu

Field Name	Type	Length	Decimals	Not NULL	
YMIL_ID	NUMBER	30		N	Unique ID
YMIL_YSME_ID	NUMBER	30		N	YMIL_YSME_ID is of YMIL
YMIL_YCMI_ID	NUMBER	30		N	YMIL_YCMI_ID is of YMIL
YMIL_COURSE	NUMBER	3		Y	YMIL_COURSE is of YMIL
YMIL_COURSEORDER	NUMBER	3		Y	YMIL_COURSEORDER is of YMIL
YMIL_INCLMENU	NUMBER	1		Y	0= not included   1 = included

### YMNT

message notes (the text)

Field Name	Type	Length	Decimals	Not NULL	
YMNT_ID	NUMBER	30		N	YMNT_ID identifies YMNT
YMNT_YMES_ID	NUMBER	30		N	YMNT_YMES_ID is of YMNT
YMNT_TEXT	LONG			N	YMNT_TEXT is of YMNT

### YMRD

Booked Menu Forecast Split

Field Name	Type	Length	Decimals	Not NULL	
YMRD_ID	NUMBER	30		N	YMRD_ID identifies YMRD
YMRD_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YMRD_YFCA_AMOUNT	NUMBER	30	4	Y	Forecast Amount
YMRD_YEMN_ID	NUMBER	30	4	Y	Link to booked Menu
YMRD_TYPE	NUMBER	1		N	1 = Forecast Split
YMRD_ZDCO_ID	NUMBER	30		N	Link to department code
YMRD_REBATE_PERC	NUMBER	3		Y	Percentage of rebate
YMRD_ORG_AMOUNT	NUMBER	30	4	Y	Original amount
YMRD_REBATE_FLAT	NUMBER	30	4	Y	Rebate flat amount
YMRD_REBATE_UNITPRICE	NUMBER	30	4	Y	Rebate unit price
YMRD_PRICE_NET	NUMBER	30	4	Y	Standard menu split net value
YMRD_PRICE_VAT	NUMBER	30	4	Y	Standard menu split tax value

### YMSG

Predefined Message text elements

Field Name	Type	Length	Decimals	Not NULL	
YMSG_ID	NUMBER	30		N	YMSG_ID identifies YMSG
YMSG_DISPLORDER	NUMBER	3		N	YMSG_DISPLORDER is of YMSG
YMSG_TEXT	VARCHAR2	60		N	Text element for YMES records whcih can be selected and copied inot YMES Text fields

### YMSP

master sub package link

Field Name	Type	Length	Decimals	Not NULL	
YMSP_ID	NUMBER	30		N	
YMSP_MASTER_YPAC_ID	NUMBER	30		N	
YMSP_SUB_YPAC_ID	NUMBER	30		N	

### YOPF

Opportunity function space requisition Details

Field Name	Type	Length	Decimals	Not NULL	
YOPF_ID	NUMBER	30		N	
YOPF_YSFT_ID	NUMBER	30		N	
YOPF_XOPP_ID	NUMBER	30		N	
YOPF_FROMDATE	DATE			N	
YOPF_TODATE	DATE			N	
YOPF_NOOFFS	NUMBER	3		N	
YOPF_PAX	NUMBER	3		N	
YOPF_COFFEE	NUMBER	1		Y	
YOPF_LUNCH	NUMBER	1		Y	
YOPF_DINNER	NUMBER	1		Y	
YOPF_NOTES	VARCHAR2	1000		Y	

### YOPL

Field Name	Type	Length	Decimals	Not NULL	
YOPL_ID	NUMBER	30		N	Table ID
YOPL_YOPF_ID	NUMBER	30		N	Opportunity Fact ID
YOPL_YEVM_ID	NUMBER	30		N	Linked Event Id

### YOPR

Opportunity Rooms requisition Details

Field Name	Type	Length	Decimals	Not NULL
YOPR_ID	NUMBER	30		N
YOPR_YSRC_ID	NUMBER	30		N
YOPR_XOPP_ID	NUMBER	30		N
YOPR_FROMDATE	DATE			N
YOPR_TODATE	DATE			N
YOPR_NOOFROOMS	NUMBER	3		N
YOPR_PAX	NUMBER	3		N
YOPR_NOTES	VARCHAR2	1000		Y

### YOUT

Outlets

Field Name	Type	Length	Decimals	Not NULL	
YOUT_ID	NUMBER	30		N	Unique ID
YOUT_SHORTDESC	VARCHAR2	3		N	Outlet Code
YOUT_LONGDESC	VARCHAR2	30		N	Outlet Description
YOUT_MC_ID	NUMBER	30		Y	Link to MC outlet
YOUT_INACTIVE	NUMBER	1		Y	1= inactive
YOUT_XADR_ID	NUMBER	30		Y	
YOUT_ADVERTISEMENT1	VARCHAR2	120		Y	
YOUT_ADVERTISEMENT2	VARCHAR2	120		Y	
YOUT_ONECHECKPERTABLE	NUMBER	1		Y	
YOUT_ASKCOURSEORDER	NUMBER	1		Y	
YOUT_ROLE	NUMBER	3		Y	
YOUT_RRST_ID	NUMBER	30		Y	

### YOVB

House overbooking and room type overbooking.

Field Name	Type	Length	Decimals	Not NULL	
YOVB_ID	NUMBER	30		N	YOVB_ID identifies YOVB
YOVB_DATE	DATE			N	Date of OVerbooking entry
YOVB_TYPE	NUMBER	1		N	1 = House Overbooking 2 = Room Type Overbooking 3=channel leave empty 4=channel house leave empty 5=channel percentage leave empty 6=channel percentage house leave empty

### YOVB

House overbooking and room type overbooking.

Field Name	Type	Length	Decimals	Not NULL	
YOVB_VALUE	NUMBER	3		N	Number of Rooms for this overbooking
YOVB_YCAT_ID	NUMBER	30		Y	Mandatory if YOVB_TYPE = 2.
YOVB_ORIGIN	NUMBER	1		Y	Overbooking source: 0=V8 User, 1=TLP 2=XML Interface
YOVB_YALG_ID	NUMBER	30		Y	

### YPAC

packages

Field Name	Type	Length	Decimals	Not NULL	
YPAC_ID	NUMBER	30		N	Unique ID for this package
YPAC_SHORTDESC	VARCHAR2	4		N	Short Description for this package
YPAC_LONGDESC	VARCHAR2	30		N	Description name of this package
YPAC_DISPLORDER	NUMBER	4		Y	Display order.
YPAC_ZDCO_ID	NUMBER	30		N	Link to which DepartmentCode this package is posted.
YPAC_VALUE	NUMBER	30	4	N	Price of Package
YPAC_SPLITTYPE	NUMBER	1		N	obsolete field, now we use YPAC_PRINTSEP and YPAC_INCLUDED
YPAC_DEFAULTFREQ_YPFR_ID	NUMBER	30		Y	YPAC_DEFAULTFREQ_YPFR_ID is of YPAC
YPAC_DEFAULTFO	NUMBER	1		Y	show in reservation screen by default even if it is not attached (unchecked)
YPAC_ALLOWANCED	NUMBER	1		Y	1 = POS Package (creates Allowance)
YPAC_FROMTIME	DATE			Y	from time for allowances
YPAC_TOTIME	DATE			Y	to time for allowances
YPAC_ALLOWANCETYPE	NUMBER	1		Y	0 = normal 1 = Floating 2 = Next Day
YPAC_OVERAGE_ZDCO_ID	NUMBER	30		Y	Dept. code for overage
YPAC_PROFIT_ZDCO_ID	NUMBER	30		Y	Dept. code for package profit.
YPAC_LOSS_ZDCO_ID	NUMBER	30		Y	Dept. code for package loss
YPAC_ALLOWANCE_AUTOINCREMNT	NUMBER	1		Y	1 = True, whenever a posting is exceeding trhe allowed amount we increment the allowance
YPAC_FULLDAY	NUMBER	1		Y	Flag for full day allowance - no time limitation. 1=true
YPAC_INVALID	NUMBER	1		Y	YPAC_INVALID is of YPAC
YPAC_INCLUDED	NUMBER	1		Y	together with YPAC_PRINTSEP configuring the split type
YPAC_PRINTSEP	NUMBER	1		Y	YPAC_PRINTSEP is of YPAC
YPAC_ZCUR_ID	NUMBER	30		Y	Package Currency Link for foreign Currency RateCodes
YPAC_NORMALNEXTDAYBOTH	NUMBER	1		Y	0 = regular packages are normal 1 = breakfast is next day 2 = some half board could be both Used for reporting at this time. Maybe this will change later so dont believe this comment
YPAC_DISCTOBASE	NUMBER	1		Y	Percentage Package - apply discounts to base rate amount

### YPAC

packages

Field Name	Type	Length	Decimals	Not NULL	
YPAC_FIXTOBASE	NUMBER	1		Y	Percentage Package - add fixed charges to base rate amount
YPAC_PERCTOBASE	NUMBER	1		Y	Percentage Package - add non perc. packages to base rate amount
YPAC_MANUALPRICE	NUMBER	1		Y	Percentage Package - apply manual price if entered
YPAC_PERCENTAGE	NUMBER	1		Y	Package price is a percentage value
YPAC_REPORT_GROUP	NUMBER	1		Y	
YPAC_NODISCOUNT	NUMBER	1		N	Discount is not allowed on package (only available if not percentage package)
YPAC_YPRG_ID	NUMBER	30		Y	Package Report Group link
YPAC_SINGLEPERRES	NUMBER	1		Y	If set package is linkable only to one guestprofile otherwise all guestprofiles can have the package
YPAC_RETURNABLE	NUMBER	1		Y	1=item needs to be returned on checkout
YPAC_NORETURNFEE	NUMBER	30	4	Y	amount charged if item is not returned on checkout
YPAC_NORETURN_ZDCO_ID	NUMBER	30		Y	department code for noreturn fee
YPAC_DEPOSIT	NUMBER	1		Y	noreturn fee is posted as a deposit and later cancelled if item is returned
YPAC_DONTPOSTZERO	NUMBER	1		N	1 = package will not be posted if amount is 0
YPAC_WEBENABLED	NUMBER	1		Y	Web package description
YPAC_WEBINFO	VARCHAR2	1000		Y	Web Short Information
YPAC_WELLNESS	NUMBER	1		Y	
YPAC_STATVALUE	NUMBER	30	4	Y	statistical value field for some hotel
YPAC_MASTER_YPAC_ID	NUMBER	30		Y	Obsolete column, not used anymore, table ymsp used instead
YPAC_FOLIOTEXT	VARCHAR2	60		Y	text printed on folio if package is print separate
YPAC_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information
YPAC_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information for Mobile Device
YPAC_MD_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information for Mobile Device
YPAC_SUBSTRACTINCLUDEDPACK AGE	NUMBER	1		Y	subtract included packages from base. ypac_perctobase adds addtorate packages only
YPAC_SUPPRESSPRICE	NUMBER	1		Y	Flag if package price should be suppressed on rate query
YPAC_WEBSSELLROLE	NUMBER	1		Y	webselling option of the package
YPAC_BOARDTYPE	NUMBER	1		N	0=NO BOARD 1=BREAKFAST 2=BREAKFAST+LUNCH 3=BREAKFAST+DINNER 4=FULL BOARD 5=ALL INCLUSIVE (same as yrch_boardtype so far) 6=only lunch 7=only dinner
YPAC_FORECASTTYPE	NUMBER	1		Y	0=once per room 1=adults 2=adults and children
YPAC_ISFORMULA	NUMBER	1		N	Special package type with formula price configuration
YPAC_REDUCE	NUMBER	1		N	

### YPAG

Package groups

Field Name	Type	Length	Decimals	Not NULL	
YPAG_ID	NUMBER	30		N	Unique Identifier
YPAG_SHORTDESC	VARCHAR2	3		N	Short description
YPAG_LONGDESC	VARCHAR2	30		N	Long description

### YPAL

package link to reservation ydet

Field Name	Type	Length	Decimals	Not NULL	
YPAL_ID	NUMBER	30		N	Unique Package Link Id
YPAL_YPAC_ID	NUMBER	30		N	Link to Package Table
YPAL_YDET_ID	NUMBER	30		N	Link to Reservation Details.
YPAL_MULTIPLIER	NUMBER	2		Y	The multiplier is used if more than one package are setup for the same reservation detail.
YPAL_YPRL_ID	NUMBER	30		Y	assigned manually if empty. otherwise the source of data for automatic calculation
YPAL_NEGATIVE	NUMBER	1		Y	the user wants to have it under no circumstances (ie: automatic assignment is not allowed)
YPAL_VALUE	NUMBER	30	4	Y	YPAL_VALUE is of YPAL
YPAL_LIMIT	NUMBER	30	4	Y	YPAL_LIMIT is of YPAL
YPAL_FOREIGNVALUE	NUMBER	30	4	Y	YPAL_FOREIGNVALUE is of YPAL
YPAL_FOREIGNLIMIT	NUMBER	30	4	Y	YPAL_FOREIGNLIMIT is of YPAL
YPAL_INCLUDED	NUMBER	1		Y	YPAL_INCLUDED is of YPAL
YPAL_MANUALPRICE	NUMBER	1		Y	1 = Manual Changed Price
YPAL_OVALUE	NUMBER	30	4	Y	
YPAL_OLIMIT	NUMBER	30	4	Y	
YPAL_OFOREIGNVALUE	NUMBER	30	4	Y	
YPAL_OFOREIGNLIMIT	NUMBER	30	4	Y	
YPAL_MASTER_YPAC_ID	NUMBER	30		Y	

### YPAP

package price configuration

Field Name	Type	Length	Decimals	Not NULL	
YPAP_ID	NUMBER	30		N	YPAP_ID identifies YPAP
YPAP_YPAT_ID	NUMBER	30		N	YPAP_YPAT_ID is of YPAP
YPAP_XCAC_ID	NUMBER	30		Y	optional zero or more to zero or more relationship
YPAP_TYPE	NUMBER	1		N	0=per YPAP_XCAC_ID , 1=per adult, 2=flat

## YPAP

package price configuration

Field Name	Type	Length	Decimals	Not NULL	
YPAP_VALUE	NUMBER	30	4	N	YPAP_VALUE is of YPAP
YPAP_ALLOWANCE_VALUE	NUMBER	30	4	Y	YPAP_ALLOWANCE_VALUE is of YPAP
YPAP_INVALID	NUMBER	1		Y	YPAP_INVALID is of YPAP

## YPAT

package price time intervals

Field Name	Type	Length	Decimals	Not NULL	
YPAT_ID	NUMBER	30		N	YPAT_ID identifies YPAT
YPAT_YPAC_ID	NUMBER	30		N	YPAT_YPAC_ID is of YPAT
YPAT_FROM	DATE			N	YPAT_FROM is of YPAT
YPAT_UNTIL	DATE			Y	YPAT_UNTIL is of YPAT
YPAT_INVALID	NUMBER	1		Y	YPAT_INVALID is of YPAT
YPAT_YFOR_ID	NUMBER	30		Y	Formula link to package Detail

## YPAZ

Other Department Codes posting against allowance.

Field Name	Type	Length	Decimals	Not NULL	
YPAZ_ID	NUMBER	30		N	YPAZ_ID identifies YPAZ
YPAZ_YPAC_ID	NUMBER	30		Y	YPAZ_YPAC_ID is of YPAZ
YPAZ_ZDCO_ID	NUMBER	30		Y	YPAZ_ZDCO_ID is of YPAZ
YPAZ_INVALID	NUMBER	1		Y	YPAZ_INVALID is of YPAZ
YPAZ_ZCUR_ID	NUMBER	30		Y	link if package is a foreign currency package

## YPCF

Custom Fields for XCMS

Field Name	Type	Length	Decimals	Not NULL	
YPCF_ID	NUMBER	30		N	
YPCF_XCMS_ID	NUMBER	30		N	
YPCF_FREETEXT1	VARCHAR2	2000		Y	
YPCF_CREATEDINHOTEL	VARCHAR2	100		Y	DO NOT REMOVE FROM TABLE

### YPFR

predefined frequencies

Field Name	Type	Length	Decimals	Not NULL	
YPFR_ID	NUMBER	30		N	YPFR_ID identifies YPFR
YPFR_SHORTDESC	VARCHAR2	3		N	YPFR_SHORTDESC is of YPFR
YPFR_LONGDESC	VARCHAR2	30		N	YPFR_LONGDESC is of YPFR
YPFR_DISPLORDER	NUMBER	3		Y	YPFR_DISPLORDER is of YPFR
YPFR_YFRQ_ID	NUMBER	30		N	YPFR_YFRQ_ID is of YPFR
YPFR_DELETED	NUMBER	1		Y	Deleted = 1
YPFR_SHORTWEBINFO	VARCHAR2	1000		Y	Web Information
YPFR_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Information for Mobile Device

### YPGL

Package group link table

Field Name	Type	Length	Decimals	Not NULL	
YPGL_ID	NUMBER	30		N	Unique Identifier
YPGL_YPAC_ID	NUMBER	30		N	Link to package header table
YPGL_YPAG_ID	NUMBER	30		N	Link to package group table

### YPIL

inventory items linked to packages

Field Name	Type	Length	Decimals	Not NULL	
YPIL_ID	NUMBER	30		N	
YPIL_YPAC_ID	NUMBER	30		N	
YPIL_YCIT_ID	NUMBER	30		N	
YPIL_NUMBER	NUMBER	4		N	
YPIL_CALCTYPE	NUMBER	1		N	0=Flat 1=Per Adult 2=Per child 3=Per Person

### YPKD

Booked Packages

Field Name	Type	Length	Decimals	Not NULL	
YPKD_ID	NUMBER	30		N	unique id for this booked package
YPKD_YBOM_ID	NUMBER	30		N	booking id for this booked package
YPKD_YPKG_ID	NUMBER	30		Y	ackage id for this booked package
YPKD_NAME	VARCHAR2	50		N	name of this booked package

### YPKD

Booked Packages

Field Name	Type	Length	Decimals	Not NULL	Description
YPKD_PRICE	NUMBER	30	4	Y	price for this booked package
YPKD_NOOFATTENDEES	NUMBER	30		N	no of attendees this booked package
YPKD_STARTTIME	DATE			Y	package starttime
YPKD_ENDTIME	DATE			Y	package endtime
YPKD_COPIEDFROM	NUMBER	30	4	Y	Ypkd_id from which originate
YPKD_DISPLORDER	NUMBER	30		Y	Package display order
YPKD_ALTERNATIVE	NUMBER	1		Y	Alternative=1

### YPKE

Package Configuration: Linked Events

Field Name	Type	Length	Decimals	Not NULL	Description
YPKE_ID	NUMBER	30		N	YPKE_ID identifies YPKE
YPKE_YPKG_ID	NUMBER	30		N	Link to package
YPKE_YETY_ID	NUMBER	30		N	Link to event type
YPKE_STARTTIME	DATE			Y	Start time (pre-define)
YPKE_ENDTIME	DATE			Y	End Time (pre-define)
YPKE_FROMDAY	NUMBER	3		Y	start day number for the event
YPKE_TODAY	NUMBER	3		Y	end day number for the event
YPKE_ZDCO_ID	NUMBER	30		Y	YPKE_ZDCO_ID is of YPKE
YPKE_MASTER_YPKE_ID	NUMBER	30		Y	Reference to the owner of current event
YPKE_POSTTYPE	NUMBER	1		Y	YPKE_POSTTYPE is of YPKE

### YPKF

Package Configuration: Forecast / Revenue Split

Field Name	Type	Length	Decimals	Not NULL	Description
YPKF_ID	NUMBER	30		N	unique id for this package forecast split
YPKF_YFCA_ID	NUMBER	30		Y	NOT USED ANYMORE
YPKF_YPKE_ID	NUMBER	30		N	Forecast event type id
YPKF_FOR_PRICE	NUMBER	30	4	Y	Expected per person
YPKF_REV_PRICE	NUMBER	30	4	Y	Forecast per person
YPKF_ZDCO_ID	NUMBER	30		N	Link to Department Code
YPKF_POSTTYPE	NUMBER	1		Y	YPKF_POSTTYPE is of YPKF

### YPKG

Package Configuration

Field Name	Type	Length	Decimals	Not NULL	
YPKG_ID	NUMBER	30		N	YPKG_ID identifies YPKG
YPKG_NAME	VARCHAR2	50		Y	Package Name
YPKG_PRICE	NUMBER	30	4	Y	Package Price
YPKG_DISPLORDER	NUMBER	3		Y	Display Order
YPKG_VALIDFROM	DATE			Y	rate valid date from
YPKG_VALIDTO	DATE			Y	rate valid date to
YPKG_INACTIVE	NUMBER	1		Y	0 = active   1 = inactive
YPKG_SHORTDESC	VARCHAR2	4		Y	Package Short Description
YPKG_WEBSTATUS	NUMBER	1		Y	0=No 1=Yes
YPKG_WEBENABLED	NUMBER	1		Y	0=No 1=Yes
YPKG_YCWI_ID	NUMBER	30		Y	Linked to web config

### YPKM

Package Configuration: Linked Standard Menus

Field Name	Type	Length	Decimals	Not NULL	
YPKM_ID	NUMBER	30		N	unique id for this package menu
YPKM_YPKE_ID	NUMBER	30		N	Package event id for this package menu
YPKM_YSME_ID	NUMBER	30		N	Package Standard menu id

### YPKR

Packages Configuration: Linked Miscellaneous Items

Field Name	Type	Length	Decimals	Not NULL	
YPKR_ID	NUMBER	30		N	YPKR_ID identifies YPKR
YPKR_YPKE_ID	NUMBER	30		N	Link to package event
YPKR_YCIT_ID	NUMBER	30		N	Contains link of misc item
YPKR_YCIA_ID	NUMBER	30		Y	Contains ID of misc item attribute
YPKR_QUANTITY	NUMBER	5		Y	YPKR_QUANTITY is of YPKR
YPKR_NOOFPAX	NUMBER	1		Y	1=yes

### YPKS

Link Functions Spaces / Package Events

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YPKS

Link Functions Spaces / Package Events

Field Name	Type	Length	Decimals	Not NULL	
YPKS_ID	NUMBER	30		N	Unique ID
YPKS_YPKE_ID	NUMBER	30		N	Link to Conference Package Events
YPKS_YFSC_ID	NUMBER	30		N	Link to Function Spaces

### YPLR

link table to link rules to promotions

Field Name	Type	Length	Decimals	Not NULL	
YPLR_ID	NUMBER	30		N	YPLR_ID identifies YPLR
YPLR_YPRD_ID	NUMBER	30		Y	YPLR_YPRD_ID is of YPLR
YPLR_YPRR_ID	NUMBER	30		Y	YPLR_YPRR_ID is of YPLR

### YPOL

police export triggers

Field Name	Type	Length	Decimals	Not NULL	
YPOL_ID	NUMBER	30		N	
YPOL_STATUS	NUMBER	1		N	0=New, not sent yet 1=Sent 2=response received 3=error 4=not needed to send
YPOL_YRES_ID	NUMBER	30		N	
YPOL_TYPE	NUMBER	1		N	0=new reservation 1=modified reservation
YPOL_RESPONSE	VARCHAR2	20		Y	response received from police. can be an error message
YPOL_TIMESTAMP	DATE			N	timestamp of the ypol record
YPOL_EXPORTTEXT	VARCHAR2	270		Y	
YPOL_EXPORTTIME	DATE			Y	
YPOL_IMPORTTIME	DATE			Y	
YPOL_INCOMPLETE	NUMBER	1		Y	
YPOL_XCMS_ID	NUMBER	30		N	

### YPOS

Revenue Forecast

Field Name	Type	Length	Decimals	Not NULL	
YPOS_ID	NUMBER	30		N	YPOS_ID identifies YPOS
YPOS_XCMS_ID	NUMBER	30		N	YPOS_XCMS_ID is of YPOS
YPOS_YRES_ID	NUMBER	30		N	YPOS_YRES_ID is of YPOS

### YPOS

Revenue Forecast

Field Name	Type	Length	Decimals	Not NULL	
YPOS_DATE	DATE			N	YPOS_DATE is of YPOS
YPOS_ZDCO_ID	NUMBER	30		N	YPOS_ZDCO_ID is of YPOS
YPOS_UNITPRICE	NUMBER	30	4	N	YPOS_UNITPRICE is of YPOS
YPOS_QUANTITY	NUMBER	10		N	YPOS_QUANTITY is of YPOS
YPOS_TAXLINK_ID	NUMBER	30		N	YPOS_TAXLINK_ID is of YPOS
YPOS_INTERNALSPLIT_ID	NUMBER	30		N	YPOS_INTERNALSPLIT_ID is of YPOS
YPOS_DT	NUMBER	1		Y	1 = Debit 2 = Tax
YPOS_TYPE	NUMBER	1		N	0=normal postings 1=fixed charges 2=package related postings
YPOS_RATEMODIFIER	NUMBER	30	4	Y	YPOS_RATEMODIFIER is of YPOS
YPOS_GROSSUNITPRICE	NUMBER	30	4	Y	
YPOS_ZCUR_ID	NUMBER	30		N	
YPOS_FOREIGNUNITPRICE	NUMBER	30	4	Y	
YPOS_FOREINGROSSUNITPRICE	NUMBER	30	4	Y	

### YPRD

promotion date ranges

Field Name	Type	Length	Decimals	Not NULL	
YPRD_ID	NUMBER	30		N	YPRD_ID identifies YPRD
YPRD_YPRM_ID	NUMBER	30		N	YPRD_YPRM_ID is of YPRD
YPRD_STARTDATE	DATE			Y	Valid Arrival Date from...
YPRD_ENDDATE	DATE			Y	Valid Arrival Date until...
YPRD_STARTBOOKING	DATE			Y	Valid Booking Date from...
YPRD_ENDBOOKING	DATE			Y	Valid Booking Date until...
YPRD_STAYDATERANGE	NUMBER	1		Y	Date ranges applies to the reservation stay not only arrivaldate
YPRD_PRIORTOARRIVAL	NUMBER	1		Y	if yprd_staydaterange and this field set: only if res is prior or equal to arrival to prom startdate will be applied, if staydaterange not set: only for overlapping dates prrm will be set

### YPRG

Package Report Groups

Field Name	Type	Length	Decimals	Not NULL	
YPRG_ID	NUMBER	30		N	
YPRG_SHORTDESC	VARCHAR2	3		N	

### YPRG

Package Report Groups

Field Name	Type	Length	Decimals	Not NULL
YPRG_LONGDESC	VARCHAR2	30		N
YPRG_DISPLORDER	NUMBER	4		Y
YPRG_INACTIVE	NUMBER	1		Y
YPRG_ISBREAKFAST	NUMBER	1		Y

### YPRL

package link to reservation and frequency. in frequency 0 means no 1 means yes 2 means don't change. don't change means other criteria will decide if yes or no.

Field Name	Type	Length	Decimals	Not NULL	
YPRL_ID	NUMBER	30		N	YPRL_ID identifies YPRL
YPRL_YRES_ID	NUMBER	30		N	YPRL_YRES_ID is of YPRL
YPRL_YPAC_ID	NUMBER	30		N	YPRL_YPAC_ID is of YPRL
YPRL_YFRQ_ID	NUMBER	30		N	YPRL_YFRQ_ID is of YPRL
YPRL_NEGATIVE	NUMBER	1		Y	the user wants to have this package under no circumstances
YPRL_VALUE	NUMBER	30	4	Y	YPRL_VALUE is of YPRL
YPRL_LIMIT	NUMBER	30	4	Y	YPRL_LIMIT is of YPRL
YPRL_FOREIGNVALUE	NUMBER	30	4	Y	YPRL_FOREIGNVALUE is of YPRL
YPRL_FOREIGNLIMIT	NUMBER	30	4	Y	YPRL_FOREIGNLIMIT is of YPRL
YPRL_INCLUDED	NUMBER	1		Y	YPRL_INCLUDED is of YPRL
YPRL_FROMRATE	NUMBER	1		N	1 = from ratecode
YPRL_MANUALPRICE	NUMBER	1		Y	1 = Manual Price
YPRL_MULTIPLIER	NUMBER	2		Y	Package Multiplier
YPRL_VALIDFROM	DATE			Y	YPRL_VALIDFROM is of YPRL
YPRL_VALIDUNTIL	DATE			Y	YPRL_VALIDUNTIL is of YPRL
YPRL_MASTER_YPAC_ID	NUMBER	30		Y	link to master package from sub package
YPRL_OVALUE	NUMBER	30	4	Y	
YPRL_OLIMIT	NUMBER	30	4	Y	
YPRL_OFOREIGNVALUE	NUMBER	30	4	Y	
YPRL_OFOREIGNLIMIT	NUMBER	30	4	Y	

### YPRM

Promotions

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YPRM

Promotions

Field Name	Type	Length	Decimals	Not NULL	
YPRM_ID	NUMBER	30		N	YPRM_ID identifies YPRM
YPRM_YPRC_ID	NUMBER	30		Y	YPRM_YPRC_ID is of YPRM
YPRM_SHORTDESC	VARCHAR2	3		N	YPRM_SHORTDESC is of YPRM
YPRM_LONGDESC	VARCHAR2	30		N	YPRM_LONGDESC is of YPRM
YPRM_STARTDATE	DATE			Y	Promotion availability startdate >= fideliodate
YPRM_ENDDATE	DATE			Y	Promotion availability enddate <= fideliodate
YPRM_DISPLORDER	NUMBER	3		Y	YPRM_DISPLORDER is of YPRM
YPRM_EXCLUSIVE	NUMBER	1		Y	1 = take only into consideration highest level YPRM_DISPLORDER
YPRM_INACTIVE	NUMBER	1		Y	0 = Active 1 = Inactive
YPRM_WEBENABLED	NUMBER	1		Y	
YPRM_WEBDESC	VARCHAR2	100		Y	Web description
YPRM_WEBLONG	VARCHAR2	1000		Y	web long description

### YPRN

The specified freeofcharge nights of the rule, Maximal value is YPRR\_MINDAY

Field Name	Type	Length	Decimals	Not NULL	
YPRN_ID	NUMBER	30		N	YPRN_ID identifies YPRN
YPRN_YPRR_ID	NUMBER	30		Y	Link to link table for promotion rules
YPRN_FREENIGHT	NUMBER	3		Y	Number of free nights

### YPRR

Promotion rules

Field Name	Type	Length	Decimals	Not NULL	
YPRR_ID	NUMBER	30		N	YPRR_ID identifies YPRR
YPRR_SHORTDESC	VARCHAR2	3		Y	Shortdescription
YPRR_LONGDESC	VARCHAR2	30		Y	Longdescription
YPRR_RULE	NUMBER	1		Y	Discount Types: 0 - Free Nights, 1 - Percentage/Fix Amount
YPRR_VALUE	NUMBER	10	2	Y	Percentage/Fix Amount or Number of Nights for free, depends on Discount Type
YPRR_MINDAY	NUMBER	3		Y	Minimum Nights for Rule to apply
YPRR_MAXDAY	NUMBER	3		Y	Maximum Nights for Rule to apply, if MAXDAY=0 every Reservation that has equal or more Nights, the Rule applies
YPRR_AVERAGE	NUMBER	1		Y	average rates or dont post on given days
YPRR_DISPLORDER	NUMBER	3		Y	Displayorder

### YPRR

Promotion rules

Field Name	Type	Length	Decimals	Not NULL	
YPRR_INACTIVE	NUMBER	1		Y	0 = Active 1 = Inactive
YPRR_FIXSTARTDATE	NUMBER	1		Y	If set, days in advance are calculated on first arrivaldate of rule detail
YPRR_FIXAMOUNTPERNIGHT	NUMBER	1		Y	Obsolete column, not supported anymore
YPRR_ZDCO_ID	NUMBER	30		Y	
YPRR_EB_CALCMETHOD	NUMBER	1		Y	1: OBSOLETE NOT USED (was Percentage), 2:Night 3: Stay 4: Frequency
YPRR_EB_POSTDAY	NUMBER	1		Y	0: Obsolete NOT USED (was Percentage Calculation), 1: Evenly Spread, 2:First Day 3: Last Day
YPRR_MINARRIVAL	NUMBER	3		Y	minimum days in advance
YPRR_MAXARRIVAL	NUMBER	3		Y	maximum days in advance
YPRR_YPFR_ID	NUMBER	30		Y	Nights frequency
YPRR_XCAC_ID	NUMBER	30		Y	xcac_id=0 = no pax control, xcac_id=-1 = ADULT Control, xcac_id>0 xcac_id Child control
YPRR_EB_PERCENTAGE	NUMBER	1		Y	Percentage can be chosen also for daily and stay promotions

### YPRT

Party Reservation Table

Field Name	Type	Length	Decimals	Not NULL	
YPRT_ID	NUMBER	30		N	YPRT_ID identifies YPRT
YPRT_LONGDESC	VARCHAR2	60		N	YPRT_LONGDESC partly identifies YPRT
YPRT_XCMS_ID	NUMBER	30		Y	YPRT_XCMS_ID is of YPRT
YPRT_COMMENT	VARCHAR2	2000		Y	YPRT_COMMENT is of YPRT
YPRT_GROUP	NUMBER	1		Y	Flag needed for TI: 1 means the party is a group, 0 it is a family
YPRT_INACTIVE	NUMBER	1		N	

### YPUB

Public Rooms (used for Hotel Maintenance)

Field Name	Type	Length	Decimals	Not NULL	
YPUB_ID	NUMBER	30		N	Unique ID
YPUB_SHORTDESC	VARCHAR2	3		N	Shortdescription
YPUB_LONGDESC	VARCHAR2	30		N	Longdescription
YPUB_INACTIVE	NUMBER	1		Y	0 = Active 1 = Inactive
YPUB_DISPLORDER	NUMBER	3		N	Displayorder
YPUB_DEFAULTCREDITS	NUMBER	3		Y	Housekeeping credits (credits are indicating how many units as for instance minutes the maid needs to clean the public place)
YPUB_COUNTINATTENDANTPLAN	NUMBER	1		Y	1 - The public place should be taken into consideration when calculating attendant plan

### YQUE

Queue Rooms

Field Name	Type	Length	Decimals	Not NULL	
YQUE_ID	NUMBER	30		N	YQUE_ID identifies YQUE
YQUE_Q_DATE	DATE			N	Date and Time the reservation has been placed on queue
YQUE_YRES_ID	NUMBER	30		N	Link to Reservation Header Record

### YRAA

reservation - child age link

Field Name	Type	Length	Decimals	Not NULL	
YRAA_ID	NUMBER	30		N	
YRAA_YDET_ID	NUMBER	30		N	
YRAA_AGE	NUMBER	3		N	
YRAA_NUMBER	NUMBER	3		N	

### YRAC

Reservation Attribute Categories user defined categories start from 1000

Field Name	Type	Length	Decimals	Not NULL	
YRAC_ID	NUMBER	30		N	YRAC_ID identifies YRAC
YRAC_SHORTDESC	VARCHAR2	3		N	YRAC_SHORTDESC is of YRAC
YRAC_LONGDESC	VARCHAR2	30		N	YRAC_LONGDESC is of YRAC
YRAC_DISPLORDER	NUMBER	3		Y	YRAC_DISPLORDER is of YRAC
YRAC_RESORDET	NUMBER	1		Y	can be linked to yres(1) or ydet(0)
YRAC_SINGLESELECT	NUMBER	1		N	only one can be selected(1) or multiple items can be selected(0)
YRAC_SHOWRES	NUMBER	1		Y	defines whether the user can see this entry or not in the reservation edit screen
YRAC_MANDATORYRES	NUMBER	1		Y	defines whether the user must validate this entry or not in the reservation edit screen
YRAC_SHOWACCOUNTS	NUMBER	1		Y	defines whether the user can see this entry or not in the financial accounts edit screen
YRAC_MANDATORYACCOUNTS	NUMBER	1		Y	defines whether the user must validate this entry or not in the financial accounts edit screen

### YRAG

reservation attribute groups

Field Name	Type	Length	Decimals	Not NULL	
YRAG_ID	NUMBER	30		N	YRAG_ID identifies YRAG
YRAG_YRAC_ID	NUMBER	30		N	YRAG_YRAC_ID is of YRAG

### YRAG

reservation attribute groups

Field Name	Type	Length	Decimals	Not NULL	
YRAG_SHORTDESC	VARCHAR2	3		N	YRAG_SHORTDESC is of YRAG
YRAG_LONGDESC	VARCHAR2	30		N	YRAG_LONGDESC is of YRAG
YRAG_DISPLORDER	NUMBER	3		Y	YRAG_DISPLORDER is of YRAG

### YRAK

reservation attribute link to yres

Field Name	Type	Length	Decimals	Not NULL	
YRAK_ID	NUMBER	30		N	YRAK_ID identifies YRAK
YRAK_YRES_ID	NUMBER	30		N	YRAK_YRES_ID is of YRAK
YRAK_YRAS_ID	NUMBER	30		N	YRAK_YRAS_ID is of YRAK
YRAK_YRAC_ID	NUMBER	30		N	YRAK_YRAC_ID is of YRAK

### YRAL

Reservation attribute link

Field Name	Type	Length	Decimals	Not NULL	
YRAL_ID	NUMBER	30		N	YRAL_ID identifies YRAL
YRAL_YDET_ID	NUMBER	30		N	YRAL_YDET_ID is of YRAL
YRAL_YRAS_ID	NUMBER	30		N	YRAL_YRAS_ID is of YRAL
YRAL_YRAC_ID	NUMBER	30		N	YRAL_YRAC_ID is of YRAL

### YRAS

reservation attributes

Field Name	Type	Length	Decimals	Not NULL	
YRAS_ID	NUMBER	30		N	YRAS_ID identifies YRAS
YRAS_YRAC_ID	NUMBER	30		N	YRAS_YRAC_ID is of YRAS
YRAS_SHORTDESC	VARCHAR2	3		N	YRAS_SHORTDESC is of YRAS
YRAS_LONGDESC	VARCHAR2	30		N	YRAS_LONGDESC is of YRAS
YRAS_DISPLORDER	NUMBER	3		Y	YRAS_DISPLORDER is of YRAS
YRAS_YRAG_ID	NUMBER	30		Y	YRAS_YRAG_ID is of YRAS
YRAS_INACTIVE	NUMBER	1		Y	YRAS_INACTIVE is of YRAS
YRAS_DEFAULT_RES	NUMBER	1		Y	One Source or Channel Code can be selected to be defaulted to new reservations
YRAS_DEFAULT_CCM	NUMBER	1		Y	Default for new CCM bookings can be set for one source and once channel code

### YRAT

Room type restrictions on dates and rate codes

Field Name	Type	Length	Decimals	Not NULL	
YRAT_ID	NUMBER	30		N	YRAT_ID identifies YRAT
YRAT_YCAT_ID	NUMBER	30		N	Closed room type
YRAT_DATE	DATE			N	Date od restriction
YRAT_YRCH_ID	NUMBER	30		N	Rate code of closed room
YRAT_YRPG_ID	NUMBER	30		Y	Rate Plan Group link
YRAT_RATEAVAILCAT	NUMBER	1		N	0=Rate; 1=RatePlanGroup
YRAT_SCOPE	NUMBER	1		N	0=All; 1=CRS; 2=Web; 3=Local

### YRAV

Rate Availability

Field Name	Type	Length	Decimals	Not NULL	
YRAV_ID	NUMBER	30		N	YRAV_ID identifies YRAV
YRAV_YRCH_ID	NUMBER	30		N	YRAV_YRCH_ID is of YRAV
YRAV_DATE	DATE			N	YRAV_DATE is of YRAV
YRAV_TYPE	NUMBER	2		N	OPENEDRATE=0; CLOSEDRATE=1; CLOSEDTOARR=2; DAYRATE=3; LENGTHOFSTAY=4; MINSTAYTHROUGH=5; LOS14=6; ROOMFILTER=7; NORATEDetail=8; NORATE=9; HURDLETOOSMALLPRICE=10; HURDLECLOSEDROOMTYPE=11
YRAV_VALUE	NUMBER	3		Y	Values for LOS and stay through Control
YRAV_MAXVALUE	NUMBER	10		Y	
YRAV_YRPG_ID	NUMBER	30		Y	Rate Plan Group link
YRAV_RATEAVAILCAT	NUMBER	1		N	0=Rate; 1=RatePlanGroup
YRAV_SCOPE	NUMBER	1		N	0=All; 1=CRS; 2=Web; 3=Local
YRAV_YCAT_ID	NUMBER	30		Y	0 = all roomtype, or ycat_id filled. In this case the records with ycat_ids has higher priority for the given day

### YRBR

Default block borrowing configuration

Field Name	Type	Length	Decimals	Not NULL	
YRBR_ID	NUMBER	30		N	YRBR Primary key
YRBR_ORG_YCAT_ID	NUMBER	30		N	Original room type
YRBR_BORROW_YCAT_ID	NUMBER	30		N	Room type to be borrowed from

### YRCA

ratecode attribute link.

Field Name	Type	Length	Decimals	Not NULL
YRCA_ID	NUMBER	30		N
YRCA_YRCH_ID	NUMBER	30		N
YRCA_XPDA_ID	NUMBER	30		N

### YRCC

Rate Code Category (Grouping and Rate Category Availability Control)

Field Name	Type	Length	Decimals	Not NULL	
YRCC_ID	NUMBER	30		N	YRCC_ID identifies YRCC
YRCC_SHORTDESC	VARCHAR2	3		N	YRCC_SHORTDESC is of YRCC
YRCC_LONGDESC	VARCHAR2	30		N	YRCC_LONGDESC is of YRCC
YRCC_DISPLORDER	NUMBER	3		Y	YRCC_DISPLORDER is of YRCC

### YRCD

RATE CODE Details

Field Name	Type	Length	Decimals	Not NULL	
YRCD_ID	NUMBER	30		N	YRCD_ID identifies YRCD
YRCD_YRCH_ID	NUMBER	30		N	Link to Rate Code Header
YRCD_YRSE_ID	NUMBER	30		Y	If you have defined rate seasons, you may simply select the season; the From and Until dates are then entered automatically.
YRCD_STARTDATE	DATE			N	Earliest date for which this rate detail is valid.
YRCD_ENDDATE	DATE			N	Last date for which this rate is valid.
YRCD_XCMA_ID	NUMBER	30		Y	Default market code. If blank, the market code defined for the rate code is the default
YRCD_PPPN	NUMBER	30	4	Y	Rate modifier per person per night
YRCD_PPPS	NUMBER	30	4	Y	Rate modifier per person per stay
YRCD_PRPN	NUMBER	30	4	Y	Rate modifier per room per night
YRCD_PRPS	NUMBER	30	4	Y	Rate modifier per room per stay
YRCD_YPRM_ID	NUMBER	30		Y	Linked promotion
YRCD_BASE_TYPE	NUMBER	1		Y	Base rate type is 0=percentage, 1= discount amount
YRCD_BASE_ROUNDING	NUMBER	1		Y	rounding of the rate values, 0=no rounding, 1=round up, 2=round down, 3=round decimal up, 4= round decimal down
YRCD_BASE_VALUE	NUMBER	10	4	Y	Base rate value
YRCD_YRAS_ID	NUMBER	30		Y	Customer Source Code
YRCD_BASE_TYPE_WE	NUMBER	1		Y	Weekend Base rate type is 0=percentage, 1= discount amount

### YRCD

RATE CODE Details

Field Name	Type	Length	Decimals	Not NULL	
YRCD_BASE_ROUNDING_WE	NUMBER	1		Y	Weekend rounding of the rate values, 0=no rounding, 1=round up, 2=round down, 3=round decimal up, 4=round decimal down
YRCD_BASE_VALUE_WE	NUMBER	10	4	Y	Weekend Base rate value

### YRCF

User definable Fields to be linked to YRES

Field Name	Type	Length	Decimals	Not NULL	
YRCF_ID	NUMBER	30		N	YRCF_ID identifies YRCF
YRCF_YRES_ID	NUMBER	30		N	Link to corresponding YRES record
YRCF_BOOKINGDATE	DATE			Y	

### YRCH

Ratecode header

Field Name	Type	Length	Decimals	Not NULL	
YRCH_ID	NUMBER	30		N	YRCH_ID identifies YRCH
YRCH_YRCC_ID	NUMBER	30		N	Rate Header Link to Rate Category
YRCH_SHORTDESC	VARCHAR2	10		N	Thats what is known as ratecode itself.
YRCH_LONGDESC	VARCHAR2	30		N	YRCH_LONGDESC is of YRCH
YRCH_DISPLORDER	NUMBER	3		Y	YRCH_DISPLORDER is of YRCH
YRCH_FOLIOTEXT	VARCHAR2	60		Y	Text to be printed on the guest folio. Overrides what is defined in the department code.
YRCH_XCMA_ID	NUMBER	30		Y	Default Market Code for this rate code.
YRCH_ZDCO_ID	NUMBER	30		Y	Department Code regular rate
YRCH_WEEKEND_ZDCO_ID	NUMBER	30		Y	Department Code Weekend Rate
YRCH_STARTSELL	DATE			Y	Valid rate code / sell date range (start). This is distinct from the range of actual stay dates, which is defined in the rate detail. A rate with one sell range may have several rate details with different rates for different periods of availability.
YRCH_ENDSELL	DATE			Y	Valid rate code / sell date range (end)
YRCH_MIN_LOS	NUMBER	3		Y	Minimum Length of stay
YRCH_MAX_LOS	NUMBER	3		Y	Maximum Length of stay
YRCH_ADV_BOOK	NUMBER	3		Y	Advanced Booking Days. Minimum number of days in advance that the reservation must be made.
YRCH_RHYTHM	NUMBER	1		Y	0 - daily, 1 - weekly, 2 - monthly, 3 - yearly, 4 - Flat, fixed prices for the given daterange type
YRCH_RATEINFO	VARCHAR2	2000		Y	YRCH_RATEINFO is Marketing description for rates and what they include. This is used for Hotelbank
YRCH_PUBLIC	NUMBER	1		Y	1 = true

### YRCH

Ratecode header

Field Name	Type	Length	Decimals	Not NULL	
YRCH_PRINTRATE	NUMBER	1		Y	1 = Rate Printed on REGCARD This setting will copied into YRES_PRINTRATE for the rate code selected ratecode for the arrival day.
YRCH_COMPSTATUS	NUMBER	1		Y	1 = Complimentary 2 = House Status, we will not again copy this to the reservation (TF)
YRCH_SELECTORDER	NUMBER	3		Y	Order for Rate Availability Display
YRCH_BOARDTYPE	NUMBER	1		Y	0=NO BOARD 1=BREAKFAST 2=BREAKFAST+LUNCH 3=BREAKFAST+DINNER 4=FULL BOARD 5=ALL INCLUSIVE
YRCH_WEEKEND_MON	NUMBER	1		Y	YRCH_WEEKEND_MON is of YRCH
YRCH_WEEKEND_TUE	NUMBER	1		Y	YRCH_WEEKEND_TUE is of YRCH
YRCH_WEEKEND_WED	NUMBER	1		Y	YRCH_WEEKEND_WED is of YRCH
YRCH_WEEKEND_THU	NUMBER	1		Y	YRCH_WEEKEND_THU is of YRCH
YRCH_WEEKEND_FRI	NUMBER	1		Y	YRCH_WEEKEND_FRI is of YRCH
YRCH_WEEKEND_SAT	NUMBER	1		Y	YRCH_WEEKEND_SAT is of YRCH
YRCH_WEEKEND_SUN	NUMBER	1		Y	YRCH_WEEKEND_SUN is of YRCH
YRCH_ZCUR_ID	NUMBER	30		Y	Foreign Currency
YRCH_YIELDABLE	NUMBER	1		Y	0 = Non Yieldable, 1 = Fully Yieldable, 2 = Stay Pattern Yieldable
YRCH_PPPN	NUMBER	30	4	Y	Rate modifier per person per night
YRCH_PPPS	NUMBER	30	4	Y	Rate modifier per person per stay
YRCH_PRPN	NUMBER	30	4	Y	Rate modifier per room per night
YRCH_PRPS	NUMBER	30	4	Y	Rate modifier per room per stay
YRCH_XCHTYPE	NUMBER	1		Y	Exchange rate refresh options
YRCH_XCHVALUE	NUMBER	10	4	Y	Echange rate refresh value
YRCH_XCHDEFAULT	NUMBER	1		Y	Refresh exchange rates at checkin
YRCH_CALCMETHOD	NUMBER	1		Y	0 - normal, 1 - robinson style, daylist price calculation
YRCH_CALCDAYCOUNT	NUMBER	2		Y	number of days used in the daygrid if calcmethod is daybased
YRCH_WEBENABLED	NUMBER	1		Y	Is available for WEB
YRCH_TCOD_ID	NUMBER	30		Y	Id of TAP commission code
YRCH_FLAT	NUMBER	1		Y	Flat rate calculation, number of guests doesnt count
YRCH_INACTIVE	NUMBER	1		Y	Rate inactive flag
YRCH_XPDA_ID	NUMBER	30		Y	Interest Code
YRCH_WEBINFO	VARCHAR2	2000		Y	Web Short Information
YRCH_DAYTYPE	NUMBER	1		Y	Include /exclude of day type calculation with this rate code
YRCH_YRDS_ID	NUMBER	30		Y	Day Types Schema Link
YRCH_COMM_PERC	NUMBER	10	4	Y	Commission percentage field to have Conmpatibility with Myfidelio.net
YRCH_YRVL_ID	NUMBER	30		Y	Rate Availability Level Link

### YRCH

Ratecode header

Field Name	Type	Length	Decimals	Not NULL	
YRCH_BARRATE	NUMBER	1		Y	Rate code is available for BAR Yield management
YRCH_FIXED	NUMBER	1		Y	yrch_fixed=1 rate amount or modifiers can not be changed in reservation if selected rate is fixed
YRCH_ZARR_ID	NUMBER	30		Y	default arrangement code for all department codes posted with this rate code (also packages) - in case it is empty, arrangement code from department code setup will be used instead
YRCH_YCDP_ID	NUMBER	30		Y	policy link
YRCH_BASERATE	NUMBER	1		Y	Rate is a baserate
YRCH_BASE_YRCH_ID	NUMBER	30		Y	The parent Rate where the base rate is linked to
YRCH_BASE_TYPE	NUMBER	1		Y	Base rate type is 0=percentage, 1= discount amount
YRCH_BASE_ROUNDING	NUMBER	1		Y	rounding of the rate values, 0=no rounding, 1=round up, 2=round down, 3=round decimal up, 4= round decimal down
YRCH_BASE_VALUE	NUMBER	10	4	Y	Base rate value
YRCH_XGCA_ID	NUMBER	30		N	childage category group
YRCH_WRPT_ID	NUMBER	30		Y	default confirmation letter of rate
YRCH_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information
YRCH_MD_SHORTWEBINFO	VARCHAR2	1000		Y	Web Short Information for Mobile Device
YRCH_MD_LONGWEBINFO	VARCHAR2	2000		Y	Web Long Information for Mobile Device
YRCH_SUPRESSRATE	NUMBER	1		Y	Rate is supressed for users doesnt match the corresponding userrgiht
YRCH_FAVOURITE	NUMBER	1		Y	new option on ratecalc to calculate first favourite rates
YRCH_IGNORECHANGE	NUMBER	1		Y	On rate selection the rate price on arrival date will be used for the whole stay
YRCH_AVAIL_YRCH_ID	NUMBER	30		Y	Follow availability of linked rate
YRCH_BASE_DETAILS	NUMBER	1		Y	setting to deide if base rate detail setup is used or only header configuration
YRCH_YRAS_ID	NUMBER	30		Y	Customer Source Code
YRCH_BASERATECALC_ADDTORATE	NUMBER	1		Y	calculating base rate price before or after addtoratepackages. 0 = before, 1= after
YRCH_BASERATECALC_DAYTYPE	NUMBER	1		Y	calculating base rate price before or after Daytypes. 0 = before, 1= after
YRCH_AUTOEXTENDDAYS	NUMBER	4		Y	if greater than zero, at night audit rate details ending on this day will be extended with confugured number of days, if confilct, log is written in wilg
YRCH_ONLINEINTERFACEENABLED	NUMBER	1		Y	CRS Rate Code
YRCH_OTA_RULENOTIFRQ	NUMBER	1		Y	If online interface rate code than depending on this flag, policy information will be uploaded or not
YRCH_BASE_TYPE_WE	NUMBER	1		Y	Weekend Base rate type is 0=percentage, 1= discount amount
YRCH_BASE_ROUNDING_WE	NUMBER	1		Y	Weekend rounding of the rate values, 0=no rounding, 1=round up, 2=round down, 3=round decimal up, 4= round decimal down
YRCH_BASE_VALUE_WE	NUMBER	10	4	Y	Weekend Base rate value
YRCH_SUPRESSOLDDDETAILS	NUMBER	1		N	hide rate details on edit screen ending in the past (system date)
YRCH_TYPE	NUMBER	1		Y	0=Normal Rate , 1= Service Rate

### YRCH

Ratecode header

Field Name	Type	Length	Decimals	Not NULL	
YRCH_ASB	NUMBER	1		N	Apartment style billing
YRCH_POSTINGRHYTHM	NUMBER	1		N	0=Weekly 1=Monthly 2=Yearly 3=CustomDays
YRCH_POSTINGRHYTHMDAYS	NUMBER	3		Y	Number of days for "Custom" posting rhythm
YRCH_POSTINGRHYTHMSTART	NUMBER	1		N	0=Check in date 1=First day of posting rhythm
YRCH_TAXEXEMPT_ZDCO_ID	NUMBER	30		Y	Department code for tax exempt part of room charge
YRCH_TAXED_ZDCO_ID	NUMBER	30		Y	Department code for taxed part of room charge

### YRCL

Reservation Credit Card Link

Field Name	Type	Length	Decimals	Not NULL	
YRCL_ID	NUMBER	30		N	Unique Identifier
YRCL_YRES_ID	NUMBER	30		Y	Reservation Number
YRCL_ZFAC_ID	NUMBER	30		Y	if linked to financial account
YRCL_XCCS_ID	NUMBER	30		N	link to credit card
YRCL_GUARANTEECARD	VARCHAR2	1		Y	If the guest does not turn up, the hotel should charge this card for noshow.
YRCL_TRACK1	VARCHAR2	150		Y	Crypted Track 1 Information
YRCL_TRACK2	VARCHAR2	150		Y	Crypted Track 2 Information. Removed in Night Audit after Check out.
YRCL_TRACK3	VARCHAR2	150		Y	Crypted Track 3 Information.
YRCL_USAGETYPE	NUMBER	1		Y	if the card is a usage choice card we ask how to handle and store here: 1 = Credit card 2 = Bank card (local, scandinavia) 3 = Debit card (scandinavia , uk)
YRCL_SWIPED	NUMBER	1		Y	flag to know, if this card was ever swiped for Track2 info (0.Not swiped 1.swiped)
YRCL_FOREIGN_CURR_CODE	VARCHAR2	6		Y	Foreign Currency code
YRCL_FOREIGN_CURR_OPTION	NUMBER	1		Y	Guest choice to pay in Foreign Currency 0. Not confirmed by guest 1. Guest Choice (NO) 2. Guest Choice (Yes)
YRCL_ZCUC_ID	NUMBER	30		Y	
YRCL_FIDCRSID	VARCHAR2	60		Y	

### YRCM

res (vacation) contract members

Field Name	Type	Length	Decimals	Not NULL	
YRCM_ID	NUMBER	30		N	
YRCM_YRCS_ID	NUMBER	30		N	
YRCM_XCMS_ID	NUMBER	30		N	

### YRCO

Reservation confirmation letter

Field Name	Type	Length	Decimals	Not NULL	
YRCO_ID	NUMBER	30		N	YRCO_ID identifies YRCO
YRCO_YRES_ID	NUMBER	30		Y	Reservation number of this confirmation letter print out
YRCO_DONE	NUMBER	1		N	already printed (1) should be printed in future (0)
YRCO_TIME	DATE			Y	YRCO_TIME is of YRCO
YRCO_WTXT_ID	NUMBER	30		Y	link to file or table where we store all printouts
YRCO_WRPT_ID	NUMBER	30		Y	Link to Letter template
YRCO_YBOM_ID	NUMBER	30		Y	Linked Booking Number
YRCO_YGRP_ID	NUMBER	30		Y	Link for Group Confirmation Letters
YRCO_WACT_ID	NUMBER	30		Y	Linked with activity id
YRCO_WMAI_ID	NUMBER	30		Y	Reference to the sent e-mail. If exists - means the confirmation letter has been e-mailed
YRCO_PRINTEDFROM	NUMBER	2		Y	from which level report is printed: 1-booking level; 2-events level
YRCO_FAXNUMBER	VARCHAR2	64		Y	fax number where letter was sent
YRCO_SAVEDONLY	NUMBER	1		N	0 if the letter was printed 1 - temporary saved copy
YRCO_XCMS_ID	NUMBER	30		Y	Profile id in case of profile letters
YRCO_CONTACT_XCMS_ID	NUMBER	30		Y	contact id in case of profile letters in order to search them back easier
YRCO_ALLOWSEND	NUMBER	1		Y	if user has no right to send letters but allowsend=1 then employee can send the letter, 2=denied
YRCO_FAX_XCMS_ID	NUMBER	30		Y	
YRCO_PHONE	VARCHAR2	30		Y	Phone number if have been send by SMS
YRCO_YRCS_ID	NUMBER	30		Y	
YRCO_YRCS_YEAR	NUMBER	4		Y	
YRCO_YBLH_ID	NUMBER	30		Y	
YRCO_DOCNAME	VARCHAR2	200		Y	Document description if not based on the report
YRCO_RRES_ID	NUMBER	30		Y	Linked to table reservation id
YRCO_XMLS_ID	NUMBER	30		Y	Linked to incoming email id
YRCO_REPORTNAME	VARCHAR2	60		Y	CRS does not sync reports. This stores report name and gets synchronized
YRCO_TYPE	NUMBER	1		Y	CRS does not have all information, but needs to know what kind of confirmation letter it was on the other side.
YRCO_VBOK_ID	NUMBER	30		Y	

### YRCP

rate code package link

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YRCP

rate code package link

Field Name	Type	Length	Decimals	Not NULL	
YRCP_ID	NUMBER	30		N	YRCP_ID identifies YRCP
YRCP_YRCH_ID	NUMBER	30		N	YRCP_YRCH_ID is of YRCP
YRCP_YPAC_ID	NUMBER	30		N	YRCP_YPAC_ID is of YRCP
YRCP_YPFR_ID	NUMBER	30		N	YRCP_YPFR_ID is of YRCP
YRCP_INVALID	NUMBER	1		Y	YRCP_INVALID is of YRCP

### YRCR

Rate Detail Link to rooms. Rooms for which charges apply. Leave blank if the rate is the same for all rooms. Specific room numbers, as opposed to room types, to which these charges apply. The system accepts either room types or room numbers, but not both in the same rate detail.

Field Name	Type	Length	Decimals	Not NULL	
YRCR_ID	NUMBER	30		N	YRCR_ID identifies YRCR
YRCR_YRCD_ID	NUMBER	30		N	Link to Rate Details
YRCR_YRMS_ID	NUMBER	30		N	Link to Rooms Table

### YRCS

Vacation sharer contracts (reservation contracts)

Field Name	Type	Length	Decimals	Not NULL	
YRCS_ID	NUMBER	30		N	
YRCS_XCMS_ID	NUMBER	30		N	
YRCS_VALIDFROM	DATE			N	
YRCS_VALIDUNTIL	DATE			Y	
YRCS_STAYFROM	DATE			Y	year part is ignored. also ignored if week values are filled
YRCS_STAYUNTIL	DATE			Y	year part is ignored. also ignored if week values are filled
YRCS_YCRT_ID	NUMBER	30		Y	
YRCS_WEEK	NUMBER	2		Y	on which week the stay begins
YRCS_LENGTHWEEKS	NUMBER	2		Y	length of stay in weeks
YRCS_FLOATING	NUMBER	1		Y	1=week value needs to be defined for every year separately. yrsc_week is ignored
YRCS_YCAT_ID	NUMBER	30		Y	filled only if different from template
YRCS_YRMS_ID	NUMBER	30		Y	fixed room
YRCS_YRCH_ID	NUMBER	30		Y	reservation rate code
YRCS_CONTRACT_YRCH_ID	NUMBER	30		Y	contract yearly charges rate code
YRCS_XCMA_ID	NUMBER	30		Y	
YRCS_COMMENT	VARCHAR2	2000		Y	

## YRCS

Vacation sharer contracts (reservation contracts)

Field Name	Type	Length	Decimals	Not NULL	
YRCS_NOOFPERSONS	NUMBER	3		Y	
YRCS_ARRIVALDAYOFWEEK	NUMBER	1		Y	1=sunday 7=saturday
YRCS_ACTIONTIMESTAMP	DATE			Y	
YRCS_ERRORTEXT	VARCHAR2	2000		Y	error information from last automatic reservation creation procedure
YRCS_LASTACTIONYEAR	NUMBER	4		Y	
YRCS_CONTRACTNUMBER	VARCHAR2	50		Y	
YRCS_SOURCE_YRAS_ID	NUMBER	30		Y	

## YRCT

Roomtype and RateDetail Link Table. Determines which roomtypes are linked to the specified ratedetail. Room types for which charges apply. Leave blank if the rate is the same for all room types.

Field Name	Type	Length	Decimals	Not NULL	
YRCT_ID	NUMBER	30		N	YRCT_ID identifies YRCT
YRCT_YRCD_ID	NUMBER	30		N	Link to Rate Detail Record
YRCT_YCAT_ID	NUMBER	30		N	Link to Room Type. We can link multiple room types to one rate Detail.

## YRCV

Rate Code Details for adult rates

Field Name	Type	Length	Decimals	Not NULL	
YRCV_ID	NUMBER	30		N	YRCV_ID identifies YRCV
YRCV_YRCD_ID	NUMBER	30		N	Link to Rate Details
YRCV_NOOFADULTS	NUMBER	2		N	Number of Adults entered in the MATRIX Edit Screen
YRCV_VALUE	NUMBER	30	4	N	Value for the adults. Will be added to the total rate amount by all linked rate additions, as for instance Child Age Category Rate Calculation from YRXC
YRCV_DEFAULT	NUMBER	1		Y	Default rate detail. 0=no, 1=yes
YRCV_WEEKEND_VALUE	NUMBER	30	4	Y	weekend price
YRCV_DAYNUM	NUMBER	2		Y	Identifier for the given day for ratecalculation method 2 (robinson)

## YRCX

Rate code detail for children rates

Field Name	Type	Length	Decimals	Not NULL	
YRCX_ID	NUMBER	30		N	YRCX_ID identifies YRCX
YRCX_XCAC_ID	NUMBER	30		N	YRCX_XCAC_ID is of YRCX
YRCX_NOOFCHILDS	NUMBER	3		N	YRCX_NOOFCHILDS is of YRCX

### YRCX

Rate code detail for children rates

Field Name	Type	Length	Decimals	Not NULL	
YRCX_VALUE	NUMBER	30	4	N	YRCX_VALUE is of YRCX
YRCX_YRCV_ID	NUMBER	30		N	YRCX_YRCV_ID is of YRCX
YRCX_DEFAULT	NUMBER	1		Y	Default rate detail. 0=no, 1=yes
YRCX_WEEKEND_VALUE	NUMBER	30	4	Y	YRCX_WEEKEND_VALUE is of YRCX

### YRCY

Vacation sharing years for exception and floating weeks

Field Name	Type	Length	Decimals	Not NULL	
YRCY_ID	NUMBER	30		N	
YRCY_YRCS_ID	NUMBER	30		N	
YRCY_YEAR	NUMBER	4		N	
YRCY_WEEK	NUMBER	2		Y	
YRCY_WEEKTO	NUMBER	2		Y	
YRCY_YEARLYFEE_PERSTAY	NUMBER	30	4	Y	
YRCY_YCAT_ID	NUMBER	30		Y	
YRCY_YRMS_ID	NUMBER	30		Y	

### YRCZ

Vacation sharing yearly fee postings to zfac

Field Name	Type	Length	Decimals	Not NULL	
YRCZ_ID	NUMBER	30		N	
YRCZ_YRCS_ID	NUMBER	30		N	
YRCZ_YEAR	NUMBER	4		N	
YRCZ_WEEKFROM	NUMBER	2		N	
YRCZ_WEEKTO	NUMBER	2		N	
YRCZ_FEE	NUMBER	30	4	N	
YRCZ_TIMESTAMP	DATE			N	
YRCZ_XCED_ID	NUMBER	30		N	
YRCZ_XCMS_ID	NUMBER	30		N	
YRCZ_ZFAC_ID	NUMBER	30		N	

### YRDA

MENITY LINK TO RES DETAIL

Field Name	Type	Length	Decimals	Not NULL	
YRDA_ID	NUMBER	30		N	YRDA_ID identifies YRDA
YRDA_YDET_ID	NUMBER	30		Y	YRDA_YDET_ID is of YRDA
YRDA_YAMN_ID	NUMBER	30		Y	YRDA_YAMN_ID is of YRDA
YRDA_MANUAL	NUMBER	1		N	

### YRDB

automatic day type rules

Field Name	Type	Length	Decimals	Not NULL	
YRDB_ID	NUMBER	30		N	
YRDB_DISPLORDER	NUMBER	5		N	
YRDB_TYPE	NUMBER	2		N	0=definite occupancy is over x 1=definite occupancy is below x 2=definite occupancy is over x % 3=definite occupancy is below x %
YRDB_VALUE	NUMBER	5		N	
YRDB_YRDT_ID	NUMBER	30		N	
YRDB_MINDAYS	NUMBER	5		Y	rule can be applied to a minimum number of days in the future from current day
YRDB_MAXDAYS	NUMBER	5		Y	rule can be applied to a maximum number of days in the future from current day
YRDB_TENTATIVERES	NUMBER	1		N	

### YRDC

DAY TYPE CALENDAR

Field Name	Type	Length	Decimals	Not NULL	
YRDC_ID	NUMBER	30		N	
YRDC_YRDT_ID	NUMBER	30		Y	
YRDC_DATE	DATE			Y	
YRDC_AUTOMATIC	NUMBER	1		N	1=assigned automatically 0=manually
YRDC_YCAD_ID	NUMBER	30		N	Day type calendar value link to Hotel Segment

### YRDD

RATES DAY TYPE PER ROOMTYPE ADULT VALUES TABLE

Field Name	Type	Length	Decimals	Not NULL	
YRDD_ID	NUMBER	30		N	
YRDD_YRDT_ID	NUMBER	30		Y	
YRDD_YRDS_ID	NUMBER	30		Y	

## YRDD

RATES DAY TYPE PER ROOMTYPE ADULT VALUES TABLE

Field Name	Type	Length	Decimals	Not NULL
YRDD_AVERAGE	NUMBER	1		Y
YRDD_FIRSTDAY	NUMBER	1		Y
YRDD_TYPE	NUMBER	1		Y

## YRDE

Day type schema date range details

Field Name	Type	Length	Decimals	Not NULL	
YRDE_ID	NUMBER	30		N	
YRDE_YRDD_ID	NUMBER	30		N	
YRDE_STARTDATE	DATE			Y	Daytype detail start date, if empty valid for the past
YRDE_ENDDATE	DATE			Y	Daytype detail end date, if empty valid for the future

## YRDF

User definable Fields to be linked to YDET

Field Name	Type	Length	Decimals	Not NULL	
YRDF_ID	NUMBER	30		N	Unique Identifier
YRDF_YDET_ID	NUMBER	30		N	Link to corresponding YDET record

## YRDL

day type lock to disable automatic changes for a day

Field Name	Type	Length	Decimals	Not NULL
YRDL_DATE	DATE			N
YRDL_CREATIONDATE	DATE			N
YRDL_REASON	VARCHAR2	2000		Y

## YRDM

auto daytype rule to hotelsegment linktable

Field Name	Type	Length	Decimals	Not NULL
YRDM_ID	NUMBER	30		N
YRDM_YRDB_ID	NUMBER	30		N
YRDM_YCAD_ID	NUMBER	30		N

### YRDP

rate code detail packages

Field Name	Type	Length	Decimals	Not NULL	
YRDP_ID	NUMBER	30		N	YRDP_ID identifies YRDP
YRDP_YRCD_ID	NUMBER	30		N	YRDP_YRCD_ID is of YRDP
YRDP_YPAC_ID	NUMBER	30		N	YRDP_YPAC_ID is of YRDP
YRDP_YPFR_ID	NUMBER	30		N	YRDP_YPFR_ID is of YRDP
YRDP_INVALID	NUMBER	1		Y	YRDP_INVALID is of YRDP

### YRDR

Rate difference Reasons

Field Name	Type	Length	Decimals	Not NULL	
YRDR_ID	NUMBER	30		N	YRDR_ID identifies YRDR
YRDR_REASON	VARCHAR2	30		N	YRDR_REASON is of YRDR
YRDR_DISPLORDER	NUMBER	3		N	YRDR_DISPLORDER is of YRDR
YRDR_INACTIVE	NUMBER	1		Y	1 = inactive

### YRDS

DAY TYPE SCHEMA

Field Name	Type	Length	Decimals	Not NULL	
YRDS_ID	NUMBER	30		N	
YRDS_SHORTDESC	VARCHAR2	3		Y	
YRDS_LONGDESC	VARCHAR2	60		Y	
YRDS_DISPLORDER	NUMBER	3		Y	
YRDS_INACTIVE	NUMBER	1		Y	

### YRDT

RATES DAY TYPE TABLE

Field Name	Type	Length	Decimals	Not NULL	
YRDT_ID	NUMBER	30		N	
YRDT_SHORTDESC	VARCHAR2	6		Y	
YRDT_LONGDESC	VARCHAR2	60		Y	
YRDT_DISPLORDER	NUMBER	3		Y	
YRDT_INACTIVE	NUMBER	1		Y	
YRDT_WCOL_ID	NUMBER	30		Y	

### YRDT

RATES DAY TYPE TABLE

Field Name	Type	Length	Decimals	Not NULL	
YRDT_ROLE	NUMBER	1		Y	null, 0 = Normal Daytype; 1=BAR Daytype
YRDT_BARCODE	VARCHAR2	30		Y	BAR Interface Bar Code Linkage

### YRDU

Field Name	Type	Length	Decimals	Not NULL	
YRDU_ID	NUMBER	30		N	
YRDU_FIDELIODATE	DATE			N	
YRDU_PCDATE	DATE			N	
YRDU_YRDC_FOR_DATE	DATE			N	
YRDU_YRDC_OLD_DATE	DATE			Y	
YRDU_YRDT_ID	NUMBER	30		N	
YRDU_OLD_YRDT_ID	NUMBER	30		Y	
YRDU_TYPE	NUMBER	1		N	

### YRDV

Day type adult values

Field Name	Type	Length	Decimals	Not NULL	
YRDV_ID	NUMBER	30		N	
YRDV_YRDY_ID	NUMBER	30		Y	
YRDV_ADULTCOUNT	NUMBER	2		Y	
YRDV_VALUE	NUMBER	10	4	Y	

### YRDX

RATES DAY TYPE PER ROOMTYPE CHILD VALUES TABLE

Field Name	Type	Length	Decimals	Not NULL	
YRDX_ID	NUMBER	30		N	
YRDX_YRDD_ID	NUMBER	30		Y	
YRDX_XCAC_ID	NUMBER	30		Y	
YRDX_VALUE	NUMBER	10	4	Y	
YRDX_YRDV_ID	NUMBER	30		Y	

## YRDY

Day type schema/daytype value configuration per room type

Field Name	Type	Length	Decimals	Not NULL	
YRDY_ID	NUMBER	30		N	
YRDY_YRDD_ID	NUMBER	30		Y	Obsolete column, not used anymore
YRDY_YCAT_ID	NUMBER	30		Y	
YRDY_YRDE_ID	NUMBER	30		Y	

## YRES

YRES is the reservation master record contains reservation data which does not (necessarily) change during the guests stay.

Field Name	Type	Length	Decimals	Not NULL	
YRES_ID	NUMBER	30		N	YRES_ID is the unique identifier of YRES.
YRES_YBOM_ID	NUMBER	30		Y	YRES_YBOM_ID is the link into YBOM (Booking Master Database)
YRES_XCMS_ID	NUMBER	30		Y	Main link to guest profile database (XCMS)
YRES_EXPARRTIME	DATE			N	Expected arrival date and time
YRES_ACTARRTIME	DATE			Y	Actual arrival date and time stamp of the moment of Check In.
YRES_EXPDEPTIME	DATE			N	Expected departure date and time.
YRES_ACTDEPTIME	DATE			Y	Actual departure date and time stamp at Check Out.
YRES_CRSSRESNR	VARCHAR2	50		Y	Unique ID coming from CRS Sytem, linked to YRES_CRSSYSTEM in order to support multiple CRS systems.
YRES_CRSSYSTEM	VARCHAR2	30		Y	ID of the CRS system the reservation originates from. Linked to YRES_CRSSRESNR.
YRES_HASSHARE	NUMBER	1		Y	Indicates a sharing during the stay (1) or not (0 or null). The share link itself is related to YDET in order to support different share relations during a stay.
YRES_YGCO_ID	NUMBER	30		Y	Link to guarantee types (YGCO)
YRES_RESSTATUS	NUMBER	1		N	0=tentative 1=definitive 2= reserved for future purpose 3=not effecting availability, as an example reservation offers and waitlist entries will have a YRES_RESSTATUS=3. this field can be found in yres and ybst
YRES_REQUESTED	CHAR			Y	YRES_REQUESTED is of YRES (whats that for??)
YRES_LASTFIXPOSTTIME	DATE			Y	Last date of posting fix charges. Needed for tracking this information if an advance folio has been performed.
YRES_DEFPAYMETH_ZDCO_ID	NUMBER	30		Y	YRES_DEFPAYMETH_ZDCO_ID is the default payment method for this reservation. This is directly linked to the department code setuo database (ZDCO)
YRES_NOAVAILREASON	NUMBER	1		Y	Reason why not affecting availability. 1 = Waitlist 2 = Offer 3 = Canceled 4 = No Show 5 = Voucher Template If the reservation status is 3 this field must be filled controlled by the business logic.
YRES_PREVRESSTATUS	NUMBER	1		Y	previous reservation status (to know if it was definite or tentative when reactivating a waitlisted or other reservation)
YRES_NOPOST	NUMBER	1		Y	No post flag for POS interfaces. 1 = no posting allowed on POS 0 or null = postings allowed
YRES_VID_CHKO	NUMBER	1		Y	Video checkout allowed = '1'
YRES_WALKIN	NUMBER	1		Y	1 = Walkin 0 or null = nothing

### YRES

YRES is the reservation master record contains reservation data which does not (necessarily) change during the guests stay.

Field Name	Type	Length	Decimals	Not NULL	Description
YRES_WCOL_ID	NUMBER	30		Y	Color for display in Room Rack
YRES_YGRP_ID	NUMBER	30		Y	YRES_YGRP_ID is of YRES
YRES_CONTRACT_ZCUR_ID	NUMBER	30		Y	YRES_CONTRACT_ZCUR_ID is of YRES
YRES_CONTRACT_EXCHRATE	NUMBER	38	18	Y	YRES_CONTRACT_EXCHRATE is of YRES
YRES_CONFIRMATIONNO	VARCHAR2	10		N	Confirmation number string. Last value read from wuss and group reservation split gets the original string with /number
YRES_RATEDIFFREASON	VARCHAR2	30		Y	YRES_RATEDIFFREASON is of YRES
YRES_VACANT	NUMBER	1		Y	if guest leaves the room but does not pay the invoice (former px) we populate with 1 until check out
YRES_PRINTRATE	NUMBER	1		Y	1 = Print Rate on RegCard
YRES_CREDITSTAT	NUMBER	1		Y	Obsolete field, not used anymore
YRES_SHARETYPE	NUMBER	1		Y	Type of share (0=independent 1=master 2=slave). In first release we will only support independant share. Which is the same handling as in Version 7, but a parameter will control if the system comes up with rate calculation or does allow easy sharing functionality
YRES_FREETEXT1	VARCHAR2	100		Y	Free text fields for flexilbe purpose, later we will move these fields to a userdefinable table where udef fields can be setup.
YRES_FREETEXT2	VARCHAR2	100		Y	YRES_FREETEXT2 is of YRES
YRES_OPTION	DATE			Y	reservation option date.
YRES_LAST_YDET_ID	NUMBER	30		Y	last reservation detail id
YRES_CURRENT_YDET_ID	NUMBER	30		Y	most current reservation detail id
YRES_EXPDEPHOUR	DATE			Y	expected departure time
YRES_YRMS_ID	NUMBER	30		Y	for scheduled room move. when the room move is performed we will with new room. actual occupancy reads from this field, availability from ydet_yrms_id
YRES_ADULTTAXFREE	NUMBER	1		Y	1 if adults are tax free, used in swiss, former handled by rkz5
YRES_EXPARRHOUR	DATE			Y	expected arrival time
YRES_ACTARRTIMENULL	NUMBER	1		Y	Used for speed in queries, 1 as long as guest is not checked in
YRES_ACTDEPTIMENULL	NUMBER	1		Y	Used for speed in queries, 1 as long as guest is not checked out
YRES_REGCARDNUMBER	NUMBER	30		Y	Regcard number (if system is configured to use that)
YRES_LAST_YCXL_ID	NUMBER	30		Y	Last Cancellation ID
YRES_REINSTATED	NUMBER	1		Y	1 = checked out guests get reinstated and 0 again after next check out
YRES_CALCSTATUS	NUMBER	2		N	0=expected(future) 1=expected today 2=checked in today 3=in house 4=exp dep today 5=departed today 6=history 7=day use exp 8=day use in house 9=day use history 10=waitlist 11=offer 12=cancelled 13=noshow 14=voucher template 15=day use exp today 17=day use departed today
YRES_ORGDEPTIME	DATE			N	Original Departure Date to retrieve info about early departures and extended stays

### YRES

YRES is the reservation master record contains reservation data which does not (necessarily) change during the guests stay.

Field Name	Type	Length	Decimals	Not NULL	Description
YRES_REVERSEEXCHRATE	NUMBER	1		Y	0 means amount*exchrates=foreignamount. 1 means amount=foreignamount/exchrates. in fact it tells in which direction the exchange rate was entered by the user
YRES_YCDP_ID	NUMBER	30		Y	Policy for this reservation, copied from profile on reservation creation.
YRES_YACC_ID	NUMBER	30		Y	Selected Amenity Cycle for this reservation
YRES_EXCH_LASTMODTIME	DATE			Y	DATE OF LAST EXCHRATES UPDATE
YRES_EXCH_UPDATECHKIN	NUMBER	1		Y	UPDATE EXCHANGE RATE AT CHECK IN
YRES_EXCH_UPDATETYPE	NUMBER	1		Y	0=NOT AUTOMATIC 1=MONTHLY 2=CERTAIN DAY OF MONTH 3=CERTAIN DAY OF WEEK(1=SUNDAY 0ISINVALID) 4=EVERY X DAYS AFTER ARRIVAL 5=FIRST CHANGE OF THE CURRENCY IN THE MONTH 6=DONT USE CONTRACTED EXCHANGE RATE, ALWAYS USE CURRENT
YRES_EXCH_UPDVALUE	NUMBER	30	16	Y	VALUES NEEDED FOR DIFFERENT TYPES
YRES_YPRT_ID	NUMBER	30		Y	Link to Party Reservation
YRES_YACC_MANUAL	NUMBER	1		Y	INDICATES IF YACC ID WAS SET MANUALLY
YRES_CREDITLIMIT	NUMBER	30	4	Y	Credit limit manual override
YRES_LASTDAYOF_YRES_ID	NUMBER	30		Y	Day use res connected to real res
YRES_ZFST_ID	NUMBER	30		Y	Default Folio Style for Reservation
YRES_UPLOADTIME	DATE			Y	Reservation upload to master hotel
YRES_SALEDATE	DATE			Y	Booking date of the reservation used to calculate promotions (instead of systemdate we store here the fidelio date, when the reservation was made)
YRES_DESIRED_YRMS_ID	NUMBER	30		Y	
YRES_ALLOWANCE_ZFAC_ID	NUMBER	30		Y	
YRES_DESIRED_YCAT_ID	NUMBER	30		Y	
YRES_ZTXX_ID	NUMBER	30		Y	
YRES_SUITE_YRES_ID	NUMBER	30		Y	
YRES_NOTCLOSED_ZFAC_ID	NUMBER	30		Y	
YRES_CHKOUTSHARESTATUS	NUMBER	1		Y	
YRES_LOCKROOM	NUMBER	1		N	
YRES_NOZRDF	NUMBER	1		Y	user definitely asked for no zrdf to be linked ever
YRES_POLICEEXPORT	NUMBER	1		Y	0=no export necessary 1=export to ypol is needed 2=export to ypol was performed
YRES_BONUS_XMNR_ID	NUMBER	30		Y	link to bonus point card
YRES_YRCS_ID	NUMBER	30		Y	Link to vacation sharer
YRES_DENYKIOSKCHECKIN	NUMBER	1		Y	
YRES_YRFR_ID	NUMBER	30		Y	reservation - Multiple Offers Link
YRES_NO_EFT_AUTHORIZATION	NUMBER	1		Y	

### YRES

YRES is the reservation master record contains reservation data which does not (necessarily) change during the guests stay.

Field Name	Type	Length	Decimals	Not NULL	
YRES_NOBONUSPOINT	NUMBER	1		N	
YRES_SUITE_YRMS_ID	NUMBER	30		Y	
YRES_SELLINGLIMITSCOPE	NUMBER	1		N	0=General limit 1=Web limit
YRES_FROMCRS	NUMBER	1		N	1=crs system created reservation 0=pms uploaded reservation to crs
YRES_CENTRALCORRESPONDENCE	NUMBER	1		N	
YRES_CRSMAIN	NUMBER	1		Y	Main reservation of sharers when uploading them as a single reservation to crs systems

### YRET

returnable item packages linked to reservation

Field Name	Type	Length	Decimals	Not NULL	
YRET_ID	NUMBER	30		N	
YRET_YRES_ID	NUMBER	30		N	
YRET_YPAC_ID	NUMBER	30		N	
YRET_QUANTITY	NUMBER	3		N	
YRET_OUTTIME	DATE			N	
YRET_BACKTIME	DATE			Y	
YRET_DEPOSIT_ZPOS_ID	NUMBER	30		Y	
YRET_ANTIDEPOSIT_ZPOS_ID	NUMBER	30		Y	
YRET_NORETURN_ZPOS_ID	NUMBER	30		Y	

### YRFL

FLIGHT LINK (MORE THAN ONE ARRIVAL AND MORE THAN ONE DEPARTURE COULD BE LINKED TO THE SAME YRES)

Field Name	Type	Length	Decimals	Not NULL	
YRFL_ID	NUMBER	30		N	Unique Identifier
YRFL_WFLT_ID	NUMBER	30		Y	YRFL_WFLT_ID is of YRFL
YRFL_YRES_ID	NUMBER	30		N	YRFL_YRES_ID is of YRFL
YRFL_WGPT_ID	NUMBER	30		Y	YRFL_WGPT_ID is of YRFL
YRFL_PICKUPEMP_XCED_ID	NUMBER	30		Y	EMPLOYEE WHO IS RESPONSIBLE FOR PICK UP
YRFL_TIME	DATE			N	FROM WFLT BUT THEY CAN CHANGE IT MANUALLY
YRFL_NOTES	VARCHAR2	200		Y	WHY IT HAS A DIFFERENT TIME
YRFL_PAX	NUMBER	3		N	NUMBER OF PEOPLE TO PICK UP
YRFL_PICKUPTYPE	VARCHAR2	200		Y	CAN BE SELECTED FROM WPGT AND CHANGED HERE MANUALLY

### YRFL

FLIGHT LINK (MORE THAN ONE ARRIVAL AND MORE THAN ONE DEPARTURE COULD BE LINKED TO THE SAME YRES)

Field Name	Type	Length	Decimals	Not NULL	
YRFL_ARRDEP	NUMBER	1		N	0=ARRIVAL 1=DEPARTURE

### YRFR

reservation - Multiple Offers

Field Name	Type	Length	Decimals	Not NULL	
YRFR_ID	NUMBER	30		N	
YRFR_DATE	DATE			N	
YRFR_XCED_ID	NUMBER	30		N	

### YRFT

0 = active 1= inactive

Field Name	Type	Length	Decimals	Not NULL	
YRFT_ID	NUMBER	30		N	YRFT_ID identifies YRFT
YRFT_SHORTDESC	VARCHAR2	3		N	YRFT_SHORTDESC is of YRFT
YRFT_LONGDESC	VARCHAR2	30		N	YRFT_LONGDESC is of YRFT
YRFT_DISPLORDER	NUMBER	3		Y	YRFT_DISPLORDER is of YRFT
YRFT_INACTIVE	NUMBER	1		Y	0 = active 1= inactive

### YRGA

Reservation Multi Guest Amounts

Field Name	Type	Length	Decimals	Not NULL	
YRGA_ID	NUMBER	30		N	YRGA_ID identifies YRGA
YRGA_YDET_ID	NUMBER	30		N	YRGA_YDET_ID is of YRGA
YRGA_XCAC_ID	NUMBER	30		N	YRGA_XCAC_ID is of YRGA
YRGA_YRPL_ID	NUMBER	30		Y	YRGA_YRPL_ID is of YRGA
YRGA_AMOUNT	NUMBER	30	4	Y	YRGA_AMOUNT is of YRGA
YRGA_FAMOUNT	NUMBER	30	4	Y	YRGA_FAMOUNT is of YRGA
YRGA_XCACINDEX	NUMBER	3		Y	YRGA_XCACINDEX is of YRGA

### YRGL

Reservation age link from YDET into XCAC

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

## YRGL

Reservation age link from YDET into XCAC

Field Name	Type	Length	Decimals	Not NULL	
YRGL_ID	NUMBER	30		N	YRGL_ID identifies YRGL
YRGL_YDET_ID	NUMBER	30		N	YRGL_YDET_ID is the link into YDET.
YRGL_XCAC_ID	NUMBER	30		N	YRGL_XCAC_ID is the Link into XCAC.
YRGL_NUMBER	NUMBER	3		N	YRGL_NUMBER is the number of selected Age for selected YDET record.

## YRGP

Reservation Multi Guest Package Prices

Field Name	Type	Length	Decimals	Not NULL	
YRGP_ID	NUMBER	30		N	YRGP_ID identifies YRGP
YRGP_YPAC_ID	NUMBER	30		N	YRGP_YPAC_ID is of YRGP
YRGP_YRGA_ID	NUMBER	30		N	YRGP_YRGA_ID is of YRGP
YRGP_VALUE	NUMBER	30	4	N	YRGP_VALUE is of YRGP
YRGP_FVALUE	NUMBER	30	4	N	YRGP_FVALUE is of YRGP
YRGP_MULTIPLIER	NUMBER	2		Y	
YRGP_LIMIT	NUMBER	30	4	Y	limit value for allowance packages
YRGP_FLIMIT	NUMBER	30	4	Y	foreign currency limit value for allowance packages
YRGP_OVALUE	NUMBER	30	4	Y	
YRGP_OLIMIT	NUMBER	30	4	Y	
YRGP_OFVALUE	NUMBER	30	4	Y	
YRGP_OFLIMIT	NUMBER	30	4	Y	

## YRGV

Government room value evaluation for tax exempt part of room charge

Field Name	Type	Length	Decimals	Not NULL	
YRGV_ID	NUMBER	30		N	
YRGV_YRMS_ID	NUMBER	30		N	
YRGV_FROM	DATE			N	
YRGV_TO	DATE			N	
YRGV_VALUE	NUMBER	30	4	N	

### YRHV

Rate Hourly Price Setup Table child age price link table

Field Name	Type	Length	Decimals	Not NULL
YRHV_ID	NUMBER	30		N
YRHV_YRCH_ID	NUMBER	30		N
YRHV_YCAT_ID	NUMBER	30		N
YRHV_RATEDATE	DATE			N
YRHV_RATETIME	NUMBER	2		N
YRHV_VALUE	NUMBER	10	4	Y

### YRHX

Storage of manipulated HSK Screen to be printed from

Field Name	Type	Length	Decimals	Not NULL
YRHX_ID	NUMBER	30		N
YRHX_YRHV_ID	NUMBER	30		N
YRHX_XCAC_ID	NUMBER	30		N
YRHX_VALUE	NUMBER	10	4	Y

### YRKP

Stores Room Key PIN

Field Name	Type	Length	Decimals	Not NULL
YRKP_ID	NUMBER	30		N
YRKP_YRES_ID	NUMBER	30		Y
YRKP_ZFAC_ID	NUMBER	30		Y
YRKP_PIN	VARCHAR2	30		Y

### YRKR

Predefined Keycard Attributes linked to Rooms

Field Name	Type	Length	Decimals	Not NULL	
YRKR_ID	NUMBER	30		N	Unique ID
YRKR_XPDA_ID	NUMBER	30		N	Link to attribute table
YRKR_YRMS_ID	NUMBER	30		N	Link to room table

### YRLD

Attribute Link to YDET

Field Name	Type	Length	Decimals	Not NULL	
YRLD_ID	NUMBER	30		N	YRLD_ID identifies YRLD
YRLD_XPAC_ID	NUMBER	30		N	YRLD_XPAC_ID is of YRLD
YRLD_XPDA_ID	NUMBER	30		N	YRLD_XPDA_ID is of YRLD
YRLD_YDET_ID	NUMBER	30		N	YRLD_YDET_ID is of YRLD

### YRLR

Attribute Link to reservation (YRES)

Field Name	Type	Length	Decimals	Not NULL	
YRLR_ID	NUMBER	30		N	YRLR_ID identifies YRLR
YRLR_XPAC_ID	NUMBER	30		N	YRLR_XPAC_ID is of YRLR
YRLR_XPDA_ID	NUMBER	30		N	YRLR_XPDA_ID is of YRLR
YRLR_YRES_ID	NUMBER	30		N	YRLR_YRES_ID is of YRLR

### YRMD

reservation room move details

Field Name	Type	Length	Decimals	Not NULL	
YRMD_ID	NUMBER	30		N	
YRMD_YRES_ID	NUMBER	30		N	
YRMD_DAY	DATE			N	date when room move is to be performed. this identifies a ydet
YRMD_REASON	VARCHAR2	200		Y	
YRMD_TIME	DATE			Y	scheduled time to perform the room move. date part is not used

### YRMR

Reservation room move reasons

Field Name	Type	Length	Decimals	Not NULL	
YRMR_ID	NUMBER	30		N	
YRMR_REASON	VARCHAR2	200		N	
YRMR_DISPLORDER	NUMBER	3		Y	

### YRMS

YRMS is the setup database for the rooms. This is linked to YCAT which does contain the room types. if the room changes in time we duplicate the record and change details in new record and change validuntil in the original and add id of original in field originalrecord in the new record

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### YRMS

YRMS is the setup database for the rooms. This is linked to YCAT which does contain the room types. If the room changes in time we duplicate the record and change details in new record and change validuntil in the original and add id of original in field originalrecord in the new record

Field Name	Type	Length	Decimals	Not NULL	
YRMS_ID	NUMBER	30		N	YRMS_ID identifies YRMS
YRMS_YCAT_ID	NUMBER	30		N	YRMS_YCAT_ID is Link to YCAT (room types)
YRMS_SHORTDESC	VARCHAR2	10		N	YRMS_SHORTDESC is the room number itself.
YRMS_LONGDESC	VARCHAR2	30		N	YRMS_LONGDESC is of YRMS
YRMS_DISPLORDER	NUMBER	5		Y	Counter for custom room display order
YRMS_VALIDFROM	DATE			N	YRMS_VALIDFROM is of YRMS
YRMS_VALIDUNTIL	DATE			N	YRMS_VALIDUNTIL is of YRMS
YRMS_ORIGINALRECORD_YRMS_ID	NUMBER	30		Y	YRMS_ORIGINALRECORD_YRMS_ID is of YRMS
YRMS_YHKS_ID	NUMBER	30		N	YRMS_YHKS_ID is of YRMS
YRMS_DEFAULT_YRCH_ID	NUMBER	30		Y	Code of the rack rate for this room. It is used only for calculating the rate variance and has no bearing on the reservation process.
YRMS_DEFAULT_RATE	NUMBER	30	4	Y	Actual rack rate, if for some reason the rack rate code is not used. Like the rate code, it is used only in calculating the rate variance and is not used in making a reservation. It is recommended to use ratecode instead of this rate amount as this would require manual update when rate changes are performed.
YRMS_NOOFPERSONS	NUMBER	2		N	YRMS_NOOFPERSONS is of YRMS
YRMS_FLOOR	NUMBER	3		Y	Floor number.
YRMS_DEFAULTCREDITS	NUMBER	3		Y	Housekeeping credits (credits are indicating how many units , as for instance minutes the maid needs to clean the room)
YRMS_DEPARTURECREDITS	NUMBER	3		Y	Housekeeping credits on departure
YRMS_HSK_OCCUPIED	NUMBER	1		Y	Information about housekeeping status of this room: 1 = occupied as per house keeping 0 = vacant as per house keeping
YRMS_MAX_BEDS	NUMBER	2		Y	YRMS_MAX_BEDS is of YRMS
YRMS_FREETEXT	VARCHAR2	1000		Y	YRMS_FREETEXT is of YRMS
YRMS_PICTURE	LONG RAW			Y	
YRMS_L_STATUS	DATE			Y	Last HouseKeeping Staus changed Date
YRMS_HSK_NOOFPERSONS	NUMBER	30		Y	Number Persons Entered by HouseKeeping Maid
YRMS_CLEANCREDITS	NUMBER	3		Y	credits for clean rooms
YRMS_SUITE_PRIMARY_YRMS_ID	NUMBER	30		Y	YRMS_PICTURE is of YRMS
YRMS_SUITE	NUMBER	1		N	
YRMS_GUESTSERVICE_STATUS	NUMBER	1		Y	1. Make up Room, 2. Do not Disturb, 3. Reset
YRMS_IGNORE_NA_CHECK	NUMBER	1		Y	1. Ignore from Night audit expiry check routine
YRMS_WALKORDER	NUMBER	5		Y	Walking order of the rooms
YRMS_MINNOOFPERSONS	NUMBER	3		Y	Miniumum number of persons (Including children) that can be booked for this room

### YROF

Reservation Offers Details

Field Name	Type	Length	Decimals	Not NULL	
YROF_ID	NUMBER	30		N	YROF_ID identifies YROF
YROF_YRES_ID	NUMBER	30		N	YROF_YRES_ID is of YROF
YROF_OFFEREDDATE	DATE			N	YROF_OFFEREDDATE is of YROF
YROF_ACCEPTEDDATE	DATE			Y	YROF_ACCEPTEDDATE is of YROF
YROF_XCOM_ID	NUMBER	30		Y	preferred communication method of this guest, how he wants to be contacted again.
YROF_TEXT	LONG			Y	YROF_TEXT is of YROF

### YROG

Groups of Room Owners' percentage rates

Field Name	Type	Length	Decimals	Not NULL	
YROG_ID	NUMBER	30		N	Unique ID
YROG_SHORTDESC	VARCHAR2	3		N	Short description
YROG_LONGDESC	VARCHAR2	30		N	Long description
YROG_INACTIVE	NUMBER	1		Y	Inactive flag

### YROL

Link between Room Owners' percentages and room owner linkage

Field Name	Type	Length	Decimals	Not NULL	
YROL_ID	NUMBER	30		N	Unique ID
YROL_YROG_ID	NUMBER	30		N	Link to group of room owners
YROL_YROS_ID	NUMBER	30		N	Link to time sharing table

### YROP

Room Owners' percentages

Field Name	Type	Length	Decimals	Not NULL	
YROP_ID	NUMBER	30		N	Unique ID
YROP_PERCENTAGE	NUMBER	5	2	N	YROP_PERCENTAGE is of YROP
YROP_ZDCO_STATS_TYPE	NUMBER	1		N	YROP_ZDCO_STATS_TYPE is of YROP
YROP_YROG_ID	NUMBER	30		Y	YROP_YROG_ID is of YROP
YROP_DOPOST	NUMBER	1		Y	YROP_DOPOST is of YROP

### YROS

Time Sharing functionality (owner management)

Field Name	Type	Length	Decimals	Not NULL	
YROS_ID	NUMBER	30		N	Unique ID
YROS_XCMS_ID	NUMBER	30		N	link to owner
YROS_YRMS_ID	NUMBER	30		N	link to bought room
YROS_VALIDFROM	DATE			N	start of bought time interval
YROS_VALIDUNTIL	DATE			N	end of bought time interval

### YRPG

Rate Plan Group

Field Name	Type	Length	Decimals	Not NULL	
YRPG_ID	NUMBER	30		N	
YRPG_SHORTDESC	VARCHAR2	10		N	Group Code
YRPG_LONGDESC	VARCHAR2	40		N	Group Name
YRPG_WEBENABLED	NUMBER	1		Y	Web enabled flag
YRPG_DISPLORDER	NUMBER	30		Y	
YRPG_INTERFACECODE	VARCHAR2	1		Y	Best Western level code

### YRPH

Suite8 Homepage, link Packages to Rate Codes, so some packages only available for some Rate Codes

Field Name	Type	Length	Decimals	Not NULL	
YRPH_ID	NUMBER	30		N	
YRPH_YRCH_ID	NUMBER	30		N	
YRPH_YPAC_ID	NUMBER	30		N	
YRPH_TYPE	NUMBER	1		Y	1 = include 0 = Exclude

### YRPI

Best Western Policy and guarantee code config

Field Name	Type	Length	Decimals	Not NULL	
YRPI_ID	NUMBER	30		N	
YRPI_YCDP_ID	NUMBER	30		N	
YRPI_YGCO_ID	NUMBER	30		N	
YRPI_LINKTABLE	VARCHAR2	4		Y	
YRPI_LINKID	NUMBER	30		Y	

## YRPI

Best Western Policy and guarantee code config

Field Name	Type	Length	Decimals	Not NULL
YRPI_STARTDATE	DATE			Y
YRPI_ENDDATE	DATE			Y
YRPI_MON	NUMBER	1		Y
YRPI_TUE	NUMBER	1		Y
YRPI_WED	NUMBER	1		Y
YRPI_THU	NUMBER	1		Y
YRPI_FRI	NUMBER	1		Y
YRPI_SAT	NUMBER	1		Y
YRPI_SUN	NUMBER	1		Y

## YRPL

CUSTOMER LINK TO YRES

Field Name	Type	Length	Decimals	Not NULL	
YRPL_ID	NUMBER	30		N	Unique Identifier
YRPL_YRES_ID	NUMBER	30		N	Link to YRES
YRPL_XCMS_ID	NUMBER	30		N	Link to XMCS
YRPL_AGE	NUMBER	3		Y	

## YRRC

Regcard numbers stored to guest profiles

Field Name	Type	Length	Decimals	Not NULL
YRRC_ID	NUMBER			N
YRRC_YRES_ID	NUMBER			Y
YRRC_XCMS_ID	NUMBER			Y
YRRC_REGCARDNUMBER	NUMBER			Y

## YRRL

reservation rebate link

Field Name	Type	Length	Decimals	Not NULL	
YRRL_ID	NUMBER	30		N	
YRRL_YRES_ID	NUMBER	30		N	reservation id
YRRL_ZRDF_ID	NUMBER	30		N	rebate id

### YRSC

room status category

Field Name	Type	Length	Decimals	Not NULL	
YRSC_ID	NUMBER	30		N	YRSC_ID identifies YRSC
YRSC_SHORTDESC	VARCHAR2	3		N	YRSC_SHORTDESC is of YRSC
YRSC_LONGDESC	VARCHAR2	30		N	YRSC_LONGDESC is of YRSC
YRSC_DISPLORDER	NUMBER	3		Y	YRSC_DISPLORDER is of YRSC
YRSC_AFFECTAILABILITY	NUMBER	1		Y	Indicates if this room status is deducting from availability or not 1 = deduct room from availability 0 = do not deduct from availability
YRSC_REQUIREBACKTIME	NUMBER	1		Y	If the user selects this for a room, also must enter a time when it comes back to original status or the status the user defines. 1 = True 0 = False
YRSC_WCOL_ID	NUMBER	30		Y	
YRSC_RETURN_YHKS_ID	NUMBER	30		Y	Default return Status

### YRSE

Rate Seasons Date Ranges

Field Name	Type	Length	Decimals	Not NULL	
YRSE_ID	NUMBER	30		N	YRSE_ID identifies YRSE
YRSE_STARTDATE	DATE			N	Start date of season
YRSE_ENDDATE	DATE			N	End date of season
YRSE_YRCH_ID	NUMBER	30		Y	Rate code to which the season is linked. If the rate code is left blank, then the season may be linked to all rate codes.
YRSE_YRSG_ID	NUMBER	30		N	YRSE_YRSG_ID is of YRSE

### YRSG

Rate Season Groups, Low season or High Season For instance, different date ranges can be linked to one rate season group

Field Name	Type	Length	Decimals	Not NULL	
YRSG_ID	NUMBER	30		N	YRSG_ID identifies YRSG
YRSG_LONGDESC	VARCHAR2	30		N	YRSG_LONGDESC is of YRSG

### YRSL

Link Table between Room Type and Sales Room Type

Field Name	Type	Length	Decimals	Not NULL	
YRSL_ID	NUMBER	30		N	
YRSL_YSRC_ID	NUMBER	30		N	
YRSL_YCAT_ID	NUMBER	30		N	

## YRSL

Link Table between Room Type and Sales Room Type

Field Name	Type	Length	Decimals	Not NULL
YRSL_DISPLORDER	NUMBER	3		Y

## YRSM

reservation methods

Field Name	Type	Length	Decimals	Not NULL	
YRSM_ID	NUMBER	30		N	YRSM_ID identifies YRSM
YRSM_SHORTDESC	VARCHAR2	3		N	YRSM_SHORTDESC is of YRSM
YRSM_LONGDESC	VARCHAR2	30		N	YRSM_LONGDESC is of YRSM
YRSM_DISPLORDER	NUMBER	3		Y	YRSM_DISPLORDER is of YRSM

## YRSR

room status reasons

Field Name	Type	Length	Decimals	Not NULL	
YRSR_ID	NUMBER	30		N	YRSR_ID identifies YRSR
YRSR_SHORTDESC	VARCHAR2	3		N	YRSR_SHORTDESC is of YRSR
YRSR_LONGDESC	VARCHAR2	30		N	YRSR_LONGDESC is of YRSR
YRSR_DISPLORDER	NUMBER	3		Y	YRSR_DISPLORDER is of YRSR

## YRSS

Field Name	Type	Length	Decimals	Not NULL
YRSS_ID	NUMBER	30		N
YRSS_SUITE_YRMS_ID	NUMBER	30		N
YRSS_ROOM_YRMS_ID	NUMBER	30		N

## YRST

Room Status Tracking (former known as out of order)

Field Name	Type	Length	Decimals	Not NULL	
YRST_ID	NUMBER	30		N	YRST_ID identifies YRST
YRST_YRMS_ID	NUMBER	30		N	YRST_YRMS_ID is of YRST
YRST_FROMTIME	DATE			N	YRST_FROMTIME is of YRST
YRST_UNTILTIME	DATE			N	YRST_UNTILTIME is of YRST

## YRST

Room Status Tracking (former known as out of order)

Field Name	Type	Length	Decimals	Not NULL	
YRST_YRSC_ID	NUMBER	30		N	YRST_YRSC_ID is of YRST
YRST_RETURN_YHKS_ID	NUMBER	30		N	YRST_RETURN_YHKS_ID is of YRST
YRST_YRSR_ID	NUMBER	30		N	YRST_YRSR_ID is of YRST
YRST_REMARK	VARCHAR2	60		Y	This remark field is defaulting to the valid predefined and selected YRSR_LONGDESC. But this can be overwritten.

## YRVL

Rate Availability Levels

Field Name	Type	Length	Decimals	Not NULL	
YRVL_ID	NUMBER	30		N	
YRVL_SHORTDESC	VARCHAR2	4		Y	
YRVL_LONGDESC	VARCHAR2	60		Y	
YRVL_DISPLORDER	NUMBER	4		Y	
YRVL_INACTIVE	NUMBER	1		Y	
YRVL_BARCODE	VARCHAR2	10		Y	BAR Interface barcode link

## YSAC

Function Space Attribute Categories

Field Name	Type	Length	Decimals	Not NULL	
YSAC_ID	NUMBER	30		N	Unique ID
YSAC_SHORTDESC	VARCHAR2	3		N	Short description
YSAC_LONGDESC	VARCHAR2	30		N	Long description
YSAC_DIPLORDER	NUMBER	3		Y	Display order

## YSAL

Function Space Attribute Link

Field Name	Type	Length	Decimals	Not NULL	
YSAL_ID	NUMBER	30		N	Unique ID
YSAL_YRAS_ID	NUMBER	30		Y	YSAL_YRAS_ID is of YSAL
YSAL_YFSC_ID	NUMBER	30		Y	YSAL_YFSC_ID is of YSAL
YSAL_NUMBER	NUMBER	5		Y	YSAL_NUMBER is of YSAL

### YSAS

function space attribute (elements of categories)

Field Name	Type	Length	Decimals	Not NULL	
YSAS_ID	NUMBER	30		N	YSAS_ID identifies YSAS
YSAS_SHORTDESC	VARCHAR2	3		N	YSAS_SHORTDESC is of YSAS
YSAS_LONGDESC	VARCHAR2	30		N	YSAS_LONGDESC is of YSAS
YSAS_DIPLORDER	NUMBER	3		Y	YSAS_DIPLORDER is of YSAS
YSAS_Y SAC_ID	NUMBER	30		N	YSAS_Y SAC_ID is of YSAS
YSAS_CANENTERNUMBER	NUMBER	1		N	YSAS_CANENTERNUMBER is of YSAS

### YSCH

Status change

Field Name	Type	Length	Decimals	Not NULL	
YSCH_ID	NUMBER	30		N	YSCH_ID identifies YSCH
YSCH_YBOM_ID	NUMBER	30		N	for link to booking master
YSCH_STATUS_TYPE	NUMBER	1		N	1=Conference and 2=Rooms to > differentiate which status it is
YSCH_YEST_FROM_ID	NUMBER	30		N	will track the current status (old)
YSCH_YEST_TO_ID	NUMBER	30		N	will track the next status (new)
YSCH_XCMS_ID	NUMBER	30		N	will track the user that changed status
YSCH_CHANGETIME	DATE			N	YSCH_CHANGETIME is of YSCH

### YSCM

Function Space Communication Values

Field Name	Type	Length	Decimals	Not NULL	
YSCM_ID	NUMBER	30		N	YSCM_ID identifies YSCM
YSCM_Y SCT_ID	NUMBER	30		N	YSCM_Y SCT_ID is of YSCM
YSCM_VALUE	VARCHAR2	60		N	YSCM_VALUE is of YSCM
YSCM_Y FSC_ID	NUMBER	30		N	YSCM_Y FSC_ID is of YSCM

### YSCO

function space combination

Field Name	Type	Length	Decimals	Not NULL	
YSCO_ID	NUMBER	30		N	YSCO_ID identifies YSCO
YSCO_OWNER_Y FSC_ID	NUMBER	30		N	YSCO_OWNER_Y FSC_ID is of YSCO
YSCO_CHILD_Y FSC_ID	NUMBER	30		N	YSCO_CHILD_Y FSC_ID is of YSCO

### YSCP

function space closed periods

Field Name	Type	Length	Decimals	Not NULL	
YSCP_ID	NUMBER	30		N	YSCP_ID identifies YSCP
YSCP_YFSC_ID	NUMBER	30		N	YSCP_YFSC_ID is of YSCP
YSCP_FROM	DATE			N	YSCP_FROM is of YSCP
YSCP_TO	DATE			N	YSCP_TO is of YSCP
YSCP_REASON	VARCHAR2	60		Y	YSCP_REASON is of YSCP
YSCP_ORIGINAL	NUMBER	1		Y	the originally closed

### YSCT

function space communication types

Field Name	Type	Length	Decimals	Not NULL	
YSCT_ID	NUMBER	30		N	YSCT_ID identifies YSCT
YSCT_SHORTDESC	VARCHAR2	3		N	YSCT_SHORTDESC is of YSCT
YSCT_LONGDESC	VARCHAR2	30		N	YSCT_LONGDESC is of YSCT
YSCT_DISPLORDER	NUMBER	3		Y	YSCT_DISPLORDER is of YSCT

### YSEA

Search Criteria for House keeping control

Field Name	Type	Length	Decimals	Not NULL	
YSEA_ID	NUMBER	30		N	YSEA_ID identifies YSEA
YSEA_SHORTDESC	VARCHAR2	3		N	YSEA_SHORTDESC is of YSEA
YSEA_LONGDESC	VARCHAR2	30		N	YSEA_LONGDESC is of YSEA
YSEA_VACANT	NUMBER	30		Y	YSEA_VACANT is of YSEA
YSEA_OCCUPIED	NUMBER	30		Y	YSEA_OCCUPIED is of YSEA
YSEA_INCLUDEOOO	NUMBER	1		Y	1 = True
YSEA_ONLYOOO	NUMBER	1		Y	1 = True
YSEA_VAC_CHECKEDOUT	NUMBER	1		Y	1 = True
YSEA_VAC_EXPARR	NUMBER	1		Y	1 = True
YSEA_OCC_CHECKEDIN	NUMBER	1		Y	1 = True
YSEA_OCC_EXPARR	NUMBER	1		Y	1 = True
YSEA_OCC_DUEOUT	NUMBER	1		Y	1 = True
YSEA_VAC_HISTORY	NUMBER	1		Y	1 = True
YSEA_DISPLORDER	NUMBER	3		Y	

### YSEA

Search Criteria for House keeping control

Field Name	Type	Length	Decimals	Not NULL	
YSEA_ONLYQROOMS	NUMBER	1		Y	1=true

### YSEC

Room Sections Table

Field Name	Type	Length	Decimals	Not NULL	
YSEC_ID	NUMBER	30		N	YSEC_ID identifies YSEC
YSEC_LONGDESC	VARCHAR2	30		N	YSEC_LONGDESC is of YSEC
YSEC_SHORTDESC	VARCHAR2	3		N	YSEC_SHORTDESC is of YSEC
YSEC_DISPLORDER	NUMBER	3		Y	Display Order

### YSES

search criteria link to housekeeping status types

Field Name	Type	Length	Decimals	Not NULL	
YSES_ID	NUMBER	30		N	YSES_ID identifies YSES
YSES_YSEA_ID	NUMBER	30		N	YSES_YSEA_ID is of YSES
YSES_YHKS_ID	NUMBER	30		N	YSES_YHKS_ID is of YSES

### YSET

SEARCH CRITERIA LINK TO ROOM TYPE

Field Name	Type	Length	Decimals	Not NULL	
YSET_ID	NUMBER	30		N	YSET_ID identifies YSET
YSET_YSEA_ID	NUMBER	30		N	YSET_YSEA_ID is of YSET
YSET_YCAT_ID	NUMBER	30		N	YSET_YCAT_ID is of YSET

### YSFL

Link Table between Function Space Type and Sales Function Space Type

Field Name	Type	Length	Decimals	Not NULL	
YSFL_ID	NUMBER	30		N	
YSFL_YSTY_ID	NUMBER	30		N	
YSFL_YSFT_ID	NUMBER	30		N	
YSFL_DISPLORDER	NUMBER	3		Y	

### YSFT

Sales Function Space Types

Field Name	Type	Length	Decimals	Not NULL
YSFT_ID	NUMBER	30		N
YSFT_SHORTDESC	VARCHAR2	5		N
YSFT_LONGDESC	VARCHAR2	30		N
YSFT_DISPLORDER	NUMBER	3		N
YSFT_INACTIVE	NUMBER	1		Y

### YSIA

Sub item attributes

Field Name	Type	Length	Decimals	Not NULL	
YSIA_ID	NUMBER	30		N	YSIA_ID identifies YSIA
YSIA_YSIT_ID	NUMBER	30		N	YSIA_YSIT_ID is of YSIA
YSIA_YCIA_ID	NUMBER	30		N	YSIA_YCIA_ID is of YSIA

### YSIL

Sub item link to reservation (link goes to the link record between reservation and ycit (item) record)

Field Name	Type	Length	Decimals	Not NULL	
YSIL_ID	NUMBER	30		N	YSIL_ID identifies YSIL
YSIL_YEBR_ID	NUMBER	30		N	YSIL_YEBR_ID is of YSIL
YSIL_YSIT_ID	NUMBER	30		N	YSIL_YSIT_ID is of YSIL

### YSIT

Table of YSIT

Field Name	Type	Length	Decimals	Not NULL	
YSIT_ID	NUMBER	30		N	YSIT_ID identifies YSIT
YSIT_SHORTDESC	VARCHAR2	3		N	YSIT_SHORTDESC is of YSIT
YSIT_LONGDESC	VARCHAR2	30		N	YSIT_LONGDESC is of YSIT
YSIT_DISPLORDER	NUMBER	3		Y	YSIT_DISPLORDER is of YSIT
YSIT_YCIT_ID	NUMBER	30		N	YSIT_YCIT_ID is of YSIT

### YSLM

Maximum selling limit per day for Rate/ packages etc.

Field Name	Type	Length	Decimals	Not NULL
------------	------	--------	----------	----------

### YSLM

Maximum selling limit per day for Rate/ packages etc.

Field Name	Type	Length	Decimals	Not NULL	
YSLM_ID	NUMBER	30		N	Id of yslm
YSLM_DATE	DATE			N	Selling limit Date
YSLM_TYPE	NUMBER	1		N	Rates - 0, Packages - 1, Rate Levels - 2 (currently only used for Best Western)
YSLM_RECID	NUMBER	30		N	Linked Table id e.g yrch_id, ypac_id
YSLM_WEBLIMIT	NUMBER	30		Y	Web selling limit
YSLM_GENERALLIMIT	NUMBER	5		Y	General Selling Limit
YSLM_TYPE2	NUMBER	1		Y	
YSLM_RECID2	NUMBER	30		Y	

### YSLR

Field Name	Type	Length	Decimals	Not NULL	
YSLR_ID	NUMBER	30		N	
YSLR_ONE_YRMS_ID	NUMBER	30		N	
YSLR_OTHER_YRMS_ID	NUMBER	30		N	

### YSMC

catering standard menu categories

Field Name	Type	Length	Decimals	Not NULL	
YSMC_ID	NUMBER	30		N	YSMC_ID identifies YSMC
YSMC_LONGDESC	VARCHAR2	30		N	YSMC_LONGDESC is of YSMC
YSMC_DISPLORDER	NUMBER	3		Y	YSMC_DISPLORDER is of YSMC
YSMC_FOODORBEVERAGE	NUMBER	1		Y	Food (1) or Beverage (0)

### YSME

Standard menus

Field Name	Type	Length	Decimals	Not NULL	
YSME_ID	NUMBER	30		N	YSME_ID identifies YSME
YSME_LONGDESC	VARCHAR2	50		N	YSME_LONGDESC is of YSME
YSME_DISPLORDER	NUMBER	3		Y	YSME_DISPLORDER is of YSME
YSME_YSMC_ID	NUMBER	30		N	YSME_YSMC_ID is of YSME
YSME_MINIMUMAMOUNT	NUMBER	4		Y	YSME_MINIMUMAMOUNT is of YSME

### YSME

Standard menus

Field Name	Type	Length	Decimals	Not NULL	
YSME_MAXIMUMAMOUNT	NUMBER	4		Y	YSME_MAXIMUMAMOUNT is of YSME
YSME_SERVEDPERPERSON	NUMBER	1		Y	YSME_SERVEDPERPERSON is of YSME
YSME_ARTICLENUMBER	VARCHAR2	10		Y	YSME_ARTICLENUMBER is of YSME
YSME_CHARGEDONCONSUMPTION	NUMBER	1		Y	YSME_CHARGEDONCONSUMPTION is of YSME
YSME_ZDCO_ID	NUMBER	30		Y	Standard Menu - Department code link
YSME_POSTTYPE	NUMBER	1		Y	YSME_POSTTYPE is of YSME
YSME_DESCRIPTION	LONG			Y	YSME_DESCRIPTION is of YSME
YSME_INACTIVE	NUMBER	1		Y	0 = active   1 = inactive
YSME_COSTPRICE	NUMBER	30	4	Y	Cost price
YSME_YCWI_ID	NUMBER	30		Y	Extends Standard menue with a config for web

### YSMR

Standard Menu Rates

Field Name	Type	Length	Decimals	Not NULL	
YSMR_ID	NUMBER	30		N	YSMR_ID identifies YSMR
YSMR_YSME_ID	NUMBER	30		N	YSMR_YSME_ID is of YSMR
YSMR_PRICE	NUMBER	30	4	Y	YSMR_PRICE is of YSMR
YSMR_VALIDFROM	DATE			Y	YSMR_VALIDFROM is of YSMR
YSMR_VALIDTO	DATE			Y	YSMR_VALIDTO is of YSMR
YSMR_DEFAULT	NUMBER	1		Y	Default Rate
YSMR_YOUT_ID	NUMBER	30		Y	Link to Outlet
YSMR_COSTPRICE	NUMBER	30	4	Y	Cost price
YSMR_YCWI_ID	NUMBER	30		Y	Extends Standard menue rates with a config for web

### YSRC

Sales Room Categories

Field Name	Type	Length	Decimals	Not NULL	
YSRC_ID	NUMBER	30		N	
YSRC_SHORTDESC	VARCHAR2	5		N	
YSRC_LONGDESC	VARCHAR2	30		N	
YSRC_DISPLORDER	NUMBER	3		N	
YSRC_INACTIVE	NUMBER	1		Y	

## YSRC

Sales Room Categories

Field Name	Type	Length	Decimals	Not NULL
YSRC_SHORTWEBINFO	VARCHAR2	1000		Y
YSRC_LONGWEBINFO	VARCHAR2	2000		Y
YSRC_MD_LONGWEBINFO	VARCHAR2	2000		Y
YSRC_MD_SHORTWEBINFO	VARCHAR2	1000		Y
YSRC_EXTENDEDWEBINFO	VARCHAR2	2000		Y
YSRC_MD_EXTENDEDWEBINFO	VARCHAR2	2000		Y

## YSRL

Room Section and Room Linking Table

Field Name	Type	Length	Decimals	Not NULL	
YSRL_ID	NUMBER	30		N	YSRL_ID identifies YSRL
YSRL_YSEC_ID	NUMBER	30		N	YSRL_YSEC_ID is of YSRL
YSRL_YRMS_ID	NUMBER	30		N	YSRL_YRMS_ID is of YSRL
YSRL_SECTIONVALUE	NUMBER	3		N	The real section value, i.e. Day section, value 1 indicates the room belongs to day section 1.

## YSSC

function space seating configuration categories

Field Name	Type	Length	Decimals	Not NULL	
YSSC_ID	NUMBER	30		N	YSSC_ID identifies YSSC
YSSC_SHORTDESC	VARCHAR2	3		N	YSSC_SHORTDESC is of YSSC
YSSC_LONGDESC	VARCHAR2	30		N	YSSC_LONGDESC is of YSSC
YSSC_DISPLORDER	NUMBER	3		Y	YSSC_DISPLORDER is of YSSC
YSSC_WEBENABLED	NUMBER	1		Y	0=No 1=Yes
YSSC_RPDW_ID	NUMBER	30		Y	Link to Roomplanner drawing
YSSC_INACTIVE	NUMBER	1		Y	1 = inactive

## YSSL

function space seating configuration link

Field Name	Type	Length	Decimals	Not NULL	
YSSL_ID	NUMBER	30		N	YSSL_ID identifies YSSL
YSSL_YFSC_ID	NUMBER	30		Y	YSSL_YFSC_ID is of YSSL
YSSL_YSSC_ID	NUMBER	30		N	YSSL_YSSC_ID is of YSSL

### YSSL

function space seating configuration link

Field Name	Type	Length	Decimals	Not NULL	
YSSL_MINCAPACITY	NUMBER	4		Y	YSSL_MINCAPACITY is of YSSL
YSSL_MAXCAPACITY	NUMBER	4		Y	YSSL_MAXCAPACITY is of YSSL
YSSL_SETUPTIME	NUMBER	3		Y	time needed to set up the room in minutes
YSSL_SETDOWNTIME	NUMBER	3		Y	time needed to set down the room in minutes
YSSL_SHAREDOK	NUMBER	1		Y	can be applied in shared mode
YSSL_DEFAULT	NUMBER	1		Y	Default seating arrangement for reserving multiple function spaces (0=no, 1=yes)
YSSL_INACTIVE	NUMBER	1		Y	1 = Inactive
YSSL_RPDW_ID	NUMBER	30		Y	Link to Roomplanner drawing
YSSL_FREETEXT	VARCHAR2	1000		Y	Free text
YSSL_PICTURE	LONG RAW			Y	Picture
YSSL_YCWI_ID	NUMBER	30		Y	Extends function space seating with a config for web

### YSSS

search criteria link to room status categories

Field Name	Type	Length	Decimals	Not NULL	
YSSS_ID	NUMBER	30		N	YSSS_ID identifies YSSS
YSSS_YSEA_ID	NUMBER	30		N	YSSS_YSEA_ID is of YSSS
YSSS_YRSC_ID	NUMBER	30		N	YSSS_YRSC_ID is of YSSS

### YSTY

function space types

Field Name	Type	Length	Decimals	Not NULL	
YSTY_ID	NUMBER	30		N	YSTY_ID identifies YSTY
YSTY_SHORTDESC	VARCHAR2	3		N	YSTY_SHORTDESC is of YSTY
YSTY_LONGDESC	VARCHAR2	30		N	YSTY_LONGDESC is of YSTY
YSTY_DISPLORDER	NUMBER	3		Y	YSTY_DISPLORDER is of YSTY

### YTAA

turnaway attributes

Field Name	Type	Length	Decimals	Not NULL	
YTAA_ID	NUMBER	30		N	
YTAA_YTAW_ID	NUMBER	30		N	

### YTAA

turnaway apptributes

Field Name	Type	Length	Decimals	Not NULL
YTAA_XPDA_ID	NUMBER	30		N
YTAA_XPAC_ID	NUMBER	30		Y

### YTAC

Turn Away details

Field Name	Type	Length	Decimals	Not NULL	
YTAC_ID	NUMBER	30		N	ID
YTAC_SHORTDESC	VARCHAR2	3		N	SHORT DESC
YTAC_LONGDESC	VARCHAR2	60		N	LONG DESC
YTAC_DISPORDER	NUMBER	3		Y	DISPORDER
YTAC_INACTIVE	NUMBER	1		Y	1 = inactive

### YTAW

Turn Away details

Field Name	Type	Length	Decimals	Not NULL	
YTAW_ID	NUMBER	30		N	ID
YTAW_YRES_ID	NUMBER	30		Y	res id
YTAW_YTAC_ID	NUMBER	30		N	turn away id
YTAW_DATE	DATE			Y	date
YTAW_RESDATE	DATE			N	res date
YTAW_NOOFROOMS	NUMBER	3		N	rooms
YTAW_XCMA_ID	NUMBER	30		N	market id
YTAW_XCMS_ID	NUMBER	30		Y	profile id
YTAW_NOOFNIGHTS	NUMBER	3		Y	nights
YTAW_NOOFADULTS	NUMBER	3		N	adults
YTAW_LINK_ID	NUMBER	30		N	link for turnaways for more than 1 night

### YTRA

Transponder link to reservations

Field Name	Type	Length	Decimals	Not NULL	
YTRA_ID	NUMBER	30		N	Unique ID
YTRA_YRES_ID	NUMBER	30		N	Link to reservation

## YTRA

Transponder link to reservations

Field Name	Type	Length	Decimals	Not NULL	
YTRA_ZTRA_ID	NUMBER	30		N	Link to transponder
YTRA_ZFAC_ID	NUMBER	30		N	Link to financial account
YTRA_TIMESTAMP	DATE			N	Time of linkage

## YTRD

Trend Analysis

Field Name	Type	Length	Decimals	Not NULL	
YTRD_ID	NUMBER	30		N	Unique Identifier
YTRD_YCAT_ID	NUMBER	30		N	Number of Definite booked Rooms for CalcForDate
YTRD_CALCDATE	DATE			N	Date of Calculation
YTRD_CALCFORDATE	DATE			N	Date for Calculation
YTRD_NOOFROOMS	NUMBER	3		N	Number of Rooms in Hotel for this Roomtype
YTRD_DEFROOMS	NUMBER	3		N	CALCULATED DEFINITE OCCUPANCY FOR GIVEN DATE AND ROOMTYPE
YTRD_TENTROOMS	NUMBER	3		Y	CALCULATED TENTATIVE OCCUPANCY FOR GIVEN DATE AND ROOMTYPE
YTRD_DEFADULTNO	NUMBER	10		Y	
YTRD_TENTADULTNO	NUMBER	10		Y	
YTRD_DEFCHILDNO	NUMBER	10		Y	
YTRD_TENTCHILDNO	NUMBER	10		Y	
YTRD_DEFCHILDNODOMESTIC	NUMBER	10		Y	
YTRD_TENTCHILDNODOMESTIC	NUMBER	10		Y	

## YTRX

Trend analysis Market Code per Roomtype per reservationtype Forecast

Field Name	Type	Length	Decimals	Not NULL	
YTRX_ID	NUMBER	30		N	
YTRX_CALCDATE	DATE			Y	
YTRX_CALCFORDATE	DATE			Y	
YTRX_RESTYPE	NUMBER	1		Y	1=Individual reservation, 2= Group, 3=Block
YTRX_YCAT_ID	NUMBER	30		Y	
YTRX_XCMA_ID	NUMBER	30		Y	
YTRX_GROSS_TOTAL	NUMBER	30	4	Y	
YTRX_NET_TOTAL	NUMBER	30	4	Y	

### YTRX

Trend analysis Market Code per Roomtype per reservationtype Forecast

Field Name	Type	Length	Decimals	Not NULL
YTRX_GROSS_ROOM	NUMBER	30	4	Y
YTRX_NET_ROOM	NUMBER	30	4	Y
YTRX_NOOFROOMS	NUMBER	3		Y
YTRX_DEFROOMS	NUMBER	3		Y
YTRX_ADULTNO	NUMBER	10		Y
YTRX_DEFADULTNO	NUMBER	10		Y
YTRX_CHILDNO	NUMBER	10		Y
YTRX_DEFCHILDNO	NUMBER	10		Y
YTRX_CHILDNODOMESTIC	NUMBER	10		Y
YTRX_DEFCHILDNODOMESTIC	NUMBER	10		Y

### YUVC

user defined Forecast value categories (data added to ydet mainly for forecast purposes), user can define what they want to add as values to the reservation and can then calculate forecast and statistics for that configured elements

Field Name	Type	Length	Decimals	Not NULL	
YUVC_ID	NUMBER	30		N	YUVC_ID identifies YUVC
YUVC_SHORTDESC	VARCHAR2	3		N	YUVC_SHORTDESC is of YUVC
YUVC_LONGDESC	VARCHAR2	30		N	YUVC_LONGDESC is of YUVC
YUVC_DISPLORDER	NUMBER	3		Y	YUVC_DISPLORDER is of YUVC

### YUVS

user defined values (values added to ydet mainly for forecasting)

Field Name	Type	Length	Decimals	Not NULL	
YUVS_ID	NUMBER	30		N	YUVS_ID identifies YUVS
YUVS_YDET_ID	NUMBER	30		N	YUVS_YDET_ID is of YUVS
YUVS_YUVC_ID	NUMBER	30		N	YUVS_YUVC_ID is of YUVS
YUVS_VALUE	NUMBER	30	4	N	YUVS_VALUE is of YUVS

### YVNA

virtual number assignments

Field Name	Type	Length	Decimals	Not NULL	
YVNA_ID	NUMBER	30		N	YVNA_ID identifies YVNA
YVNA_YVNS_ID	NUMBER	30		N	YVNA_YVNS_ID is of YVNA

### YVNA

virtual number assignments

Field Name	Type	Length	Decimals	Not NULL	
YVNA_YDET_ID	NUMBER	30		N	YVNA_YDET_ID is of YVNA

### YVNG

permanent linking of virtual numbers to guests

Field Name	Type	Length	Decimals	Not NULL	
YVNG_ID	NUMBER	30		N	YVNG_ID identifies YVNG
YVNG_YVNS_ID	NUMBER	30		N	YVNG_YVNS_ID is of YVNG
YVNG_XCMS_ID	NUMBER	30		N	YVNG_XCMS_ID is of YVNG

### YVNP

virtual number pools

Field Name	Type	Length	Decimals	Not NULL	
YVNP_ID	NUMBER	30		N	YVNP_ID identifies YVNP
YVNP_NUMBER	NUMBER	2		N	pool number. needed for interface i guess
YVNP_LONGDESC	VARCHAR2	30		N	text representation
YVNP_TYPE	NUMBER	1		N	we have to ask interface guys
YVNP_ACTIVE	NUMBER	1		N	YVNP_ACTIVE is of YVNP
YVNP_ASSIGN	NUMBER	1		N	0=computer 1=user will assign it
YVNP_REQUIRED	NUMBER	1		N	must be assigned when guest check is or not

### YVNS

virtual numbers available in the system.

Field Name	Type	Length	Decimals	Not NULL	
YVNS_ID	NUMBER	30		N	YVNS_ID identifies YVNS
YVNS_YVNP_ID	NUMBER	30		N	YVNS_YVNP_ID is of YVNS
YVNS_NUMBER	NUMBER	10		N	YVNS_NUMBER is of YVNS

### YWLP

Waitlist Priorities

Field Name	Type	Length	Decimals	Not NULL	
YWLP_ID	NUMBER	30		N	YWLP_ID identifies YWLP
YWLP_SHORTDESC	VARCHAR2	3		N	YWLP_SHORTDESC partly identifies YWLP

### YWLP

Waitlist Priorities

Field Name	Type	Length	Decimals	Not NULL	
YWLP_LONGDESC	VARCHAR2	30		N	Description of Priority Level
YWLP_PRIORITY	NUMBER	3		N	Internal validated field. User can move up and down the priorities on the configuration level.

### YWLR

Wait List Reasons

Field Name	Type	Length	Decimals	Not NULL	
YWLR_ID	NUMBER	30		N	YWLR_ID identifies YWLR
YWLR_SHORTDESC	VARCHAR2	3		N	YWLR_SHORTDESC is of YWLR
YWLR_LONGDESC	VARCHAR2	30		N	Description of the Waitlist Reason, such as "Fully Booked" or "Room Type not available"
YWLR_DISPLORDER	NUMBER	3		Y	YWLR_DISPLORDER is of YWLR

### YWLT

Waitlist

Field Name	Type	Length	Decimals	Not NULL	
YWLT_ID	NUMBER	30		N	YWLT_ID identifies YWLT
YWLT_YRES_ID	NUMBER	30		N	YWLT_YRES_ID is of YWLT
YWLT_YWLR_ID	NUMBER	30		N	Waitlist reason link
YWLT_YWLP_ID	NUMBER	30		N	Waitlist Priority Link
YWLT_TEXT	LONG			Y	Free editable text.
YWLT_DISPLORDER	NUMBER	30		Y	This displayorder is the 2nd level sorting. First level sorting of waitlist records is on the priority link.
YWLT_WAITLISTEDDATE	DATE			N	Date when reservation was moved to waitlist.
YWLT_ACCEPTEDDATE	DATE			Y	Date when waitlist reservation was accepted.
YWLT_ORGRESSTATUS	NUMBER	1		N	Original reservation status from YRES_RESSTATUS at the moment when this reservation was waitlisted.
YWLT_XCOM_ID	NUMBER	30		Y	Preferred Communication method to inform guest when the reservation can be accepted. We allow to select from existing XCOM records and to create a new one.

### YWRA

Web restriction Event type - Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YWRA_ID	NUMBER	30		N	
YWRA_YFSC_ID	NUMBER	30		N	Function Space restricted
YWRA_YETY_ID	NUMBER	30		N	Event type ID

### YWRB

Web restriction Seattings - Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YWRB_ID	NUMBER	30		N	
YWRB_YFSC_ID	NUMBER	30		N	Function Space restricted
YWRB_YSSC_ID	NUMBER	30		N	Seattng ID

### YWRC

Web restriction Hotel Segment - Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YWRC_ID	NUMBER	30		N	
YWRC_YFSC_ID	NUMBER	30		N	Function Space restricted
YWRC_YCAD_ID	NUMBER	30		N	Hotel Segment ID

### YWRD

Web restriction Packages - Function Spaces

Field Name	Type	Length	Decimals	Not NULL	
YWRD_ID	NUMBER	30		N	
YWRD_YFSC_ID	NUMBER	30		N	Function Space restricted
YWRD_YPKG_ID	NUMBER	30		N	Package ID

### YXCH

Exchange rate management for packages and fixed charges (under construction)

Field Name	Type	Length	Decimals	Not NULL	
YXCH_ID	NUMBER	30		N	Unique ID
YXCH_YRES_ID	NUMBER	30		N	Link to reservation table
YXCH_ZCUR_ID	NUMBER	30		N	Link to currency
YXCH_PACKAGEORFC	NUMBER	1		N	0 = Package 1 = Fixed Charge
YXCH_EXCHANGERATE	NUMBER	30	18	N	Stores current exchange rate
YXCH_REVERSE	NUMBER	1		N	0 = exchange rate 1 = backrate
YXCH_LASTUPDATE	DATE			N	Date of last exchange rate update

### YXLS

Roominglist Excel Import, Excel Configuration Table

Field Name	Type	Length	Decimals	Not NULL	
YXLS_ID	NUMBER	30		N	
YXLS_LONGDESC	VARCHAR2	60		Y	
YXLS_COLUMNS	VARCHAR2	800		Y	
YXLS_INACTIVE	NUMBER	1		Y	
YXLS_DISPLORDER	NUMBER	3		Y	
YXLS_FIRSTDATAROW	NUMBER	10		Y	Data starts on this Row
YXLS_FIRSTDATA COL	NUMBER	10		Y	Data starts on this column

### ZAAL

account attribute link

Field Name	Type	Length	Decimals	Not NULL	
ZAAL_ID	NUMBER	30		N	ZAAL_ID identifies ZAAL
ZAAL_ZFAC_ID	NUMBER	30		N	ZAAL_ZFAC_ID is of ZAAL
ZAAL_YRAS_ID	NUMBER	30		N	ZAAL_YRAS_ID is of ZAAL
ZAAL_YRAC_ID	NUMBER	30		N	ZAAL_YRAC_ID is of ZAAL

### ZACT

Cashier Activities

Field Name	Type	Length	Decimals	Not NULL	
ZACT_ID	NUMBER	30		N	ZACT_ID identifies ZACT
ZACT_TIME	DATE			N	Timestamp
ZACT_ACTIVITY_TYPE	NUMBER	2		N	0 = Open Cashier 1 = Close Cashier 2 = Money transfer from or to Cashier
ZACT_ZCAS_ID	NUMBER	30		N	Cashier Number Link to ZCAS
ZACT_XCMS_ID	NUMBER	30		N	User Id of the Cashier
ZACT_MAX_ZPOS_ID	NUMBER	30		Y	here we store the max value from zpos when opening the cashier, doing this we can exactly determine records from zpos since opening.

### ZADR

Copy of the data on the moment of printing folio (Polish legal requirements)

Field Name	Type	Length	Decimals	Not NULL	
ZADR_ID	NUMBER	30		N	
ZADR_ZINV_ID	NUMBER	30		N	
ZADR_XADR_ID	NUMBER	30		N	

### ZADR

Copy of the data on the moment of printing folio (Polish legal requirements)

Field Name	Type	Length	Decimals	Not NULL
ZADR_XATY_ID	NUMBER	30		Y
ZADR_XCOU_ID	NUMBER	30		Y
ZADR_XSTA_ID	NUMBER	30		Y
ZADR_ZIP	VARCHAR2	15		Y
ZADR_STREET1	VARCHAR2	60		Y
ZADR_STREET2	VARCHAR2	60		Y
ZADR_STREET3	VARCHAR2	60		Y
ZADR_CITY	VARCHAR2	60		Y
ZADR_VAT_NUMBER	VARCHAR2	30		Y
ZADR_NAME1	VARCHAR2	35		Y
ZADR_NAME2	VARCHAR2	35		Y
ZADR_NAME3	VARCHAR2	35		Y

### ZALD

department codes of allowances

Field Name	Type	Length	Decimals	Not NULL	
ZALD_ID	NUMBER	30		N	ZALD_ID identifies ZALD
ZALD_ZALL_ID	NUMBER	30		N	ZALD_ZALL_ID is of ZALD
ZALD_ZDCO_ID	NUMBER	30		N	ZALD_ZDCO_ID is of ZALD

### ZALK

Invoice link table for Egyptian A/R Invoice printing

Field Name	Type	Length	Decimals	Not NULL
ZALK_ID	NUMBER	30		N
ZALK_AHDR_ID	NUMBER	30		N
ZALK_ZINV_ID	NUMBER	30		N

### ZALL

Package Allowances

Field Name	Type	Length	Decimals	Not NULL	
ZALL_ID	NUMBER	30		N	ZALL_ID identifies ZALL
ZALL_FROMTIME	DATE			Y	Start time of allowance, when YPAC_FULLDAY=0

## ZALL

### Package Allowances

Field Name	Type	Length	Decimals	Not NULL	
ZALL_TOTIME	DATE			Y	End time of allowance, when YPAC_FULLDAY=0
ZALL_FROMDATE	DATE			Y	Start date of allowance, if YPAC_FULLDAY=1
ZALL_TODATE	DATE			Y	End date of allowance, when YPAC_FULLDAY=1
ZALL_YRES_ID	NUMBER	30		Y	Reservation ID
ZALL_ZFAC_ID	NUMBER	30		Y	Fin. acc. ID
ZALL_YPAC_ID	NUMBER	30		Y	link to package element
ZALL_VALUE	NUMBER	30	4	N	calculated from ypap_value where ypac_allowed = 1
ZALL_LIMIT	NUMBER	30	4	N	calculated from ypap_allowance_value where ypac_allowed = 1
ZALL_TYPE	NUMBER	1		N	0 = normal 1 = Floating 2 = Next Day
ZALL_OVERAGE_ZDCO_ID	NUMBER	30		Y	ZALL_OVERAGE_ZDCO_ID is of ZALL
ZALL_PROFIT_ZDCO_ID	NUMBER	30		Y	ZALL_PROFIT_ZDCO_ID is of ZALL
ZALL_LOSS_ZDCO_ID	NUMBER	30		Y	ZALL_LOSS_ZDCO_ID is of ZALL
ZALL_AUTOINCREMENT	NUMBER	1		Y	if autoincrement is 1 the allowance is incremented automatically if the charges against this package exceed the allowance (for all inclusive hotels where nothing at all is ever charged to the guest)
ZALL_INTERNALSPLIT_ZPOS_ID	NUMBER	30		Y	ZALL_INTERNALSPLIT_ZPOS_ID is of ZALL
ZALL_MANUAL	NUMBER	1		Y	For Allowances created manually
ZALL_CLOSED	NUMBER	1		Y	1 = closed
ZALL_XCMS_ID	NUMBER	30		N	xcms id of a guest linked by multiprofile or main guest id if not available
ZALL_XCAC_ID	NUMBER	30		Y	zall_xcac_id and zall_xcacindex actually link to yrga but yrga can be deleted and recreated for the same combination and i want to avoid frequent allowance modifications so i better link by these fields
ZALL_XCACINDEX	NUMBER	3		Y	zall_xcac_id and zall_xcacindex actually link to yrga but yrga can be deleted and recreated for the same combination and i want to avoid frequent allowance modifications so i better link by these fields
ZALL_DESC	VARCHAR2	30		N	Some description to be able to show something meaningful on screen for messages ie when allowance gets deleted
ZALL_CANCEL_ZPOS_ID	NUMBER	30		Y	if this linked zpos is cancelled, zall should be closed too. this is the posting that was created at the same time with the zall. this is different than zall_zpos_id for sameday allowances
ZALL_PROFORMA	NUMBER	1		Y	1 indicates that the zall record was created during a proforma invoice generation as temporary allowance

## ZARG

### Article Groups

Field Name	Type	Length	Decimals	Not NULL	
ZARG_ID	NUMBER	30		N	
ZARG_SHORTDESC	VARCHAR2	5		N	

### ZARG

Article Groups

Field Name	Type	Length	Decimals	Not NULL
ZARG_LONGDESC	VARCHAR2	30		N
ZARG_DISPLORDER	NUMBER	3		Y
ZARG_WCOL_ID	NUMBER	30		Y

### ZARR

arrangements for postings

Field Name	Type	Length	Decimals	Not NULL	
ZARR_ID	NUMBER	30		N	ZARR_ID identifies ZARR
ZARR_SHORTDESC	VARCHAR2	3		N	ZARR_SHORTDESC is of ZARR
ZARR_LONGDESC	VARCHAR2	30		N	ZARR_LONGDESC is of ZARR
ZARR_DISPLORDER	NUMBER	3		Y	ZARR_DISPLORDER is of ZARR
ZARR_INACTIVE	NUMBER	1		Y	ZARR_INACTIVE is of ZARR
ZARR_CENTRAL	NUMBER	1		N	

### ZART

articles

Field Name	Type	Length	Decimals	Not NULL	
ZART_ID	NUMBER	30		N	ZART_ID identifies ZART
ZART_NUMERICDESC	NUMBER	5		N	Numeric Description for this Article, used as well for interface relations into PMS articles.
ZART_LONGDESC	VARCHAR2	30		N	ZART_LONGDESC is of ZART
ZART_DISPLORDER	NUMBER	3		Y	ZART_DISPLORDER is of ZART
ZART_ZDCO_ID	NUMBER	30		N	ZART_ZDCO_ID is of ZART
ZART_PRICE	NUMBER	30	4	Y	ZART_PRICE is of ZART
ZART_ZARG_ID	NUMBER	30		Y	
ZART_SHORTDESC	VARCHAR2	8		Y	
ZART_MANUALPRICE	NUMBER	1		Y	allow the user to enter a price manually

### ZBAL

Daily Balance

Field Name	Type	Length	Decimals	Not NULL	
ZBAL_ID	NUMBER	30		N	ZBAL_ID identifies ZBAL
ZBAL_DATE	DATE			N	ZBAL_DATE is of ZBAL

### ZBAL

Daily Balance

Field Name	Type	Length	Decimals	Not NULL	
ZBAL_GUESTLEDGER	NUMBER	30	4	N	ZBAL_GUESTLEDGER is of ZBAL
ZBAL_PREBILLLEDGER	NUMBER	30	4	N	ZBAL_PREBILLLEDGER is of ZBAL
ZBAL_CITYLEDGER	NUMBER	30	4	N	ZBAL_CITYLEDGER is of ZBAL
ZBAL_ALLOWANCELEDGER	NUMBER	30	4	Y	Obsolete column, not used anymore
ZBAL_INIT	NUMBER	1		Y	if init is 1 next night audit will initialize zbal, result of
ZBAL_CALCTYPE	NUMBER	1		Y	calctype 2 will be written to calctype as well 1 = based on yesterdays calculation, yesterdays balance + postings of today - payments of today + ledgermovements; 2 = calculation of all current records valid for this ledger; 1 and 2 must be the same if everything is fine
ZBAL_ADVPOSLEDGER	NUMBER	30	4	Y	Advance posting ledger

### ZBAT

Credit card Batch Settlements, to store the CC\_BATCH execution times

Field Name	Type	Length	Decimals	Not NULL	
ZBAT_ID	NUMBER	30		N	unique id
ZBAT_BATCH_NUM	VARCHAR2	16		N	unique batch id
ZBAT_BATCH_START	DATE			N	batch start timestamp
ZBAT_BATCH_END	DATE			Y	batch end timestamp
ZBAT_BATCH_ENTERED	DATE			Y	batch entered timestamp
ZBAT_XCED_ID	NUMBER	30		Y	user xcms id

### ZBCF

bonus point membership type config

Field Name	Type	Length	Decimals	Not NULL	
ZBCF_ID	NUMBER	30		N	
ZBCF_XMTY_ID	NUMBER	30		N	
ZBCF_STAYPERADULT	NUMBER	1		N	
ZBCF_FIRSTSTAYPERADULT	NUMBER	1		N	
ZBCF_NIGHTPERADULT	NUMBER	1		N	
ZBCF_RATECODESTAYPERADULT	NUMBER	1		N	
ZBCF_RATECODEFIRSTSTAYPERADULT	NUMBER	1		N	
ZBCF_RATECODENIGHTPERADULT	NUMBER	1		N	
ZBCF_ROOMTYPESTAYPERADULT	NUMBER	1		N	
ZBCF_ROOMTYPEFIRSTSTAYPERADULT	NUMBER	1		N	

### ZBCF

bonus point membership type config

Field Name	Type	Length	Decimals	Not NULL	
ZBCF_ROOMTYPENIGHTPERADULT	NUMBER	1		N	
ZBCF_CARDROLE	NUMBER	1		N	0=rules for guest card linked to reservation 1=rules for bookers card

### ZBDP

Bank Debit Payment Details

Field Name	Type	Length	Decimals	Not NULL	
ZBDP_ID	NUMBER	30		N	
ZBDP_ACCOUNTNUMBER	VARCHAR2	50		N	Account number
ZBDP_HOLDERNAME	VARCHAR2	50		N	Account Holder Name
ZBDP_BANKCODE	VARCHAR2	20		N	Bank Identification number
ZBDP_CARDNUMBER	VARCHAR2	30		Y	Account Debit Card Number
ZBDP_CARDEXPIRY	VARCHAR2	4		Y	Debit Card Expiry Date
ZBDP_SWIFTCODE	VARCHAR2	30		Y	Bank Swift Code
ZBDP_ZPOS_ID	NUMBER	30		Y	linked ZPOS id

### ZBIC

billing instruction codes

Field Name	Type	Length	Decimals	Not NULL	
ZBIC_ID	NUMBER	30		N	Unique internal ID
ZBIC_SHORTDESC	VARCHAR2	3		N	Short description of billing instruction
ZBIC_LONGDESC	VARCHAR2	30		N	Long description of billing instruction
ZBIC_LANGID	NUMBER	30		Y	obsolete
ZBIC_DISPLORDER	NUMBER	3		Y	Display order of billing instructions
ZBIC_ALL	NUMBER	1		Y	1 = if all department codes are included in this billing instruction code
ZBIC_INACTIVE	NUMBER	1		Y	1 = inactive

### ZBIL

billing instruction link (link between billing instruction codes and revenue department codes/billing instruction codes ) this enables to create a hierarchy of billing instruction codes

Field Name	Type	Length	Decimals	Not NULL	
ZBIL_ID	NUMBER	30		N	Unique internal ID
ZBIL_ZBIC_ID	NUMBER	30		N	Link to billing instruction code
ZBIL_SUB_ZDCO_ID	NUMBER	30		Y	Link to revenue department code or billing instruction code. Depends on field ZBIL_DEPORBILL

### ZBIL

billing instruction link (link between billing instruction codes and revenue department codes/billing instruction codes ) this enables to create a hierarchy of billing instruction codes

Field Name	Type	Length	Decimals	Not NULL	
ZBIL_SUB_ZBIC_ID	NUMBER	30		Y	Link is to department(1) or to billing instruction(0)

### ZBLI

Balance link. One of the FROM and one of the TO fields must be filled

Field Name	Type	Length	Decimals	Not NULL	
ZBLI_ID	NUMBER	30		N	
ZBLI_FROM_YRES_ID	NUMBER	30		Y	ID of the source reservation from where the balance is linked
ZBLI_FROM_ZFAC_ID	NUMBER	30		Y	
ZBLI_TO_YRES_ID	NUMBER	30		Y	ID of the target reservation where the balance is linked
ZBLI_TO_ZFAC_ID	NUMBER	30		Y	

### ZBOF

Back Office Interface user definable fields

Field Name	Type	Length	Decimals	Not NULL	
ZBOF_ID	NUMBER	30		N	Unique ID
ZBOF_ZDCO_ID	NUMBER	30		N	Link to department code
ZBOF_FIELDNAME	VARCHAR2	30		N	Description of the field
ZBOF_FIELDTYPE	NUMBER	2		N	0=number, 1=float, 2=string
ZBOF_NUMVALUE	NUMBER	30		Y	Numeric value
ZBOF_FLOATVALUE	NUMBER	30	4	Y	Floating point value
ZBOF_STRINGVALUE	VARCHAR2	255		Y	String value

### ZBPC

bonus point configuration

Field Name	Type	Length	Decimals	Not NULL	
ZBPC_ID	NUMBER	30		N	
ZBPC_XMTY_ID	NUMBER	30		N	
ZBPC_XMTL_ID	NUMBER	30		Y	
ZBPC_ZDCO_ID	NUMBER	30		Y	filled only if zbpc_type=5 (payment department code)
ZBPC_CARDROLE	NUMBER	1		N	0=rules for guest card linked to reservation 1=rules for bookers card
ZBPC_TYPE	NUMBER	1		N	0=% of total revenue 1=% of revenue per department code 2=per stay 3=for first stay 4=per night 5=redemption (payment rules with points)
ZBPC_VALUE	NUMBER	30	4	N	

### ZBPD

bonus point earning configuration for department codes

Field Name	Type	Length	Decimals	Not NULL	
ZBPD_ID	NUMBER	30		N	
ZBPD_XMTY_ID	NUMBER	30		N	
ZBPD_XMTL_ID	NUMBER	30		Y	
ZBPD_CARDROLE	NUMBER	1		N	0=rules for guest card linked to reservation 1=rules for bookers card
ZBPD_ZDCO_ID	NUMBER	30		Y	
ZBPD_VALUE	NUMBER	20		Y	
ZBPD_FLATVALUE	NUMBER	20		Y	

### ZBPP

bonus point product catalog

Field Name	Type	Length	Decimals	Not NULL	
ZBPP_ID	NUMBER	30		N	
ZBPP_SHORTDESC	VARCHAR2	5		N	
ZBPP_LONGDESC	VARCHAR2	60		N	
ZBPP_PRICE	NUMBER	30		N	price in points
ZBPP_ONSTOCK	NUMBER	30		Y	number of products available
ZBPP_INACTIVE	NUMBER	30		Y	
ZBPP_CHECKAVL	NUMBER	1		N	1=check availability 0=dont
ZBPP_TYPE	NUMBER	1		N	0=earning 1=redemption

### ZBPR

bonus point redemption

Field Name	Type	Length	Decimals	Not NULL	
ZBPR_ID	NUMBER	30		N	
ZBPR_XMNR_ID	NUMBER	30		N	
ZBPR_VALUE	NUMBER	30		N	
ZBPR_TIMESTAMP	DATE			N	
ZBPR_MANUAL	NUMBER	1		N	
ZBPR_XCED_ID	NUMBER	30		N	
ZBPR_ZPOS_ID	NUMBER	30		Y	payment posting
ZBPR_ZBPP_ID	NUMBER	30		Y	product id
ZBPR_QUANTITY	NUMBER	3		Y	product quantity

## ZBPR

bonus point redemption

Field Name	Type	Length	Decimals	Not NULL	
ZBPR_WPHS_ID	NUMBER	30		Y	
ZBPR_COMMENT	VARCHAR2	200		Y	
ZBPR_TRANSFERTO_XMNR_ID	NUMBER	30		Y	transferred to

## ZBPS

bonus points (earned)

Field Name	Type	Length	Decimals	Not NULL	
ZBPS_ID	NUMBER	30		N	
ZBPS_XMNR_ID	NUMBER	30		N	
ZBPS_VALUE	NUMBER	30		N	
ZBPS_TIMESTAMP	DATE			N	
ZBPS_MANUAL	NUMBER	1		N	
ZBPS_YRES_ID	NUMBER	30		Y	
ZBPS_XCED_ID	NUMBER	30		N	
ZBPS_CARDROLE	NUMBER	1		Y	0=guest card linked to reservation 1=bookers card
ZBPS_EXPIRY	DATE			Y	
ZBPS_CONSUMED	NUMBER	30		N	number of consumed point. to be able to calculate balance considering expiry dates
ZBPS_TYPE	NUMBER	1		Y	copied from zbpc type when zbps is created automatically
ZBPS_WPHS_ID	NUMBER	30		Y	
ZBPS_UPLOADSTATUS	NUMBER	1		Y	1=upload in progress 2=upload successful 3=upload failed
ZBPS_UPLOADTIMESTAMP	DATE			Y	
ZBPS_ARRIVAL	DATE			Y	
ZBPS_DEPARTURE	DATE			Y	
ZBPS_ZBPP_ID	NUMBER	30		Y	
ZBPS_QUANTITY	NUMBER	3		Y	
ZBPS_COMMENT	VARCHAR2	200		Y	
ZBPS_TRANSFERFROM_XMNR_ID	NUMBER	30		Y	transferred from

## ZBPX

bonus point earning configuration for ratecode and roomtype

Field Name	Type	Length	Decimals	Not NULL
ZBPX_ID	NUMBER	30		N

### ZBPX

bonus point earning configuration for ratecode and roomtype

Field Name	Type	Length	Decimals	Not NULL
ZBPX_XMTY_ID	NUMBER	30		N
ZBPX_XMTL_ID	NUMBER	30		Y
ZBPX_CARDROLE	NUMBER	1		N
ZBPX_YRCH_ID	NUMBER	30		Y
ZBPX_YCAT_ID	NUMBER	30		Y
ZBPX_PERSTAY	NUMBER	20		Y
ZBPX_PERNIGHT	NUMBER	20		Y
ZBPX_FIRSTSTAY	NUMBER	20		Y

0=rules for guest card linked to reservation 1=rules for bookers card

### ZBST

bonus point card statement

Field Name	Type	Length	Decimals	Not NULL
ZBST_ID	NUMBER	30		N
ZBST_XMNR_ID	NUMBER	30		N
ZBST_TIMESTAMP	DATE			N
ZBST_BALANCE	NUMBER	15		N
ZBST_STATEMENTNUMBER	NUMBER	15		N
ZBST_LAST_ZBPS_ID	NUMBER	30		Y
ZBST_WTXT_ID	NUMBER	30		Y
ZBST_WRPT_ID	NUMBER	30		Y
ZBST_DELIVERYMETHOD	NUMBER	1		Y
ZBST_PREV_ZBST_ID	NUMBER	30		Y
ZBST_WMAI_ID	NUMBER	30		Y
ZBST_DRAFT	NUMBER	1		Y

### ZBTL

Field Name	Type	Length	Decimals	Not NULL
ZBTL_ID	NUMBER	30		N
ZBTL_FROM_ZWIN_ID	NUMBER	30		N
ZBTL_TO_ZWIN_ID	NUMBER	30		N
ZBTL_FROM_ZPOS_ID	NUMBER	30		N

### ZBTL

Field Name	Type	Length	Decimals	Not NULL
ZBTL_TO_ZPOS_ID	NUMBER	30		N
ZBTL_DATE	DATE			Y

### ZCAC

Credit Card Approval Calculation Methods

Field Name	Type	Length	Decimals	Not NULL	
ZCAC_ID	NUMBER	30		N	ZCAC_ID identifies ZCAC
ZCAC_DISPLORDER	NUMBER	3		N	ZCAC_DISPLORDER is of ZCAC
ZCAC_CALCRULE	NUMBER	1		N	ZCAC_CALCRULE is of ZCAC
ZCAC_AMOUNT	NUMBER	30	4	Y	ZCAC_AMOUNT is of ZCAC
ZCAC_AUTH_TYPE	NUMBER	1		N	ZCAC_AUTH_TYPE is of ZCAC
ZCAC_SETTL_TYPE	NUMBER	1		N	ZCAC_SETTL_TYPE is of ZCAC

### ZCAL

Transponder customer arrangement link

Field Name	Type	Length	Decimals	Not NULL	
ZCAL_ID	NUMBER	30		N	Unique Identifier
ZCAL_XCMS_ID	NUMBER	30		N	Link to Customer
ZCAL_ZTSA_ID	NUMBER	30		N	Link to Transponder Standard Arrangement
ZCAL_DEFAULT	NUMBER	1		Y	1 - Default

### ZCAS

Cashiers, including starting amount and all the cashier controls

Field Name	Type	Length	Decimals	Not NULL	
ZCAS_ID	NUMBER	30		N	Unique Identifier
ZCAS_NUMBER	NUMBER	30		N	The Cashier number
ZCAS_LONGDESCRIPTION	VARCHAR2	30		N	Name of this cashier number ( Cashier name or shift)
ZCAS_MAXOPENPERDAY	NUMBER	2		N	Number of times it can be used per day
ZCAS_OPEN	NUMBER	1		N	Status of the cashier (1=open, 2=closed)
ZCAS_ONLYALLOWEXCLOPEN	NUMBER	1		N	If the Cashier is set to exclusive opened, only one user may use each cashier number at the same time. This functionality will replace the former parameter Cash control. 1=excl. opening 0=multiple opening
ZCAS_IFC	NUMBER	1		Y	1 = only used for ifc, can not be opened or closed in Front Office

### ZCAS

Cashiers, including starting amount and all the cashier controls

Field Name	Type	Length	Decimals	Not NULL	
ZCAS_STOCKRESET	NUMBER	1		Y	1 - reset stock to default value on every opening, 0 - don't
ZCAS_INACTIVE	NUMBER	1		Y	0 - active, 1 - inactive

### ZCCA

Credit Card Types Table ZCCA links from XCCS (Customer Credit Card Link) to ZDCO (Department Codes)

Field Name	Type	Length	Decimals	Not NULL	
ZCCA_ID	NUMBER	30		N	ZCCA_ID identifies ZCCA
ZCCA_ZDCO_ID	NUMBER	30		Y	ZCCA_ZDCO_ID is the link from ZCCA into ZDCO (Department Codes)
ZCCA_LONGDESC	VARCHAR2	30		N	ZCCA_LONGDESC is the long name of the Credit Card (i.e. 'American Express') - might be moved to ZDCO itself.
ZCCA_SHORTDESC	VARCHAR2	3		N	ZCCA_SHORTDESC is the short description ( i.e. 'AX' or 'MC')
ZCCA_USAGETYPE	NUMBER	1		Y	0 No valid usage at this site 1 Credit card usage only 2 Bank card usage only 3 Debit card usage only 4 Combined credit and bank card 5 Combined credit and debit card 6 Combined bank and debit card 7 All usages
ZCCA_DISPLORDER	NUMBER	3		Y	ZCCA_DISPLORDER is of ZCCA
ZCCA_INACTIVE	NUMBER	1		Y	0=active, 1=inactive
ZCCA_AACC_ID	NUMBER	30		Y	if credit cards should be transferred to ar the link to the corresponding aacc record must be stored here.
ZCCA_TRANSFER_AR	NUMBER	1		Y	1 = transferred to ar when posted
ZCCA_TYPE_CHECK	NUMBER	1		Y	1 = Fidelio Checks the type , else not
ZCCA_ZCCT_ID	NUMBER	30		Y	Link to Credit Card Type Checks
ZCCA_SEND_TO_IFC	NUMBER	1		Y	1 = Send to Credit Card IFC
ZCCA_MANDATORYNUMBER	NUMBER	1		Y	ZCCA_MANDATORYNUMBER is of ZCCA
ZCCA_EFT_ONLINECHECK	NUMBER	1		Y	If EFT Interface is active this card can get checked from the EFT system (if supported by EFT System). Also even if Global Setting for online type check is active and the card is for some reason not recognized we can swipe the card if this flag is not '1'.
ZCCA_EFT_TYPE_REPLY	VARCHAR2	3		Y	When EFT Online Type Check is active, this is what we get back from EFT.
ZCCA_EFT_MERCHANT_ID	VARCHAR2	20		Y	Merchant id for eft
ZCCA_EFT_CREDITLIMIT	NUMBER	30	4	Y	EFT Credit Limit
ZCCA_ZCAC_ID	NUMBER	30		Y	ZCCA_ZCAC_ID is of ZCCA
ZCCA_TERMINALNUMBER	VARCHAR2	30		Y	Terminal number of FIDELIO within hotel
ZCCA_ISSUE_NUMBER_OPTION	NUMBER	1		Y	0.Not Applicable, 1.Applicable 2. Applicable and Mandatory
ZCCA_ISSUE_DATE_OPTION	NUMBER	1		Y	0.Not Applicable, 1. Applicable 2. Applicable and Mandatory
ZCCA_CHIP_PIN	NUMBER	1		Y	Indicates if this Credit Card Payment type supports Chip and Pin
ZCCA_AUTH_VALID_DAYS	NUMBER	3		Y	Validity Time Period (number of Days) of an old active Authorisation, 0 value indicate no timeframe is applicable

## ZCCA

Credit Card Types Table ZCCA links from XCCS (Customer Credit Card Link) to ZDCO (Department Codes)

Field Name	Type	Length	Decimals	Not NULL	
ZCCA_CC_SECURITY_CODE	NUMBER	1		Y	0 = Credit Card Security code not required 1 = Credit Card Security code required

## ZCCL

Cashier Closure Control File for multi Currency

Field Name	Type	Length	Decimals	Not NULL	
ZCCL_ID	NUMBER	30		N	ZCCL_ID identifies ZCCL
ZCCL_ZDCO_ID	NUMBER	30		N	ZCCL_ZDCO_ID is of ZCCL
ZCCL_ZACT_ID	NUMBER	30		N	ZCCL_ZACT_ID is of ZCCL
ZCCL_CALC_AMOUNT	NUMBER	30	4	N	System calculated amount (starting amount + actual posting since opening)
ZCCL_DIFFERENCE_AMOUNT	NUMBER	30	4	Y	If the user is entering short and over the difference of the manual entered amount and the calculated is stored here (manual-calculated)
ZCCL_DROPPED_AMOUNT	NUMBER	30	4	Y	amount shift dropped by the user (meaningful only for closure)
ZCCL_STARTING_AMOUNT	NUMBER	30	4	Y	Here we store the starting amount for this opening period.it is the same for open and close record.

## ZCCS

Credit Card Type Check SCHEMA, Hardcoded

Field Name	Type	Length	Decimals	Not NULL	
ZCCS_ID	NUMBER	30		N	ZCCS_ID identifies ZCCS
ZCCS_SCHEMA	NUMBER	3		N	Hardcoded Schema IDs, refer zccs_schema_name for description.
ZCCS_SCHEMA_NAME	VARCHAR2	50		Y	
ZCCS_PREFIX	VARCHAR2	50		Y	
ZCCS_CARD_LENGTH	VARCHAR2	50		Y	
ZCCS_VALIDATION_RULE	NUMBER	1		Y	0= No Validation 1= MOD 10 Luhn Check 2= User defined
ZCCS_USER_DEFINED	NUMBER	1		Y	
ZCCS_DISPLORDER	NUMBER	3		Y	
ZCCS_INACTIVE	NUMBER	1		Y	

## ZCCT

Credit Card Type Setup

Field Name	Type	Length	Decimals	Not NULL	
ZCCT_ID	NUMBER	30		N	Unique Identifier
ZCCT_SHORTDESC	VARCHAR2	3		N	Short Description
ZCCT_LONGDESC	VARCHAR2	30		N	Long Description

### ZCCT

Credit Card Type Setup

Field Name	Type	Length	Decimals	Not NULL	
ZCCT_DISPLORDER	NUMBER	3		N	Display Order
ZCCT_INACTIVE	NUMBER	1		Y	1 = inactive

### ZCCU

Credit Card Type Check Link to Card Schema available

Field Name	Type	Length	Decimals	Not NULL	
ZCCU_ID	NUMBER	30		N	ZCCU_ID identifies ZCCU
ZCCU_ZCCT_ID	NUMBER	30		N	ZCCU_ZCCT_ID is of ZCCU
ZCCU_ZCCS_ID	NUMBER	30		N	ZCCU_ZCCS_ID is of ZCCU

### ZCFC

Stores the foreign currency and conversion details of a credit settlement transaction

Field Name	Type	Length	Decimals	Not NULL	
ZCFC_ID	NUMBER	30		N	
ZCFC_XCAP_ID	NUMBER	30		N	
ZCFC_CURR_CODE	VARCHAR2	6		N	
ZCFC_CURR_RATE	NUMBER	30	8	Y	
ZCFC_AMOUNT	NUMBER	30	6	Y	

### ZCHE

POS Guest Checks

Field Name	Type	Length	Decimals	Not NULL	
ZCHE_ID	NUMBER	30		N	Unique identifier for ZCHE
ZCHE_GUESTCHECK	LONG			N	Guest Check Text
ZCHE_CHECKDATE	DATE			N	Date of Check
ZCHE_CHECKNUM	VARCHAR2	20		N	Check number

### ZCIF

Cashiers used by interfaces

Field Name	Type	Length	Decimals	Not NULL	
ZCIF_ID	NUMBER	30		N	Unique Identifier
ZCIF_ZCAS_ID	NUMBER	30		N	Link to cashier table

### ZCIF

Cashiers used by interfaces

Field Name	Type	Length	Decimals	Not NULL	
ZCIF_INTERFACECODE	NUMBER	2		N	Interface code. 1- TopVital Interface 2.Kiosk 3.Video Checkout

### ZCLN

linking diferent customer types like travel agent etc to the financial accounts

Field Name	Type	Length	Decimals	Not NULL	
ZCLN_ID	NUMBER	30		N	ZCLN_ID identifies ZCLN
ZCLN_ZFAC_ID	NUMBER	30		N	ZCLN_ZFAC_ID is of ZCLN
ZCLN_XCMS_ID	NUMBER	30		N	ZCLN_XCMS_ID is of ZCLN
ZCLN_XCCA_INTERNALCATEGORY	NUMBER	2		N	ZCLN_XCCA_INTERNALCATEGORY is of ZCLN

### ZCNR

Credit card number Ranges of User defined schemas

Field Name	Type	Length	Decimals	Not NULL	
ZCNR_ID	NUMBER	30		N	
ZCNR_RANGE_START	VARCHAR2	40		N	
ZCNR_RANGE_END	VARCHAR2	40		N	
ZCNR_ZCCS_ID	NUMBER	30		N	

### ZCNV

Field Name	Type	Length	Decimals	Not NULL	
ZCNV_ID	NUMBER	30		N	
ZCNV_TYPE	NUMBER	2		N	see constantsandtypes.tconversioninterfacetypes. in example 0=mmod interfaces
ZCNV_INTERFACEID	NUMBER	30		Y	for mmod interfaces this is mmod_id.
ZCNV_SHORTDESC	VARCHAR2	5		Y	Conversion rule shortdes
ZCNV_LONGDESC	VARCHAR2	30		Y	Conversion rule description

### ZCOX

Track table for checkout, to see if V8 was killed during C/O and it wasn't properly completed

Field Name	Type	Length	Decimals	Not NULL	
ZCOX_ID	NUMBER	30		N	
ZCOX_YRES_ID	NUMBER	30		Y	

### ZCOX

Track table for checkout, to see if V8 was killed during C/O and it wasn't properly completed

Field Name	Type	Length	Decimals	Not NULL
ZCOX_ZFAC_ID	NUMBER	30		Y
ZCOX_USER_XCMS_ID	NUMBER	30		Y
ZCOX_WPCA_ID	NUMBER	30		Y
ZCOX_COSTART	DATE			Y

### ZCPL

Credit Card Payment Link

Field Name	Type	Length	Decimals	Not NULL	
ZCPL_ID	NUMBER	30		N	Unique Identifier
ZCPL_YRCL_ID	NUMBER	30		N	ZCPL_YRCL_ID is of ZCPL
ZCPL_ZPOS_ID	NUMBER	30		N	ZCPL_ZPOS_ID is of ZCPL
ZCPL_TRANSID	VARCHAR2	30		Y	Transaction ID from EFT System
ZCPL_XCAP_ID	NUMBER	30		Y	
ZCPL_CC_INSTALLMENTS	NUMBER	2		Y	

### ZCRL

Credit Limits

Field Name	Type	Length	Decimals	Not NULL	
ZCRL_ID	NUMBER	30		N	Unique ID
ZCRL_SHORTDESC	VARCHAR2	3		N	Short description
ZCRL_LONGDESC	VARCHAR2	30		N	Long description
ZCRL_DEFAULT	NUMBER	1		Y	Default Credit Limit
ZCRL_CREDIT	NUMBER	30	4	Y	Credit Limit Amount

### ZCTS

CITYTAX LOG

Field Name	Type	Length	Decimals	Not NULL	
ZCTS_ID	NUMBER	30		N	primary key
ZCTS_DATE	DATE			N	date and time of separation
ZCTS_ZPOS_ID	NUMBER	30		N	the separated tax's id
ZCTS_REASON	VARCHAR2	30		Y	reason of separation
ZCTS_USER_XCMS_ID	NUMBER	30		N	user id

### ZCTS

CITYTAX LOG

Field Name	Type	Length	Decimals	Not NULL	
ZCTS_ZCAS_ID	NUMBER	30		N	cashier id

### ZCUC

Stores the details of the possible usage options for each ZCCA

Field Name	Type	Length	Decimals	Not NULL	
ZCUC_ID	NUMBER	30		N	
ZCUC_ZCCA_ID	NUMBER	30		N	
ZCUC_DESCRIPTION	VARCHAR2	30		N	
ZCUC_CHOICE	NUMBER	2		N	
ZCUC_USAGE_ZCCA_ID	NUMBER	30		N	

### ZCUR

currencies

Field Name	Type	Length	Decimals	Not NULL	
ZCUR_ID	NUMBER	30		N	ZCUR_ID identifies ZCUR
ZCUR_SHORTDESC	VARCHAR2	3		N	ZCUR_SHORTDESC is of ZCUR
ZCUR_LONGDESC	VARCHAR2	30		N	ZCUR_LONGDESC is of ZCUR
ZCUR_DISPLORDER	NUMBER	3		Y	ZCUR_DISPLORDER is of ZCUR
ZCUR_ZDCO_ID	NUMBER	30		Y	The payment types credit cards will be need to setup in ZDCO and we link the information about Currency symbol, decimal digits and so on to ZCUR. ZCUR itself is more or less the selection if they create Foreign Currencies as department codes they select from ZCUR.
ZCUR_DECDIGITS	NUMBER	1		Y	number of decimal digits to display on screen
ZCUR_ACTIVE	NUMBER	1		Y	Indicates if the hotel want to use this currency. 1 = active On Currency configuration screen the user can select if the currency is active. All other currency related screens will only come up with active currencies.
ZCUR_ISO3	VARCHAR2	3		Y	Iso 3 Standard Code
ZCUR_MONTHLY	NUMBER	1		N	1= indicates if the currency exchange rate is fixed on a monthly basis, 0= not 1

### ZDAT

binary invoice printout storage

Field Name	Type	Length	Decimals	Not NULL	
ZDAT_ID	NUMBER	30		N	ZDAT_ID identifies ZDAT
ZDAT_DATA	LONG RAW			N	binary field

## ZDAT

binary invoice printout storage

Field Name	Type	Length	Decimals	Not NULL	
ZDAT_PAGENUM	NUMBER	10		Y	he exported html's page number
ZDAT_RESOURCE_NAME	VARCHAR2	60		Y	resource filename
ZDAT_RESOURCE_TIMESTAMP	DATE			Y	resource file timestamp for caching
ZDAT_TYPE	NUMBER	2		Y	ZINB_TYPE is null or 0 means HTML, 1 means other resource (jpg,gif)
ZDAT_LINKTABLE_NAME	VARCHAR2	4		Y	exported html linktable zinb=folio history, ztxt= depends on ztxt.type, 1=cashier closure reports
ZDAT_LINKTABLE_ID	NUMBER	30		Y	id of the linktable

## ZDC2

Physical Originator of Posting, as Coffe Shop, Bar, Restaurant. These codes can be linked to Department Codes and to postings. This is for statistical reason.

Field Name	Type	Length	Decimals	Not NULL	
ZDC2_ID	NUMBER	30		N	ZDC2_ID identifies ZDC2
ZDC2_SHORTDESC	VARCHAR2	3		N	ZDC2_SHORTDESC is of ZDC2
ZDC2_LONGDESC	VARCHAR2	30		N	ZDC2_LONGDESC is of ZDC2
ZDC2_DISPLORDER	NUMBER	3		Y	ZDC2_DISPLORDER is of ZDC2
ZDC2_IFC_VALUE	VARCHAR2	30		Y	

## ZDCC

Defines which physical origin (ZDC2) can be paired to which department Code in the posting. Example beer can come from bar and restaurant

Field Name	Type	Length	Decimals	Not NULL	
ZDCC_ID	NUMBER	30		N	ZDCC_ID identifies ZDCC
ZDCC_ZDCO_ID	NUMBER	30		N	ZDCC_ZDCO_ID is of ZDCC
ZDCC_ZDC2_ID	NUMBER	30		N	ZDCC_ZDC2_ID is of ZDCC
ZDCC_PRIMARY	NUMBER	1		N	If multiple ZDC2 records are linked to one department code: 1 = Default 0 = not default This is used for manual posting-

## ZDCG

department code groups

Field Name	Type	Length	Decimals	Not NULL	
ZDCG_ID	NUMBER	30		N	ZDCG_ID identifies ZDCG
ZDCG_SHORTDESC	VARCHAR2	3		N	ZDCG_SHORTDESC is of ZDCG
ZDCG_LONGDESC	VARCHAR2	30		N	ZDCG_LONGDESC is of ZDCG
ZDCG_DISPLORDER	NUMBER	3		Y	ZDCG_DISPLORDER is of ZDCG
ZDCG_ZDMG_ID	NUMBER	30		Y	ZDCG_ZDMG_ID is of ZDCG

### ZDCG

department code groups

Field Name	Type	Length	Decimals	Not NULL	
ZDCG_INACTIVE	NUMBER	1		Y	ZDCG_INACTIVE is of ZDCG
ZDCG_CENTRAL	NUMBER	1		N	

### ZDCL

Enhanced Print Separate Citytax Handling, department code link table

Field Name	Type	Length	Decimals	Not NULL	
ZDCL_ID	NUMBER	30		N	ZDCL_ID identifies ZDCL
ZDCL_ZDCO_ID	NUMBER	30		N	ZDCL_ZDCO_ID is of ZDCL
ZDCL_SUB_ZDCO_ID	NUMBER	30		N	ZDCL_SUB_ZDCO_ID is of ZDCL
ZDCL_CALCTYPE	NUMBER	1		N	1 - percentage   2 - flatrate
ZDCL_CALCONNET	NUMBER	1		Y	ZDCL_CALCONNET is of ZDCL
ZDCL_NOPOSTIFMANUAL	NUMBER	1		Y	ZDCL_NOPOSTIFMANUAL is of ZDCL
ZDCL_AMOUNT	NUMBER	30	4	Y	ZDCL_AMOUNT is of ZDCL
ZDCL_POSTONLYIFMANUAL	NUMBER	1		Y	Post Citytax only for manual postings
ZDCL_INCLUDEINGROUP	NUMBER	1		Y	1 = Include citytax postings in the orginial posting's internalgroup
ZDCL_CALCINCLUDED	NUMBER	1		Y	1 - indicates that the City Tax has to be calculated like it was an included tax
ZDCL_UDF	VARCHAR2	200		Y	User defined formula for the City Tax calculation

### ZDCO

Department codes

Field Name	Type	Length	Decimals	Not NULL	
ZDCO_ID	NUMBER	30		N	ZDCO_ID identifies ZDCO
ZDCO_SHORTDESC	VARCHAR2	3		Y	Short description
ZDCO_LONGDESC	VARCHAR2	30		N	Long description
ZDCO_NUMERICDESC	NUMBER	10		N	department code number
ZDCO_DISPLORDER	NUMBER	3		Y	Display order
ZDCO_CDT	NUMBER	1		N	ZDCO_CDT Comments 1 = debit 2 = tax 5 = credit
ZDCO_MANUALPOST	NUMBER	1		Y	manual post allowed (1) or not (0) for debit departments only
ZDCO_ZARR_ID	NUMBER	30		Y	This is valid for debit departments only. On the DepartmentCode Edit Screen this should be only available on Debit Department Codes Section.
ZDCO_UNITDESCRIPTION	VARCHAR2	10		Y	description of units (pcs,kg etc) for debit departments only
ZDCO_GOVCODE	VARCHAR2	30		Y	government code
ZDCO_CITYLEDGER	NUMBER	1		Y	obsolete. City Ledger is now identified by ZDCO_PAYM_TYPE= 2

### ZDCO

Department codes

Field Name	Type	Length	Decimals	Not NULL	
ZDCO_ZDCG_ID	NUMBER	30		Y	Department code group ID
ZDCO_PAYM_TYPE	NUMBER	2		Y	0= cash (base currency), 1= cheque, 2= city ledger, 3= credit card, 4= foreign currency, 5= miscellaneous, 6=bank payments / for credit departments only.
ZDCO_PAIDOUT	NUMBER	1		Y	Only marked dept. codes can be used for paid out postings. 1 = true, anything else = false For credit dept. codes only.
ZDCO_DISABLED_PREARR	NUMBER	1		Y	Flag to disable the usage of the dept. code in the pre-arrival.
ZDCO_DISABLED_BILLING	NUMBER	1		Y	Flag to disable the usage of the dept. code in the billing.
ZDCO_DISABLED_AR	NUMBER	1		Y	Flag to disable the usage of the dept. code in the AR module.
ZDCO_NONHTLREV	NUMBER	1		Y	1 if it is a non hotel revenue code, like for theater tickets (former Inr between 850 and 899)
ZDCO_STATS_TYPE	NUMBER	1		Y	1 = LOGIS 2 = Food and Beverage 3 = Minibar 4 = Telephone 5 = Miscellaneous
ZDCO_BOF_CR_ACC	NUMBER	10		Y	ZDCO_BOF_CR_ACC is of ZDCO
ZDCO_BOF_DB_ACC	NUMBER	10		Y	ZDCO_BOF_DB_ACC is of ZDCO
ZDCO_BOF_DEP	NUMBER	5		Y	ZDCO_BOF_DEP is of ZDCO
ZDCO_FOLIOTEXT	VARCHAR2	30		Y	Used for those hotels which like to have different descriptions on the guests invoices , but do not want to use arrangements for that purpose. If not empty(ZDCO_FOLIOTEXT), ZDCO_FOLIOTEXT ELSE ZDCO_LONGDESC.
ZDCO_DISABLED_CCM	NUMBER	1		Y	1 = not available for ccm
ZDCO_BOF_UDEF_NUM_1	NUMBER	1		Y	GENERIC FIELDS for Back Office Interface
ZDCO_BOF_UDEF_AMNT_1	NUMBER	30	4	Y	GENERIC FIELDS for Back Office Interface
ZDCO_BOF_UDEF_CHAR_1	VARCHAR2	30		Y	GENERIC FIELDS for Back Office Interface
ZDCO_UDEF_NUM_1	NUMBER	1		Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_NUM_2	NUMBER	1		Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_NUM_3	NUMBER	1		Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_AMNT_1	NUMBER	30	4	Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_AMNT_2	NUMBER	30	4	Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_AMNT_3	NUMBER	30	4	Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_CHAR_1	VARCHAR2	30		Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_CHAR_2	VARCHAR2	30		Y	Additional Fields without hardcoded functionality.
ZDCO_UDEF_CHAR_3	VARCHAR2	30		Y	Additional Fields without hardcoded functionality.
ZDCO_INACTIVE	NUMBER	1		Y	Indicates that the department code is not active (deleted, out of use): 0-active, 1-not active
ZDCO_DEPOSIT	NUMBER	1		Y	Valid for Deposit Revenue Posting (when posting deposit payment)
ZDCO_DISABLED_PAY_ONLY	NUMBER	1		Y	1 - disbled in payments, 0 - not disabled
ZDCO_XCHFEE TYPE	NUMBER	1		Y	shows the currency exchange fee type: null, 0 - no exchange fee defined, 1 - percentage, 2 - flatrate
ZDCO_XCHFEE	NUMBER	30	4	Y	contains the currency exchange rate fee value

### ZDCO

Department codes

Field Name	Type	Length	Decimals	Not NULL	
ZDCO_XCHFEE_ZDCO_ID	NUMBER	30		Y	department code of the fee
ZDCO_SUBFUNCTION	NUMBER	1		Y	0 - None; 1 - Room Charge; 2 - Breakfast next day
ZDCO_ZCRL_ID	NUMBER	30		Y	only valid for payment department codes, default credit limit
ZDCO_OPEN_CASH_DRAWER	NUMBER	1		Y	Is Cash drawer should be opened when using this department
ZDCO_CERTREDEMPTION	NUMBER	1		Y	Use Varibon Certificate redemption for this type of payments
ZDCO_NOOFCOPIES	NUMBER	2		Y	Number of copies for invoices can be defined based on payments
ZDCO_BOF_CR_ACC_DEPOSIT	NUMBER	10		Y	BOF Credit Account for Deposits
ZDCO_BOF_DB_ACC_DEPOSIT	NUMBER	10		Y	BOF Debit Account for Deposits
ZDCO_CITYTAX	NUMBER	1		Y	for Enhanced Print Separate Citytax Handling
ZDCO_ADJUST_ZDCO_ID	NUMBER	30		Y	The department code where rebate goes when user selects Adjust
ZDCO_HOSTESSEENABLED	NUMBER	1		Y	0 - not enabled for hostesses, 1 - Enabled for hostesses
ZDCO_FISCAL	NUMBER	1		Y	
ZDCO_FOREIGN_CC_ZCUR_ID	NUMBER	30		Y	
ZDCO_XCHFEE_MULTIPLYBYCHEQ UES	NUMBER	1		Y	Multiply by Number of Cheques when flatrate fee is set
ZDCO_COMMENTDISABLED	NUMBER	1		Y	0 = ZPOS_COMMENT shown on invoice, 1 = ZPOS_COMMENT hidden on invoice
ZDCO_BANK_DEBITPAYMENT	NUMBER	1		Y	Allow Direct Bank Debit Payment
ZDCO_DISABLE_FISCALPRINTER	NUMBER	1		Y	
ZDCO_CENTRAL	NUMBER	1		N	
ZDCO_GENERATETHAIVAT	NUMBER	1		N	
ZDCO_ZDSG_ID	NUMBER	30		Y	Department code group CCM ID
ZDCO_BAVEL_TYPE	NUMBER	1		Y	0 = ZDCO_BAVEL_TYPE EarlyPayment, 1 = ZDCO_BAVEL_TYPE EarlyBooking, 2 = ZDCO_BAVEL_TYPE Commercial, 3 = ZDCO_BAVEL_TYPE Other, 4 = ZDCO_BAVEL_TYPE Room, -1 = ZDCO_BAVEL_TYPE None
ZDCO_SAFT_PAYMENTMECHANISMVARCHA2		2		Y	
ZDCO_CCCOMMISSION_ZDCO_ID	NUMBER	30		Y	Department code for Credit Card Commission posting
ZDCO_CCCOMMISSION_PERCENT	NUMBER	4	2	Y	Percentage of Credit Card Commission

### ZDDP

department code default price

Field Name	Type	Length	Decimals	Not NULL	
ZDDP_ID	NUMBER	30		N	ZDDP_ID identifies ZDDP
ZDDP_ZDCO_ID	NUMBER	30		N	ZDDP_ZDCO_ID is of ZDDP
ZDDP_FROMTIME	DATE			N	ZDDP_FROMTIME is of ZDDP

### ZDDP

department code default price

Field Name	Type	Length	Decimals	Not NULL	
ZDDP_TOTIME	DATE			N	ZDDP_TOTIME is of ZDDP
ZDDP_PRICE	NUMBER	30	4	N	ZDDP_PRICE is of ZDDP

### ZDGT

Field Name	Type	Length	Decimals	Not NULL	
ZDGT_ID	NUMBER	30		N	
ZDGT_SHORTDESC	VARCHAR2	3		N	
ZDGT_LONGDESC	VARCHAR2	30		N	
ZDGT_TYPE	NUMBER	2		N	0-daily guest, 1-family, 2-promotion, 3-member, 4-overnight guest, 5-other
ZDGT_BESTPRICEROLE	NUMBER	3		Y	defines a grouping for best price finding
ZDGT_WCOL_ID	NUMBER	30		Y	Color for buttons

### ZDMG

department code main groups

Field Name	Type	Length	Decimals	Not NULL	
ZDMG_ID	NUMBER	30		N	ZDMG_ID identifies ZDMG
ZDMG_SHORTDESC	VARCHAR2	3		N	ZDMG_SHORTDESC is of ZDMG
ZDMG_LONGDESC	VARCHAR2	30		N	ZDMG_LONGDESC is of ZDMG
ZDMG_DISPLORDER	NUMBER	3		Y	ZDMG_DISPLORDER is of ZDMG
ZDMG_INACTIVE	NUMBER	1		Y	ZDMG_INACTIVE is of ZDMG
ZDMG_CENTRAL	NUMBER	1		N	

### ZDMP

Transponder Links - Department codes linked to external (MF-)Ticket types

Field Name	Type	Length	Decimals	Not NULL	
ZDMP_ID	NUMBER	30		N	Unique ID
ZDMP_ZDCO_ID	NUMBER	30		N	Link to Department Code
ZDMP_TO_POSTICKETTYPE	NUMBER	30		N	Link to Ticket Type (external MF-Ticket Database)
ZDMP_ZDGT_ID	NUMBER	30		Y	
ZDMP_DISPLORDER	NUMBER	5		Y	
ZDMP_INACTIVE	NUMBER	1		N	

## ZDMP

Transponder Links - Department codes linked to external (MF-)Ticket types

Field Name	Type	Length	Decimals	Not NULL	
ZDMP_WCOL_ID	NUMBER	30		Y	Color for buttons

## ZDSG

department code group CCM - Sales and Catering

Field Name	Type	Length	Decimals	Not NULL	
ZDSG_ID	NUMBER	30		N	ZDSG_ID identifies ZDSG
ZDSG_SHORTDESC	VARCHAR2	3		N	ZDSG_SHORTDESC is of ZDSG
ZDSG_LONGDESC	VARCHAR2	30		N	ZDSG_LONGDESC is of ZDSG
ZDSG_DISPLORDER	NUMBER	3		Y	ZDSG_DISPLORDER is of ZDSG
ZDSG_INACTIVE	NUMBER	1		Y	ZDSG_INACTIVE is of ZDSG
ZDSG_CENTRAL	NUMBER	1		N	ZDSG_CENTRAL used for CRS or HCN

## ZDTL

department tax link //do not allow overlapping time ranges for one department code on that level

Field Name	Type	Length	Decimals	Not NULL	
ZDTL_ID	NUMBER	30		N	ZDTL_ID identifies ZDTL
ZDTL_ZDCO_ID	NUMBER	30		N	ZDTL_ZDCO_ID is of ZDTL
ZDTL_ZTXC_ID	NUMBER	30		N	ZDTL_ZTXC_ID is of ZDTL
ZDTL_FROMTIME	DATE			N	ZDTL_FROMTIME is of ZDTL
ZDTL_TOTIME	DATE			Y	ZDTL_TOTIME is of ZDTL
ZDTL_TAX_PREARR	CHAR			Y	Flag for tax applicable to pre-arrival only. 1=true
ZDTL_ZTXX_ID	NUMBER	30		Y	link to tax exemption
ZDTL_IGNORE_NA_CHECK	NUMBER	1		Y	1. Ignore from Night audit expiry check routine
ZDTL_CALCRULE	NUMBER	1		Y	Indian Luxury Tax / calculation rule for this tax / 0 Not assigned, 1 - Charged Rate, 2 - Rack Rate, 3 - Higher Rate

## ZELL

Early Arrival/Late Departure posting log

Field Name	Type	Length	Decimals	Not NULL	
ZELL_ID	NUMBER	30		N	
ZELL_YRES_ID	NUMBER	30		Y	
ZELL_ZPOS_ID	NUMBER	30		Y	
ZELL_TYPE	NUMBER	1		N	0 - Early Arrival, 1 - Late Departure

## ZELL

Early Arrival/Late Departure posting log

Field Name	Type	Length	Decimals	Not NULL
ZELL_POSTTIME	DATE			Y
ZELL_HOURS	NUMBER	2		Y

## ZEMS

Energy management interface notification

Field Name	Type	Length	Decimals	Not NULL	
ZEMS_ID	NUMBER	30		N	ZEMS PK
ZEMS_YRES_ID	NUMBER	30		N	Reservation link
ZEMS_ON_NOTIFICATION_TIME	DATE			Y	Time of the switching ON
ZEMS_OFF_NOTIFICATION_TIME	DATE			Y	Time of the switching OFF
ZEMS_YRMS_ID	NUMBER	30		Y	Room number link

## ZFAC

financial accounts

Field Name	Type	Length	Decimals	Not NULL	
ZFAC_ID	NUMBER	30		N	ZFAC_ID identifies ZFAC
ZFAC_XCMS_ID	NUMBER	30		Y	ZFAC_XCMS_ID is of ZFAC
ZFAC_LONGDESC	VARCHAR2	30		Y	ZFAC_LONGDESC is of ZFAC
ZFAC_EXPVALIDFROM	DATE			Y	ZFAC_EXPVALIDFROM is of ZFAC
ZFAC_EXPVALIDUNTIL	DATE			Y	ZFAC_EXPVALIDUNTIL is of ZFAC
ZFAC_XCMA_ID	NUMBER	30		Y	ZFAC_XCMA_ID is of ZFAC
ZFAC_ZFAN_ID	NUMBER	30		Y	ZFAC_ZFAN_ID is of ZFAC
ZFAC_ACTVALIDFROM	DATE			Y	ZFAC_ACTVALIDFROM is of ZFAC
ZFAC_ACTVALIDUNTIL	DATE			Y	ZFAC_ACTVALIDUNTIL is of ZFAC
ZFAC_ZFAG_ID	NUMBER	30		Y	ZFAC_ZFAG_ID is of ZFAC
ZFAC_AUTONUMBER	NUMBER	30		Y	if financial accounts are set to autonumber style we will fill this with incrementing numbers.
ZFAC_ACTVALIDFROMNULL	NUMBER	1		Y	Used for speed in queries, 1 as long as guest is not checked in
ZFAC_ACTVALIDUNTILNULL	NUMBER	1		Y	Used for speed in queries, 1 as long as guest is not checked out
ZFAC_YBOM_ID	NUMBER	30		Y	link to booking master
ZFAC_REINSTATED	NUMBER	1		Y	1 = checked out FA get reinstated and 0 again after next check out
ZFAC_ZTRA_ID	NUMBER	30		Y	Transponder id
ZFAC_ZCRL_ID	NUMBER	30		Y	Credit limit

### ZFAC

financial accounts

Field Name	Type	Length	Decimals	Not NULL	
ZFAC_YPRT_ID	NUMBER	30		Y	Party zfac
ZFAC_CREDITLIMIT	NUMBER	30	4	Y	Credit limit manual override
ZFAC_NOPOST	NUMBER	1		Y	No post flag for POS interfaces. 1 = no posting allowed on POS   0 or null = postings allowed
ZFAC_CHECKOUTTIME	DATE			Y	timestamp for checkout
ZFAC_SOURCE_YRAS_ID	NUMBER	30		Y	
ZFAC_CHANNEL_YRAS_ID	NUMBER	30		Y	
ZFAC_CURRENT_PTIK_ID	NUMBER	30		Y	
ZFAC_ZTXX_ID	NUMBER	30		Y	
ZFAC_CONTRACT_ZCUR_ID	NUMBER	30		Y	
ZFAC_FREETEXT1	VARCHAR2	100		Y	
ZFAC_FREETEXT2	VARCHAR2	100		Y	
ZFAC_NOBONUSPOINT	NUMBER	1		N	

### ZFAG

Financial Account Group, as POS account or account for stuff

Field Name	Type	Length	Decimals	Not NULL	
ZFAG_ID	NUMBER	30		N	ZFAG_ID identifies ZFAG
ZFAG_SHORTDESC	VARCHAR2	3		N	ZFAG_SHORTDESC is of ZFAG
ZFAG_LONGDESC	VARCHAR2	30		N	ZFAG_LONGDESC is of ZFAG
ZFAG_DEFAULT	NUMBER	1		N	1 = is Default 0 = not default The default is normal Financial account if no one cares about grouping. However when creating an account the user could select another account number of group
ZFAG_TYPE	NUMBER	2		Y	0 = Financial Account (Paymaster)   1 = AR Revenue Charges   2 = AR Payments   3 = Foreign Currency Exchange   4 = for Booth telephone charges paid cash   5 = Internal Interface Type for POS Accounts or Lost Posting Account, these financial accounts are getting checked in automatically after check out.   6 = Petty Cash accounts   7 = Transponder reading   8 = Deposits, Cancellation and NoShow   9 = Personal (Staff) Accounts (TI)   10 = type for Dont close folio   11= Financial Account for automatic creation   12 = Vouchers or what
ZFAG_AUTONUMBER	NUMBER	1		Y	1 = no selection done from zfan when creating a zfac record for this type. automatic we will increment the number for the created financial account of this type in ZINN and propagate to zfac_autonumber
ZFAG_SEND_IFC	NUMBER	1		Y	Flag to Notify Key card Interface. 0(null) : Do not Notify the IFC, 1: Notify Interface but do not show make key screen, 2: Show make key screen and then Notify Interface
ZFAG_DEFAULT_ZFST_ID	NUMBER	30		Y	the ability to set one default folio style for reservations and another default folio style for fin. acc.
ZFAG_INACTIVE	NUMBER	1		Y	1 = inactive group

### ZFAG

Financial Account Group, as POS account or account for stuff

Field Name	Type	Length	Decimals	Not NULL	
ZFAG_SHOWINROOMPLAN	NUMBER	1		Y	If this FA group should be shown in room rack
ZFAG_WCOL_ID	NUMBER	30		Y	Color for the Room Rack
ZFAG_YCAD_ID	NUMBER	30		Y	FA Link to Hotel Segments
ZFAG_AUTOWINDOWS	NUMBER	1		Y	used only for staff accounts, when 1 fa gets special windows created on checkin
ZFAG_AUTOCHECKOUT	NUMBER	1		Y	1-gets automatically checked out during NA
ZFAG_AUTOCHECKOUT_ZDCO_ID	NUMBER	30	4	Y	predefined payment dept code for automatic checkout
ZFAG_DEPDATEYPE	NUMBER	1		Y	
ZFAG_IGNOREFISCAL	NUMBER	1		Y	
ZFAG_DEFAULT_NOPOST	NUMBER	1		Y	Default Nopost flag for FAs of this group
ZFAG_KEYIFC_ICFG_ID	NUMBER	30		Y	linked Key Interface
ZFAG_IGNOREINVOICE	NUMBER	1		Y	1 - Ignore invoice creation

### ZFAN

Financial Account Numbers

Field Name	Type	Length	Decimals	Not NULL	
ZFAN_ID	NUMBER	30		N	ZFAN_ID identifies ZFAN
ZFAN_LONGDESC	VARCHAR2	30		N	ZFAN_LONGDESC is of ZFAN
ZFAN_ZFAG_ID	NUMBER	30		N	ZFAN_ZFAG_ID is of ZFAN
ZFAN_DESCRIPTION	VARCHAR2	30		Y	Shown on list when creating financial account
ZFAN_DISPLORDER	NUMBER	4		Y	Displayorder on screen

### ZFCF

Invoice custom fileds. Usually used with Fiscal Printer Interface

Field Name	Type	Length	Decimals	Not NULL	
ZFCF_ID	NUMBER	30		N	
ZFCF_ZINV_ID	NUMBER	30		N	
ZFCF_GENERATION_DATE	DATE			Y	
ZFCF_RESPONSE_XML	XMLTYPE			Y	
ZFCF_STATUS	VARCHAR2	30		Y	

### ZFGR

Needed for TI. Several FAs are linked together in a group. They all should belong to one guest. They are bound together, so if the master gets checked out, all the others must be checked out too.

Field Name	Type	Length	Decimals	Not NULL	
ZFGR_ID	NUMBER	30		N	Unique Identifier
ZFGR_MASTER_ZFAC_ID	NUMBER	30		N	Master zfac id
ZFGR_ZFAC_ID	NUMBER	30		N	Linked zfac id

### ZFPD

Link returnable items to FAs

Field Name	Type	Length	Decimals	Not NULL	
ZFPD_ID	NUMBER	30		N	Unique ID
ZFPD_XPDA_ID	NUMBER	30		N	ZFPD_XPDA_ID is of ZFPD
ZFPD_ZFAC_ID	NUMBER	30		N	ZFPD_ZFAC_ID is of ZFPD
ZFPD_ORIGINATED_ZFAC_ID	NUMBER	30		Y	TI: Id of the linked FA where the item belongs to
ZFPD_CREATED	DATE			Y	date of the creation (handout of the returnable item)
ZFPD_RETURNED	DATE			Y	date of receiving the returnable item back

### ZFRL

Fattura Riepilogativa Link table

Field Name	Type	Length	Decimals	Not NULL	
ZFRL_ID	NUMBER	30		N	Unique Identifier
ZFRL_ACOMP_ID	NUMBER	30		N	Link to A/R Compression table
ZFRL_ZINV_ID	NUMBER	30		N	Link to Invoice table

### ZFST

Folio Style Configuration

Field Name	Type	Length	Decimals	Not NULL	
ZFST_ID	NUMBER	30		N	Unique identifier for ZFST
ZFST_LONGDESC	VARCHAR2	30		N	Long Description for Folio Style
ZFST_WRPT_ID	NUMBER	30		N	Link to binary storage of report template
ZFST_DEFAULT	NUMBER	1		Y	1 = Default Folio Style
ZFST_DISPLORDER	NUMBER	3		N	Display Order on Folio Style selection
ZFST_INACTIVE	NUMBER	1		Y	1 = Inactive
ZFST_ZINN_ID	NUMBER	30		Y	If INVOICE NUMBER CIRCLE is linked to Folio Style the Folio will pick up the invoice number from the relevant INVOICE NUMBER CIRCLE

### ZFST

Folio Style Configuration

Field Name	Type	Length	Decimals	Not NULL	
ZFST_PURPOSE	NUMBER	1		Y	intended purpose of the folio 0=information and check out, 1=only information, 2=only check out, 3 - only accounts receivable (ar fattura italy), 4 - hostess only
ZFST_NDC	NUMBER	1		Y	=0 means: always available; =1 means: only available if balance < zero; =2 means: only available if balance > zero

### ZFTT

Field Name	Type	Length	Decimals	Not NULL	
ZFTT_ID	NUMBER	30		N	
ZFTT_ZFAC_ID	NUMBER	30		N	
ZFTT_TIMESTAMP	DATE			Y	
ZFTT_TYPE	NUMBER	1		Y	1-checkin, 2-checkout, 3-change
ZFTT_USER_XCMS_ID	NUMBER	30		Y	
ZFTT_ZDGT_ID	NUMBER	30		Y	
ZFTT_MFD_TICKET_POSTTYPE	NUMBER	30		N	

### ZFZP

plz abfrage bei check out

Field Name	Type	Length	Decimals	Not NULL	
ZFZP_ID	NUMBER	30		N	
ZFZP_ZFAC_ID	NUMBER	30		N	
ZFZP_XCOU_ID	NUMBER	30		N	
ZFZP_ZIP	VARCHAR2	15		Y	

### ZIBN

Lost invoice number storage

Field Name	Type	Length	Decimals	Not NULL	
ZIBN_ID	NUMBER	30		N	ZIBN_ID identifies ZIBN
ZIBN_NUMBER	VARCHAR2	60		N	ZIBN_NUMBER is of ZIBN
ZIBN_DATE	DATE			Y	ZIBN_DATE is of ZIBN
ZIBN_ZINN_ID	NUMBER	30		Y	ZIBN_ZINN_ID is of ZIBN
ZIBN_FAILED_ZWIN_ID	NUMBER	30		Y	ZIBN_FAILED_ZWIN_ID is of ZIBN

### ZINB

binary invoice printout storage

Field Name	Type	Length	Decimals	Not NULL	
ZINB_ID	NUMBER	30		N	ZINB_ID identifies ZINB
ZINB_DATA	LONG RAW			Y	ZINB_DATA is of ZINB
ZINB_TYPE	NUMBER	2		Y	ZINB_TYPE is null or 0 means rpt binary, 1 means html
ZINB_PARENT_ZINB_ID	NUMBER	30		Y	revision to link to original invoice
ZINB_EDITOR_XCMS_ID	NUMBER	30		Y	ZINB_EDITOR_XCMS_ID is of ZINB
ZINB_EDITOR_DATETIME	DATE			Y	ZINB_EDITOR_DATETIME is of ZINB
ZINB_REVISION_NUMBER	NUMBER	30		Y	Revision number
ZINB_NOTE	VARCHAR2	200		Y	modification note
ZINB_COMPRESSED	NUMBER	1		Y	indicator if the record is compressed or not

### ZINK

Table for special polish invoice correction report

Field Name	Type	Length	Decimals	Not NULL	
ZINK_ID	NUMBER	30		N	
ZINK_ZINV_ID	NUMBER	30		N	
ZINK_OLD_ZTXC_ID0	NUMBER	30		Y	
ZINK_OLD_NET0	NUMBER	30	4	Y	
ZINK_OLD_TAX0	NUMBER	30	4	Y	
ZINK_OLD_ZTXC_ID1	NUMBER	30		Y	
ZINK_OLD_NET1	NUMBER	30	4	Y	
ZINK_OLD_TAX1	NUMBER	30	4	Y	
ZINK_OLD_ZTXC_ID2	NUMBER	30		Y	
ZINK_OLD_NET2	NUMBER	30	4	Y	
ZINK_OLD_TAX2	NUMBER	30	4	Y	
ZINK_OLD_ZTXC_ID3	NUMBER	30		Y	
ZINK_OLD_NET3	NUMBER	30	4	Y	
ZINK_OLD_TAX3	NUMBER	30	4	Y	
ZINK_OLD_ZTXC_ID4	NUMBER	30		Y	
ZINK_OLD_NET4	NUMBER	30	4	Y	
ZINK_OLD_TAX4	NUMBER	30	4	Y	
ZINK_OLD_ZTXC_ID5	NUMBER	30		Y	
ZINK_OLD_NET5	NUMBER	30	4	Y	
ZINK_OLD_TAX5	NUMBER	30	4	Y	

## ZINK

Table for special polish invoice correction report

Field Name	Type	Length	Decimals	Not NULL
ZINK_OLD_ZTXC_ID6	NUMBER	30		Y
ZINK_OLD_NET6	NUMBER	30	4	Y
ZINK_OLD_TAX6	NUMBER	30	4	Y
ZINK_OLD_ZTXC_ID7	NUMBER	30		Y
ZINK_OLD_NET7	NUMBER	30	4	Y
ZINK_OLD_TAX7	NUMBER	30	4	Y
ZINK_OLD_ZTXC_ID8	NUMBER	30		Y
ZINK_OLD_NET8	NUMBER	30	4	Y
ZINK_OLD_TAX8	NUMBER	30	4	Y
ZINK_OLD_ZTXC_ID9	NUMBER	30		Y
ZINK_OLD_NET9	NUMBER	30	4	Y
ZINK_OLD_TAX9	NUMBER	30	4	Y
ZINK_ZTXC_ID0	NUMBER	30		Y
ZINK_NET0	NUMBER	30	4	Y
ZINK_TAX0	NUMBER	30	4	Y
ZINK_ZTXC_ID1	NUMBER	30		Y
ZINK_NET1	NUMBER	30	4	Y
ZINK_TAX1	NUMBER	30	4	Y
ZINK_ZTXC_ID2	NUMBER	30		Y
ZINK_NET2	NUMBER	30	4	Y
ZINK_TAX2	NUMBER	30	4	Y
ZINK_ZTXC_ID3	NUMBER	30		Y
ZINK_NET3	NUMBER	30	4	Y
ZINK_TAX3	NUMBER	30	4	Y
ZINK_ZTXC_ID4	NUMBER	30		Y
ZINK_NET4	NUMBER	30	4	Y
ZINK_TAX4	NUMBER	30	4	Y
ZINK_ZTXC_ID5	NUMBER	30		Y
ZINK_NET5	NUMBER	30	4	Y
ZINK_TAX5	NUMBER	30	4	Y
ZINK_ZTXC_ID6	NUMBER	30		Y
ZINK_NET6	NUMBER	30	4	Y
ZINK_TAX6	NUMBER	30	4	Y

### ZINK

Table for special polish invoice correction report

Field Name	Type	Length	Decimals	Not NULL
ZINK_ZTXC_ID7	NUMBER	30		Y
ZINK_NET7	NUMBER	30	4	Y
ZINK_TAX7	NUMBER	30	4	Y
ZINK_ZTXC_ID8	NUMBER	30		Y
ZINK_NET8	NUMBER	30	4	Y
ZINK_TAX8	NUMBER	30	4	Y
ZINK_ZTXC_ID9	NUMBER	30		Y
ZINK_NET9	NUMBER	30	4	Y
ZINK_TAX9	NUMBER	30	4	Y
ZINK_DATE	DATE			Y
ZINK_REASON	VARCHAR2	200		N

### ZINN

invoice number storage

Field Name	Type	Length	Decimals	Not NULL	
ZINN_ID	NUMBER	30		N	ZINN_ID identifies ZINN
ZINN_NAME	VARCHAR2	30		N	Description of numbering: CurrExchangeNumber= for currency exchange zfac numbers
ZINN_VALUE	VARCHAR2	60		Y	??
ZINN_STARTINGNUMBER	VARCHAR2	60		Y	Starting number of numbering
ZINN_LOCK	NUMBER	1		Y	The number stays locked until the print out is done. 1 = locked, null = unlocked.
ZINN_TYPE	NUMBER	2		N	1 = invoices, 2 = user definable number cycles, 3 = currency exchange (zfag_type 3), 4 = autonumber for booth telephone charges paid cash, 5 = City Ledger Number for ZINV_CITYLEDGERNUMBER, 6 = Information Folio, 7 = Simplified Invoice (Portugal), 8 = City Ledger Folio, 11 = autonumber zfag_type 1 (ar postings), 12 = autonumber zfag_type 2 (ar payments), 13 = void invoice, 14 = fattura (for italy), 15 = nota di credito (for Italy or credit note for Greece, Portugal or Spain), 16 = proforma, 17 = fattura and nota di credito (for italy), 18 = nota korekta (for poland), 19 = Egyptian AR Invoice, 20 = AR Payment Receipt, 21 = registration cards, 22 = Ticket BarCode, 23 = Contract Numbers, 31 = automatic fa numbers (zfac_autonumber), 32 = lost and found, 33 = police export, 34 = tourist export, 35 = jetweb interface, 36 = Voucher, 37 = membership numbers, 38 = AR Compressions, 40 = Portugal Manual Invoice, 41 = Portugal Manual Credit Note, 42 = Portugal Manual Void Invoice, 43 = Portugal Manual Simple Invoice, 44 = Manual City Ledger Invoice

### ZINN

invoice number storage

Field Name	Type	Length	Decimals	Not NULL	
ZINN_DEFAULT	NUMBER	1		Y	indicates which number cycle to be used if none is linked to the folio. 1 - default, 0 - not default
ZINN_RESEDATE	DATE			Y	If set, then the value will be reset to startingnumber on this date
ZINN_YEARLY	NUMBER	1		Y	1 - it will be reset every year on the month/day set in the resetdate field; 0 - will be reset once, only on the date marked in resetdate; 2 - it will be reset every month on the day set in the resetdate field

### ZINS

Portuguese Invoice Signatures

Field Name	Type	Length	Decimals	Not NULL	
ZINS_ID	NUMBER	30		N	
ZINS_ZINV_ID	NUMBER	30		Y	
ZINS_ZINN_ID	NUMBER	30		Y	
ZINS_NUMBER	VARCHAR2	60		Y	
ZINS_AMOUNT	NUMBER	30	4	Y	
ZINS_SIGNATURE	VARCHAR2	172		N	
ZINS_MANUALNUMBER	NUMBER	1		Y	
ZINS_KEYVERSION	VARCHAR2	40		Y	

### ZINV

invoices

Field Name	Type	Length	Decimals	Not NULL	
ZINV_ID	NUMBER	30		N	ZINV_ID identifies ZINV
ZINV_DATE	DATE			N	ZINV_DATE is of ZINV
ZINV_NUMBER	VARCHAR2	60		N	ZINV_NUMBER is of ZINV
ZINV_ZINN_ID	NUMBER	30		N	ZINV_ZINN_ID is of ZINV
ZINV_XCMS_ID	NUMBER	30		Y	ZINV_XCMS_ID is of ZINV
ZINV_ZFST_ID	NUMBER	30		Y	ZINV_ZFST_ID is of ZINV
ZINV_CITYLEDGER	NUMBER	1		Y	0=everything is paid 1=not paid yet(city ledger)
ZINV_ZWIN_ID	NUMBER	30		Y	ZINV_ZWIN_ID is of ZINV
ZINV_XADR_ID	NUMBER	30		Y	ZINV_XADR_ID is of ZINV
ZINV_CONTACT_XCMS_ID	NUMBER	30		Y	ZINV_CONTACT_XCMS_ID is of ZINV
ZINV_PRINTED	NUMBER	1		Y	0 = Not yet printed 1 = Printed 2 = Printing not successful
ZINV_PCDATE	DATE			Y	Exact pc date and time when folio was generated

### ZINV

invoices

Field Name	Type	Length	Decimals	Not NULL	
ZINV_ROLE	NUMBER	2		Y	0 or null = regular invoice   1 = Deposit Folio   2 = City Ledger Folio (not yet implemented)   3 = Credit Note, 31=Faktura Korekta (polish credit note)  10 = Fattura Riepilogativa (used for Italy)  4 - Egyptian A/R Invoice   5 - AR Ricevuta Fiscale   6 - Stored Info/Proforma Invoice
ZINV_VOID_ZINV_ID	NUMBER	30		Y	Internal id of voided invoice
ZINV_FISCALNUMBER	VARCHAR2	100		Y	Fiscal number retrieved from fiscal folio printer (i.e. used in Poland)
ZINV_CORRECTING_ZINV_ID	NUMBER	30		Y	Invoice has been corrected with a correction invoice, which id stored here. Used for Polish Faktura Korrekta und Italian Fattura
ZINV_CITYLEDGERNUMBER	VARCHAR2	60		Y	The city ledger folio number
ZINV_MANUALNUMBER	VARCHAR2	60		Y	
ZINV_FISCALINVOICE	NUMBER	1		Y	1 = Turkey e-invoice

### ZIPF

INTERFACE PROCESS LIST (STORES WHICH IFC IS INTERESTED IN THIS ZITR. AFTER IT HAS PROCESSED THE ZITR RECORD, ZIPF\_PROCESSED SHOULD BE FILLED WITH 1.)

Field Name	Type	Length	Decimals	Not NULL	
ZIPF_ID	NUMBER	30		N	ZIPF_ID identifies ZIPF
ZIPF_ZITR_ID	NUMBER	30		N	ZIPF_ZITR_ID is of ZIPF
ZIPF_PROCESSED	NUMBER	1		N	0 = NOT PROCESSED 1 = PROCESSED
ZIPF_ZITI_ID	NUMBER	30		N	

### ZIPH

COPIED INTERFACE PROCESS LIST FROM HISTORY (WE MOVE ZIPF RECORDS HERE WHEN ZITR IS MOVED TO ZIPT)

Field Name	Type	Length	Decimals	Not NULL	
ZIPH_ID	NUMBER	30		N	ZIPH_ID identifies ZIPH
ZIPH_ZIPT_ID	NUMBER	30		N	ZIPH_ZIPT_ID is of ZIPH
ZIPH_ZITI_ID	NUMBER	30		N	

### ZIPL

invoice print log

Field Name	Type	Length	Decimals	Not NULL	
ZIPL_ID	NUMBER	30		N	ZIPL_ID identifies ZIPL
ZIPL_TIME	DATE			N	ZIPL_TIME is of ZIPL
ZIPL_ZINV_ID	NUMBER	30		N	ZIPL_ZINV_ID is of ZIPL
ZIPL_ZINB_ID	NUMBER	30		Y	ZIPL_ZINB_ID is of ZIPL

### ZIPL

invoice print log

Field Name	Type	Length	Decimals	Not NULL	
ZIPL_COPIES	NUMBER	2		N	printed copies including original
ZIPL_PAPERLAYERS	NUMBER	2		N	number of layers of paper on matrix

### ZIPT

PROCESSED TRIGGERS (WE MOVE RECORDS THAT WERE PROCESSED BY EVERY INTERFACE HERE TO MAKE ZITR SMALLER BUT TO KEEP THE RECORDS)

Field Name	Type	Length	Decimals	Not NULL	
ZIPT_ID	NUMBER	30		N	ZIPT_ID identifies ZIPT
ZIPT_TABLENAME	VARCHAR2	4		N	ZIPT_TABLENAME is of ZIPT
ZIPT_TABLEID	NUMBER	30		Y	ZIPT_TABLEID is of ZIPT
ZIPT_TYPE	NUMBER	1		N	0 = NEW 1 = MODIFY 2 = DELETE
ZIPT_TIME	DATE			N	ZIPT_TIME is of ZIPT
ZIPT_MOVETIME	DATE			N	TIME WHEN RECORD WAS MOVED FROM ZITR TO ZIPT
ZIPT_FROMDATE	DATE			Y	ZIPT_FROMDATE is of ZIPT
ZIPT_TODATE	DATE			Y	ZIPT_TODATE is of ZIPT
ZIPT_TABLEID2	NUMBER	30		Y	
ZIPT_TNAME1	VARCHAR2	4		Y	
ZIPT_TNAME2	VARCHAR2	4		Y	
ZIPT_INFO	VARCHAR2	100		Y	

### ZITF

INTERFACE TRIGGER FIELDS

Field Name	Type	Length	Decimals	Not NULL	
ZITF_ID	NUMBER	30		N	ZITF_ID identifies ZITF
ZITF_FIELDNAME	VARCHAR2	30		N	ZITF_FIELDNAME is of ZITF
ZITF_ZITI_ID	NUMBER	30		Y	

### ZITI

Field Name	Type	Length	Decimals	Not NULL	
ZITI_ID	NUMBER	30		N	
ZITI_TYPE	NUMBER	2		N	see constantsandtypes.triggerinterfacetypes. in example 0=mmod interfaces
ZITI_INTERFACEID	NUMBER	30		Y	for mmod interfaces this is mmod_id.

### ZITR

Interface Triggers

Field Name	Type	Length	Decimals	Not NULL	
ZITR_ID	NUMBER	30		N	ZITR_ID identifies ZITR
ZITR_TABLENAME	VARCHAR2	4		N	ZITR_TABLENAME is of ZITR
ZITR_TABLEID	NUMBER	30		Y	ZITR_TABLEID is of ZITR
ZITR_TYPE	NUMBER	1		N	0 = NEW 1 = MODIFY 2 = DELETE
ZITR_TIME	DATE			N	ZITR_TIME is of ZITR
ZITR_FROMDATE	DATE			Y	ZITR_FROMDATE is of ZITR
ZITR_TODATE	DATE			Y	ZITR_TODATE is of ZITR
ZITR_TABLEID2	NUMBER	30		Y	
ZITR_TNAME1	VARCHAR2	4		Y	
ZITR_TNAME2	VARCHAR2	4		Y	
ZITR_INFO	VARCHAR2	100		Y	

### ZITS

INTERFACE TRIGGER SETUP (WHICH INTERFACE NEEDS WHICH TRIGGER)

Field Name	Type	Length	Decimals	Not NULL	
ZITS_ID	NUMBER	30		N	ZITS_ID identifies ZITS
ZITS_TABLENAME	VARCHAR2	4		N	TRIGGER TYPE THAT IS NEEDED FOR THE INTERFACE
ZITS_ZITI_ID	NUMBER	30		N	

### ZIXC

Interface dept.code/foreign currency link table (for minibar articles, Video, etc. not quoted in local currency)

Field Name	Type	Length	Decimals	Not NULL	
ZIXC_ID	NUMBER	30		N	Unique ID
ZIXC_ZDCO_ID	NUMBER	30		N	Link to department code
ZIXC_ZCUR_ID	NUMBER	30		N	Link to foreign currency
ZIXC_RATE_TYPE	NUMBER	1		Y	0-Rate, 1-Cash Rate, 2-RatecodeRate

### ZLOG

ZPOS Log

Field Name	Type	Length	Decimals	Not NULL	
ZLOG_ID	NUMBER	30		N	

### ZLOG

ZPOS Log

Field Name	Type	Length	Decimals	Not NULL	
ZLOG_ZPOS_ID	NUMBER	30		N	when moving posting the zpos_id is filled, but when deleting posting, the field is filled with the zpos_internalgroup_id
ZLOG_WPCA_ID	NUMBER	30		N	
ZLOG_XCED_ID	NUMBER	30		N	
ZLOG_PCDATE	DATE			N	
ZLOG_DATE	DATE			N	
ZLOG_TEXT	VARCHAR2	200		Y	
ZLOG_TYPE	NUMBER	2		Y	0-transfer, 1-negative posting, 2-posting split, 3-posting delete, 4-posting correction, 5-rebate posting, 6-posting adjustment, 7-Tax exemption, 8-Recalc Tax after Exemption
ZLOG_FROM_ZWIN_ID	NUMBER	30		Y	Needed for transfers: The source window
ZLOG_TO_ZWIN_ID	NUMBER	30		Y	Needed for transfers: The target window
ZLOG_2_ZPOS_ID	NUMBER	30		Y	used for rebates or adjustments
ZLOG_AMOUNT	NUMBER	30	4	Y	posting amount, used on posting deletion
ZLOG_ZDCO_ID	NUMBER	30		Y	posting dept code, used on posting deletion
ZLOG_ZCAS_ID	NUMBER	30		Y	cashier id

### ZLSM

Ledger Movement Log

Field Name	Type	Length	Decimals	Not NULL	
ZLSM_ID	NUMBER	30		N	ZLSM_ID identifies ZLSM
ZLSM_ZPOS_ID	NUMBER	30		N	ZLSM_ZPOS_ID is of ZLSM
ZLSM_DATE	DATE			N	ZLSM_DATE partly identifies ZLSM
ZLSM_FROMLEDGER	NUMBER	1		Y	ZLSM_FROMLEDGER is of ZLSM
ZLSM_TOLEDGER	NUMBER	1		Y	ZLSM_TOLEDGER is of ZLSM
ZLSM_TYPE	NUMBER	1		N	Type of ledger movement: 1-check in, 2-night audit, 3-Billing instruction

### ZMOV

Stores Posting Movement

Field Name	Type	Length	Decimals	Not NULL	
ZMOV_ID	NUMBER	30		N	ZMOV_ID identifies ZMOV
ZMOV_FROM_XCMS_ID	NUMBER	30		N	From Guest
ZMOV_TO_XCMS_ID	NUMBER	30		N	To Guest
ZMOV_ZPOS_ID	NUMBER	30		N	Link to ZPOS record

### ZMOV

Stores Posting Movement

Field Name	Type	Length	Decimals	Not NULL	
ZMOV_USER_XCMS_ID	NUMBER	30		N	User performed this move
ZMOV_FROM_ZWIN_ID	NUMBER	30		Y	ZMOV_FROM_ZWIN_ID is of ZMOV
ZMOV_TO_ZWIN_ID	NUMBER	30		Y	ZMOV_TO_ZWIN_ID is of ZMOV
ZMOV_TYPE	NUMBER	1		Y	Indicates the type of movement: 0-manual, 1-routing
ZMOV_TIME	DATE			Y	The actual time of the movement

### ZMUC

Table of ZMUC

Field Name	Type	Length	Decimals	Not NULL	
ZMUC_ID	NUMBER	30		N	ZMUC_ID identifies ZMUC
ZMUC_ZCAS_ID	NUMBER	30		N	Link to Cashier Definition Table
ZMUC_ZDCO_ID	NUMBER	30		N	Link to referncing Department Code, must be
ZMUC_STARTINGAMOUNT	NUMBER	30	4	N	payment record, either cash or foreign currency starting amount of this definition, must be >=0

### ZNCR

Nota correction details (Polish legal requirements)

Field Name	Type	Length	Decimals	Not NULL	
ZNCR_ID	NUMBER	30		N	
ZNCR_ZINB_ID	NUMBER	30		Y	
ZNCR_NUMBER	NUMBER	30		Y	
ZNCR_BEFORE	VARCHAR2	1000		Y	
ZNCR_AFTER	VARCHAR2	1000		Y	
ZNCR_REASON	VARCHAR2	200		Y	

### ZORG

Store for posting origination to ease translation in reports

Field Name	Type	Length	Decimals	Not NULL	
ZORG_ID	NUMBER	30		N	
ZORG_ZPOS_ID	NUMBER	30		N	
ZORG_ROLE	NUMBER	1		Y	1/Rate Code Posting (YRCH), 2/Article Posting (ZART), 3/Package Posting (YPAC), 4/Department Code Posting (ZDCO)
ZORG_TABLE_ID	NUMBER	30		Y	

## ZOTA

Configuration of Upload OTA spec based Availability messages

Field Name	Type	Length	Decimals	Not NULL	
ZOTA_ID	NUMBER	30		N	
ZOTA_NAME	VARCHAR2	30		N	
ZOTA_URL	VARCHAR2	120		Y	
ZOTA_YALG_ID	NUMBER	30		Y	
ZOTA_AGENTSINE	VARCHAR2	60		Y	
ZOTA_AGENTDUTYCODE	VARCHAR2	60		Y	
ZOTA_REQUESTORURL	VARCHAR2	60		Y	
ZOTA_REQUESTORTYPE	VARCHAR2	30		Y	
ZOTA_REQUESTORID	VARCHAR2	30		Y	
ZOTA_INACTIVE	NUMBER	1		Y	
ZOTA_OVERBOOKING	NUMBER	1		Y	
ZOTA_TENTATIVE	NUMBER	1		Y	
ZOTA_ZCNV_ID	NUMBER	30		Y	
ZOTA_BACKUP	NUMBER	1		Y	Activate the backup functionality
ZOTA_REQ_BACKUP	VARCHAR2	100		Y	Backup folder of request messages
ZOTA_RSP_BACKUP	VARCHAR2	100		Y	Backup folder of response messages
ZOTA_SYNC_INTERVAL	NUMBER	4		Y	Interval to check for trigger
ZOTA_HOTELCODE	VARCHAR2	30		Y	Hotel Code to identify correct hotel
ZOTA_WPSS_ID	NUMBER	30		Y	Id of used profile match settings
ZOTA_VENDOR_ID	VARCHAR2	20		Y	Vendor name used for identification
ZOTA_REINSTATE	NUMBER	1		Y	Indicates whether reinstate functionality is supported
ZOTA_THRESHOLD	NUMBER	1		Y	indicates whether room type threshild should be considered for inventory upload
ZOTA_USE_RTFORRCAVAIL	NUMBER	1		Y	indicates whether room types should be sent also for rate availability
ZOTA_HTTP_USER	VARCHAR2	30		Y	http authentication user
ZOTA_HTTP_PWD	VARCHAR2	30		Y	http authentication password
ZOTA_RESOLVE_TIMEOUT	NUMBER	6		Y	timeout setting for URL resolve
ZOTA_CONNECT_TIMEOUT	NUMBER	6		Y	timeout setting for URL connect
ZOTA_SEND_TIMEOUT	NUMBER	6		Y	timeout setting for http send
ZOTA_RECEIVE_TIMEOUT	NUMBER	6		Y	timeout setting for http receive
ZOTA_USE_NETRATES	NUMBER	1		Y	Indicates whether net or gross rates are used
ZOTA_USE_TABLERESERVATION	NUMBER	1		Y	
ZOTA_USE_RR_FROM_RC	NUMBER	1		Y	Indicates whether we upload minlos/maxlos from rate code if ravl indicates open
ZOTA_RESEND	NUMBER	2		Y	number of resend tries. 0 = infinity (til successfull)

### ZOTA

Configuration of Upload OTA spec based Availability messages

Field Name	Type	Length	Decimals	Not NULL	
ZOTA_RATE_DAYS_IN_ADVANCE	NUMBER	4		Y	Number of days in advance for rate and rate restriction upload. CRS determines this value
ZOTA_INV_DAYS_IN_ADVANCE	NUMBER	4		Y	Number of days in advance for inventory upload. CRS determines this value
ZOTA_USE_RATELEVEL_RESTRICTION	NUMBER	1		Y	indicates whether rate level restrictions are used
ZOTA_UPLOAD_WEEKEND_RATES	NUMBER	1		Y	indicates whether we also upload weekend rates
ZOTA_UPLOAD_CHILDREN_RATES	NUMBER	1		Y	indicates whether we also upload children rates
ZOTA_UPLOAD_ALL_RES	NUMBER	1		Y	Indicates whether all reservations or only the one of the OTA XML will be uploaded
ZOTA_UPLOAD_ONLY_DEFAULT_RATE	NUMBER	1		Y	indicates whether only the default rate will be loaded or all rates
ZOTA_DOWNLOAD_RES	NUMBER	1		Y	indicates whether XML OTA downloads reservation. Configurable on config screen
ZOTA_UPLOAD_ALL_RT	NUMBER	1		Y	Upload for all room types availability with 0, if house availability = 0

### ZPCF

Additional Fields to ZPOS

Field Name	Type	Length	Decimals	Not NULL	
ZPCF_ID	NUMBER	30		N	Unique Id
ZPCF_ZPOS_ID	NUMBER	30		N	Links to posting record
ZPCF_CUSTOMORIGINATORNAME	VARCHAR2	121		Y	Guest Name of Originator

### ZPCS

petty cash configuration

Field Name	Type	Length	Decimals	Not NULL	
ZPCS_ID	NUMBER	30		N	unique id
ZPCS_SHORTDESC	VARCHAR2	3		N	short description of the petty cash account
ZPCS_LONGDESC	VARCHAR2	30		N	description of the petty cash account
ZPCS_INACTIVE	NUMBER	1		N	0 - active   1 - inactive
ZPCS_DEFAULT_ZDCO_ID	NUMBER	30		N	default department code to post on
ZPCS_MOVEMENT_ZDCO_ID	NUMBER	30		N	department code to post the negative counterpart on
ZPCS_DEFAULT_XCMS_ID	NUMBER	30		N	default customer for fas created automatically for petty cash transactions

### ZPFL

petty cash configuration, fa link

Field Name	Type	Length	Decimals	Not NULL	
ZPFL_ID	NUMBER	30		N	unique id

### ZPFL

petty cash configuration, fa link

Field Name	Type	Length	Decimals	Not NULL	
ZPFL_ZPCS_ID	NUMBER	30		N	petty cash account id
ZPFL_ZPOS_ID	NUMBER	30		N	financial account id

### ZPI2

link between postings and saved information/proforma invoices

Field Name	Type	Length	Decimals	Not NULL	
ZPI2_ID	NUMBER	30		N	
ZPI2_ZINV_ID	NUMBER	30		N	
ZPI2_ZPOS_ID	NUMBER	30		Y	
ZPI2_ZPO2_ID	NUMBER	30		Y	

### ZPIL

link between postings and invoice (sometimes we reprint folios and one posting belongs to two invoices)

Field Name	Type	Length	Decimals	Not NULL	
ZPIL_ID	NUMBER	30		N	ZPIL_ID identifies ZPIL
ZPIL_ZINV_ID	NUMBER	30		N	ZPIL_ZINV_ID is of ZPIL
ZPIL_ZPOS_ID	NUMBER	30		N	ZPIL_ZPOS_ID is of ZPIL

### ZPO2

Storage for removed postings - used with the Parameter Polish Faktura Korekta

Field Name	Type	Length	Decimals	Not NULL	
ZPO2_ID	NUMBER	30		N	Unique identifier of zpo2
ZPO2_XCMS_ID	NUMBER	30		N	Link to Customer
ZPO2_YRES_ID	NUMBER	30		Y	Link to reservation Not {not null} for ZFAC postings
ZPO2_ZFAC_ID	NUMBER	30		Y	zpo2_ZFAC_ID is of zpo2
ZPO2_ZDCO_ID	NUMBER	30		N	Link to Department Code
ZPO2_ZDC2_ID	NUMBER	30		Y	zpo2_ZDC2_ID is of zpo2
ZPO2_UNITPRICE	NUMBER	30	4	N	Unit Price must be multiplied with zpo2_QUANTITY
ZPO2_QUANTITY	NUMBER	10		N	zpo2_QUANTITY is of zpo2
ZPO2_DESCRIPT	VARCHAR2	30		N	Description, usually taken from Department Code description. Can be overwritten manually.
ZPO2_POSTDATE	DATE			N	Posting date (Fidelio date)
ZPO2_PCDATE	DATE			N	PC Date

### ZPO2

Storage for removed postings - used with the Parameter Polish Faktura Korekta

Field Name	Type	Length	Decimals	Not NULL	Description
ZPO2_THIRDPARTYDATE	DATE			Y	zpo2_THIRDPARTYDATE is of zpo2
ZPO2_ZCUR_ID	NUMBER	30		Y	Link to Currency Table
ZPO2_EXCHANGERATE	NUMBER	30	4	Y	Exchange rate value
ZPO2_FOREIGNPRICE	NUMBER	30	4	Y	Posted Amount in ForeignPrice
ZPO2_ZCAS_ID	NUMBER	30		N	Cashier Number
ZPO2_USER_XCMS_ID	NUMBER	30		Y	UserId of the user who charged this posting.
ZPO2_ORIGINATED_XCMS_ID	NUMBER	30		Y	zpo2_ORIGINATED_XCMS_ID is of zpo2
ZPO2_ORIGINATED_YRES_ID	NUMBER	30		Y	zpo2_ORIGINATED_YRES_ID is of zpo2
ZPO2_ORIGINATED_ZFAC_ID	NUMBER	30		Y	zpo2_ORIGINATED_ZFAC_ID is of zpo2
ZPO2_ZARR_ID	NUMBER	30		Y	zpo2_ZARR_ID is of zpo2
ZPO2_COMMENT	VARCHAR2	60		Y	zpo2_COMMENT is of zpo2
ZPO2_ZART_ID	NUMBER	30		Y	zpo2_ZART_ID is of zpo2
ZPO2_COVERS	NUMBER	4		Y	number of restaurant covers (people)
ZPO2_TAXLINK_ID	NUMBER	30		N	Link Id between related records
ZPO2_SUMUPID	NUMBER	30		Y	zpo2_SUMUPID is the link of several postings from rate codes which are set up as weekly or monthly
ZPO2_INTERNALSPLIT_ZPO2_ID	NUMBER	30		N	ID of main zpo2 record for internal split, as for rate code splitting.
ZPO2_CDT	NUMBER	1		N	1 = debit 2 = tax 5 = credit (payment)
ZPO2_PHONENR	VARCHAR2	30		Y	Dialed Phone Number, duplicated information for invoice printing, actual link to call history is handled differently
ZPO2_MANUALSPLIT_ID	NUMBER	30		Y	zpo2_MANUALSPLIT_ID is of zpo2
ZPO2_PAIDOUT	NUMBER	1		Y	Flag for paid out posting. 1 = true, anything else = false
ZPO2_ZWIN_ID	NUMBER	30		N	zpo2_ZWIN_ID is of zpo2
ZPO2_ZALL_ID	NUMBER	30		Y	zpo2_ZALL_ID is of zpo2
ZPO2_IHST_ID	NUMBER	30		Y	Link to interface call history table
ZPO2_LEDGERSTATUS	NUMBER	1		N	0= posting made in the guest ledger; 1= posting made in the PreArrival ledger; 2= posting made in the PreArrival ledger and transferred to the guest ledger (at check-in for reservations, manually for fin. acc.); 3= posting made in the city ledger (accounts receivable) 4=internal negative payment when city ledger gets paid 5=advance posting 6=when advance posting is moved to guest ledger 7=when advance posting is moved to pre arrival Ledger
ZPO2_SUMUPAMOUNT	NUMBER	30	4	Y	summed up amount from zpo2_INTERNALSPLIT_ID + Taxes of internal Splits + Allowances. Speeds up invoice printing.
ZPO2_PACK_LOSS	NUMBER	1		Y	3 = allowance consumption 2 = revenue between value and allowance (overage) 1 = LOSS (For MINUS loss Postings on package allowances. These records are not taken in calculation for remaining allowance. 4 = revenue exceeding the allowance (allowance) 5 = package profit

### ZPO2

Storage for removed postings - used with the Parameter Polish Faktura Korekta

Field Name	Type	Length	Decimals	Not NULL	
ZPO2_POSCHECK_NR	VARCHAR2	20		Y	POS Check Number
ZPO2_GROSSUNITPRICE	NUMBER	30	4	Y	zpo2_GROSSUNITPRICE is of zpo2
ZPO2_GROSSFOREIGNPRICE	NUMBER	30	4	Y	zpo2_GROSSFOREIGNPRICE is of zpo2
ZPO2_ZCHE_ID	NUMBER	30		Y	Link to ZCHE Guest Check
ZPO2_DEPOSIT	NUMBER	1		Y	Filled if posted as revenue or tax department on deposit payment. Implemented for Parameter 'Latin American Deposit Handling' for advance postings
ZPO2_ORGDATE	DATE			Y	
ZPO2_HIDDEN	NUMBER	1		Y	0 - normal; 1 - do not show on screen; 2 - do not show on reports; 3 - do not show anywhere
ZPO2_FOREIGNSUMUPAMOUNT	NUMBER	30	4	Y	summed up amount in foreign currency from zpo2_INTERNALSPLIT_ID + Taxes of internal Splits + Allowances. Speeds up invoice printing.
ZPO2_PROFORMA	NUMBER	30		Y	PROFORMA INVOICE NUMBER
ZPO2_REVERSEEXCHRATE	NUMBER	1		Y	0 means amount*exchrates=foreignamount. 1 means amount=foreignamount/exchrates. in fact it tells in which direction the exchange rate was entered by the user
ZPO2_ZTCD_ID	NUMBER	30		Y	link to the corresponding tax detail
ZPO2_GUEST_XCMS_ID	NUMBER	30		Y	
ZPO2_INTERNALGROUP_ID	NUMBER	30		Y	Internally used grouping to ease reading and working with excluded taxes
ZPO2_NOREPRINT	NUMBER	1		Y	0-Posting is not on a valid folio   1-The posting is printed on an invoice   2-Posting is on a void invoice
ZPO2_ZUDD_ID	NUMBER	30		Y	
ZPO2_MANUALPOST	NUMBER	1		Y	1-posting was made manually

### ZPOS

Price / Amount of the posting

Field Name	Type	Length	Decimals	Not NULL	
ZPOS_ID	NUMBER	30		N	Unique identifier of ZPOS
ZPOS_XCMS_ID	NUMBER	30		N	Link to Customer
ZPOS_YRES_ID	NUMBER	30		Y	Link to reservation Not {not null} for ZFAC postings
ZPOS_ZFAC_ID	NUMBER	30		Y	ZPOS_ZFAC_ID is of ZPOS
ZPOS_ZDCO_ID	NUMBER	30		N	Link to Department Code
ZPOS_ZDC2_ID	NUMBER	30		Y	ZPOS_ZDC2_ID is of ZPOS
ZPOS_UNITPRICE	NUMBER	30	4	N	Unit Price must be multiplied with ZPOS_QUANTITY
ZPOS_QUANTITY	NUMBER	10		N	ZPOS_QUANTITY is of ZPOS
ZPOS_DESCRIPT	VARCHAR2	30		N	Description, usually taken from Department Code description. Can be overwritten manually.
ZPOS_POSTDATE	DATE			N	Posting date (Fidelio date)
ZPOS_PCDATE	DATE			N	PC Date

### ZPOS

Price / Amount of the posting

Field Name	Type	Length	Decimals	Not NULL	Description
ZPOS_THIRDPARTYDATE	DATE			Y	ZPOS_THIRDPARTYDATE is of ZPOS
ZPOS_ZCUR_ID	NUMBER	30		Y	Link to Currency Table
ZPOS_EXCHANGERATE	NUMBER	30	4	Y	Exchange rate value
ZPOS_FOREIGNPRICE	NUMBER	30	4	Y	Posted Amount in ForeignPrice
ZPOS_ZCAS_ID	NUMBER	30		N	Cashier Number
ZPOS_USER_XCMS_ID	NUMBER	30		Y	UserId of the user who charged this posting.
ZPOS_ORIGINATED_XCMS_ID	NUMBER	30		Y	ZPOS_ORIGINATED_XCMS_ID is of ZPOS
ZPOS_ORIGINATED_YRES_ID	NUMBER	30		Y	ZPOS_ORIGINATED_YRES_ID is of ZPOS
ZPOS_ORIGINATED_ZFAC_ID	NUMBER	30		Y	ZPOS_ORIGINATED_ZFAC_ID is of ZPOS
ZPOS_ZARR_ID	NUMBER	30		Y	ZPOS_ZARR_ID is of ZPOS
ZPOS_COMMENT	VARCHAR2	60		Y	ZPOS_COMMENT is of ZPOS
ZPOS_ZART_ID	NUMBER	30		Y	ZPOS_ZART_ID is of ZPOS
ZPOS_COVERS	NUMBER	4		Y	number of restaurant covers (people)
ZPOS_TAXLINK_ID	NUMBER	30		N	Link Id between related records
ZPOS_SUMUPID	NUMBER	30		Y	ZPOS_SUMUPID is the link of several postings from rate codes which are set up as weekly or monthly
ZPOS_INTERNALSPLIT_ZPOS_ID	NUMBER	30		N	ID of main ZPOS record for internal split, as for rate code splitting.
ZPOS_CDT	NUMBER	1		N	1 = debit 2 = tax 5 = credit (payment)
ZPOS_PHONENR	VARCHAR2	30		Y	Dialed Phone Number, duplicated information for invoice printing, actual link to call history is handled differently
ZPOS_MANUALSPLIT_ID	NUMBER	30		Y	ZPOS_MANUALSPLIT_ID is of ZPOS
ZPOS_PAIDOUT	NUMBER	1		Y	Flag for paid out posting. 1 = true, anything else = false
ZPOS_ZWIN_ID	NUMBER	30		N	ZPOS_ZWIN_ID is of ZPOS
ZPOS_ZALL_ID	NUMBER	30		Y	ZPOS_ZALL_ID is of ZPOS
ZPOS_IHST_ID	NUMBER	30		Y	Link to interface call history table
ZPOS_LEDGERSTATUS	NUMBER	1		N	0= posting made in the guest ledger; 1= posting made in the PreArrival ledger; 2= posting made in the PreArrival ledger and transferred to the guest ledger (at check-in for reservations, manually for fin. acc.); 3= adjustment and payment posting made in the city ledger (accounts receivable); 4= internal negative payment when city ledger gets paid (accounts receivable); 5= advance posting; 6= when advance posting is moved to guest ledger; summed up amount from ZPOS_INTERNALSPLIT_ID + Taxes of internal Splits + Allowances. Speeds up invoice printing.
ZPOS_SUMUPAMOUNT	NUMBER	30	4	Y	
ZPOS_PACK_LOSS	NUMBER	1		Y	3 = allowance consumption 2 = revenue between value and allowance (overage) 1 = LOSS (For MINUS loss Postings on package allowances. These records are not taken in calculation for remaining allowance. 4 = revenue exceeding the allowance (allowance) 5 = package profit

### ZPOS

Price / Amount of the posting

Field Name	Type	Length	Decimals	Not NULL	
ZPOS_POSCHECK_NR	VARCHAR2	20		Y	POS Check Number
ZPOS_GROSSUNITPRICE	NUMBER	30	4	Y	ZPOS_GROSSUNITPRICE is of ZPOS
ZPOS_GROSSFOREIGNPRICE	NUMBER	30	4	Y	ZPOS_GROSSFOREIGNPRICE is of ZPOS
ZPOS_ZCHE_ID	NUMBER	30		Y	Link to ZCHE Guest Check
ZPOS_DEPOSIT	NUMBER	1		Y	Filled if posted as revenue or tax department on deposit payment. Implemented for Parameter 'Latin American Deposit Handling' for advance postings
ZPOS_ORGDATE	DATE			Y	
ZPOS_HIDDEN	NUMBER	1		Y	0 - normal; 1 - do not show on screen; 2 - do not show on reports; 3 - do not show anywhere
ZPOS_FOREIGNSUMUPAMOUNT	NUMBER	30	4	Y	summed up amount in foreign currency from ZPOS_INTERNALSPLIT_ID + Taxes of internal Splits + Allowances. Speeds up invoice printing.
ZPOS_PROFORMA	NUMBER	30		Y	proforma invoice number
ZPOS_REVERSEEXCHRATE	NUMBER	1		Y	0 means amount*exchrates=foreignamount. 1 means amount=foreignamount/exchrates. in fact it tells in which direction the exchange rate was entered by the user
ZPOS_ZTCD_ID	NUMBER	30		Y	link to the corresponding tax detail
ZPOS_GUEST_XCMS_ID	NUMBER	30		Y	Multi Guest Link to XCMS
ZPOS_INTERNALGROUP_ID	NUMBER	30		Y	Internally used grouping to ease reading and working with excluded taxes
ZPOS_MANUALPOST	NUMBER	2		Y	1-posting was made manually; 5 - it is a cancelled advance posting (hijacked this field to avoid adding a new); 10 - the posting is a tax exemption correction
ZPOS_ZUDD_ID	NUMBER	30		Y	Link to user definable folio description table
ZPOS_NOREPRINT	NUMBER	1		Y	0-Posting is not on a valid folio   1-The posting is printed on an invoice   2-Posting is on a void invoice   3-Posting has been voided
ZPOS_INVOICEDATE	DATE			Y	date to use in israeli trial balance calculation
ZPOS_POSCHECK_UID	VARCHAR2	40		Y	UID for guest checks
ZPOS_XCAC_ID	NUMBER	30		Y	ID of child age category in case multi guest and rate amount per guest is used, for reporting purpose only
ZPOS_DEPOSIT_ZINV_ID	NUMBER	30		Y	Reference to ZINV_ID of the deposit invoice (using enhanced deposit handling)
ZPOS_WPCA_ID	NUMBER	30		Y	
ZPOS_RESERVATIONDAY	DATE			Y	Date of daily postings. Ie When all nights of a reservation are posted in advance, this stores each night's date.

### ZQUE

queue for OTA XML interface messages not sent as of issues with URL

Field Name	Type	Length	Decimals	Not NULL	
ZQUE_ID	NUMBER	30		N	
ZQUE_ZOTA_ID	NUMBER	30		N	
ZQUE_MESSAGE	CLOB			Y	

### ZQUE

queue for OTA XML interface messages not sent as of issues with URL

Field Name	Type	Length	Decimals	Not NULL
ZQUE_RESEND	NUMBER	2		N

### ZRCC

Rebate Card Config for XMTY

Field Name	Type	Length	Decimals	Not NULL	
ZRCC_ID	NUMBER	30		N	SAME AS XMTY_ID
ZRCC_FREENIGHTS	NUMBER	4		N	ZRCC_FREENIGHTS is of ZRCC
ZRCC_FREEADULTS	NUMBER	2		Y	HOW MANY ADULTS CAN STAY AT MAXIMUM FOR THOSE DAYS FOR FREE
ZRCC_PRICE	NUMBER	30	4	Y	NULL MEANS PRICE COMES FROM ZFAG PRICE CONFIG
ZRCC_PRICE_ZDCO_ID	NUMBER	30	4	Y	ZRCC_PRICE_ZDCO_ID is of ZRCC
ZRCC_LENGTHOFVALIDITY	NUMBER	4		N	ZRCC_LENGTHOFVALIDITY is of ZRCC
ZRCC_VALIDITYTYPE	NUMBER	1		N	0=YEARS 1=MONTHS 2=WEEKS 3=DAYS
ZRCC_ZFAG_ID	NUMBER	30		N	ZRCC_ZFAG_ID is of ZRCC
ZRCC_TRANSFERABLE	NUMBER	1		N	0=CAN NOT GIVE FREE NIGHTS CREATED BY THIS CARD TO OTHER PERSON 1=CAN
ZRCC_ACCOUNTCLOSERHYTHM	NUMBER	1		N	0=NOTHING 1=CLOSE AND REOPEN ZFAC AT THE END OF CALENDAR MONTH MONTH 2=MONTH LENGTH
ZRCC_ACCOUNTCLOSENUMBER	NUMBER	1		N	ZRCC_ACCOUNTCLOSENUMBER is of ZRCC
ZRCC_PAYMENT_ZDCO_ID	NUMBER	30		Y	ZRCC_PAYMENT_ZDCO_ID is of ZRCC
ZRCC_ZCRL_ID	NUMBER	30		Y	ZRCC_ZCRL_ID is of ZRCC
ZRCC_CREDITLIMIT	NUMBER	30	4	Y	ZRCC_CREDITLIMIT is of ZRCC
ZRCC_EXPIRYATENDOFCALENDAR UNIT	NUMBER	1		Y	

### ZRCR

Rebate Card Rebate Config

Field Name	Type	Length	Decimals	Not NULL	
ZRCR_ID	NUMBER	30		N	ZRCR_ID identifies ZRCR
ZRCR_XMTY_ID	NUMBER	30		Y	ZRCR_XMTY_ID is of ZRCR
ZRCR_ZDCO_ID	NUMBER	30		N	ZRCR_ZDCO_ID is of ZRCR
ZRCR_REBATE	NUMBER	7	4	N	PERCENTAGE DISCOUNT
ZRCR_REBATETOGETHER	NUMBER	7	4	N	PERCENTAGE DISCOUNT IF GUEST HAS OTHER REBATE CARDS FOR THIS DEPT TOO
ZRCR_MAXNOOFREBATE	NUMBER	3		N	HOW MANY TIMES WE GIVE THE REBATE. OVER THIS NUMBER THEY GET NO REBATE. 0= INFINITE
ZRCR_REBATE_ZDCO_ID	NUMBER	30		N	WHERE TO POST REBATE POSTINGS (THOSE NEGATIVE VALUES SUBSTRACTED FROM THE POSTING)
ZRCR_ZRDF_ID	NUMBER	30		Y	

## ZRCR

Rebate Card Rebate Config

Field Name	Type	Length	Decimals	Not NULL
ZRCR_FLATAMOUNT	NUMBER	30	4	Y

## ZRDF

Rebate Configuration (without cards)

Field Name	Type	Length	Decimals	Not NULL	
ZRDF_ID	NUMBER	30		N	
ZRDF_SHORTDESC	VARCHAR2	10		N	
ZRDF_LONGDESC	VARCHAR2	30		N	
ZRDF_INACTIVE	NUMBER	1		N	
ZRDF_DISPLORDER	NUMBER	4		N	
ZRDF_FROMTIME	DATE			Y	
ZRDF_UNTILTIME	DATE			Y	
ZRDF_WCOL_ID	NUMBER	30		Y	
ZRDF_BARCODE	VARCHAR2	30		Y	String associated with barcode (full string will contain global rebate prefix)
ZRDF_BOOKING	NUMBER	1		Y	Valid for bookings
ZRDF_RESERVATION	NUMBER	1		Y	Valid for reservations

## ZRDL

Link between Rebate Configuration and FA/Res

Field Name	Type	Length	Decimals	Not NULL	
ZRDL_ID	NUMBER	30		N	
ZRDL_YRES_ID	NUMBER	30		Y	
ZRDL_ZFAC_ID	NUMBER	30		Y	
ZRDL_ZRDF_ID	NUMBER	30		N	
ZRDL_INACTIVE	NUMBER	1		Y	
ZRDL_XCMS_ID	NUMBER	30		Y	Link to CCM Booking
ZRDL_YBOM_ID	NUMBER	30		Y	

## ZRDP

Link between Rebate Configuration and Postings

Field Name	Type	Length	Decimals	Not NULL
ZRDP_ID	NUMBER	30		N

### ZRDP

Link between Rebate Configuration and Postings

Field Name	Type	Length	Decimals	Not NULL	
ZRDP_REBATED_ZPOS_ID	NUMBER	30		N	
ZRDP_REBATING_ZPOS_ID	NUMBER	30		N	
ZRDP_ZRDF_ID	NUMBER	30		N	
ZRDP_REBATEORIGIN	NUMBER	1		Y	0 = not defined, 1 = day rebate, 2 = account rebate, 3 = window rebate

### ZRDS

Field Name	Type	Length	Decimals	Not NULL	
ZRDS_ID	NUMBER	30		N	Unique Id
ZRDS_YCEV_ID	NUMBER	30		N	Link to the calendar event
ZRDS_FROMDATE	DATE			Y	
ZRDS_TODATE	DATE			Y	
ZRDS_ZRDF_ID	NUMBER	30		N	

### ZRLZ

Rebate counter posting log table

Field Name	Type	Length	Decimals	Not NULL	
ZRLZ_ID	NUMBER	30		N	Unique ID
ZRLZ_ZPOS_ID	NUMBER	30		N	Link to the posting
ZRLZ_ZRZC_ID	NUMBER	30		N	Link to the counter header

### ZRZC

Rebate counter table

Field Name	Type	Length	Decimals	Not NULL	
ZRZC_ID	NUMBER	30		N	Unique ID
ZRZC_ZRCR_ID	NUMBER	30		N	Link to the rebate card setup
ZRZC_AUTOMATIC_COUNTER	NUMBER	5		N	Counts the usage of rebates, stores the usage of the original number of rebates from setup (zrcr_maxnoofrebate)
ZRZC_MANUAL_COUNTER	NUMBER	5		N	In case the user wants to manually override the usage info, then it gets stored here
ZRZC_XMNR_ID	NUMBER	30		N	Link to the particular customer card
ZRZC_XCMS_ID	NUMBER	30		N	Link to the customer using the card

## ZTAA

Transponder arrangement adult rates

Field Name	Type	Length	Decimals	Not NULL	
ZTAA_ID	NUMBER	30		N	Unique Identifier
ZTAA_ZTSA_ID	NUMBER	30		N	Link to Template for Group Arrangement
ZTAA_XCLR_ID	NUMBER	30		N	Link to Individual category
ZTAA_ZCRL_ID	NUMBER	30		Y	Link to credit limits
ZTAA_FROMTIME	DATE			N	Valid from Date
ZTAA_TOTIME	DATE			N	Valid until Date
ZTAA_VALUE	NUMBER	30	4	N	Rate
ZTAA_SECONDARY_VALUE	NUMBER	30	4	Y	
ZTAA_PTIK_ID	NUMBER	30		Y	

## ZTAK

Transponder arrangement kids rates

Field Name	Type	Length	Decimals	Not NULL	
ZTAK_ID	NUMBER	30		N	Unique Identifier
ZTAK_ZTSA_ID	NUMBER	30		N	Link to Template for Group Arrangement
ZTAK_XCAC_ID	NUMBER	30		N	Link to Child age category
ZTAK_ZCRL_ID	NUMBER	30		Y	Link to credit limits
ZTAK_FROMTIME	DATE			N	Valid from Date
ZTAK_TOTIME	DATE			N	Valid until Date
ZTAK_VALUE	NUMBER	30	4	N	Rate
ZTAK_SECONDARY_VALUE	NUMBER	30	4	Y	
ZTAK_PTIK_ID	NUMBER	30		Y	

## ZTAP

Field Name	Type	Length	Decimals	Not NULL	
ZTAP_ID	NUMBER	30		N	
ZTAP_ZTAA_ID	NUMBER	30		N	
ZTAP_ZTAK_ID	NUMBER	30		N	
ZTAP_CUSTOMER_ZDCO_ID	NUMBER	30		Y	
ZTAP_MASTER_ZDCO_ID	NUMBER	30		Y	
ZTAP_VALUE	NUMBER	30	4	N	

### ZTCD

tax configuration detail

Field Name	Type	Length	Decimals	Not NULL	
ZTCD_ID	NUMBER	30		N	ZTCD_ID identifies ZTCD
ZTCD_ZTXC_ID	NUMBER	30		N	Link to Taxes Description
ZTCD_POSTTO_ZDCO_ID	NUMBER	30		N	Link to Taxes Department Code Number
ZTCD_UDF	VARCHAR2	200		N	ZTCD_UDF is of ZTCD
ZTCD_ORDER	NUMBER	3		N	order of calculation
ZTCD_VALIDFROM	DATE			N	ZTCD_VALIDFROM is of ZTCD
ZTCD_VALIDUNTIL	DATE			N	ZTCD_VALIDUNTIL is of ZTCD
ZTCD_INCLUDE	NUMBER	1		Y	ZTCD_INCLUDE is of ZTCD
ZTCD_NAME	VARCHAR2	30		Y	ZTCD_NAME is of ZTCD
ZTCD_PRINTSEPARATE	NUMBER	1		Y	1 = Shows separate on billing screen and invoice
ZTCD_POSTZERO	NUMBER	1		Y	1 = post even if calculated tax amount is 0
ZTCD_IGNORE_NA_CHECK	NUMBER	1		Y	1. Ignore from Night audit expiry check routine

### ZTDR

Indian Luxury Tax / Link tax detail to rate codes

Field Name	Type	Length	Decimals	Not NULL	
ZTDR_ID	NUMBER	30		N	
ZTDR_ZTCD_ID	NUMBER	30		Y	
ZTDR_YRCH_ID	NUMBER	30		Y	

### ZTIS

Indian Luxury Tax / SLAB configuration

Field Name	Type	Length	Decimals	Not NULL	
ZTIS_ID	NUMBER	30		N	
ZTIS_ZTCD_ID	NUMBER	30		Y	Link to tax detail
ZTIS_ORDER	NUMBER	4		Y	The order number associated with this amount range
ZTIS_FROMAMOUNT	NUMBER	30	4	Y	The amount range's lower limit, inclusive
ZTIS_TOAMOUNT	NUMBER	30	4	Y	The amount range's upper limit, exclusive
ZTIS_UDF	VARCHAR2	200		Y	The tax formula associated with this amount range

## ZTIV

Log for printeg tour operator invoices and link to the reservations

Field Name	Type	Length	Decimals	Not NULL	
ZTIV_ID	NUMBER	30		N	Unique Identifier for ZTIV
ZTIV_YRES_ID	NUMBER	30		N	Link to Reservation
ZTIV_TARGET_ZFAC_ID	NUMBER	30		Y	Link to the Target FA
ZTIV_DATE	DATE			Y	DAte of creating the room charges

## ZTRA

Transponder Table (Tropical Island)

Field Name	Type	Length	Decimals	Not NULL	
ZTRA_ID	NUMBER	30		N	Unique ID
ZTRA_NUMBER	VARCHAR2	30		N	Transponder Number
ZTRA_TABLENAME	VARCHAR2	4		Y	id of card type. ie xmnr_id
ZTRA_TABLEID	NUMBER	30		Y	ID of card type, i.e. xmnr_id
ZTRA_INVALID	NUMBER	1		Y	0 or null=valid 1= invalid
ZTRA_ZTRI_ID	NUMBER	30		Y	current invalidation record. all others are just history
ZTRA_LOCKERNUMBER	VARCHAR2	30		Y	

## ZTRC

Child age category link to Family templates

Field Name	Type	Length	Decimals	Not NULL	
ZTRC_ID	NUMBER	30		N	Unique ID
ZTRC_ZTRF_ID	NUMBER	30		N	Link to Family template
ZTRC_XCAC_ID	NUMBER	30		N	Link to Child age category
ZTRC_NUMBER	NUMBER	2		N	Number of members of this kind
ZTRC_ZCRL_ID	NUMBER	30		Y	Default credit limit
ZTRC_DEF_PTIK_ID	NUMBER	30		Y	

## ZTRF

Family creation templates for Transponder reading

Field Name	Type	Length	Decimals	Not NULL	
ZTRF_ID	NUMBER	30		N	Unique ID
ZTRF_SHORTDESC	VARCHAR2	30		N	Family template code
ZTRF_LONGDESC	VARCHAR2	30		N	Family template description

### ZTRF

Family creation templates for Transponder reading

Field Name	Type	Length	Decimals	Not NULL	
ZTRF_DEFAULT	NUMBER	1		Y	1-default   0-not default

### ZTRI

TRANSPONDER INVALIDATION RECORDS

Field Name	Type	Length	Decimals	Not NULL	
ZTRI_ID	NUMBER	30		N	ZTRI_ID identifies ZTRI
ZTRI_ZTRA_ID	NUMBER	30		N	ZTRI_ZTRA_ID is of ZTRI
ZTRI_TIME	DATE			N	ZTRI_TIME is of ZTRI
ZTRI_XCED_ID	NUMBER	30		N	ZTRI_XCED_ID is of ZTRI
ZTRI_REASON	VARCHAR2	2000		Y	ZTRI_REASON is of ZTRI
ZTRI_VALIDINVALID	NUMBER	1		N	0 = VALID 1 = INVALID

### ZTRM

Individual category link to Family templates

Field Name	Type	Length	Decimals	Not NULL	
ZTRM_ID	NUMBER	30		N	Unique ID
ZTRM_ZTRF_ID	NUMBER	30		N	Link to Family template
ZTRM_XCLR_ID	NUMBER	30		N	Link to Individual category
ZTRM_NUMBER	NUMBER	2		N	Number of members of this kind
ZTRM_ZCRL_ID	NUMBER	30		Y	Default credit limit
ZTRM_DEF_PTIK_ID	NUMBER	30		Y	

### ZTSA

Transponder Standard Arrangement for group creation

Field Name	Type	Length	Decimals	Not NULL	
ZTSA_ID	NUMBER	30		N	Unique Identifier
ZTSA_SHORTDESC	VARCHAR2	3		N	Transponder Standard Arrangement Code
ZTSA_LONGDESC	VARCHAR2	30		N	Transponder Standard Arrangement Description
ZTSA_ROLE	NUMBER	1		N	0 - No Posting will be done, 1 - Only one Posting for Revenue will be done direct on the FA (ZTSA_CUSTOMER_ZDCO_ID), 2 - All Members will get a negative Posting (ZTSA_CUSTOMER_ZDCO_ID) and a sum Postings will be done on the Master FA (ZTSA_MASTER_ZDCO_ID), 5 - Single Financial Account creation and Posting
ZTSA_CUSTOMER_ZDCO_ID	NUMBER	30		Y	Department Code for Posting direct to FA

### ZTSA

Transponder Standard Arrangement for group creation

Field Name	Type	Length	Decimals	Not NULL	
ZTSA_MASTER_ZDCO_ID	NUMBER	30		Y	Department Code for sum Posting for the Master FA
ZTSA_DEFAULT	NUMBER	1		Y	Default for Transponder Standard Arrangements
ZTSA_INACTIVE	NUMBER	1		Y	0 or null - Active 1 - Inactive
ZTSA_SECONDARY_ZDCO_ID	NUMBER	30		Y	
ZTSA_SECONDARY_MASTER_ZCO_ID	NUMBER	30		Y	

### ZTTL

Thai tax invoice table

Field Name	Type	Length	Decimals	Not NULL	
ZTTL_ID	NUMBER	30		N	
ZTTL_TYPE	VARCHAR2	2		N	
ZTTL_PAYM_ZPOS_ID	NUMBER	30		N	
ZTTL_ZINV_ID	NUMBER	30		Y	
ZTTL_TAXNUMBER	VARCHAR2	14		N	
ZTTL_TAXINVOICEDATE	DATE			Y	
ZTTL_TIMESTAMP	DATE			Y	
ZTTL_TAXALLOCATIONVAT	NUMBER	30	4	Y	
ZTTL_TAXALLOCATIONPROV	NUMBER	30	4	Y	
ZTTL_VATABLEAMOUNT	NUMBER	30	4	Y	
ZTTL_NONVATAMOUNT	NUMBER	30	4	Y	
ZTTL_AMOUNTBEFOREVAT	NUMBER	30	4	Y	

### ZTTP

Thai tax invoice payment to postings link table

Field Name	Type	Length	Decimals	Not NULL	
ZTTP_ID	NUMBER	30		N	
ZTTP_ZTTL_ID	NUMBER	30		N	
ZTTP_ZPOS_ID	NUMBER	30		N	

### ZTTX

Thai tax credit note link table

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

## ZTTX

Thai tax credit note link table

Field Name	Type	Length	Decimals	Not NULL	
ZTTX_ID	NUMBER	30		N	
ZTTX_ZTTL_ID	NUMBER	30		N	
ZTTX_CN_ZTTL_ID	NUMBER	30		N	The tax invoice's ID which is negated by the zttx_zttl_id tax invoice
ZTTX_TIMESTAMP	DATE			Y	
ZTTX_USER_XCMS_ID	NUMBER	30		N	

## ZTXC

tax configuration

Field Name	Type	Length	Decimals	Not NULL	
ZTXC_ID	NUMBER	30		N	ZTXC_ID identifies ZTXC
ZTXC_SHORTDESC	VARCHAR2	3		N	ZTXC_SHORTDESC is of ZTXC
ZTXC_LONGDESC	VARCHAR2	60		N	ZTXC_LONGDESC is of ZTXC
ZTXC_DISPLORDER	NUMBER	3		Y	ZTXC_DISPLORDER is of ZTXC
ZTXC_BOF_VATCODE	VARCHAR2	1		Y	Back Office Interface VAT Code
ZTXC_SFTX_ORDER	NUMBER	1		Y	A number between 0-9 indicating in which column this tax should appear in SFTX
ZTXC_CITYTAX	NUMBER	1		Y	1 - indicating that this tax is a city tax and should not be calculated into gross figures
ZTXC_BOF_DEFAULT_DEPOSIT	NUMBER	1		Y	Default tax code for deposit postings used for Back Office Interface, 1 = default, 0 or null = not default
ZTXC_TAX_EXEMPTION	NUMBER	1		Y	Flag for Italian tax exemption functionality

## ZTXT

Binary storage of cashiering receipts/ reports/ AR reminder and statements

Field Name	Type	Length	Decimals	Not NULL	
ZTXT_ID	NUMBER	30		N	Unique identifier
ZTXT_WRPT_ID	NUMBER	30		Y	Report used.
ZTXT_DATA	LONG RAW			Y	Binary storage of report/ receipt.
ZTXT_USER_XCMS_ID	NUMBER	30		Y	User ID
ZTXT_TYPE	NUMBER	2		Y	1 = cashier closure report, 2 = cheque receipt, 3 = credit card receipt, 4 = currency exchange receipt, 5 = deposit receipt, 6 = paid out receipt, 7 = AR Reminder Letter, 8 = AR Statement
ZTXT_TIME	DATE			Y	ZTXT_TIME is of ZTXT
ZTXT_COPIES	NUMBER	2		Y	Number of copies
ZTXT_TABLELINKEDTO	CHAR			Y	Name of linked table.
ZTXT_TABLE_ID	NUMBER	30		Y	ID of linked table.

### ZTXT

Binary storage of cashiering receipts/ reports/ AR reminder and statements

Field Name	Type	Length	Decimals	Not NULL	
ZTXT_EXPORTTYPE	NUMBER	1		Y	0 = Crystal Reports, 1= Html, 2 = Rtf
ZTXT_DATE	DATE			Y	systemdate of execution

### ZTXX

TAX EXEMPTIONS

Field Name	Type	Length	Decimals	Not NULL	
ZTXX_ID	NUMBER	30		N	ZTXX_ID identifies ZTXX
ZTXX_SHORTDESC	VARCHAR2	10		N	ZTXX_SHORTDESC is of ZTXX
ZTXX_LONGDESC	VARCHAR2	30		N	ZTXX_LONGDESC is of ZTXX

### ZUDD

User definable folio descriptions

Field Name	Type	Length	Decimals	Not NULL	
ZUDD_ID	NUMBER	30		N	Unique ID
ZUDD_DESCRIPTION	VARCHAR2	60		Y	Description

### ZURL

Field Name	Type	Length	Decimals	Not NULL	
ZURL_ID	NUMBER	30		N	unique id
ZURL_ZOTA_ID	NUMBER	30		N	link to mmod
ZURL_MSG_NAME	VARCHAR2	100		Y	name of xml message
ZURL_URL	VARCHAR2	150		Y	URL used to send message
ZURL_INACTIVE	NUMBER	1		Y	Indicates which setup URL is really used
ZURL_MSG_TYPE	NUMBER	1		Y	Indicates the type of message 0 = Room Type Inventory, 1 = Rate Availability, 2 = Rate Code, 3 = Reservation

### ZWIN

Billing Window Control File

Field Name	Type	Length	Decimals	Not NULL	
ZWIN_ID	NUMBER	30		N	Unique Identifier
ZWIN_WINDOW	NUMBER	3		N	Window Number

### ZWIN

Billing Window Control File

Field Name	Type	Length	Decimals	Not NULL	
ZWIN_YRES_ID	NUMBER	30		Y	Reservation Number
ZWIN_ZFAC_ID	NUMBER	30		Y	Financial Account Id
ZWIN_INVOICE_TO_XCMS_ID	NUMBER	30		Y	Profile where the invoice will be addressed to
ZWIN_INVOICE_TO_XADR_ID	NUMBER	30		Y	Address selected from addresses of linked profile.
ZWIN_INVOICE_TO_CONTACT_ID	NUMBER	30		Y	Contact selected from list of available contacts for attached profile
ZWIN_BILLVIEW	NUMBER	1		Y	1 - billview allowed on that window
ZWIN_VIDEO_CO	NUMBER	1		Y	1 - Video Check Out allowed on that window
ZWIN_FREETEXT1	VARCHAR2	60		Y	Free Text Edit per Billing Window, for printing on folio, Former P1 and P2
ZWIN_FREETEXT2	VARCHAR2	60		Y	Free Text Edit per Billing Window, for printing on folio, Former P1 and P2
ZWIN_PAYMENT_ZDCO_ID	NUMBER	30		Y	Payment for that window. If entered it overwrites YRES_DEFPAYMETH_ZDCO_ID, if a credit card is selected the credit card from YRCL can be selected and attached to that window.
ZWIN_YRCL_ID	NUMBER	30		Y	ZWIN_YRCL_ID is of ZWIN
ZWIN_FREETEXT3	VARCHAR2	60		Y	Free Text Edit per Billing Window, for printing on folio, Former P1 and P2
ZWIN_FREETEXT4	VARCHAR2	60		Y	Free Text Edit per Billing Window, for printing on folio, Former P1 and P2
ZWIN_ZFST_ID	NUMBER	30		Y	Link to Folio Style Configuration
ZWIN_ZWIT_ID	NUMBER	30		N	Link to Billing Window Types
ZWIN_BALANCEBEFORECLOSE	NUMBER	30	4	Y	filled on checkout before settling the window balance
ZWIN_NOBONUSPOINTS	NUMBER	1		N	
ZWIN_ZRDF_ID	NUMBER	30		Y	A Rebate Code can be linked per window

### ZWIT

billing window types

Field Name	Type	Length	Decimals	Not NULL	
ZWIT_ID	NUMBER	30		N	Unique ID
ZWIT_TYPE	NUMBER	2		N	0 - normal   1 - personal rebate   2 - personal lunch   3 - personal not discountable
ZWIT_SHORTDESC	VARCHAR2	5		N	Short description
ZWIT_LONGDESC	VARCHAR2	30		N	Long description
ZWIT_WCOL_ID	NUMBER	30		Y	Color assigned

### ZWRL

Billing window rules

Field Name	Type	Length	Decimals	Not NULL	
------------	------	--------	----------	----------	--

### ZWRL

Billing window rules

Field Name	Type	Length	Decimals	Not NULL	
ZWRL_ID	NUMBER	30		N	Unique identifier
ZWRL_ZFAG_ID	NUMBER	30		N	Link to financial account group
ZWRL_ZWIT_ID	NUMBER	30		N	Link to billing window types
ZWRL_MONTHLYAMOUNT	NUMBER	30	4	Y	monthly discount amount to post on the first day of month
ZWRL_CO_ZDCO_ID	NUMBER	30		Y	checkout department code
ZWRL_TR_ZDCO_ID	NUMBER	30		Y	balance transfer department code
ZWRL_OP_ZDCO_ID	NUMBER	30		Y	monthly opening department code
ZWRL_TRANSFER_MONTH1	NUMBER	1		N	If balance transfer should take place at the end of January -> 1, otherwise 0. Same for the other fields too.
ZWRL_TRANSFER_MONTH2	NUMBER	1		N	If balance transfer should take place at the end of February -> 1, otherwise 0
ZWRL_TRANSFER_MONTH3	NUMBER	1		N	If balance transfer should take place at the end of March -> 1, otherwise 0
ZWRL_TRANSFER_MONTH4	NUMBER	1		N	If balance transfer should take place at the end of April -> 1, otherwise 0
ZWRL_TRANSFER_MONTH5	NUMBER	1		N	If balance transfer should take place at the end of May -> 1, otherwise 0
ZWRL_TRANSFER_MONTH6	NUMBER	1		N	If balance transfer should take place at the end of June -> 1, otherwise 0
ZWRL_TRANSFER_MONTH7	NUMBER	1		N	If balance transfer should take place at the end of July -> 1, otherwise 0
ZWRL_TRANSFER_MONTH8	NUMBER	1		N	If balance transfer should take place at the end of August -> 1, otherwise 0
ZWRL_TRANSFER_MONTH9	NUMBER	1		N	If balance transfer should take place at the end of September -> 1, otherwise 0
ZWRL_TRANSFER_MONTH10	NUMBER	1		N	If balance transfer should take place at the end of October -> 1, otherwise 0
ZWRL_TRANSFER_MONTH11	NUMBER	1		N	If balance transfer should take place at the end of November -> 1, otherwise 0
ZWRL_TRANSFER_MONTH12	NUMBER	1		N	If balance transfer should take place at the end of December -> 1, otherwise 0

### ZWTR

Offline notification of wellness interfaces

Field Name	Type	Length	Decimals	Not NULL	
ZWTR_ID	NUMBER	30		N	
ZWTR_MSG	NUMBER	2		N	Message type. 1 - Reservation changed, 2 - Profile Changed, 3 - Reservation cancel / Delete FA, 4 - C/I, 5 - C/O
ZWTR_INTF	NUMBER	2		N	Interface to notify. 1 - Bellavita, 2 - HIS, 3 - MyVisitors
ZWTR_XCMS_ID	NUMBER	30		Y	Profile ID
ZWTR_YRES_ID	NUMBER	30		Y	Reservation ID
ZWTR_WPCA_ID	NUMBER	30		Y	ID of the terminal where the change has been made

### ZXCH

exchange rates

Field Name	Type	Length	Decimals	Not NULL	
ZXCH_ID	NUMBER	30		N	ZXCH_ID identifies ZXCH
ZXCH_ZCUR_ID	NUMBER	30		N	ZXCH_ZCUR_ID is of ZXCH
ZXCH_FROMTIME	DATE			N	ZXCH_FROMTIME is of ZXCH
ZXCH_RATE	NUMBER	38	18	Y	Default or Check out Exchange Rate.
ZXCH_BACKRATE	NUMBER	38	18	Y	Obsolete field, not supported anymore
ZXCH_CASH_RATE	NUMBER	38	18	Y	Exchange rate used for currency exchange, if not configured the default exchange rate is taken into consideration.
ZXCH_CASH_BACKRATE	NUMBER	38	18	Y	Obsolete field, not supported anymore
ZXCH_RATECODE_RATE	NUMBER	38	18	Y	Rate Code Exchange rate.
ZXCH_RATECODE_BACKRATE	NUMBER	38	18	Y	Obsolete field, not supported anymore
ZXCH_PRIMARY	NUMBER	1		Y	0-rate selected as primary; 1-backrate selected as primary
ZXCH_CURRENT	NUMBER	1		Y	EXCHANGE RATE CURRENT FIELD

### ZYPC

Config of TI yearly tickets payment cycles

Field Name	Type	Length	Decimals	Not NULL	
ZYPC_ID	NUMBER	30		N	
ZYPC_SHORTDESC	VARCHAR2	3		N	
ZYPC_LONGDESC	VARCHAR2	30		Y	
ZYPC_DISPLORDER	NUMBER	3		Y	
ZYPC_INACTIVE	NUMBER	1		Y	
ZYPC_DEFAULT	NUMBER	1		Y	

### ZYTG

Yearly Ticket Groups for Tropical Islands

Field Name	Type	Length	Decimals	Not NULL	
ZYTG_ID	NUMBER	30		N	
ZYTG_SHORTDESC	VARCHAR2	3		N	
ZYTG_LONGDESC	VARCHAR2	30		Y	
ZYTG_DISPLORDER	NUMBER	3		Y	
ZYTG_ROLE	NUMBER	3		Y	0 - No role, 1 - Yearly Tickets

## ZYTT

Config of TI yearly tickets

Field Name	Type	Length	Decimals	Not NULL	
ZYTT_ID	NUMBER	30		N	
ZYTT_SHORTDESC	VARCHAR2	3		N	
ZYTT_LONGDESC	VARCHAR2	30		Y	
ZYTT_DISPLORDER	NUMBER	3		Y	
ZYTT_INACTIVE	NUMBER	1		Y	
ZYTT_DEFAULT	NUMBER	1		Y	
ZYTT_FROMNUMBER	VARCHAR2	6		Y	start of the card number range
ZYTT_TONUMBER	VARCHAR2	6		Y	end of the card number range

## ZYTX

TI yearly tickets

Field Name	Type	Length	Decimals	Not NULL	
ZYTX_ID	NUMBER	30		N	
ZYTX_ZYTT_ID	NUMBER	30		N	
ZYTX_ZYPC_ID	NUMBER	30		N	
ZYTX_ZTRA_ID	NUMBER	30		N	
ZYTX_VALIDFROM	DATE			Y	
ZYTX_VALIDUNTIL	DATE			Y	
ZYTX_GUEST_XCMS_ID	NUMBER	30		N	link to guest profile
ZYTX_CONTRACTPARTNER_XCMS_ID	NUMBER	30		N	link to contract partner profile
ZYTX_SALESCONTACT_XCMS_ID	NUMBER	30		N	link to sales contact profile
ZYTX_INACTIVE	NUMBER	1		Y	
ZYTX_INACTIVE_REASON	VARCHAR2	200		Y	
ZYTX_CANCELDATE	DATE			Y	
ZYTX_CANCEL_REASON	VARCHAR2	200		Y	

## ZYZF

Link table between ZYTX and ZFAC to identify transponders used with one yearly ticket

Field Name	Type	Length	Decimals	Not NULL	
ZYZF_ID	NUMBER	30		N	
ZYZF_ZYTX_ID	NUMBER	30		N	
ZYZF_ZFAC_ID	NUMBER	30		N	

## Find out more about what MICROS-Fidelio can do for you

For more information about Suite8  
please contact us at [sales-eu@micros.com](mailto:sales-eu@micros.com).

## About MICROS-Fidelio

Serving the hospitality and speciality retail industries, we are the world's leading developer of enterprise applications. Our global presence and local support have helped us build a long list of references - hotels, restaurants, conference centres, retail, stadiums, theme parks, casinos and cruise ships. We maintain an intense dialogue with colleagues throughout these industries. The result is a wide range of integrated software, hardware and business technology solutions and services. These help to optimise your operation and increase profits by providing your guests with a personalised service.

### MICROS-FIDELIO GmbH

Europadamm 2-6  
41460 Neuss  
Germany  
Phone: +49-(0)2131-137 0  
Fax: +49-(0)2131-137 777

[www.micros-fidelio.eu](http://www.micros-fidelio.eu)

micros® and micros-fidelio® are registered trademarks of MICROS Systems, Inc. Certain product and company names appearing here may be the trademarks or service marks owned and/or registered by third parties. All other product and brand names are the property of their respective owners.

© Copyright 2014 MICROS Systems, Inc. All rights reserved.